

FCC Part 15C Measurement and Test Report

For

Shenzhen ThreeNH Technology Co., Ltd

4/F, Building 8, Nangang Second Industry Zone, Xili, Nanshan

District, Shenzhen, Guangdong, China

FCC ID: 2AMRM-YS6060

FCC Rule(s):	<u>FCC Part 15.247</u>
Product Description:	<u>Benchtop Spectrophotometer</u>
Tested Model:	<u>YS6060</u>
Report No.:	<u>STR18118245I</u>
Sample Receipt Date:	<u>2018-11-20</u>
Tested Date:	<u>2018-11-20 to 2018-12-05</u>
Issued Date:	<u>2018-12-06</u>
Tested By:	<u>Mike Shi / Engineer</u>
Reviewed By:	<u>Silin Chen / EMC Manager</u>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u>
Prepared By:	

Mike Shi

Silin Chen

Jandy So

Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND TEST MODE.....	5
1.6 MEASUREMENT UNCERTAINTY.....	5
1.7 TEST EQUIPMENT LIST AND DETAILS.....	6
2. SUMMARY OF TEST RESULTS.....	7
3. RF EXPOSURE.....	8
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
4. ANTENNA REQUIREMENT.....	9
4.1 STANDARD APPLICABLE.....	9
4.2 EVALUATION INFORMATION.....	9
5. POWER SPECTRAL DENSITY.....	10
5.1 STANDARD APPLICABLE.....	10
5.2 TEST PROCEDURE.....	10
5.3 SUMMARY OF TEST RESULTS/PLOTS.....	10
6. DTS BANDWIDTH.....	12
6.1 STANDARD APPLICABLE.....	12
6.2 TEST PROCEDURE.....	12
6.3 SUMMARY OF TEST RESULTS/PLOTS.....	12
7. RF OUTPUT POWER.....	14
7.1 STANDARD APPLICABLE.....	14
7.2 TEST PROCEDURE.....	14
7.3 SUMMARY OF TEST RESULTS/PLOTS.....	14
8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....	16
8.1 STANDARD APPLICABLE.....	16
8.2 TEST PROCEDURE.....	16
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	17
8.4 SUMMARY OF TEST RESULTS/PLOTS.....	17
9. OUT OF BAND EMISSIONS.....	25
9.1 STANDARD APPLICABLE.....	25
9.2 TEST PROCEDURE.....	25
9.3 SUMMARY OF TEST RESULTS/PLOTS.....	26
10. CONDUCTED EMISSIONS.....	32
10.1 TEST PROCEDURE.....	32
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	32
10.3 TEST RECEIVER SETUP.....	32
10.4 SUMMARY OF TEST RESULTS/PLOTS.....	32

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen ThreeNH Technology Co., Ltd
Address of applicant: 4/F, Building 8, Nangang Second Industry Zone, Xili, Nanshan District, Shenzhen, Guangdong, China

Manufacturer: Shenzhen ThreeNH Technology Co., Ltd
Address of manufacturer: 4/F, Building 8, Nangang Second Industry Zone, Xili, Nanshan District, Shenzhen, Guangdong, China

General Description of EUT	
Product Name:	Benchtop Spectrophotometer
Brand Name:	3nh
Model No.:	YS6060
Adding Model(s):	YS6010, YS6020, YS6080, YS6090, YS6002, YS6003, YS6022, YS6023
Rated Voltage:	DC24V
Power Adapter:	MODEL: B06240030 INPUT: AC100-240V 50-60Hz 1.6A OUTPUT: DC24V, 3A
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model YS6060, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Bluetooth Version:	V4.0 (BLE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	2.92dBm (Conducted)
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	Chip
Antenna Gain:	-0.5dBi
Lowest Internal Frequency of EUT:	32.768kHz

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

558074 D01 15.247 Meas Guidance v05: Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The Fcc Rules

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low	2402MHz
TM2	Middle	2440MHz
TM3	High	2480MHz

Test Conditions	
Temperature:	22~25 °C
Relative humidity	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
AC CALBE	1.5	Unshielded	Without Cor
DC CABLE	1.5	Unshielded	With Core

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.42dB
Occupied Bandwidth	Conducted	±1.5%
Power Spectral Density	Conducted	±1.8dB
Conducted Spurious Emission	Conducted	±2.17dB
Conducted Emissions	Conducted	9-150kHz ±3.74dB
		0.15-30MHz ±3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz ±4.52dB
		0.2-1GHz ±5.56dB
		1-6GHz ±3.84dB
		6-18GHz ±3.92dB

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2018-05-22	2019-05-21
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2018-05-22	2019-05-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2018-05-22	2019-05-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2018-05-22	2019-05-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2018-05-22	2019-05-21
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2018-05-22	2019-05-21
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2018-05-22	2019-05-21
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2018-05-22	2019-05-21
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2018-05-22	2019-05-21
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2018-05-22	2019-05-21
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2018-05-22	2019-05-21
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2018-05-22	2019-05-21
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2018-05-22	2019-05-21
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2018-05-22	2019-05-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2018-03-19	2019-03-18
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2018-03-19	2019-03-18
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2018-03-19	2019-03-18
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2018-03-19	2019-03-18
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	DTS Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has a chip antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure




According to the KDB 558074 D01 v05 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.2, the test method of power spectral density as below:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 Summary of Test Results/Plots

Test Mode	Test Channel	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
GFSK(BLE)	Low	-12.58	8
	Middle	-13.69	8
	High	-13.26	8

Please refer to the following test plots:

<p>Low</p>	 <p>MARKER 1 2.401576 GHz Val: 20 dBm Att: 30 dB Span: 3.0 MHz Center: 2.402 GHz 150 kHz</p>
<p>Middle</p>	 <p>MARKER 1 2.439976 GHz Val: 20 dBm Att: 30 dB Span: 3.0 MHz Center: 2.44 GHz 150 kHz</p>
<p>High</p>	 <p>MARKER 1 2.479976 GHz Val: 20 dBm Att: 30 dB Span: 3.0 MHz Center: 2.48 GHz 150 kHz</p>

6. DTS Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure




According to the KDB 558074 D01 v05 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Summary of Test Results/Plots

Test Mode	Test Channel	6 dB Bandwidth kHz	Limit kHz
GFSK(BLE)	Low	732	≥ 500
	Middle	726	≥ 500
	High	732	≥ 500

Please refer to the following test plots:

<p>Low</p>	 <p>DELTA MARKER 1 *BW 100 KHZ Delta 1 (D1) T22 420 *VSW 300 KHZ -0.12 dB F2F 20 dBm *Att 30 dB SWR 1.00 T24,200000000 KHZ</p> <p>Offset 1 dB Max 1 1.000000000 KHZ Max 2 1 (71) -4.22 dBm Temp 1 (71) 0dBm Temp 2 (71) 0dBm Temp 3 (71) 0dBm Temp 4 (71) 0dBm Temp 5 (71) 0dBm</p> <p>Center 2,420 GHz 300 kHz Span 3 MHz</p>
<p>Middle</p>	 <p>DELTA MARKER 1 *BW 100 KHZ Delta 1 (D1) T24 420 *VSW 300 KHZ 0.10 dB F2F 20 dBm *Att 30 dB SWR 1.00 T24,200000000 KHZ</p> <p>Offset 1 dB Max 1 1.000000000 KHZ Max 2 1 (71) -4.29 dBm Temp 1 (71) 0dBm Temp 2 (71) 0dBm Temp 3 (71) 0dBm Temp 4 (71) 0dBm Temp 5 (71) 0dBm</p> <p>Center 2,44 GHz 300 kHz Span 3 MHz</p>
<p>High</p>	 <p>DELTA MARKER 1 *BW 100 KHZ Delta 1 (D1) T06 420 *VSW 300 KHZ 2.40 dB F2F 20 dBm *Att 30 dB SWR 1.00 T24,200000000 KHZ</p> <p>Offset 1 dB Max 1 1.047000000 KHZ Max 2 1 (71) -4.04 dBm Temp 1 (71) 0dBm Temp 2 (71) 0dBm Temp 3 (71) 0dBm Temp 4 (71) 0dBm Temp 5 (71) 0dBm</p> <p>Center 2,46 GHz 300 kHz Span 3 MHz</p>

7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.




7.2 Test Procedure

According to the KDB-558074 D01 v05 Subclause 8.3.1.1 and ANSI C63.10-2013 Subclause 11.9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW \geq DTS bandwidth.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

7.3 Summary of Test Results/Plots

Test Mode	Test Channel	Reading dBm	Output Power mW	Limit mW
GFSK(BLE)	Low	2.92	1.96	1000
	Middle	1.86	1.53	1000
	High	2.19	1.66	1000

<p>Low</p>	 <p>MARKER 1 2.40123 GHz FAT 20 dBm ATT 30 dB OFF 1 dB SPAN 5 MHz 500 kHz</p>
<p>Middle</p>	 <p>MARKER 1 2.43974 GHz FAT 20 dBm ATT 30 dB OFF 1 dB SPAN 5 MHz 500 kHz</p>
<p>High</p>	 <p>MARKER 1 2.47979 GHz FAT 20 dBm ATT 30 dB OFF 1 dB SPAN 5 MHz 500 kHz</p>

8. Field Strength of Spurious Emissions

8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of $-6\text{dB}\mu\text{V}$ means the emission is $6\text{dB}\mu\text{V}$ below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


➤ Spurious Emissions Below 1GHz

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	113.3163	43.33	-14.51	28.82	43.50	-14.68	321	100	peak
2	188.4125	52.47	-14.58	37.89	43.50	-5.61	91	100	peak
3	252.0627	52.08	-9.71	42.37	46.00	-3.63	210	100	peak
4	292.0583	47.34	-8.37	38.97	46.00	-7.03	111	100	peak
5	420.5803	42.10	-6.30	35.80	46.00	-10.20	228	100	peak
6	758.0408	39.22	-1.65	37.57	46.00	-8.43	237	100	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	63.3132	43.68	-13.77	29.91	40.00	-10.09	331	100	peak
2	92.1388	42.57	-13.83	28.74	43.50	-14.76	90	100	peak
3	130.3789	48.81	-16.91	31.90	43.50	-11.60	132	100	peak
4	184.4898	49.98	-14.99	34.99	43.50	-8.51	100	100	peak
5	420.5803	45.34	-6.30	39.04	46.00	-6.96	56	100	peak
6	560.6928	39.54	-4.47	35.07	46.00	-10.93	263	100	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	113.3163	43.51	-14.51	29.00	43.50	-14.50	224	100	peak
2	186.4409	52.66	-14.79	37.87	43.50	-5.63	158	100	peak
3	252.0627	50.90	-9.71	41.19	46.00	-4.81	63	100	peak
4	292.0583	47.32	-8.37	38.95	46.00	-7.05	118	100	peak
5	420.5803	41.83	-6.30	35.53	46.00	-10.47	161	100	peak
6	758.0408	38.77	-1.65	37.12	46.00	-8.88	187	100	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	42.1542	34.77	-12.24	22.53	40.00	-17.47	213	100	peak
2	63.3132	42.96	-13.77	29.19	40.00	-10.81	187	100	peak
3	92.1388	42.55	-13.83	28.72	43.50	-14.78	58	100	peak
4	126.7723	48.03	-16.70	31.33	43.50	-12.17	292	100	peak
5	182.5592	49.95	-15.17	34.78	43.50	-8.72	144	100	peak
6	420.5803	45.97	-6.30	39.67	46.00	-6.33	197	100	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	113.3163	43.28	-14.51	28.77	43.50	-14.73	177	100	peak
2	188.4125	52.63	-14.58	38.05	43.50	-5.45	183	100	peak
3	252.0627	51.06	-9.71	41.35	46.00	-4.65	80	100	peak
4	373.3112	44.12	-7.25	36.87	46.00	-9.13	128	100	peak
5	420.5803	41.87	-6.30	35.57	46.00	-10.43	184	100	peak
6	758.0408	38.63	-1.65	36.98	46.00	-9.02	221	100	peak

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	63.3132	44.06	-13.77	30.29	40.00	-9.71	96	100	peak
2	92.1388	42.84	-13.83	29.01	43.50	-14.49	179	100	peak
3	130.3789	48.63	-16.91	31.72	43.50	-11.78	127	100	peak
4	184.4898	49.94	-14.99	34.95	43.50	-8.55	117	100	peak
5	420.5803	44.93	-6.30	38.63	46.00	-7.37	297	100	peak
6	672.8445	37.97	-2.47	35.50	46.00	-10.50	277	100	peak

➤ Spurious Emissions Below 1GHz

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2402MHz							
4804	57.91	-3.59	54.32	74	-19.68	H	PK
4804	45.28	-3.59	41.69	54	-12.31	H	AV
7206	58.60	-0.52	58.08	74	-15.92	H	PK
7206	45.83	-0.52	45.31	54	-8.69	H	AV
4804	58.37	-3.59	54.78	74	-19.22	V	PK
4804	45.18	-3.59	41.59	54	-12.41	V	AV
7206	66.08	-0.52	65.56	74	-8.44	V	PK
7206	41.19	-0.52	40.67	54	-13.33	V	AV
Middle Channel-2440MHz							
4880	56.99	-3.48	53.51	74	-20.49	H	PK
4880	45.56	-3.48	42.08	54	-11.92	H	AV
7320	60.84	-0.49	60.35	74	-13.65	H	PK
7320	43.40	-0.49	42.91	54	-11.09	H	AV
4880	60.08	-3.48	56.60	74	-17.40	V	PK
4880	46.77	-3.48	43.29	54	-10.71	V	AV
7320	60.49	-0.49	60.00	74	-14.00	V	PK
7320	45.04	-0.49	44.55	54	-9.45	V	AV
High Channel-2480MHz							
4960	61.09	-3.41	57.68	74	-16.32	H	PK
4960	42.83	-3.41	39.42	54	-14.58	H	AV
7440	56.95	-0.42	56.53	74	-17.47	H	PK
7440	42.37	-0.42	41.95	54	-12.05	H	AV
4960	59.96	-3.41	56.55	74	-17.45	V	PK
4960	44.86	-3.41	41.45	54	-12.55	V	AV
7440	63.73	-0.42	63.31	74	-10.69	V	PK
7440	44.62	-0.42	44.20	54	-9.80	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074D01 v05 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9/
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Summary of Test Results/Plots


➤ Radiated test

Test Channel	Low	Polarity:	Vertical(worst case)
--------------	-----	-----------	----------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.71	-7.78	33.93	54.00	-20.07	Average Detector
		53.31	-7.78	45.53	74.00	-28.47	Peak Detector
2	2390.000	41.58	-7.32	34.26	54.00	-19.74	Average Detector
		54.22	-7.32	46.90	74.00	-27.10	Peak Detector
3	2402.000	91.32	-7.25	84.07	/	/	Average Detector
		100.02	-7.25	92.77	/	/	Peak Detector



Test Channel	High	Polarity:	Vertical(worst case)
--------------	------	-----------	----------------------





No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.975	88.58	-6.79	81.79	/	/	Average Detector
	2479.950	100.07	-6.79	93.28	/	/	Peak Detector
2	2483.500	46.95	-6.77	40.18	54.00	-13.82	Average Detector
	2483.500	60.62	-6.77	53.85	74.00	-20.15	Peak Detector
3	2500.000	40.51	-6.67	33.84	54.00	-20.16	Average Detector
	2500.000	53.12	-6.67	46.45	74.00	-27.55	Peak Detector

➤ Conducted test



Low



Middle



High




10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram




10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
 Stop Frequency 30 MHz
 Sweep Speed Auto
 IF Bandwidth..... 10 kHz
 Quasi-Peak Adapter Bandwidth 9 kHz
 Quasi-Peak Adapter Mode Normal


10.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1580	44.41	10.10	54.51	65.57	-11.06	QP
2	0.1580	33.70	10.10	43.80	55.57	-11.77	AVG
3*	0.5900	33.59	10.33	43.92	46.00	-2.08	AVG
4	0.5980	42.07	10.34	52.41	56.00	-3.59	QP
5	1.1100	32.70	10.51	43.21	56.00	-12.79	QP
6	1.7580	24.40	10.58	34.98	46.00	-11.02	AVG

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	43.35	10.10	53.45	66.00	-12.55	QP
2	0.1660	31.35	10.11	41.46	55.16	-13.70	AVG
3	0.6100	40.27	10.35	50.62	56.00	-5.38	QP
4*	0.6100	34.22	10.35	44.57	46.00	-1.43	AVG
5	0.9540	26.07	10.48	36.55	46.00	-9.45	AVG
6	0.9860	34.29	10.50	44.79	56.00	-11.21	QP

***** END OF REPORT *****