



September 7, 2017

TUV SUD BABT FCB
Octagon House,
Segensworth Road,
Fareham,
Hampshire,
PO15 5RL

Attention: Director of Certification

RE: Analysis of RF Exposure for Portable and Mobile use per KDB 447498 D01 RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices v06 and RSS-102 Issue 5 March 2015

FCC ID: 2AMRYLEVEL11

Portable exposure SAR Exemption Calculation using a 6mm separation distance:

As per Clause 4.3.1 (a) of KDB 447498 D01 v06:

$$\left(\frac{\text{max.power of channel,including tune-up tolerance,mW}}{\text{min.test separation distance,mm}} \right) \times \left(\sqrt{f \text{ (GHz)}} \right) \leq 3.0$$

$$\left(\frac{0.033 \text{ mW}}{5 \text{ mm}} \right) \times \left(\sqrt{2.440 \text{ (GHz)}} \right) \leq 3.0$$

$$0.0103 \leq 3.0 \text{ (complies)}$$

All calculations were based on peak power (worst case than source-based time-averaged maximum conducted output power).

Sincerely,

A handwritten signature in black ink that reads 'Kathy MacKenzie'.

Kathy MacKenzie

Name

Authorized Signatory

Title: Senior EMC/Wireless Test Technician