

TEST REPORT

Product : Ultra-Thin Wireless Keyboard
Trade mark : MINISO
Model/Type reference : CK910B
Serial Number : N/A
Report Number : EED32N80528501
FCC ID : 2AMSRCK910B
Date of Issue : Aug. 11, 2021
Test Standards : 47 CFR Part 15 Subpart C
Test result : PASS

Prepared for:

Dongguan Couso Technology Co.,Ltd
No.26 minye road,tangxia town,Dongguan City,
Guangdong Province. China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Frazer Li

Reviewed by:

Aaron Ma

Frazer Li

Aaron Ma

Approved by:

David Wang

Date:

Aug. 11, 2021

David Wang

Check No.:9704290621



2 Content

1 COVER PAGE	1
2 CONTENT	2
3 VERSION	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF EUT.....	5
5.3 TEST CONFIGURATION.....	8
5.4 TEST ENVIRONMENT.....	8
5.5 DESCRIPTION OF SUPPORT UNITS.....	9
5.6 TEST LOCATION.....	9
5.7 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2).....	9
6 EQUIPMENT LIST	10
7 TEST RESULTS AND MEASUREMENT DATA	12
7.1 ANTENNA REQUIREMENT.....	12
7.2 CONDUCTED EMISSIONS.....	13
7.3 MAXIMUM CONDUCTED OUTPUT POWER.....	14
7.4 DTS BANDWIDTH.....	15
7.5 MAXIMUM POWER SPECTRAL DENSITY.....	16
7.6 BAND EDGE MEASUREMENTS AND CONDUCTED SPURIOUS EMISSION.....	17
7.7 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS.....	18
8 APPENDIX A	28
PHOTOGRAPHS OF TEST SETUP	29
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	31

3 Version

Version No.	Date	Description
00	Aug. 11, 2021	Original

4 Test Summary

Test Item	Test Requirement	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	N/A
DTS Bandwidth	47 CFR Part 15 Subpart C Section 15.247 (a)(2)	PASS
Maximum Conducted Output Power	47 CFR Part 15 Subpart C Section 15.247 (b)(3)	PASS
Maximum Power Spectral Density	47 CFR Part 15 Subpart C Section 15.247 (e)	PASS
Band Edge Measurements	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
Conducted Spurious Emissions	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
Radiated Spurious Emission & Restricted bands	47 CFR Part 15 Subpart C Section 15.205/15.209	PASS

Remark:

Company Name and Address shown on Report, the sample(s) and sample Information were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

N/A:Only DC power supply is supported and this item is not considered.

Model:CK910B,Ultra-Thin Wireless keyboard,Ultra-Thin Wireless keyboard (White),Ultra-Thin Wireless keyboard (silver) ,CS1000,CS1100,CS1200,CS1300,CS1400,CS1500,CS1600,CS1700, CS1800,CS1900,CS2000, CS2100,CS2200,CS2300,CS2400,CS2500,CS2600,CS2700,CS2800,CS2900, CS3000,CS3100,CS3200,CS3300,CS3400, CS3500,CS3600,CS3610,CS3620,CS3630,CS3640,CS3650, CS3660,CS3670,CS3680,CS3690,CS3700,CS3710,CS3720,CS3730,CS3740,CS3750,CS3760,CS3770, CS3780,CS3790,CS3800, CS3810,CS3820,CS3830,CS3840,CS3850,CS3860,CS3870,CS3880, CS3890, CS4000, CS4100, CS4200, CS4300, CS4400, CS4500, CS4570, CS4380,CS4550 CS4600,CS4650, CS4700, CS4800, CS4900, CS5000, CS5100, CS5200, CS5300, CS5400, CS5500, CS5600, CS5700, CS5800, CS5900, CS6000, CS6100, CS6200, CS6300, CS6400, CS6500, CS6600, CS6700, CS6800, CS6900, CS7000, CS7100, CS7200, CS7300, CS7400, CS7500, CS7600, CS7700, CS7800, CS7900, CS8000, CS8100, CS8200, CS8300, CS8400, CS8500, CS8600, CS8700, CS8800, CS8900, CS9000, CS9100, CS9200, CS9300, CS9400, CS9500, CS9600, CS9700, CS9800, CS9900,CK300,CK310,CK320,CK330, CK340,CK350,CK360,CK370,CK380,CK390,CK400, CK410, CK420, CK430, CK440, CK450, CK455 ,CK465, CK460, CK470T, CK480, CK490,CK500 CK510, CK520, CK530, CK540, CK550, CK560, CK570, CK580, CK590, CK600,CK601,CK700,CK710,CK720,CK730,CK740,CK750,CK760,CK770,CK780,CK790, CK800, CK801,CK802,CK803,CK804,CK805,CK806,CK807,CK808,CK809,CK900, CK920, CK921, CK923, CK925, CK926, CK927,CK928,CK929, CK930, CK940, CK950, CK960, CK970, CK980, CK990.

Only the model CK910B was tested, their electrical circuit design, layout, components used and internal wiring are identical, Only the model , color of the appearance is different.

5 General Information

5.1 Client Information

Applicant:	Dongguan Couso Technology Co.,Ltd
Address of Applicant:	No.26 minye road,tangxia town,Dongguan City,Guangdong Province. China
Manufacturer:	Dongguan Couso Technology Co.,Ltd
Address of Manufacturer:	No.26 minye road,tangxia town,Dongguan City,Guangdong Province. China
Factory:	Dongguan Couso Technology Co.,Ltd
Address of Factory:	No.26 minye road,tangxia town,Dongguan City,Guangdong Province. China

5.2 General Description of EUT

Product Name:	Ultra-Thin Wireless Keyboard
Mode No.(EUT):	CK910B
Add model:	Ultra-Thin Wireless keyboard,Ultra-Thin Wireless keyboard (White),Ultra-Thin Wireless keyboard (sliver) ,CS1000,CS1100,CS1200,CS1300,CS1400,CS1500,CS1600,CS1700,CS1800,CS1900,CS2000,CS2100,CS2200,CS2300,CS2400,CS2500,CS2600,CS2700,CS2800,CS2900,CS3000,CS3100,CS3200,CS3300,CS3400,CS3500,CS3600,CS3610,CS3620,CS3630,CS3640,CS3650,CS3660,CS3670,CS3680,CS3690,CS3700,CS3710,CS3720,CS3730,CS3740,CS3750,CS3760,CS3770,CS3780,CS3790,CS3800,CS3810,CS3820,CS3830,CS3840,CS3850,CS3860,CS3870,CS3880,CS3890,CS4000,CS4100,CS4200,CS4300,CS4400,CS4500,CS4570,CS4380,CS4550,CS4600,CS4650,CS4700,CS4800,CS4900,CS5000,CS5100,CS5200,CS5300,CS5400,CS5500,CS5600,CS5700,CS5800,CS5900,CS6000,CS6100,CS6200,CS6300,CS6400,CS6500,CS6600,CS6700,CS6800,CS6900,CS7000,CS7100,CS7200,CS7300,CS7400,CS7500,CS7600,CS7700,CS7800,CS7900,CS8000,CS8100,CS8200,CS8300,CS8400,CS8500,CS8600,CS8700,CS8800,CS8900,CS9000,CS9100,CS9200,CS9300,CS9400,CS9500,CS9600,CS9700,CS9800,CS9900,CK300,CK310,CK320,CK330,CK340,CK350,CK360,CK370,CK380,CK390,CK400,CK410,CK420,CK430,CK440,CK450,CK455,CK465,CK460,CK470T,CK480,CK490,CK500,CK510,CK520,CK530,CK540,CK550,CK560,CK570,CK580,CK590,CK600,CK601,CK700,CK710,CK720,CK730,CK740,CK750,CK760,CK770,CK780,CK790,CK800,CK801,CK802,CK803,CK804,CK805,CK806,CK807,CK808,CK809,CK900,CK920,CK921,CK923,CK925,CK926,CK927,CK928,CK929,CK930,CK940,CK950,CK960,CK970,CK980,CK990.
Trade mark:	MINISO
Bluetooth Version:	4.2
Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK
Transfer Rate:	<input checked="" type="checkbox"/> 1Mbps <input type="checkbox"/> 2Mbps
Number of Channel:	40
Antenna Type:	PCB antenna
Antenna Gain:	0.55dBi

Power Supply:	2X1.5V Batteries; size AAA
Test Voltage:	DC 3V
Sample Received Date:	Jul. 09, 2021
Sample tested Date:	Jul. 09, 2021 to Jul. 14, 2021

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH0)	2402MHz
The middle channel (CH19)	2440MHz
The highest channel (CH39)	2480MHz

5.3 Test Configuration

EUT Test Software Settings:				
Software:	fcc_test_tool v1.6			
EUT Power Grade:	Class2 (Power level is built-in set parameters and cannot be changed and selected)			
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.				
Test Mode	Modulation	Rate	Channel	Frequency(MHz)
Mode a	GFSK	1Mbps	CH0	2402
Mode b	GFSK	1Mbps	CH19	2440
Mode c	GFSK	1Mbps	CH39	2480

5.4 Test Environment

Operating Environment:	
Radiated Spurious Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
Conducted Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
RF Conducted:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar

5.5 Description of Support Units

The EUT has been tested with associated equipment below.

Associated equipment name		Manufacture	model	S/N serial number	Supplied by	Certification
AE	Notebook	DELL	DELL 3490	D245DX2	DELL	CE&FCC

5.6 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

5.7 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-18GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.3dB (30MHz-1GHz)
		4.5dB (1GHz-18GHz)
		3.4dB (18GHz-40GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

6 Equipment List

Conducted disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Receiver	R&S	ESCI	100435	04-15-2021	04-14-2022
Temperature/ Humidity Indicator	Defu	TH128	/	---	---
LISN	R&S	ENV216	100098	03-04-2021	03-03-2022
Barometer	changchun	DYM3	1188	---	---

RF test system					
Equipment	Manufacturer	Mode No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Spectrum Analyzer	R&S	FSV40	101200	12-28-2020	12-27-2021
Signal Generator	Keysight	N5182B	MY53051549	12-28-2020	12-27-2021
High-pass filter	Sinoscite	FL3CX03WG18 NM12-0398-002	---	---	---
High-pass filter	MICRO- TRONICS	SPA-F-63029-4	---	---	---
DC Power	Keysight	E3642A	MY56376072	12-28-2020	12-27-2021
PC-1	Lenovo	R4960d	---	---	---
Power unit	R&S	OSP120	101374	12-28-2020	12-27-2021
RF control unit	JS Tonscend	JS0806-2	158060006	12-28-2020	12-27-2021
BT&WI-FI Automatic test software	JS Tonscend	JS1120-3	---	---	---

3M Semi/full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	05-24-2019	05-23-2022
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	9163-618	05-16-2021	05-15-2022
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04-15-2021	04-14-2024
Receiver	R&S	ESC17	100938-003	10-16-2020	10-15-2021
Multi device Controller	matur	NCD/070/10711 112	---	---	---
Cable line	Fulai(7M)	SF106	5219/6A	---	---
Cable line	Fulai(6M)	SF106	5220/6A	---	---
Cable line	Fulai(3M)	SF106	5216/6A	---	---
Cable line	Fulai(3M)	SF106	5217/6A	---	---

3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
RSE Automatic test software	JS Tonscend	JS36-RSE	10166	---	---
Receiver	Keysight	N9038A	MY57290136	03-04-2021	03-03-2022
Spectrum Analyzer	Keysight	N9020B	MY57111112	03-04-2021	03-03-2022
Spectrum Analyzer	Keysight	N9030B	MY57140871	03-04-2021	03-03-2022
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-15-2021	04-14-2024
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-15-2021	04-14-2024
Horn Antenna	ETS-LINDGREN	3117	00057407	07-10-2018 07-04-2021	07-09-2021 07-03-2024
Preamplifier	EMCI	EMC184055SE	980597	05-20-2021	05-19-2022
Preamplifier	EMCI	EMC001330	980563	04-15-2021	04-14-2022
Preamplifier	JS Tonscend	980380	EMC051845 SE	12-31-2020	12-30-2021
Temperature/ Humidity Indicator	biaozhi	GM1360	EE1186631	04-16-2021	04-15-2022
Fully Anechoic Chamber	TDK	FAC-3	---	01-09-2021	01-08-2024
Cable line	Times	SFT205-NMSM-2.50M	394812-0001	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	---	---
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	---	---
Cable line	Times	EMC104-NMNM-1000	SN160710	---	---
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	---	---
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	---	---
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	---	---
Cable line	Times	HF160-KMKM-3.00M	393493-0001	---	---

7 Test results and Measurement Data


7.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
EUT Antenna:	Please see Internal photos
The antenna is PCB antenna. The best case gain of the antenna is 0.55dBi.	


7.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207	
Test Method:	ANSI C63.10: 2013	
Test Frequency Range:	150kHz to 30MHz	
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto	
Limit:	Frequency range (MHz)	Limit (dBuV)
		Quasi-peak Average
	0.15-0.5	66 to 56* 56 to 46*
	0.5-5 5-30	56 46 60 50
* Decreases with the logarithm of the frequency.		
Test Setup:		
Test Procedure:	<ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane. 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 	
Test Mode:	Only DC power supply is supported and this item is not considered.	
Test Results:	Only DC power supply is supported and this item is not considered.	


7.3 Maximum Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Test Procedure:	<ul style="list-style-type: none"> a) Set the RBW \geq DTS bandwidth. b) Set VBW $\geq 3 \times$ RBW. c) Set span $\geq 3 \times$ RBW d) Sweep time = auto couple. e) Detector = peak. f) Trace mode = max hold. g) Allow trace to fully stabilize. h) Use peak marker function to determine the peak amplitude level.
Limit:	30dBm
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix A


7.4 DTS Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Test Procedure:	<ol style="list-style-type: none"> Set RBW = 100 kHz. Set the VBW $\geq [3 \times \text{RBW}]$. Detector = peak. Trace mode = max hold. Sweep = auto couple. Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
Limit:	≥ 500 kHz
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix A

7.5 Maximum Power Spectral Density




Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Test Procedure:	<ol style="list-style-type: none"> Set analyzer center frequency to DTS channel center frequency. Set the span to 1.5 times the DTS bandwidth. Set the RBW to $3 \text{ kHz} < \text{RBW} < 100 \text{ kHz}$. Set the VBW $> [3 \times \text{RBW}]$. Detector = peak. Sweep time = auto couple. Trace mode = max hold. Allow trace to fully stabilize. Use the peak marker function to determine the maximum amplitude level within the RBW. If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.
Limit:	$\leq 8.00 \text{ dBm}/3 \text{ kHz}$
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix A

7.6 Band Edge measurements and Conducted Spurious Emission

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Test Procedure:	<ul style="list-style-type: none"> a) Set RBW =100KHz. b) Set VBW = 300KHz. c) Sweep time = auto couple. d) Detector = peak. e) Trace mode = max hold. f) Allow trace to fully stabilize. g) Use peak marker function to determine the peak amplitude level.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix A

7.7 Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10kHz	Average	
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
<p>Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.</p>					



Test Procedure:


- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the

	<p>measurement.</p> <ul style="list-style-type: none"> d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Test Mode:	Refer to clause 5.3
Test Results:	Pass

Radiated Spurious Emission below 1GHz:


During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes, only the worst case mode b was recorded in the report.

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	41.8352	-17.71	40.58	22.87	40.00	17.13	PASS	Horizontal	PK
2	95.9666	-19.10	51.72	32.62	43.50	10.88	PASS	Horizontal	PK
3	192.006	-18.58	48.98	30.40	43.50	13.10	PASS	Horizontal	PK
4	288.045	-15.76	49.66	33.90	46.00	12.10	PASS	Horizontal	PK
5	455.096	-11.63	35.33	23.70	46.00	22.30	PASS	Horizontal	PK
6	750.103	-7.00	29.09	22.09	46.00	23.91	PASS	Horizontal	PK

Test Graph



Suspected List

NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	37.9548	-18.67	40.72	22.05	40.00	17.95	PASS	Vertical	PK
2	95.9666	-19.10	43.44	24.34	43.50	19.16	PASS	Vertical	PK
3	184.342	-19.36	40.75	21.39	43.50	22.11	PASS	Vertical	PK
4	284.941	-15.83	41.35	25.52	46.00	20.48	PASS	Vertical	PK
5	450.828	-11.71	32.74	21.03	46.00	24.97	PASS	Vertical	PK
6	829.456	-6.09	32.09	26.00	46.00	20.00	PASS	Vertical	PK

Radiated Spurious Emission above 1GHz:

Mode:		BLE GFSK Transmitting					Channel:		2402MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark	
1	1882.8883	3.90	41.27	45.17	74.00	28.83	PASS	Horizontal	PK	
2	3209.0139	-20.30	59.00	38.70	74.00	35.30	PASS	Horizontal	PK	
3	4804.1203	-16.23	64.17	47.94	74.00	26.06	PASS	Horizontal	PK	
4	6405.2270	-12.85	63.90	51.05	74.00	22.95	PASS	Horizontal	PK	
5	11174.5450	-6.37	53.65	47.28	74.00	26.72	PASS	Horizontal	PK	
6	14369.7580	0.72	49.78	50.50	74.00	23.50	PASS	Horizontal	PK	
7	1366.8367	1.28	41.07	42.35	74.00	31.65	PASS	Vertical	PK	
8	1998.2998	4.54	40.57	45.11	74.00	28.89	PASS	Vertical	PK	
9	4804.1203	-16.23	63.39	47.16	74.00	26.84	PASS	Vertical	PK	
10	6405.2270	-12.85	57.83	44.98	74.00	29.02	PASS	Vertical	PK	
11	9744.4496	-7.56	52.32	44.76	74.00	29.24	PASS	Vertical	PK	
12	13737.7158	-1.72	51.84	50.12	74.00	23.88	PASS	Vertical	PK	

Mode:		BLE GFSK Transmitting					Channel:		2440MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark	
1	1162.2162	0.82	42.42	43.24	74.00	30.76	PASS	Horizontal	PK	
2	1893.4893	3.98	40.39	44.37	74.00	29.63	PASS	Horizontal	PK	
3	3259.0173	-20.03	58.85	38.82	74.00	35.18	PASS	Horizontal	PK	
4	4880.1253	-16.21	63.54	47.33	74.00	26.67	PASS	Horizontal	PK	
5	7320.2880	-11.65	54.41	42.76	74.00	31.24	PASS	Horizontal	PK	
6	12010.6007	-5.31	52.95	47.64	74.00	26.36	PASS	Horizontal	PK	
7	1799.2799	3.28	41.40	44.68	74.00	29.32	PASS	Horizontal	PK	
8	3222.0148	-20.23	59.05	38.82	74.00	35.18	PASS	Vertical	PK	
9	4880.1253	-16.21	63.59	47.38	74.00	26.62	PASS	Vertical	PK	
10	7994.3330	-11.69	55.63	43.94	74.00	30.06	PASS	Vertical	PK	
11	11372.5582	-6.27	53.09	46.82	74.00	27.18	PASS	Vertical	PK	
12	13874.7250	-1.88	51.11	49.23	74.00	24.77	PASS	Vertical	PK	

Mode:		BLE GFSK Transmitting					Channel:		2480MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark	
1	1926.0926	4.17	40.62	44.79	74.00	29.21	PASS	Horizontal	PK	
2	3382.0255	-20.13	59.41	39.28	74.00	34.72	PASS	Horizontal	PK	
3	4960.1307	-15.97	62.68	46.71	74.00	27.29	PASS	Horizontal	PK	
4	6614.2409	-12.78	60.46	47.68	74.00	26.32	PASS	Horizontal	PK	
5	10262.4842	-6.71	52.92	46.21	74.00	27.79	PASS	Horizontal	PK	
6	13703.7136	-1.76	51.82	50.06	74.00	23.94	PASS	Horizontal	PK	
7	1796.4796	3.27	40.87	44.14	74.00	29.86	PASS	Vertical	PK	
8	3413.0275	-20.18	57.22	37.04	74.00	36.96	PASS	Vertical	PK	
9	4959.1306	-15.98	62.05	46.07	74.00	27.93	PASS	Vertical	PK	
10	7426.2951	-11.40	54.39	42.99	74.00	31.01	PASS	Vertical	PK	
11	9864.4576	-7.18	51.89	44.71	74.00	29.29	PASS	Vertical	PK	
12	14394.7597	1.13	49.08	50.21	74.00	23.79	PASS	Vertical	PK	

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$
- 2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

Restricted bands:

Test plot as follows:

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:			


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.00	5.77	40.35	46.12	74.00	27.88	PASS	Horizontal	PK
2	2390.00	5.77	29.25	35.02	54.00	18.98	PASS	Horizontal	AV

Mode:	BLE GFSK Transmitting	Channel:	2440
Remark:			


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.00	5.77	42.06	47.83	74.00	26.17	PASS	Vertical	PK
2	2390.00	5.77	29.24	35.01	54.00	18.99	PASS	Vertical	AV

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:			

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.50	6.57	47.63	54.20	74.00	19.80	PASS	Horizontal	PK
2	2483.50	6.57	29.72	36.29	54.00	17.71	PASS	Horizontal	AV

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

8 Appendix A

Refer to Appendix: Bluetooth LE of EED32N80528501.