



**DURACELL® M150**

Model: MAA150W-01Wh  
Rated Capacity: 91.25Wh 18.25V/5Ah  
Dock Input: 24V  $\Rightarrow$  2.5A (60W Max.)

USB-C Input/Output: 5V  $\Rightarrow$  3A, 9V  $\Rightarrow$  3A, 15V  $\Rightarrow$  3A, 20V  $\Rightarrow$  3A, 20V  $\Rightarrow$  5A (Input: 60W Max. / Output: 100W Max.)  
USB-C Output: 5V  $\Rightarrow$  3A, 9V  $\Rightarrow$  3A, 15V  $\Rightarrow$  3A, 20V  $\Rightarrow$  3A (60W Max.) Wireless charger output: 15W Max.  
USB-A x 2 Output: 5V  $\Rightarrow$  3A, 9V  $\Rightarrow$  3A, 12V  $\Rightarrow$  3A, 20V  $\Rightarrow$  3A (60W Max.)

DC total output: 148W Max. Ring Light: 2W Max.

FCC ID: 2AMUD-M150 IC: 23564-M150 CAN ICES-403(B)/NMB-403(B)

**CAUTION:** Risk of Electric Shock. Do not remove cover. No user serviceable parts inside. Refer servicing to qualified service personnel.  
Risk of Injury to Persons. Do not use this product if the power cord or the battery cables are damaged in any way. This device is not intended for use in a commercial repair facility.

**Charge temperature:** 39.2°F – 104°F (4°C – 40°C) **Discharge temperature:** 3.2°F – 104°F (-16°C – 40°C)

**WARNING:** Do not overcharge the internal battery. See Instruction Manual. Do not smoke, strike a match, or cause a spark in the vicinity of the power pack. Only charge the internal battery in a well ventilated area.

**DANGER:** This device is intended to be used indoors only. Do not use outdoors.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Note: L'étiquette d'avertissement en français se trouve à l'intérieur du compartiment de rangement.

www.Duracell.com  
Made in China  
Fabrique en Chine  
**1029825**

BC FC ETL Conforms to ANSICANU STD.2743

QR code

D:66mm