

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

Product Description	N300 Wi-Fi Range Extender
Model Name	MRE220
FCC ID	2AMUU-MRE220

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

According to the follow transmitter output power (  $P_t$  ) formula :

$$P_t = ( E \times d )^2 / ( 30 \times g_t )$$

$P_t$ =transmitter output power in watts

$g_t$ =numeric gain of the transmitting antenna (unitless)

$E$ =electric field strength in V/m

$d$ =measurement distance in meters (m)

$$P_t = 9.67\text{dBm} = 9.268\text{mW}$$

The result for RF exposure evaluation

$$\text{SAR} = (9.268\text{mW} / 5\text{mm}) \cdot [\sqrt{2.462(\text{GHz})}] = 2.908 < 3.0 \text{ for 1-g SAR}$$

### 4. CONCLUSION

The SAR evaluation is not required.