

# RF Exposure Evaluation Report

**Product** : Smart Wi-Fi Garage Door Opener  
**Trade mark** : meross, Refoss  
**Model/Type reference** : MSG100, MSG100Black, MSG200,  
RSG100, MSS710  
**Serial Number** : N/A  
**Report Number** : EED32L00064302  
**FCC ID** : 2AMUU-MSG100V3  
**Date of Issue** : Jul. 04, 2019  
**Test Standards** : 47 CFR Part 1.1307  
47 CFR Part 1.1310  
KDB447498D01v06  
**Test result** : PASS

Prepared for:

**Chengdu Meross Technology Co.,Ltd.**  
**No.1935, Floor 19, Unit 1, Building 7,**  
**No.1700 of Tianfu Avenue North, Gaoxin, Chengdu, China**

Prepared by:

**Centre Testing International Group Co., Ltd.**  
**Hongwei Industrial Zone, Bao'an 70 District,**  
**Shenzhen, Guangdong, China**

**TEL: +86-755-3368 3668**

**FAX: +86-755-3368 3385**

Tested By:

*Jay Zheng*

Jay Zheng

Compiled by:

*Kevin Lan*

Kevin Lan

Reviewed by:

*Ware Xin*

Ware Xin

Approved by:

*Kevin Yang*

Kevin Yang

Date:

Jul. 04, 2019

Check No.:3757574297



## 2 Version

Version No.	Date	Description
00	Jul. 04, 2019	Original

### 3 Contents

<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 VERSION.....</b>	<b>2</b>
<b>3 CONTENTS.....</b>	<b>3</b>
<b>4 GENERAL INFORMATION.....</b>	<b>4</b>
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
<b>5 RF EXPOSURE EVALUATION.....</b>	<b>6</b>
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 Limits.....	6
5.1.2 Test Procedure.....	6
5.1.3 EUT RF Exposure Evaluation.....	7
<b>PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....</b>	<b>7</b>

## 4 General Information

### 4.1 Client Information

Applicant:	Chengdu Meross Technology Co.,Ltd.
Address of Applicant:	No.1935, Floor 19, Unit 1, Building 7, No.1700 of Tianfu Avenue North, Gaoxin, Chengdu, China
Manufacturer:	Chengdu Meross Technology Co., Ltd.
Address of Manufacturer:	No.1935, Floor 19, Unit 1, Building 7, No.1700 of Tianfu Avenue North, Gaoxin, Chengdu, China
Factory 1:	Chengdu Youchuangda Technology Co.,Ltd.
Address of Factory 1:	B8 Building, IoT Industrial Park, 777 HuaFu Avenue, Shuangliu District, Chengdu, Sichuan Province
Factory 2:	CHENGDU XUGUANG TECHNOLOGY CO.,LTD.
Address of Factory 2:	2 Section of Park Road, Longquanyi, Chengdu, China

### 4.2 General Description of EUT

Product Name:	Smart Wi-Fi Garage Door Opener
Model No.(EUT):	MSG100, MSG100Black, MSG200, RSG100, MSS710
Test Model No.:	MSG100
Trade Mark:	meross, Refoss
Firmware version of the sample:	msg100_v3_rc0101(manufacturer declare)
Hardware version of the sample:	V3.0(manufacturer declare)
EUT Supports Radios application	2.4G WiFi: IEEE802.11b/g/n(20MHz)/n(40MHz)

### 4.3 Product Specification subjective to this standard

Frequency Range:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g :OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Test Software of EUT:	MT7682 QA 0.3.0.8 (manufacturer declare )
Antenna Type:	Internal Antenna
Antenna Gain:	1.5dBi
Power Supply:	AC 120V, 60Hz
Max Conducted Peak Output Power:	15.61dBm The Max Conducted Peak Output Power: data refer to the report EED32L00064301
Sample Received Date:	Mar. 27, 2019
Sample tested Date:	May 30, 2019 to Jul. 02, 2019

The tested sample(s) and the sample information are provided by the client.

Model No.: MSG100, MSG100Black, MSG200, RSG100, MSS710

Only the model MSG100 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being model name.

#### 4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

#### 4.5 Deviation from Standards

None.

#### 4.6 Abnormalities from Standard Conditions

None.

#### 4.7 Other Information Requested by the Customer

None.

## 5 RF Exposure Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the centre of radiation of the antenna

EIRP = P\*G

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user.

Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

#### 5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.

### 5.1.3 EUT RF Exposure Evaluation

Antenna Gain: 1.5dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducted Peak Output Power(dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R (cm)	S (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
Lowest	2412	15.61	1.5	17.11	51.40	20	0.01	1.0	Pass

**Note:** Refer to report No. EED32L00064301 for EUT test Max Conducted Peak Output Power value.

## PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32L00064301 for EUT external and internal photos.

\*\*\* End of Report \*\*\*

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.