

TEST REPORT

Product Name: BT module
Trade Mark: Sunitec
Model No. / HVIN: BMS001
Report Number: 190831013RFC-2
Test Standards: FCC 47 CFR Part 15 Subpart C
RSS-247 Issue 2
RSS-Gen Issue 5
FCC ID: 2AMX3BMS001
IC: 23011-BMS001
Test Result: PASS
Date of Issue: October 28, 2019

Prepared for:

Sunitec Enterprise Co., Ltd
No. 192, Runtang Ind,Danhu community, Fucheng, Longhua District,
Shenzhen, China (ZIP:518100)

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park,
Qingxiang Road No.1, Longhua New District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:


Henry Lu
Team Leader

Reviewed by:


Kevin Liang
Assistant Manager

Approved by:


Billy Li
Technical Director

Date: October 28, 2019

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

Version

Version No.	Date	Description
V1.0	October 28, 2019	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 OTHER INFORMATION	5
1.5 DESCRIPTION OF SUPPORT UNITS	5
1.6 TEST LOCATION	5
1.7 TEST FACILITY	5
1.8 DEVIATION FROM STANDARDS	6
1.9 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
1.11 MEASUREMENT UNCERTAINTY	6
2. TEST SUMMARY	7
3. EQUIPMENT LIST	8
4. TEST CONFIGURATION	9
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	9
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	9
4.1.2 RECORD OF NORMAL ENVIRONMENT	9
4.2 TEST CHANNELS	9
4.3 EUT TEST STATUS	9
4.4 TEST SETUP	10
4.4.1 FOR RADIATED EMISSIONS TEST SETUP	10
4.4.2 FOR CONDUCTED EMISSIONS TEST SETUP	11
4.4.3 FOR CONDUCTED RF TEST SETUP	12
4.5 SYSTEM TEST CONFIGURATION	12
4.6 DUTY CYCLE	13
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION	15
5.1 REFERENCE DOCUMENTS FOR TESTING	15
5.2 ANTENNA REQUIREMENT	15
5.3 CONDUCTED PEAK OUTPUT POWER	16
5.4 6 dB BANDWIDTH & OCCUPIED BANDWIDTH	17
5.5 POWER SPECTRAL DENSITY	24
5.6 CONDUCTED OUT OF BAND EMISSION	28
5.7 RADIATED SPURIOUS EMISSIONS	33
5.8 BAND EDGE MEASUREMENTS (RADIATED)	68
5.9 CONDUCTED EMISSION	73
APPENDIX 1 PHOTOS OF TEST SETUP	78
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	78

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Sunitec Enterprise Co., Ltd
Address of Applicant:	No. 192, Runtang Ind,Danhu community, Fucheng, Longhua District, Shenzhen, China (ZIP:518100)
Manufacturer:	Sunitec Enterprise Co., Ltd
Address of Manufacturer:	No. 192, Runtang Ind,Danhu community, Fucheng, Longhua District, Shenzhen, China (ZIP:518100)

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	BT module
Model No. / HVIN:	BMS001(See Note)
Trade Mark:	Sunitec
DUT Stage:	Production Unit
EUT Supports Function:	2.4 GHz ISM Band: Bluetooth 5.0
Software Version:	V4.0
Hardware Version:	V1.2
Sample Received Date:	September 6, 2019
Sample Tested Date:	September 6, 2019 to October 12, 2019

Note: The test data is gathered from a production sample, provided by the manufacturer. This test sample has a variety of combinations due to differences in components. E.g SPI Flash has 32M - 128M . We list the seven modes of type A-G according to the typical test mode, as shown in the following details:

Configuration	Chipset		SPI Flash		Switching CON		RTC	
	MT2811A	MT2811B	32M	128M	CON	Non-con	RTC	No-RTC
C type	☒			☒	☒		☒	
D type	☒			☒		☒	☒	
E type	☒		☒			☒		☒
A type		☒	☒		☒			☒
B type		☒	☒		☒			☒
F type		☒		☒	☒		☒	
G type		☒		☒		☒	☒	

1.2.2 Description of Accessories

None.

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth LE / 2LE
Type of Modulation:	GFSK
Number of Channels:	40
Channel Separation:	2 MHz

Antenna Type:	PCB Antenna
Antenna Gain:	2.84 dBi
Maximum Peak Power:	5.55 dBm
Normal Test Voltage:	3.3 Vdc

1.4 OTHER INFORMATION

Operation Frequency Each of Channel	
$f = 2402 + 2k \text{ MHz}, k = 0, \dots, 39$	
Note:	
f	is the operating frequency (MHz);
k	is the operating channel.

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	Lenovo	E450	SL10G10780	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.3 Meter	UnionTrust
1	USB Cable	USB Type B	1.2Meter	Applicant

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109
Telephone: +86 (0) 755 2823 0888
Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	±3.8 dB
2	Conducted emission 150KHz-30MHz	±3.4 dB
3	Radiated emission 9KHz-30MHz	±4.9 dB
4	Radiated emission 30MHz-1GHz	±4.7 dB
5	Radiated emission 1GHz-18GHz	±5.1 dB
6	Radiated emission 18GHz-26GHz	±5.2 dB
7	Radiated emission 26GHz-40GHz	±5.2 dB

2. TEST SUMMARY

Test Cases			
Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203/15.247 (c) RSS-Gen Issue 5, Section 6.8	N/A	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart C Section 15.207 RSS-Gen Issue 5, Section 8.8	ANSI C63.10-2013 Clause 6.2	PASS
Conducted Peak Output Power	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3) RSS-247 Issue 2, Section 5.4(d)	ANSI C63.10-2013 Clause 11.9.1.3	PASS
6dB Bandwidth	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2) RSS-247 Issue 2, Section 5.2(a)	ANSI C63.10-2013 Clause 11.8.1	PASS
Occupied Bandwidth	RSS-Gen Issue 5, Section 6.7	RSS-Gen Issue 5, Section 6.7	PASS
Power Spectral Density	FCC 47 CFR Part 15 Subpart C Section 15.247 (e) RSS-247 Issue 2, Section 5.2(b)	ANSI C63.10-2013 Clause 11.10.2	PASS
Conducted Out of Band Emission	FCC 47 CFR Part 15 Subpart C Section 15.247(d) RSS-247 Issue 2, Section 5.5	ANSI C63.10-2013 Clause 11.11	PASS
Radiated Spurious Emissions	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209 RSS-Gen Issue 5, Section 6.13/8.9/8.10	ANSI C63.10-2013 Clause 11.11 & Clause 11.12	PASS
Band Edge Measurements (Radiated)	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209 RSS-247 Issue 2, Section 5.5	ANSI C63.10-2013 Clause 11.13	PASS

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	3M Chamber & Accessory Equipment	ETS-LINDGREN	3M	N/A	Dec. 03, 2018	Dec. 03, 2021
☒	Receiver	R&S	ESIB26	100114	Nov. 24, 2018	Nov. 24, 2019
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	Dec. 03, 2018	Dec. 03, 2019
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Dec. 08, 2018	Dec. 08, 2019
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	Dec. 08, 2018	Dec. 08, 2019
☒	Preamplifier	HP	8447F	2805A02960	Nov. 24, 2018	Nov. 24, 2019
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201874	May 22, 2018	May 18, 2020
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Jan. 05, 2019	Jan. 05, 2020
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Band Rejection Filter (2400MHz~2500MHz)	Micro-Tronics	BRM50702	G248	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160333		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	Receiver	R&S	ESR7	1316.3003K07-101181-K3	Nov. 24, 2018	Nov. 24, 2019
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	Nov. 24, 2018	Nov. 24, 2019
☒	LISN	R&S	ESH2-Z5	860014/024	Nov. 24, 2018	Nov. 24, 2019
☐	LISN	ETS-Lindgren	3816/2SH	00201088	Nov. 24, 2018	Nov. 24, 2019
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted RF test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Nov. 24, 2018	Nov. 24, 2019
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	Nov. 24, 2018	Nov. 24, 2019
☐	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430023	Nov. 24, 2018	Nov. 24, 2019

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	3.3	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Tested by
AC Power Line Conducted Emission	25.4	39	99.55	Bert Xiong
Conducted Peak Output Power	25.4	45	99.80	Cage Ouyang
6dB Bandwidth & Occupied Bandwidth	25.4	45	99.80	Cage Ouyang
Power Spectral Density	25.4	45	99.80	Cage Ouyang
Conducted Out of Band Emission	25.4	45	99.80	Cage Ouyang
Radiated Spurious Emissions	25.2	51	100.03	Fire Huo
Band Edge Measurements (Radiated)	25.2	51	100.03	Fire Huo

4.2 TEST CHANNELS

Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
GFSK	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

4.3 EUT TEST STATUS

Type of Modulation	Tx Function	Description
GFSK	1Tx	1. Keep the EUT in continuously transmitting with modulation test single.

Power Setting
Power Setting: not applicable, test used software default power level.

Test Software
2LE Test software name: Command;
BLE Test software name: WCN_combo_tool;

4.4 TEST SETUP

4.4.1 For Radiated Emissions test setup




Figure 1. Below 30MHz







Figure 2. 30MHz to 1GHz



4.4.2 For Conducted Emissions test setup



4.4.3 For Conducted RF test setup



4.5 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in (see table below) orientation.

Frequency	Mode	Antenna Port	Worst-case axis positioning
Above 1GHz	1TX	Chain 0	Y axis

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.6 DUTY CYCLE

Test Procedure: ANSI C63.10-2013 Clause 11.6.


Test Results


Type of Modulation	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)	Average Factor (dB)
LE	0.3778	0.6247	0.60	60.48	2.18	2.65	-4.37
2LE	0.1695	0.6247	0.27	27.13	5.67	5.90	-11.33

Remark:

- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor = $10 * \log(1/ \text{Duty cycle})$;
- 3) Average factor = $20 \log_{10} \text{Duty Cycle}$.

The test plot as follows





5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	RSS-247 Issue 2	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
4	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
5	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
6	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi. RSS-Gen Issue 5, Section 6.8 requirement: According to RSS-Gen Issue 5, Section 6.8, a transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns.
EUT Antenna: Antenna in the interior of the equipment and no consideration of replacement. The gain of the antenna is 2.84 dBi.

5.3 CONDUCTED PEAK OUTPUT POWER

- Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3)
RSS-247 Issue 2, Section 5.4(d)
- Test Method:** ANSI C63.10-2013 Clause 11.9.1.3
- Limit:** For DTSS employing digital modulation techniques operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W.
- Test Procedure:**
1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter.
 2. Measure out each test modes' peak or average output power, record the power level.
- Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.
- Test Setup:** Refer to section 4.4.3 for details.
- Instruments Used:** Refer to section 3 for details
- Test Results:** Pass

Data Rate	Channel	Frequency (MHz)	Maximum Conducted Peak Power (dBm)	Maximum Conducted Peak Power (mW)
LE	0	2402	4.93	3.11
	19	2440	4.97	3.14
	39	2480	4.69	2.94
2LE	0	2402	5.51	3.56
	19	2440	5.55	3.59
	39	2480	5.27	3.37



Note: The antenna gain of 2.84 dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.



5.46 DB BANDWIDTH & OCCUPIED BANDWIDTH



Test Requirement:	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2) RSS-247 Issue 2, Section 5.2(a) RSS-Gen Issue 5, Section 6.7
Test Method:	ANSI C63.10-2013 Clause 11.8.1 RSS-Gen Issue 5, Section 6.7
Limit:	For digital transmission systems, the minimum 6 dB bandwidth shall be 500 kHz.
Test Procedure:	Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer. Use the following spectrum analyzer settings: a) Set RBW = 100 kHz. b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW. c) Detector = Peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.
Test Setup:	Refer to section 4.4.3 for details.
Instruments Used:	Refer to section 3 for details
Test Results:	

Type of Modulation	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Occupied Bandwidth (MHz)	6 dB Bandwidth Limit	Pass / Fail
LE	0	2402	0.7163	1.0447	> 500 kHz	Pass
	19	2440	0.7178	1.0448	> 500 kHz	Pass
	39	2480	0.7141	1.0443	> 500 kHz	Pass
2LE	0	2402	0.6542	2.0558	> 500 kHz	Pass
	19	2440	0.6488	2.0560	> 500 kHz	Pass
	39	2480	0.6505	2.0562	> 500 kHz	Pass



The test plots as follows:











99% Occupied Bandwidth:











5.5 POWER SPECTRAL DENSITY

Test Requirement:	FCC 47 CFR Part 15 Subpart C Section 15.247 (e) RSS-247 Issue 2, Section 5.2(b)
Test Method:	ANSI C63.10-2013 Clause 11.10.2
Limit:	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
Test Procedure:	Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer. Use the following spectrum analyzer settings: - Set analyzer center frequency to DTS channel center frequency. - Set the span to 1.5 times the DTS bandwidth. - Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. - Set the VBW $\geq 3 \times \text{RBW}$. - Detector = peak. - Sweep time = auto couple. - Trace mode = max hold. - Allow trace to fully stabilize. - Use the peak marker function to determine the maximum amplitude level within the RBW. - If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat. Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.
Test Setup:	Refer to section 4.4.3 for details.
Instruments Used:	Refer to section 3 for details
Test Results:	

Type of Modulation	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result (Pass / Fail)
LE	0	2402	-11.987	8	Pass
	19	2440	-11.894	8	Pass
	39	2480	-12.074	8	Pass
2LE	0	2402	-0.243	8	Pass
	19	2440	-0.224	8	Pass
	39	2480	-0.464	8	Pass

The test plots as follows:










5.6 CONDUCTED OUT OF BAND EMISSION


Test Requirement:	FCC 47 CFR Part 15 Subpart C Section 15.247(d) RSS-247 Issue 2, Section 5.5
Test Method:	ANSI C63.10-2013 Clause 11.11
Limit:	In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.
Test Procedure:	Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer. Use the following spectrum analyzer settings: Step 1: Reference level measurement a) Set instrument center frequency to DTS channel center frequency. b) Set the span to ≥ 1.5 times the DTS bandwidth. c) Set the RBW = 100 kHz. d) Set the VBW $\geq 3 \times$ RBW. e) Detector = peak. f) Sweep time = auto couple. g) Trace mode = max hold. h) Allow trace to fully stabilize. i) Use the peak marker function to determine the maximum PSD level. Note that the channel found to contain the maximum PSD level can be used to establish the reference level. Step 2: Emission level measurement a) Set RBW = 100 kHz. b) Set VBW ≥ 300 kHz. c) Detector = peak. d) Sweep = auto couple. e) Trace Mode = max hold. f) Allow trace to fully stabilize. g) Use the peak marker function to determine the maximum amplitude level. Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.
Test Setup:	Refer to section 4.4.3 for details.
Instruments Used:	Refer to section 3 for details
Test Results:	Pass

The test plot as follows:









5.7 RADIATED SPURIOUS EMISSIONS

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209
RSS-Gen Issue 5, Section 6.13/8.9/8.10

Test Method: ANSI C63.10-2013 Clause 11.11 & Clause 11.12

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

Spurious Emissions

Frequency	Field strength (microvolt/meter)	Limit (dBμV/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = 20 log Emission level (uV/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.4.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

2. Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230888

E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

- 2) Test the EUT in the lowest channel ,middle channel, the Highest channel
- 3) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the Y axis positioning which it is worse case.
- 4) Repeat above procedures until all frequencies measured was complete.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:


Radiated Emission Test Data (9 KHz ~ 30 MHz):

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value need not be reported.


Radiated Emission Test Data (30 MHz ~ 1 GHz):


LE _ Worst-Case Configuration(Type A)

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	132.149	38.61	-11.70	26.91	43.50	-16.59	Peak
2	154.243	42.24	-10.85	31.39	43.50	-12.11	Peak
3	191.784	37.73	-10.11	27.62	43.50	-15.88	Peak
4	231.853	36.54	-9.21	27.33	46.00	-18.67	Peak
5	309.271	37.06	-7.25	29.81	46.00	-16.19	Peak
6	433.340	34.07	-4.42	29.65	46.00	-16.35	Peak



Radiated Emission Test Data (30 MHz ~ 1 GHz):
LE _ Worst-Case Configuration(Type B)
Horizontal


No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	54.135	35.42	-13.80	21.62	40.00	-18.38	Peak
2	143.776	40.49	-11.07	29.42	43.50	-14.08	Peak
3	193.137	38.19	-10.09	28.10	43.50	-15.40	Peak
4	231.853	37.79	-9.21	28.58	46.00	-17.42	Peak
5	300.699	33.51	-7.22	26.29	46.00	-19.71	Peak
6	384.545	31.41	-5.44	25.97	46.00	-20.03	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	32.870	31.93	-6.14	25.79	40.00	-14.21	Peak
2	191.784	36.70	-10.11	26.59	43.50	-16.91	Peak
3	252.252	32.48	-8.48	24.00	46.00	-22.00	Peak
4	300.699	34.31	-7.22	27.09	46.00	-18.91	Peak
5	392.738	32.58	-5.35	27.23	46.00	-18.77	Peak
6	502.247	31.15	-3.54	27.61	46.00	-18.39	Peak


Radiated Emission Test Data (30 MHz ~ 1 GHz):
LE _ Worst-Case Configuration(Type C)
Horizontal


No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	143.776	38.83	-11.07	27.76	43.50	-15.74	Peak
2	154.243	37.82	-10.85	26.97	43.50	-16.53	Peak
3	191.784	37.44	-10.11	27.33	43.50	-16.17	Peak
4	231.853	34.60	-9.21	25.39	46.00	-20.61	Peak
5	309.271	37.47	-7.25	30.22	46.00	-15.78	Peak
6	346.074	34.30	-5.89	28.41	46.00	-17.59	Peak


Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	144.790	40.34	-11.06	29.28	43.50	-14.22	Peak
2	155.331	37.90	-10.77	27.13	43.50	-16.37	Peak
3	231.853	42.30	-9.21	33.09	46.00	-12.91	Peak
4	348.514	37.16	-5.82	31.34	46.00	-14.66	Peak
5	798.620	30.67	1.57	32.24	46.00	-13.76	Peak
6	925.613	28.72	3.92	32.64	46.00	-13.36	Peak

Radiated Emission Test Data (30 MHz ~ 1 GHz):**LE _ Worst-Case Configuration(Type D)****Horizontal**


No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	143.776	42.69	-11.07	31.62	43.50	-11.88	Peak
2	191.784	38.60	-10.11	28.49	43.50	-15.01	Peak
3	231.853	35.95	-9.21	26.74	46.00	-19.26	Peak
4	298.593	34.21	-7.16	27.05	46.00	-18.95	Peak
5	481.511	32.15	-3.98	28.17	46.00	-17.83	Peak
6	925.613	25.80	3.92	29.72	46.00	-16.28	Peak




Radiated Emission Test Data (30 MHz ~ 1 GHz):**LE _ Worst-Case Configuration(Type E)****Horizontal**

No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	191.784	42.44	-10.11	32.33	43.50	-11.17	Peak
2	233.488	34.71	-9.13	25.58	46.00	-20.42	Peak
3	309.271	35.59	-7.25	28.34	46.00	-17.66	Peak
4	348.514	34.23	-5.82	28.41	46.00	-17.59	Peak
5	693.910	28.64	0.11	28.75	46.00	-17.25	Peak
6	932.141	25.39	3.98	29.37	46.00	-16.63	Peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	154.243	36.20	-10.85	25.35	43.50	-18.15	Peak
2	193.137	38.19	-10.09	28.10	43.50	-15.40	Peak
3	300.699	33.47	-7.22	26.25	46.00	-19.75	Peak
4	371.268	33.56	-5.86	27.70	46.00	-18.30	Peak
5	491.770	32.04	-3.78	28.26	46.00	-17.74	Peak
6	798.620	29.94	1.57	31.51	46.00	-14.49	Peak

Radiated Emission Test Data (30 MHz ~ 1 GHz):
LE _ Worst-Case Configuration(Type F)
Horizontal


No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	144.790	40.35	-11.06	29.29	43.50	-14.21	Peak
2	193.137	40.55	-10.09	30.46	43.50	-13.04	Peak
3	231.853	41.53	-9.21	32.32	46.00	-13.68	Peak
4	298.593	34.28	-7.16	27.12	46.00	-18.88	Peak
5	491.770	30.65	-3.78	26.87	46.00	-19.13	Peak
6	798.620	27.67	1.57	29.24	46.00	-16.76	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	154.243	36.15	-10.85	25.30	43.50	-18.20	Peak
2	191.784	33.24	-10.11	23.13	43.50	-20.37	Peak
3	252.252	34.40	-8.48	25.92	46.00	-20.08	Peak
4	371.268	30.74	-5.86	24.88	46.00	-21.12	Peak
5	491.770	30.71	-3.78	26.93	46.00	-19.07	Peak
6	798.620	28.07	1.57	29.64	46.00	-16.36	Peak


Radiated Emission Test Data (30 MHz ~ 1 GHz):
LE _ Worst-Case Configuration(Type G)
Horizontal


No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	144.790	36.95	-11.06	25.89	43.50	-17.61	Peak
2	191.784	41.06	-10.11	30.95	43.50	-12.55	Peak
3	233.488	34.67	-9.13	25.54	46.00	-20.46	Peak
4	309.271	35.56	-7.25	28.31	46.00	-17.69	Peak
5	346.074	34.42	-5.89	28.53	46.00	-17.47	Peak
6	815.635	26.43	1.43	27.86	46.00	-18.14	Peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	193.137	38.56	-10.09	28.47	43.50	-15.03	Peak
2	252.252	35.83	-8.48	27.35	46.00	-18.65	Peak
3	311.452	33.12	-7.21	25.91	46.00	-20.09	Peak
4	384.545	31.87	-5.44	26.43	46.00	-19.57	Peak
5	542.610	30.26	-2.89	27.37	46.00	-18.63	Peak
6	925.613	27.67	3.92	31.59	46.00	-14.41	Peak


Radiated Emission Test Data (30 MHz ~ 1 GHz):
2LE _ Worst-Case Configuration(Type A)**Horizontal**

No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	53.756	35.47	-13.73	21.74	40.00	-18.26	Peak
2	143.776	33.57	-11.07	22.50	43.50	-21.00	Peak
3	191.784	37.49	-10.11	27.38	43.50	-16.12	Peak
4	233.488	33.49	-9.13	24.36	46.00	-21.64	Peak
5	309.271	35.66	-7.25	28.41	46.00	-17.59	Peak
6	348.514	34.57	-5.82	28.75	46.00	-17.25	Peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	32.870	32.68	-6.14	26.54	40.00	-13.46	Peak
2	193.137	35.66	-10.09	25.57	43.50	-17.93	Peak
3	252.252	33.76	-8.48	25.28	46.00	-20.72	Peak
4	300.699	34.60	-7.22	27.38	46.00	-18.62	Peak
5	373.886	33.80	-5.72	28.08	46.00	-17.92	Peak
6	925.613	28.44	3.92	32.36	46.00	-13.64	Peak


Radiated Emission Test Data (30 MHz ~ 1 GHz):
2LE _ Worst-Case Configuration(Type B)**Horizontal**

No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	143.776	41.03	-11.07	29.96	43.50	-13.54	Peak
2	156.426	39.72	-10.68	29.04	43.50	-14.46	Peak
3	231.853	42.46	-9.21	33.25	46.00	-12.75	Peak
4	309.271	34.98	-7.25	27.73	46.00	-18.27	Peak
5	346.074	30.85	-5.89	24.96	46.00	-21.04	Peak
6	925.613	27.50	3.92	31.42	46.00	-14.58	Peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	32.870	32.23	-6.14	26.09	40.00	-13.91	Peak
2	44.779	33.79	-12.32	21.47	40.00	-18.53	Peak
3	191.784	35.09	-10.11	24.98	43.50	-18.52	Peak
4	252.252	33.50	-8.48	25.02	46.00	-20.98	Peak
5	348.514	33.25	-5.82	27.43	46.00	-18.57	Peak
6	538.811	30.56	-2.89	27.67	46.00	-18.33	Peak


Radiated Emission Test Data (30 MHz ~ 1 GHz):
2LE _ Worst-Case Configuration(Type C)
Horizontal


No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	143.776	41.60	-11.07	30.53	43.50	-12.97	Peak
2	154.243	43.49	-10.85	32.64	43.50	-10.86	Peak
3	191.784	41.78	-10.11	31.67	43.50	-11.83	Peak
4	231.853	39.48	-9.21	30.27	46.00	-15.73	Peak
5	309.271	37.62	-7.25	30.37	46.00	-15.63	Peak
6	346.074	34.74	-5.89	28.85	46.00	-17.15	Peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	32.870	32.42	-6.14	26.28	40.00	-13.72	Peak
2	74.270	34.98	-13.36	21.62	40.00	-18.38	Peak
3	144.790	38.37	-11.06	27.31	43.50	-16.19	Peak
4	231.853	39.53	-9.21	30.32	46.00	-15.68	Peak
5	309.271	36.77	-7.25	29.52	46.00	-16.48	Peak
6	348.514	34.99	-5.82	29.17	46.00	-16.83	Peak


Radiated Emission Test Data (30 MHz ~ 1 GHz):
2LE _ Worst-Case Configuration(Type D)
Horizontal


No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	132.149	37.47	-11.70	25.77	43.50	-17.73	Peak
2	143.776	38.87	-11.07	27.80	43.50	-15.70	Peak
3	193.137	38.01	-10.09	27.92	43.50	-15.58	Peak
4	231.853	42.85	-9.21	33.64	46.00	-12.36	Peak
5	309.271	37.68	-7.25	30.43	46.00	-15.57	Peak
6	602.929	26.54	-1.20	25.34	46.00	-20.66	Peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	32.870	32.31	-6.14	26.17	40.00	-13.83	Peak
2	44.779	33.21	-12.32	20.89	40.00	-19.11	Peak
3	191.784	39.42	-10.11	29.31	43.50	-14.19	Peak
4	348.514	32.69	-5.82	26.87	46.00	-19.13	Peak
5	542.610	30.01	-2.89	27.12	46.00	-18.88	Peak
6	925.613	26.14	3.92	30.06	46.00	-15.94	Peak

Radiated Emission Test Data (30 MHz ~ 1 GHz):
2LE _ Worst-Case Configuration(Type E)
Horizontal


No.	Frequency (MHz)	Reading (dBUV)	Correction factor (dB)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector
1	132.149	39.01	-11.70	27.31	43.50	-16.19	Peak
2	143.776	41.61	-11.07	30.54	43.50	-12.96	Peak
3	154.243	41.20	-10.85	30.35	43.50	-13.15	Peak
4	231.853	38.56	-9.21	29.35	46.00	-16.65	Peak
5	309.271	37.08	-7.25	29.83	46.00	-16.17	Peak
6	433.340	31.74	-4.42	27.32	46.00	-18.68	Peak


Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	32.870	32.37	-6.14	26.23	40.00	-13.77	Peak
2	154.243	34.50	-10.85	23.65	43.50	-19.85	Peak
3	191.784	35.26	-10.11	25.15	43.50	-18.35	Peak
4	252.252	34.83	-8.48	26.35	46.00	-19.65	Peak
5	300.699	33.56	-7.22	26.34	46.00	-19.66	Peak
6	401.105	30.91	-4.95	25.96	46.00	-20.04	Peak


Radiated Emission Test Data (30 MHz ~ 1 GHz):
2LE _ Worst-Case Configuration(Type F)

Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	144.790	40.35	-11.06	29.29	43.50	-14.21	Peak
2	193.137	40.55	-10.09	30.46	43.50	-13.04	Peak
3	231.853	41.53	-9.21	32.32	46.00	-13.68	Peak
4	298.593	34.28	-7.16	27.12	46.00	-18.88	Peak
5	491.770	30.65	-3.78	26.87	46.00	-19.13	Peak
6	798.620	27.67	1.57	29.24	46.00	-16.76	Peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	154.243	36.15	-10.85	25.30	43.50	-18.20	Peak
2	191.784	33.24	-10.11	23.13	43.50	-20.37	Peak
3	252.252	34.40	-8.48	25.92	46.00	-20.08	Peak
4	371.268	30.74	-5.86	24.88	46.00	-21.12	Peak
5	491.770	30.71	-3.78	26.93	46.00	-19.07	Peak
6	798.620	28.07	1.57	29.64	46.00	-16.36	Peak

Radiated Emission Test Data (30 MHz ~ 1 GHz):
2LE _ Worst-Case Configuration(Type G)
Horizontal


No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	143.776	40.83	-11.07	29.76	43.50	-13.74	Peak
2	154.243	42.14	-10.85	31.29	43.50	-12.21	Peak
3	166.639	37.56	-10.53	27.03	43.50	-16.47	Peak
4	193.137	36.64	-10.09	26.55	43.50	-16.95	Peak
5	231.853	37.29	-9.21	28.08	46.00	-17.92	Peak
6	309.271	37.27	-7.25	30.02	46.00	-15.98	Peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	32.870	32.21	-6.14	26.07	40.00	-13.93	Peak
2	154.243	39.38	-10.85	28.53	43.50	-14.97	Peak
3	231.853	39.80	-9.21	30.59	46.00	-15.41	Peak
4	309.271	35.52	-7.25	28.27	46.00	-17.73	Peak
5	348.514	34.97	-5.82	29.15	46.00	-16.85	Peak
6	481.511	32.73	-3.98	28.75	46.00	-17.25	Peak

Type A - Radiated Emission Test Data (Above 1GHz):
LE _ Lowest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	41.53	3.93	45.46	74.00	-28.54	Peak	Horizontal
2	4804.00	30.50	3.93	34.43	54.00	-19.57	Average	Horizontal
3	7206.00	40.65	6.76	47.41	74.00	-26.59	Peak	Horizontal
4	7206.00	29.60	6.76	36.36	54.00	-17.64	Average	Horizontal
5	4804.00	42.26	4.93	47.19	74.00	-26.81	Peak	Vertical
6	4804.00	30.20	4.93	35.13	54.00	-18.87	Average	Vertical
7	7206.00	41.53	6.34	47.87	74.00	-26.13	Peak	Vertical
8	7206.00	29.35	6.34	35.69	54.00	-18.31	Average	Vertical

LE _ Middle Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4880.00	41.80	4.00	45.80	74.00	-28.20	Peak	Horizontal
2	4880.00	30.76	4.00	34.76	54.00	-19.24	Average	Horizontal
3	7320.00	40.90	6.98	47.88	74.00	-26.12	Peak	Horizontal
4	7320.00	28.96	6.98	35.94	54.00	-18.06	Average	Horizontal
5	4880.00	42.29	5.00	47.29	74.00	-26.71	Peak	Vertical
6	4880.00	30.88	5.00	35.88	54.00	-18.12	Average	Vertical
7	7320.00	40.89	6.48	47.37	74.00	-26.63	Peak	Vertical
8	7320.00	29.46	6.48	35.94	54.00	-18.06	Average	Vertical

LE _ Highest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4960.00	41.40	4.06	45.46	74.00	-28.54	Peak	Horizontal
2	4960.00	30.27	4.06	34.33	54.00	-19.67	Average	Horizontal
3	7440.00	41.07	7.19	48.26	74.00	-25.74	Peak	Horizontal
4	7440.00	29.11	7.19	36.30	54.00	-17.70	Average	Horizontal
5	4960.00	42.32	5.06	47.38	74.00	-26.62	Peak	Vertical
6	4960.00	30.86	5.06	35.92	54.00	-18.08	Average	Vertical
7	7440.00	40.78	6.63	47.41	74.00	-26.59	Peak	Vertical
8	7440.00	29.17	6.63	35.80	54.00	-18.20	Average	Vertical

Type B - Radiated Emission Test Data (Above 1GHz):**LE _ Lowest Channel:**

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	39.02	3.93	42.95	74.00	-31.05	Peak	Horizontal
2	4804.00	27.96	3.93	31.89	54.00	-22.11	Average	Horizontal
3	7206.00	38.51	6.76	45.27	74.00	-28.73	Peak	Horizontal
4	7206.00	26.86	6.76	33.62	54.00	-20.38	Average	Horizontal
5	4804.00	38.23	4.93	43.16	74.00	-30.84	Peak	Vertical
6	4804.00	28.13	4.93	33.06	54.00	-20.94	Average	Vertical
7	7206.00	37.50	6.34	43.84	74.00	-30.16	Peak	Vertical
8	7206.00	27.11	6.34	33.45	54.00	-20.55	Average	Vertical

Type C - Radiated Emission Test Data (Above 1GHz):**LE _ Lowest Channel:**

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	42.10	3.93	46.03	74.00	-27.97	Peak	Horizontal
2	4804.00	28.79	3.93	32.72	54.00	-21.28	Average	Horizontal
3	7206.00	40.47	6.76	47.23	74.00	-26.77	Peak	Horizontal
4	7206.00	28.47	6.76	35.23	54.00	-18.77	Average	Horizontal
5	4804.00	41.33	4.93	46.26	74.00	-27.74	Peak	Vertical
6	4804.00	30.20	4.93	35.13	54.00	-18.87	Average	Vertical
7	7206.00	40.30	6.34	46.64	74.00	-27.36	Peak	Vertical
8	7206.00	28.58	6.34	34.92	54.00	-19.08	Average	Vertical

Type D - Radiated Emission Test Data (Above 1GHz):**LE _ Lowest Channel:**

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	40.81	3.93	44.74	74.00	-29.26	Peak	Horizontal
2	4804.00	30.15	3.93	34.08	54.00	-19.92	Average	Horizontal
3	7206.00	41.49	6.76	48.25	74.00	-25.75	Peak	Horizontal
4	7206.00	30.33	6.76	37.09	54.00	-16.91	Average	Horizontal
5	4804.00	42.08	4.93	47.01	74.00	-26.99	Peak	Vertical
6	4804.00	30.33	4.93	35.26	54.00	-18.74	Average	Vertical
7	7206.00	41.35	6.34	47.69	74.00	-26.31	Peak	Vertical
8	7206.00	28.58	6.34	34.92	54.00	-19.08	Average	Vertical

Type E - Radiated Emission Test Data (Above 1GHz):
LE _ Lowest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	41.47	3.93	45.40	74.00	-28.60	Peak	Horizontal
2	4804.00	29.35	3.93	33.28	54.00	-20.72	Average	Horizontal
3	7206.00	41.67	6.76	48.43	74.00	-25.57	Peak	Horizontal
4	7206.00	30.51	6.76	37.27	54.00	-16.73	Average	Horizontal
5	4804.00	40.40	4.93	45.33	74.00	-28.67	Peak	Vertical
6	4804.00	30.72	4.93	35.65	54.00	-18.35	Average	Vertical
7	7206.00	40.52	6.34	46.86	74.00	-27.14	Peak	Vertical
8	7206.00	28.84	6.34	35.18	54.00	-18.82	Average	Vertical

Type F - Radiated Emission Test Data (Above 1GHz):
LE _ Lowest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	40.67	3.93	44.60	74.00	-29.40	Peak	Horizontal
2	4804.00	29.64	3.93	33.57	54.00	-20.43	Average	Horizontal
3	7206.00	41.47	6.76	48.23	74.00	-25.77	Peak	Horizontal
4	7206.00	29.45	6.76	36.21	54.00	-17.79	Average	Horizontal
5	4804.00	42.75	4.93	47.68	74.00	-26.32	Peak	Vertical
6	4804.00	31.13	4.93	36.06	54.00	-17.94	Average	Vertical
7	7206.00	41.45	6.34	47.79	74.00	-26.21	Peak	Vertical
8	7206.00	29.15	6.34	35.49	54.00	-18.51	Average	Vertical

Type G - Radiated Emission Test Data (Above 1GHz):
LE _ Lowest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	41.49	3.93	45.42	74.00	-28.58	Peak	Horizontal
2	4804.00	29.74	3.93	33.67	54.00	-20.33	Average	Horizontal
3	7206.00	41.27	6.76	48.03	74.00	-25.97	Peak	Horizontal
4	7206.00	29.40	6.76	36.16	54.00	-17.84	Average	Horizontal
5	4804.00	42.85	4.93	47.78	74.00	-26.22	Peak	Vertical
6	4804.00	31.13	4.93	36.06	54.00	-17.94	Average	Vertical
7	7206.00	41.78	6.34	48.12	74.00	-25.88	Peak	Vertical
8	7206.00	29.40	6.34	35.74	54.00	-18.26	Average	Vertical

Type A - Radiated Emission Test Data (Above 1GHz):
2LE _ Lowest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	39.26	3.93	43.19	74.00	-30.81	Peak	Horizontal
2	4804.00	28.47	3.93	32.40	54.00	-21.60	Average	Horizontal
3	7206.00	39.83	6.76	46.59	74.00	-27.41	Peak	Horizontal
4	7206.00	27.67	6.76	34.43	54.00	-19.57	Average	Horizontal
5	4804.00	40.47	4.93	45.40	74.00	-28.60	Peak	Vertical
6	4804.00	29.59	4.93	34.52	54.00	-19.48	Average	Vertical
7	7206.00	40.33	6.34	46.67	74.00	-27.33	Peak	Vertical
8	7206.00	28.89	6.34	35.23	54.00	-18.77	Average	Vertical

2LE _ Middle Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4880.00	40.30	4.00	44.30	74.00	-29.70	Peak	Horizontal
2	4880.00	28.68	4.00	32.68	54.00	-21.32	Average	Horizontal
3	7320.00	38.57	6.98	45.55	74.00	-28.45	Peak	Horizontal
4	7320.00	27.32	6.98	34.30	54.00	-19.70	Average	Horizontal
5	4880.00	39.31	5.00	44.31	74.00	-29.69	Peak	Vertical
6	4880.00	28.68	5.00	33.68	54.00	-20.32	Average	Vertical
7	7320.00	39.60	6.48	46.08	74.00	-27.92	Peak	Vertical
8	7320.00	28.26	6.48	34.74	54.00	-19.26	Average	Vertical

2LE _ Highest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4960.00	38.86	4.06	42.92	74.00	-31.08	Peak	Horizontal
2	4960.00	27.15	4.06	31.21	54.00	-22.79	Average	Horizontal
3	7440.00	39.49	7.19	46.68	74.00	-27.32	Peak	Horizontal
4	7440.00	28.43	7.19	35.62	54.00	-18.38	Average	Horizontal
5	4960.00	38.99	5.06	44.05	74.00	-29.95	Peak	Vertical
6	4960.00	28.17	5.06	33.23	54.00	-20.77	Average	Vertical
7	7440.00	39.27	6.63	45.90	74.00	-28.10	Peak	Vertical
8	7440.00	27.82	6.63	34.45	54.00	-19.55	Average	Vertical

Type B - Radiated Emission Test Data (Above 1GHz):
2LE _ Lowest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	38.76	3.93	42.69	74.00	-31.31	Peak	Horizontal
2	4804.00	27.49	3.93	31.42	54.00	-22.58	Average	Horizontal
3	7206.00	39.85	6.76	46.61	74.00	-27.39	Peak	Horizontal
4	7206.00	27.43	6.76	34.19	54.00	-19.81	Average	Horizontal
5	4804.00	40.03	4.93	44.96	74.00	-29.04	Peak	Vertical
6	4804.00	28.58	4.93	33.51	54.00	-20.49	Average	Vertical
7	7206.00	38.71	6.34	45.05	74.00	-28.95	Peak	Vertical
8	7206.00	27.36	6.34	33.70	54.00	-20.30	Average	Vertical

Type C - Radiated Emission Test Data (Above 1GHz):
2LE _ Lowest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	39.06	3.93	42.99	74.00	-31.01	Peak	Horizontal
2	4804.00	29.20	3.93	33.13	54.00	-20.87	Average	Horizontal
3	7206.00	41.30	6.76	48.06	74.00	-25.94	Peak	Horizontal
4	7206.00	28.63	6.76	35.39	54.00	-18.61	Average	Horizontal
5	4804.00	41.92	4.93	46.85	74.00	-27.15	Peak	Vertical
6	4804.00	30.33	4.93	35.26	54.00	-18.74	Average	Vertical
7	7206.00	40.67	6.34	47.01	74.00	-26.99	Peak	Vertical
8	7206.00	28.58	6.34	34.92	54.00	-19.08	Average	Vertical

Type D - Radiated Emission Test Data (Above 1GHz):
2LE _ Lowest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	40.74	3.93	44.67	74.00	-29.33	Peak	Horizontal
2	4804.00	29.30	3.93	33.23	54.00	-20.77	Average	Horizontal
3	7206.00	41.11	6.76	47.87	74.00	-26.13	Peak	Horizontal
4	7206.00	29.26	6.76	36.02	54.00	-17.98	Average	Horizontal
5	4804.00	41.81	4.93	46.74	74.00	-27.26	Peak	Vertical
6	4804.00	30.76	4.93	35.69	54.00	-18.31	Average	Vertical
7	7206.00	40.40	6.34	46.74	74.00	-27.26	Peak	Vertical
8	7206.00	28.63	6.34	34.97	54.00	-19.03	Average	Vertical

Type E - Radiated Emission Test Data (Above 1GHz):
2LE _ Lowest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	41.34	3.93	45.27	74.00	-28.73	Peak	Horizontal
2	4804.00	29.40	3.93	33.33	54.00	-20.67	Average	Horizontal
3	7206.00	41.55	6.76	48.31	74.00	-25.69	Peak	Horizontal
4	7206.00	29.45	6.76	36.21	54.00	-17.79	Average	Horizontal
5	4804.00	43.26	4.93	48.19	74.00	-25.81	Peak	Vertical
6	4804.00	30.89	4.93	35.82	54.00	-18.18	Average	Vertical
7	7206.00	41.17	6.34	47.51	74.00	-26.49	Peak	Vertical
8	7206.00	28.79	6.34	35.13	54.00	-18.87	Average	Vertical

Type F - Radiated Emission Test Data (Above 1GHz):
2LE _ Lowest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	40.98	3.93	44.91	74.00	-29.09	Peak	Horizontal
2	4804.00	30.15	3.93	34.08	54.00	-19.92	Average	Horizontal
3	7206.00	41.60	6.76	48.36	74.00	-25.64	Peak	Horizontal
4	7206.00	30.55	6.76	37.31	54.00	-16.69	Average	Horizontal
5	4804.00	42.30	4.93	47.23	74.00	-26.77	Peak	Vertical
6	4804.00	30.93	4.93	35.86	54.00	-18.14	Average	Vertical
7	7206.00	41.92	6.34	48.26	74.00	-25.74	Peak	Vertical
8	7206.00	29.25	6.34	35.59	54.00	-18.41	Average	Vertical

Type G - Radiated Emission Test Data (Above 1GHz):
2LE _ Lowest Channel:

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	41.80	3.93	45.73	74.00	-28.27	Peak	Horizontal
2	4804.00	29.74	3.93	33.67	54.00	-20.33	Average	Horizontal
3	7206.00	41.63	6.76	48.39	74.00	-25.61	Peak	Horizontal
4	7206.00	29.50	6.76	36.26	54.00	-17.74	Average	Horizontal
5	4804.00	43.49	4.93	48.42	74.00	-25.58	Peak	Vertical
6	4804.00	31.17	4.93	36.10	54.00	-17.90	Average	Vertical
7	7206.00	41.68	6.34	48.02	74.00	-25.98	Peak	Vertical
8	7206.00	29.40	6.34	35.74	54.00	-18.26	Average	Vertical

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit

5.8 BAND EDGE MEASUREMENTS (RADIATED)

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209
RSS-247 Issue 2, Section 5.5

Test Method: ANSI C63.10-2013 Clause 11.13

Limits:

Radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Frequency	Limit (dB μ V/m @3m)	Remark
30 MHz-88 MHz	40.0	Quasi-peak Value
88 MHz-216 MHz	43.5	Quasi-peak Value
216 MHz-960 MHz	46.0	Quasi-peak Value
960 MHz-1 GHz	54.0	Quasi-peak Value
Above 1 GHz	54.0	Average Value
	74.0	Peak Value

Test Setup: Refer to section 4.4.1 for details.

Test Procedures:



Radiated band edge measurements at 2390 MHz and 2483.5 MHz were made with the unit transmitting in the low end of the channel range and the high end closest to the restricted bands respectively. The emissions were made on the 966 Semi-Chamber. Use (resolution bandwidth (RBW) = 1 MHz, video bandwidth (VBW) = 3 MHz for peak levels and RBW = 1 MHz and VBW = 10 Hz or 1/T for average levels).



1. Use radiated spurious emission test procedure described in clause 5.10. The transmitter output (antenna port) was connected to the test receiver.
2. Set the PK and AV limit line.
3. Record the fundamental emission and emissions out of the band-edge.
4. Determine band-edge compliance as required.



Equipment Used: Refer to section 3 for details.



Test Result: Pass

The measurement data as follows:









5.9 CONDUCTED EMISSION

Test Requirement: 47 CFR Part 15C Section 15.207
RSS-Gen Issue 5, Section 8.8

Test Method: ANSI C63.10-2013 Section 6.2

Limits:

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.4.2 for details.

Test Procedures:

Test frequency range :150KHz-30MHz

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The measurement data as follows:

Quasi Peak and Average:


Mode: LE Link

Live Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.170	20.76	10.02	30.78	54.96	-24.18	Average
2	0.170	34.76	10.02	44.78	64.96	-20.18	QP
3	0.502	15.80	9.99	25.79	46.00	-20.21	Average
4	0.502	26.80	9.99	36.79	56.00	-19.21	QP
5	17.421	27.97	12.68	40.65	50.00	-9.35	Average
6	17.421	39.97	12.68	52.65	60.00	-7.35	QP

Neutral Line




No.	Frequency (MHz)	Reading (dBUV)	Correction factor (dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Detector
1	0.162	35.26	10.00	45.26	65.36	-20.10	Average
2	0.170	20.82	10.00	30.82	54.96	-24.14	QP
3	0.510	14.29	9.97	24.26	46.00	-21.74	Average
4	0.510	26.29	9.97	36.26	56.00	-19.74	QP
5	17.173	27.20	12.60	39.80	50.00	-10.20	Average
6	17.173	40.20	12.60	52.80	60.00	-7.20	QP

The measurement data as follows:

Quasi Peak and Average:


Mode: 2LE Link

Live Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.174	16.73	10.02	26.75	54.77	-28.02	Average
2	0.174	34.73	10.02	44.75	64.77	-20.02	QP
3	0.526	14.90	9.99	24.89	46.00	-21.11	Average
4	0.526	25.90	9.99	35.89	56.00	-20.11	QP
5	17.617	27.08	12.66	39.74	50.00	-10.26	Average
6	17.617	40.08	12.66	52.74	60.00	-7.26	QP

Neutral Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.158	35.58	10.00	45.58	65.57	-19.99	Average
2	0.170	18.39	10.00	28.39	54.96	-26.57	QP
3	0.526	15.83	9.97	25.80	46.00	-20.20	Average
4	0.534	26.30	9.98	36.28	56.00	-19.72	QP
5	17.273	27.45	12.58	40.03	50.00	-9.97	Average
6	17.273	39.45	12.58	52.03	60.00	-7.97	QP

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
