

Band Edge(Hopping) NVNT 3-DH1 2402MHz Ant1 Hopping Emission



Date: 16.JUN.2022 06:36:10


Band Edge NVNT 3-DH1 2402MHz Ant1 No-Hopping Emission



Date: 16.JUN.2022 05:38:23


Report No.: A2008280-C01-R02

Band Edge(Hopping) NVNT 3-DH1 2480MHz Ant1 Hopping Emission



Date: 16.JUN.2022 06:52:51


Band Edge NVNT 3-DH1 2480MHz Ant1 No-Hopping Emission



Date: 16.JUN.2022 05:44:14

10. Power Line Conducted Emissions

10.1.Block Diagram of Test Setup



10.2.Limit

	Maximum RF Line Voltage			
Frequency	Quasi-Peak Level	Average Level		
	dB(μV)	dB(μV)		
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46* 46		
500kHz ~ 5MHz	56			
5MHz ~ 30MHz	60	50		

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.


10.3.Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 10.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10KHz.
- (5) The frequency range from 150 KHz to 30MHz is checked.


10.4.Test Result

PASS. (See below detailed test data)

Note: If peak Result comply with AV limit, QP and AV Result is deemed to comply with AV limit



Neutral



No	. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margir	n	
		MHz	dBu∀	dB	dBu∀	dBu∀	dB	Detector	Comment
		0.4290	34.38	9.95	44.33	57.27	-12.94	QP	
)	0.4290	32.80	9.95	42.75	47.27	-4.52	AVG	
- 3	3	1.2839	35.32	9.89	45.21	56.00	-10.79	QP	
4	*	1.2839	32.88	9.89	42.77	46.00	-3.23	AVG	
į	,	2.1389	34.11	9.88	43.99	56.00	-12.01	QP	
()	2.1389	30.99	9.88	40.87	46.00	-5.13	AVG	
	7	3.8490	34.98	9.96	44.94	56.00	-11.06	QP	
- 8	3	3.8490	30.99	9.96	40.95	46.00	-5.05	AVG	
9)	6.8400	39.05	10.11	49.16	60.00	-10.84	QP	
10)	6.8400	34.85	10.11	44.96	50.00	-5.04	AVG	
11		9.4050	41.23	10.19	51.42	60.00	-8.58	QP	
12)	9.4050	35.73	10.19	45.92	50.00	-4.08	AVG	

x:Over limit !:over margin *:Maximum data

 $Note: Measurement = Reading \ Level + Correc \ Factor. \quad Factor = (LISN \ or \ ISN \ or \ PLC \ or \ Current \ Probe) Factor + Cable$

Remark: All modes have been tested, and only worst data of Charging was listed in this report.

11. Antenna Requirements

11.1.Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


11.2.Result

The EUT antenna is internal antenna. It complies with the standard requirement.

12. Test Setup Photo

12.1.Photos of Radiated emission





12.2.Photos of Power Line Conducted Emission Test



13. Photos Of EUT
















































































-----THE END OF REPORT-----