

FCC SAR Compliance Test Report

For

UTOPIA TOWELS INC

8 Elaine PI, Plainview, NY 11803, United States.

Model: UH0342, UH0342 UHTABLET 10.1 INCH

Test Engineer: Lily Zhao

Report Number: FCC17080777A-SAR

Report Date: 2017-07-10

FCC ID: 2AMXPGC289900

Check By: Stars Liang

Stars Liang

Approved By: Michal Ling

Michal Ling

Prepared By:
QTC Certification & Testing Co., Ltd.
2nd Floor, B1 Building, Fengyeyuan Industrial Plant,
Liuxian 2st. Road, Xin'an Street, Bao'an
District, Shenzhen, 518000
Tel: +86-755-26996144 EXT:8164
Fax: +86-755-26996253

Table of contents

1	General information	4
1.1	Notes	4
1.2	Application details	4
1.3	Statement of Compliance	5
1.4	EUT Information	6
2	Testing laboratory	7
3	Test Environment	7
4	Applicant and Manufacturer	7
5	Test standard/s:	8
5.1	RF exposure limits	9
5.2	SAR Definition	9
6	SAR Measurement System	10
6.1	The Measurement System	10
6.2	Robot	11
6.3	Probe	11
6.4	Measurement procedure	12
6.5	Description of interpolation/extrapolation scheme	12
6.6	Phantom	13
6.7	Device Holder	14
6.8	Video Positioning System	15
6.9	Tissue simulating liquids: dielectric properties	16
6.10	Tissue simulating liquids: parameters	17
7	System Check	18
7.1	System check procedure	18
7.2	System check results	19
8	SAR Test Configuration	20
8.1	GSM Test Configurations	20
8.2	Wi-Fi Test Configuration	20
9	Detailed Test Results	21
9.1	Conducted Power measurements	21
9.1.1	Conducted Power of GSM850	21

9.1.2	Conducted Power of GSM1900.....	22
9.1.3	Conducted Power of UMTS Band II.....	23
9.1.4	Conducted Power of UMTS Band V	24
9.1.5	Conducted Power of Wi-Fi 2.4G	25
9.1.6	Conducted Power of BT	25
9.1.7	Tune-up power tolerance	26
9.2	SAR test results	27
9.2.1	Results overview of GSM850.....	29
9.2.2	Results overview of GSM1900.....	30
9.2.3	Results overview of UMTS Band II.....	31
9.2.4	Results overview of UMTS Band V	32
9.2.5	Results overview of Wi-Fi 2.4G	33
10	Multiple Transmitter Information.....	34
10.1.1	Stand-alone SAR test exclusion.....	35
10.1.2	Simultaneous Transmission Possibilities.....	36
10.1.3	SAR Summation Scenario	37
11	Measurement uncertainty evaluation	40
11.1	Measurement uncertainty evaluation for SAR test	40
11.2	Measurement uncertainty evaluation for system check.....	41
12	Test equipment and ancillaries used for tests	42
Annex A:	System performance verification.....	43
Annex B:	Measurement results.....	43
Annex C:	Calibration reports	43
Annex D:	Photo documentation.....	44

Modified History

REV.	Modification Description	Issued Date	Remark
REV.1.0	Initial Test Report Relesse	2017-07-10	Stars Liang

1 General information

1.1 Notes

The test results of this test report relate exclusively to the test item specified in this test report. Shenzhen Timeway Testing Laboratories QTC Certification & Testing Co., Ltd. generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report is not to be reproduced or published in full without the prior written permission.

1.2 Application details

Date of receipt of test item: 2017-06-21
Start of test: 2017-06-21
End of test: 2017-07-10

1.3 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for UH0342 is as below:

Band	Position	MAX Reported SAR_{1g} (W/kg)
GSM850	Head	0.592
	Body & Hotspot 0mm	0.645
GSM1900	Head	0.588
	Body & Hotspot 0mm	0.590
UMTS Band II	Head	0.438
	Body & Hotspot 0mm	0.658
UMTS Band V	Head	0.454
	Body & Hotspot 0mm	0.545
Wi-Fi 2450	Head	0.481
	Body & Hotspot 0mm	0.713
The highest simultaneous SAR is 1.312W/kg per KDB690783 D01		

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits of 1.6 W/Kg as averaged over any 1g tissue according to the FCC rule §2.1093, the ANSI/IEEE C95.1:2005, the NCRP Report Number 86 for uncontrolled environment, according to the Industry Canada Radio Standards Specification RSS-102 for General Population/Uncontrolled exposure, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013.

1.4 EUT Information

Device Information:			
Product Type:	Android 3G tablet PC		
Model:	UH0342, UH0342 UHTABLET 10.1 INCH		
Brand Name:	Utopia Home		
Device Type:	Portable device		
Exposure Category:	uncontrolled environment / general population		
Production Unit or Identical Prototype:	Production Unit		
Hardware version:	AL-MT8321-101-L3-V1.2		
Software version :	M107TG-A2_20170904_174905		
Antenna Type :	Internal Antenna		
Device Operating Configurations:			
Supporting Mode(s) :	GSM850/1900, UMTS Band II /V,Wi-Fi , BT		
Modulation:	GMSK, OFDM/CCK, GFSK/ π /4-DQPSK/ 8-DPSK		
Device Class :	Class B, No DTM Mode		
Operating Frequency Range(s)	Band	TX(MHz)	RX(MHz)
	GSM850	824~849	869~894
	GSM1900	1850~1910	1930~1990
	UMTS Band II	1850~1910	1930~1990
	UMTS Band V	824~840	869~894
	Wi-Fi	2412~2462	2412~2462
	BT	2402~2480	2402~2480
GPRS class level:	GPRS class 12		
Test Channels (low-mid-high):	128-190-251(GSM850)		
	512-661-810(GSM1900)		
	9262-9400-9538(UMTS Band II)		
	4132-4182-4233(UMTS Band V)		
	1-6-11 (Wi-Fi)		
	0-39-78(BT)		
Power Source:	3.7 VDC/5000mAh Rechargeable Battery		

Model Difference:

UH0342 and UH0342 UHTABLET 10.1 INCH without any difference only the appearance not same.

2 Testing laboratory

Test Site	QTC Certification & Testing Co., Ltd.
Test Location	2nd Floor,B1 Building,Fengyeyuan Industrial Plant,, Liuxian 2st. Road, Xin'an Street, Bao'an District,,Shenzhen,518000
Telephone	+86-755-26996144 EXT:8164
Fax	+86-755-26996253

3 Test Environment

	Required	Actual
Ambient temperature:	18 – 25 °C	22 ± 2 °C
Tissue Simulating liquid:	22 ± 2 °C	22 ± 2 °C
Relative humidity content:	30 – 70 %	30 – 70 %

4 Applicant and Manufacturer

Applicant/Client Name:	UTOPIA TOWELS INC
Applicant Address:	8 Elaine Pl, Plainview, NY 11803,United States.
Manufacturer Name:	SHENZHEN LUCKYSTAR TECHNOLOGY CO.,LTD.
Manufacturer Address:	Block 1,Yu Jing Tai Industrial Park, Huarong Rd., Shuiwei Village, Dalang Office, Longhua District, Shenzhen, Guangdong, China

5 Test standard/s:

ANSI Std C95.1-2005	Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.
IEEE Std 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
RSS-102	Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands (Issue 5 March 2015))
KDB447498 D01	General RF Exposure Guidance v06
KDB648474 D04	Head set SAR v01r03
KDB941225 D06	Hot Spot SAR V02r01
KDB941225 D01	3G SAR Measurement Procedures
KDB248227 D01	SAR meas for 802.11 a/b/g v01r02
KDB865664 D01	SAR Measurement 100 MHz to 6 GHz v01r04
KDB865664 D02	RF Exposure Reporting v01r02
KDB616217 D04	SAR for laptop and tablets v01r02

5.1 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain/Body/Arms/Legs)	1.60 mW/g	8.00 mW/g
Spatial Average SAR** (Whole Body)	0.08 mW/g	0.40 mW/g
Spatial Peak SAR*** (Heads/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

The limit applied in this test report is shown in bold letters

Notes:

* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

** The Spatial Average value of the SAR averaged over the whole body.

*** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation.

5.2 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dW) absorbed by(dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ).

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dV} \right)$$

SAR is expressed in units of watts per kilogram (W/kg). SAR can be related to the electric field at a point by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

where:

σ = conductivity of the tissue (S/m)

ρ = mass density of the tissue (kg/m³)

E = rms electric field strength (V/m)


6 SAR Measurement System

6.1 The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Device holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.

6.2 Robot

The COMOSAR system uses the high precision robots KR 6 R900 sixx type out of the newer series from Satimo SA (France). For the 6-axis controller COMOSAR system, the KUKA robot controller version from Satimo is used. The KR 6 R900 sixx robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- 6-axis controller

6.3 Probe

For the measurements the Specific Dosimetric E-Field Probe SSE 5 with following specifications is used

- Dynamic range: 0.01-100 W/kg
- Tip Diameter : 5 mm
- Distance between probe tip and sensor center: 2.5mm
- Distance between sensor center and the inner phantom surface: 4 mm
(repeatability better than +/- 1mm)
- Probe linearity: <0.25 dB
- Axial Isotropy: <0.25 dB
- Spherical Isotropy: <0.50 dB
- Calibration range: 300 to 3G for head & body simulating liquid.

Angle between probe axis (evaluation axis) and surface normal line: less than 30°

6.4 Measurement procedure

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface.
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors can not directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

6.5 Description of interpolation/extrapolation scheme

- The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.
- An extrapolation is used to determine these highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.
- The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR average over 10 grams and 1 gram requires a very fine resolution in the three-dimensional scanned data array.

6.6 Phantom


For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



System Material	Permittivity	Loss Tangent
Delrin	3.7	0.005

6.7 Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.



Device holder

System Material	Permittivity	Loss Tangent
Delrin	3.7	0.005

6.8 Video Positioning System

- The video positioning system is used in OpenSAR to check the probe. Which is composed of a camera, LED, mirror and mechanical parts. The camera is piloted by the main computer with firewire link.
- During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip.
- The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.



6.9 Tissue simulating liquids: dielectric properties

The following materials are used for producing the tissue-equivalent materials.

(Liquids used for tests are marked with):

Ingredients(% of weight)	Frequency (MHz)				
frequency band	<input type="checkbox"/> 450	<input checked="" type="checkbox"/> 835	<input type="checkbox"/> 1800	<input checked="" type="checkbox"/> 1900	<input checked="" type="checkbox"/> 2450
Tissue Type	Head	Head	Head	Head	Head
Water	38.56	41.45	52.64	55.242	62.7
Salt (NaCl)	3.95	1.45	0.36	0.306	0.5
Sugar	56.32	56.0	0.0	0.0	0.0
HEC	0.98	1.0	0.0	0.0	0.0
Bactericide	0.19	0.1	0.0	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	36.8
DGBE	0.0	0.0	47.0	44.542	0.0
Ingredients(% of weight)	Frequency (MHz)				
frequency band	<input type="checkbox"/> 450	<input checked="" type="checkbox"/> 835	<input type="checkbox"/> 1800	<input checked="" type="checkbox"/> 1900	<input checked="" type="checkbox"/> 2450
Tissue Type	Body	Body	Body	Body	Body
Water	51.16	52.4	69.91	69.91	73.2
Salt (NaCl)	1.49	1.40	0.13	0.13	0.04
Sugar	46.78	45.0	0.0	0.0	0.0
HEC	0.52	1.0	0.0	0.0	0.0
Bactericide	0.05	0.1	0.0	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0
DGBE	0.0	0.0	29.96	29.96	26.7

Salt: 99+% Pure Sodium Chloride

Sugar: 98+% Pure Sucrose

Water: De-ionized, 16MΩ+ resistivity

HEC: Hydroxyethyl Cellulose

DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100(ultra pure): Polyethylene glycol mono [4-(1,1,3,3-tetramethylbutyl)phenyl]ether

6.10 Tissue simulating liquids: parameters

Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		ϵ_r (+/-5%)	σ (S/m) (+/-5%)	ϵ_r	σ (S/m)		
835MHz Head	825	41.60 (39.52~43.68)	0.90 (0.86~0.95)	40.34	0.91	21.6°C	2017-6-21
	835	41.50 (39.43~43.58)	0.90 (0.86~0.95)	40.33	0.92		
	850	41.50 (39.43~43.58)	0.92 (0.87~0.97)	40.11	0.94		
835MHz Body	825	55.20 (52.44~57.96)	0.97 (0.92~1.02)	54.04	0.98	21.6°C	2017-6-21
	835	55.20 (52.44~57.96)	0.97 (0.92~1.02)	53.93	0.99		
	850	55.20 (52.44~57.96)	0.99 (0.94~1.04)	53.69	1.01		
1900MHz Head	1850	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.93	1.37	21.6°C	2017-6-28
	1880	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.91	1.40		
	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.98	1.41		
	1910	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.97	1.42		
1900MHz Body	1850	53.30 (50.64~55.97)	1.52 (1.44~1.60)	53.23	1.49	21.6°C	2017-6-28
	1880	53.30 (50.64~55.97)	1.52 (1.44~1.60)	53.36	1.53		
	1900	53.30 (50.64~55.97)	1.52 (1.44~1.60)	53.37	1.56		
	1910	53.30 (50.64~55.97)	1.52 (1.44~1.60)	53.37	1.57		
2450MHz Head	2410	39.30 (37.34~41.26)	1.76 (1.67~1.85)	39.22	1.78	21.6°C	2017-7-10
	2435	39.20 (37.24~41.16)	1.79 (1.70~1.88)	39.25	1.77		
	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	39.24	1.76		
	2460	39.20 (37.24~41.16)	1.81 (1.72~1.90)	39.20	1.76		
2450MHz Body	2410	52.80 (50.16~55.44)	1.91 (1.81~2.00)	52.72	1.92	21.6°C	2017-7-10
	2435	52.70 (50.07~55.34)	1.94 (1.84~2.04)	52.75	1.92		
	2450	52.70 (50.07~55.34)	1.95 (1.85~2.05)	52.74	1.91		
	2460	52.70 (50.07~55.34)	1.96 (1.86~2.06)	52.70	1.91		


ϵ_r = Relative permittivity, σ = Conductivity

7 System Check

7.1 System check procedure

The System check is performed by using a System check dipole which is positioned parallel to the planar part of the SAM phantom at the reference point. The distance of the dipole to the SAM phantom is determined by a spacer. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100 mW. To adjust this power a power meter is used. The power sensor is connected to the cable before the System check to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the validation to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

System check results have to be equal or near the values determined during dipole calibration (target SAR in table above) with the relevant liquids and test system.



7.2 System check results

The system Check is performed for verifying the accuracy of the complete measurement system and performance of the software. The following table shows System check results for all frequency bands and tissue liquids used during the tests (plot(s) see annex A).

System Check	Target SAR (1W) (+/-10%)		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (mW/g)	10-g (mW/g)	1-g (mW/g)	10-g (mW/g)		
D835V2 Head	9.56 (8.60~10.52)	6.19 (5.57~6.81)	9.70	6.15	21.6°C	2017-6-21
D1900V2 Head	39.46 (35.51~43.41)	20.42 (18.38~22.46)	39.98	21.07	21.6°C	2017-6-28
D2450V2 Head	53.08 (47.77~58.39)	23.79 (21.41~26.17)	53.93	24.53	21.6°C	2017-7-10
D835V2 Body	9.86 (8.87~10.85)	6.38 (5.74~7.02)	10.15	6.45	21.6°C	2017-6-21
D1900V2 Body	40.06 (36.05~44.07)	20.76 (18.68~22.84)	39.33	20.94	21.6°C	2017-6-28
D2450V2 Body	54.76 (49.28~60.24)	24.47 (22.02~26.92)	56.33	23.33	21.6°C	2017-7-10
Note: All SAR values are normalized to 1W forward power.						

8 SAR Test Test Configuration

8.1 GSM Test Configurations

SAR tests for GSM850 and GSM1900, a communication link is set up with a base station by air link. Using CMU200 the power lever is set to “5” and “0” in SAR of GSM850 and GSM1900. The tests in the band of GSM 850 and GSM 1900 are performed in the mode of GPRS/EGPRS function. Since the GPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslot is 5.

8.2 Wi-Fi Test Configuration

For the 802.11b/g SAR tests, a communication link is set up with the test mode software for Wi-Fi mode test. The Absolute Radio Frequency Channel Number(ARFCN) is allocated to 1, 6 and 11 respectively in the case of 2450 MHz. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. Each channel should be tested at the lowest data rate. 802.11b/g operating modes are tested independently according to the service requirements in each frequency band. 802.11b/g modes are tested on channel 1, 6, 11; however, if output power reduction is necessary for channels 1 and/or 11 to meet restricted band requirements the highest output channel closest to each of these channels must be tested instead.

SAR is not required for 802.11g/n channels when the maximum average output power is less than 0.25dB higher than that measured on the corresponding 802.11b channels.

Mode	Band	GHz	Channel	“Default Test Channels”	
				802.11b	802.11g
802.11b/g	2.4 GHz	2412	1#	✓	△
		2437	6	✓	△
		2462	11#	✓	△

Notes:

✓ = “default test channels”

△ = possible 802.11g channels with maximum average output 1/4 dB the “default test channels”

= when output power is reduced for channel 1 and /or 11 to meet restricted band requirements the highest output channels closest to each of these channels should be tested.

802.11 Test Channels per FCC Requirements

9 Detailed Test Results

9.1 Conducted Power measurements

The output power was measured using an integrated RF connector and attached RF cable.

9.1.1 Conducted Power of GSM850

GSM850(SIM1)		Burst-Averaged output Power (dBm)			Division Factors	Source Based time Average Power(dBm)		
		128CH	190CH	251CH		128CH	190CH	251CH
GSM(CS)		33.26	33.30	33.25	-9.03	24.23	24.27	24.22
GPRS (GMSK)	1 Tx Slot	32.68	32.69	32.66	-9.03	23.65	23.66	23.63
	2 Tx Slots	31.55	31.59	31.52	-6.02	25.53	25.57	25.50
	3 Tx Slots	30.68	30.70	30.65	-4.26	26.42	26.44	26.39
	4 Tx Slots	29.75	29.80	29.78	-3.01	26.74	26.79	26.77
EGPRS (8-PSK)	1 Tx Slot	28.02	28.06	28.05	-9.03	18.99	19.03	19.02
	2 Tx Slots	27.10	27.20	27.12	-6.02	21.08	21.18	21.10
	3 Tx Slots	26.13	26.25	26.18	-4.26	21.87	21.99	21.92
	4 Tx Slots	25.32	25.42	25.35	-3.01	22.31	22.41	22.34

GSM850(SIM2)		Burst-Averaged output Power (dBm)			Division Factors	Source Based time Average Power(dBm)		
		128CH	190CH	251CH		128CH	190CH	251CH
GSM(CS)		33.20	33.27	33.23	-9.03	24.17	24.24	24.20
GPRS (GMSK)	1 Tx Slot	32.62	33.67	33.63	-9.03	23.59	24.64	24.60
	2 Tx Slots	31.53	31.55	33.50	-6.02	25.51	25.53	27.48
	3 Tx Slots	30.65	30.69	30.62	-4.26	26.39	26.43	26.36
	4 Tx Slots	29.72	29.76	29.75	-3.01	26.71	26.75	26.74
EGPRS (8-PSK)	1 Tx Slot	28.00	28.03	28.01	-9.03	18.97	19.00	18.98
	2 Tx Slots	27.05	27.12	27.10	-6.02	21.03	21.10	21.08
	3 Tx Slots	26.10	26.19	26.16	-4.26	21.84	21.93	21.90
	4 Tx Slots	25.29	25.35	25.32	-3.01	22.28	22.34	22.31

Note: 1) The conducted power of GSM850 is measured with RMS detector.

2) Source Based time Average Power was calculated from the measured burst-averaged output power by converting the slot powers into linear units and calculating the energy over 8 timeslots.

3) The bolded GPRS 4Tx slots mode was selected for SAR testing according the highest Source Based time Average Power table.

4) channel /Frequency: 128/824.2; 190/836.6; 251/848.8

5) For Dual SIM Operation, when the power of deviation of SIM1 and SIM2 not more than 0.5dB, which tested SIM1 mode first, and then tested SIM2 mode at the worst position from SIM1 mode .

9.1.2 Conducted Power of GSM1900

GSM1900(SIM1)		Burst-Averaged output Power (dBm)			Division Factors	Source Based time Average Power(dBm)		
		512CH	661CH	810CH		512CH	661CH	810CH
GSM(CS)		30.24	30.16	30.21	-9.03	21.21	21.13	21.18
GPRS (GMSK)	1 Tx Slot	29.49	29.40	29.45	-9.03	20.46	20.37	20.42
	2 Tx Slots	28.56	28.52	28.53	-6.02	22.54	22.50	22.51
	3 Tx Slots	27.62	27.60	27.62	-4.26	23.36	23.34	23.36
	4 Tx Slots	26.78	26.75	26.76	-3.01	23.77	23.74	23.75
EGPRS (8-PSK)	1 Tx Slot	27.25	27.20	27.23	-9.03	18.22	18.17	18.20
	2 Tx Slots	26.36	26.32	26.35	-6.02	20.34	20.30	20.33
	3 Tx Slots	25.48	25.43	25.46	-4.26	21.22	21.17	21.20
	4 Tx Slots	24.63	24.59	24.60	-3.01	21.62	21.58	21.59

GSM1900(SIM2)		Burst-Averaged output Power (dBm)			Division Factors	Source Based time Average Power(dBm)		
		512CH	661CH	810CH		512CH	661CH	810CH
GSM(CS)		30.20	30.15	30.16	-9.03	21.17	21.12	21.13
GPRS (GMSK)	1 Tx Slot	29.45	29.38	29.40	-9.03	20.42	20.35	20.37
	2 Tx Slots	28.53	28.50	28.52	-6.02	22.51	22.48	22.50
	3 Tx Slots	27.60	27.56	27.59	-4.26	23.34	23.30	23.33
	4 Tx Slots	26.75	26.70	26.73	-3.01	23.74	23.69	23.72
EGPRS (8-PSK)	1 Tx Slot	27.20	27.15	27.16	-9.03	18.17	18.12	18.13
	2 Tx Slots	26.32	26.30	26.29	-6.02	20.30	20.28	20.27
	3 Tx Slots	25.45	25.40	25.43	-4.26	21.19	21.14	21.17
	4 Tx Slots	24.60	24.56	24.58	-3.01	21.59	21.55	21.57

Note: 1) The conducted power of GSM1900 is measured with RMS detector.

2) Source Based time Average Power was calculated from the measured burst-averaged output power by converting the slot powers into linear units and calculating the energy over 8 timeslots.

3) The bolded GPRS 4Tx slots mode was selected for SAR testing according the highest Source Based time Average Power table.

4) channel /Frequency: 512/1850.2; 661/1880; 810/1909.8

5) For Dual SIM Operation, when the power of deviation of SIM1 and SIM2 not more than 0.5dB, which tested SIM1 mode first, and then tested SIM2 mode at the worst position from SIM1 mode .

9.1.3 Conducted Power of UMTS Band II

UMTS Band II		Conducted Power (dBm)		
		9262CH	9400CH	9538CH
WCDMA	12.2kbps RMC	22.26	22.20	22.23
HSDPA	Subtest 1	22.21	22.15	21.16
	Subtest 2	21.95	21.99	22.18
	Subtest 3	21.55	21.88	22.07
	Subtest 4	22.01	21.56	21.99
HSUPA	Subtest 1	22.12	22.10	22.09
	Subtest 2	21.50	21.25	21.88
	Subtest 3	21.84	21.38	21.69
	Subtest 4	21.95	21.62	21.87
	Subtest 5	21.98	21.92	22.03

Note: 1) channel /Frequency: 9262/1852.4, 9400/1880, 9538/1907.6

9.1.4 Conducted Power of UMTS Band V

UMTS Band V		Conducted Power (dBm)		
		4132CH	4182CH	4233CH
WCDMA	12.2kbps RMC	21.83	21.88	21.82
HSDPA	Subtest 1	21.59	21.79	21.65
	Subtest 2	21.82	21.80	21.58
	Subtest 3	21.53	21.48	21.32
	Subtest 4	21.82	21.55	21.53
HSUPA	Subtest 1	21.83	21.82	21.65
	Subtest 2	21.51	21.86	21.55
	Subtest 3	21.64	21.67	21.82
	Subtest 4	21.62	21.72	21.53
	Subtest 5	21.61	21.80	21.60

Note: 1) channel /Frequency: 4132/826.4, 4182/836.4, 4233/846.6

9.1.5 Conducted Power of Wi-Fi 2.4G

Mode	802.11b		
Channel / Frequency (MHz)	1(2412)	6(2437)	11(2462)
Average Power(dBm)	15.22	15.41	15.31
Mode	802.11g		
Channel / Frequency (MHz)	1(2412)	6(2437)	11(2462)
Average Power(dBm)	14.41	14.22	14.36
Mode	802.11n(HT20)		
Channel / Frequency (MHz)	1(2412)	6(2437)	11(2462)
Average Power(dBm)	14.51	14.25	14.26
Mode	802.11n(HT40)		
Channel / Frequency (MHz)	1(2412)	6(2437)	11(2462)
Average Power(dBm)	13.19	13.21	13.21

Note:

<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

(1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is ≤ 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.

(2) For Wi-Fi 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is ≤ 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.

9.1.6 Conducted Power of BT

The maximum output power of BT is:

Mode	1Mbps		
Channel / Frequency (MHz)	0(2402)	39(2441)	78(2480)
Average Power(dBm)	3.41	2.05	2.37
Mode	2Mbps		
Channel / Frequency (MHz)	0(2402)	39(2441)	78(2480)
Average Power(dBm)	2.31	1.26	0.89
Mode	3Mbps		
Channel / Frequency (MHz)	0(2402)	39(2441)	78(2480)
Average Power(dBm)	2.33	1.72	1.00

9.1.7 Tune-up power tolerance

Band	Tune-up power tolerance(dBm)		
GSM850	GSM/GPRS (GMSK)	GSM	Max output power =33.0dBm±0.5dBm
		1TXslots	Max output power =32.5dBm±0.5dBm
		2TXslots	Max output power =31.5dBm±0.5dBm
		3TXslots	Max output power =30.5dBm±0.5dBm
		4TXslots	Max output power =29.5dBm±0.5dBm
GSM850	EGPRS (8-PSK)	1TXslots	Max output power =28.0dBm±0.5dBm
		2TXslots	Max output power =27.0dBm±0.5dBm
		3TXslots	Max output power =26.0dBm±0.5dBm
		4TXslots	Max output power =25.0dBm±0.5dBm
GSM1900	GSM/GPRS (GMSK)	GSM	Max output power =30.0dBm±0.5dBm
		1TXslots	Max output power =29.0dBm±0.5dBm
		2TXslots	Max output power =28.5dBm±0.5dBm
		3TXslots	Max output power =27.5dBm±0.5dBm
		4TXslots	Max output power =26.5dBm±0.5dBm
GSM1900	EGPRS (8-PSK)	1TXslots	Max output power =27.0dBm±0.5dBm
		2TXslots	Max output power =26.0dBm±0.5dBm
		3TXslots	Max output power =25.0dBm±0.5dBm
		4TXslots	Max output power =24.5dBm±0.5dBm
WCDMA 2	Max output power =21.5dbm±1.0dbm		
WCDMA 5	Max output power =21.0dbm±1.0dbm		
2.4G Wi-Fi	802.11b	Max output power =14.5dBm±1.0dbm	
	802.11g	Max output power =13.5dBm±1.0dbm	
	802.11n (HT20)	Max output power =13.5dBm±1.0dbm	
	802.11n (HT40)	Max output power =12.5dBm±1.0dbm	
BT	1Mbps	Max output power =2.5dBm±1.0dbm	
	2Mbps	Max output power =1.5dBm±1.0dbm	
	3Mbps	Max output power =1.5dBm±1.0dbm	

9.2 SAR test results

Notes:

- 1) Per KDB447498 D01v05 r02, the SAR test shall be performed at the high, middle and low frequency channels of each operating mode. If the scaled SAR measured at mid-band channel for each test configuration is at least 3.0 dB lower than the SAR limit (< 0.8 W/kg), testing at the high and low channels is optional.
- 2) Per KDB447498 D01v05r02, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is: $\leq 0.8 \text{ W/kg}$ or 2.0 W/kg , for 1-g or 10-g respectively, when the transmission band is $\leq 100 \text{ MHz}$. When the maximum output power variation across the required test channels is $> \frac{1}{2} \text{ dB}$, instead of the middle channel, the highest output power channel must be used.
- 3) Per KDB447498 D01v05r02, All measurement SAR result is scaled-up to account for tune-up tolerance is compliant.
- 4) Per KDB648474 D04v01r02, body-worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn with headset SAR.
- 5) Per KDB248227 D01v01r02, the procedures required to establish specific device operating configurations for testing the SAR of 802.11 a/b/g transmitters.
- 6) Per KDB865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8 \text{ W/Kg}$; if the deviation among the repeated measurement is $\leq 20\%$, and the measured SAR $< 1.45 \text{ W/Kg}$, only one repeated measurement is required.
- 7) Per KDB865664 D02v01r01, SAR plot is only required for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination; Plots are also required when the measured SAR is $> 1.5 \text{ W/kg}$, or $> 7.0 \text{ W/kg}$ for occupational exposure. The published RF exposure KDB procedures may require additional plots; for example, to support SAR to peak location separation ratio test exclusion and/or volume scan post-processing (Refer to appendix B for details).
- 8) Per KDB941225 D06v01r01, the DUT Dimension is bigger than 9 cm x 5 cm, so 10mm is chosen as the test separation distance for Hotspot mode. When the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested.
- 9) KDB 941225 D01, 3G SAR Measurement Procedures, The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary

modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

9.2.1 Results overview of GSM850

Test Position of Head	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (%)	Conducted Power (dBm)	Tune-up Limit (dBm)	Scaled SAR _{1-g} (W/kg)	Scaling Factor
			1-g	10-g					
Left Head Touched	190/836.6	GPRS 4TS	0.565	0.360	2.960	29.800	30.000	0.592	1.047
Left Head Tilted 15°	190/836.6	GPRS 4TS	0.554	0.350	-2.600	29.800	30.000	0.580	1.047
Right Head Touched	190/836.6	GPRS 4TS	0.359	0.247	-1.740	29.800	30.000	0.376	1.047
Right Head Tilted 15°	190/836.6	GPRS 4TS	0.549	0.364	3.420	29.800	30.000	0.575	1.047
Test Position of Body with 0mm	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (%)	Conducted Power (dBm)	Tune-up Limit (dBm)	Scaled SAR _{1-g} (W/kg)	Scaling Factor
			1-g	10-g					
SAR Results for Hotspot Exposure Condition									
Front side	190/836.6	GPRS 4TS	0.556	0.368	-3.370	29.800	30.000	0.582	1.047
Rear side	190/836.6	GPRS 4TS	0.616	0.444	-2.340	29.800	30.000	0.645	1.047
Top side	190/836.6	GPRS 4TS	0.327	0.221	-1.850	29.800	30.000	0.342	1.047
Right side	190/836.6	GPRS 4TS	0.130	0.088	-3.810	29.800	30.000	0.136	1.047

9.2.2 Results overview of GSM1900

Test Position of Head	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (%)	Conducted Power (dBm)	Tune-up Limit (dBm)	Scaled SAR _{1-g} (W/kg)	Scalig Factor
			1-g	10-g					
Left Head Touched	512/1850.2	GPRS 4TS	0.493	0.312	0.710	26.780	27.000	0.519	1.052
Left Head Tilted 15°	512/1850.2	GPRS 4TS	0.423	0.243	-1.170	26.780	27.000	0.445	1.052
Right Head Touched	512/1850.2	GPRS 4TS	0.517	0.319	1.940	26.780	27.000	0.544	1.052
Right Head Tilted 15°	512/1850.2	GPRS 4TS	0.559	0.314	0.900	26.780	27.000	0.588	1.052
Test Position of Body with 0mm	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (%)	Conducted Power (dBm)	Tune-up Limit (dBm)	Scaled SAR _{1-g} (W/kg)	Scalig Factor
			1-g	10-g					
SAR Results for Hotspot Exposure Condition									
Front side	512/1850.2	GPRS 4TS	0.364	0.172	-3.970	26.780	27.000	0.383	1.052
Rear side	512/1850.2	GPRS 4TS	0.475	0.270	-1.670	26.780	27.000	0.500	1.052
Top side	512/1850.2	GPRS 4TS	0.395	0.222	1.410	26.780	27.000	0.416	1.052
Right side	512/1850.2	GPRS 4TS	0.561	0.317	4.230	26.780	27.000	0.590	1.052

9.2.3 Results overview of UMTS Band II

Test Position of Head	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (%)	Conducted Power (dBm)	Tune-up Limit (dBm)	Scaled SAR _{1-g} (W/kg)	Scalig Factor
			1-g	10-g					
Left Head Touched	9262/1852.4	RMC	0.390	0.234	-1.940	22.260	22.500	0.412	1.057
Left Head Tilted 15°	9262/1852.4	RMC	0.303	0.171	-3.030	22.260	22.500	0.320	1.057
Right Head Touched	9262/1852.4	RMC	0.414	0.256	-1.170	22.260	22.500	0.438	1.057
Right Head Tilted 15°	9262/1852.4	RMC	0.345	0.191	-1.180	22.260	22.500	0.365	1.057
Test Position of Body with 0mm	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (%)	Conducted Power (dBm)	Tune-up Limit (dBm)	Scaled SAR _{1-g} (W/kg)	Scalig Factor
			1-g	10-g					

SAR Results for Hotspot Exposure Condition

Front side	9262/1852.4	RMC	0.388	0.288	-1.490	22.260	22.500	0.410	1.057
Rear side	9262/1852.4	RMC	0.623	0.351	-1.570	22.260	22.500	0.658	1.057
Top side	9262/1852.4	RMC	0.598	0.325	-1.470	22.260	22.500	0.632	1.057
Right side	9262/1852.4	RMC	0.348	0.210	-1.260	22.260	22.500	0.368	1.057

9.2.4 Results overview of UMTS Band V

Test Position of Head	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (%)	Conducted Power (dBm)	Tune-up Limit (dBm)	Scaled SAR _{1-g} (W/kg)	Scalig Factor
			1-g	10-g					
Left Head Touched	4182/836.4	RMC	0.405	0.287	-0.410	21.880	22.000	0.416	1.028
Left Head Tilted 15°	4182/836.4	RMC	0.442	0.298	3.870	21.880	22.000	0.454	1.028
Right Head Touched	4182/836.4	RMC	0.328	0.224	1.860	21.880	22.000	0.337	1.028
Right Head Tilted 15°	4182/836.4	RMC	0.355	0.240	0.190	21.880	22.000	0.365	1.028
Test Position of Body with 0mm	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (%)	Conducted Power (dBm)	Tune-up Limit (dBm)	Scaled SAR _{1-g} (W/kg)	Scalig Factor
			1-g	10-g					
SAR Results for Hotspot Exposure Condition									
Front side	4182/836.4	RMC	0.460	0.296	-0.100	21.880	22.000	0.473	1.028
Rear side	4182/836.4	RMC	0.530	0.349	3.830	21.880	22.000	0.545	1.028
Top side	4182/836.4	RMC	0.343	0.215	-1.980	21.880	22.000	0.353	1.028
Right side	4182/836.4	RMC	0.027	0.020	2.590	21.880	22.000	0.028	1.028


9.2.5 Results overview of Wi-Fi 2.4G

Test Position of Head	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (%)	Conducted Power (dBm)	Tune-up Limit (dBm)	Scaled SAR _{1-g} (W/kg)	Scaling Factor
			1-g	10-g					
Left Head Touched	6/2437	802.11b	0.464	0.245	-0.880	15.410	15.500	0.474	1.021
Left Head Tilted 15°	6/2437	802.11b	0.471	0.217	-0.620	15.410	15.500	0.481	1.021
Right Head Touched	6/2437	802.11b	0.450	0.198	0.160	15.410	15.500	0.459	1.021
Right Head Tilted 15°	6/2437	802.11b	0.215	0.102	-0.420	15.410	15.500	0.220	1.021
Test Position of Body with 0mm	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (%)	Conducted Power (dBm)	Tune-up Limit (dBm)	Scaled SAR _{1-g} (W/kg)	Scaling Factor
			1-g	10-g					

SAR Results for Hotspot Exposure Condition									
Front side	6/2437	802.11b	0.698	0.298	2.770	15.410	15.500	0.713	1.021
Rear side	6/2437	802.11b	0.318	0.148	-2.940	15.410	15.500	0.325	1.021
Top side	6/2437	802.11b	0.666	0.276	4.280	15.410	15.500	0.680	1.021
Left side	6/2437	802.11b	0.026	0.013	-1.320	15.410	15.500	0.027	1.021

10 Multiple Transmitter Information

The SAR measurement positions of each side are as below:



Mode	Front Side	Rear Side	Left Side	Right Side	Top Side	Bottom Side
2G/3G Antenna	Yes	Yes	No	Yes	Yes	No
Wi-Fi	Yes	Yes	Yes	No	Yes	No

- 1) Per KDB941225 D06v01r01, the DUT Dimension is bigger than 9 cm x 5 cm, so 10mm is chosen as the test separation distance for Hotspot mode. When the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested.

10.1.1 Stand-alone SAR test exclusion

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Head position

Mode	Pmax(dBm)	Pmax(mW)	Distance(mm)	f(GHz)	Calculation Result	exclusion Threshold	SAR test exclusion
BT	3.5	2.24	5.00	2.45	0.70	3.00	Yes

Body-Worn position

Mode	Pmax(dBm)	Pmax(mW)	Distance(mm)	f(GHz)	Calculation Result	exclusion Threshold	SAR test exclusion
BT	3.5	2.24	5.00	2.45	0.70	3.00	Yes

When the standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to determine simultaneous transmission SAR test exclusion

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(\text{GHz})/x}$] W/kg for test separation distances ≤ 50 mm, where $x = 7.5$ for 1-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	Pmax(dBm)	Pmax(mW)	Distance(mm)	f(GHz)	X	Estimated SAR(W/Kg)
BT	Head	3.5	2.24	5.00	2.45	7.50	0.093
BT	Body	3.5	2.24	5.00	2.45	7.50	0.093

10.1.2 Simultaneous Transmission Possibilities

The Simultaneous Transmission Possibilities are as below:

Simultaneous Transmission Possibilities				
Simultaneous Tx Combination	Configuration	Head	Body	Hotspot
1	GSM/GPRS/UMTS +Wi-Fi	YES	YES	YES
2	GSM/GPRS/UMTS +BT	YES	YES	NO

Note: The device does not support simultaneous BT and Wi-Fi ,because the BT and Wi-Fi share the same antenna and can't transmit simultaneously.

10.1.3 SAR Summation Scenario

Test Position		Scaled SAR _{Max}		Σ _{1-g} SAR	SPLSP
		GSM850	Wi-Fi		
Head	Left Head Touched	0.592	0.474	1.066	NA
	Left Head Tilted 15°	0.580	0.481	1.061	NA
	Right Head Touched	0.376	0.459	0.835	NA
	Right Head Tilted 15°	0.575	0.220	0.795	NA
Body Hotspot	Front side	0.582	0.713	1.295	NA
	Rear side	0.645	0.325	0.970	NA
	Top side	0.342	0.680	1.022	NA
	Right side	0.136	0.000	0.136	NA

Note: Simultaneous Tx Combination of GSM850 and Wi-Fi

Test Position		Scaled SAR _{Max}		Σ _{1-g} SAR	SPLSP
		GSM1900	Wi-Fi		
Head	Left Head Touched	0.519	0.474	0.993	NA
	Left Head Tilted 15°	0.445	0.481	0.926	NA
	Right Head Touched	0.544	0.459	1.003	NA
	Right Head Tilted 15°	0.588	0.220	0.808	NA
Body Hotspot	Front side	0.383	0.713	1.096	NA
	Rear side	0.500	0.325	0.825	NA
	Top side	0.416	0.680	1.096	NA
	Right side	0.590	0.000	0.590	NA

Note: Simultaneous Tx Combination of GSM1900 and Wi-Fi

Test Position		Scaled SAR _{Max}		Σ _{1-g} SAR	SPLSP
		UMTS Band II	Wi-Fi		
Head	Left Head Touched	0.412	0.474	0.886	NA
	Left Head Tilted 15°	0.320	0.481	0.801	NA
	Right Head Touched	0.438	0.459	0.897	NA
	Right Head Tilted 15°	0.365	0.220	0.585	NA
Body Hotspot	Front side	0.410	0.713	1.123	NA
	Rear side	0.658	0.325	0.983	NA
	Top side	0.632	0.680	1.312	NA
	Right side	0.368	0.000	0.368	NA

Note: Simultaneous Tx Combination of UMTS Band II and Wi-Fi

Test Position		Scaled SAR _{Max}		Σ _{1-g} SAR	SPLSP
		UMTS Band V	Wi-Fi		
Head	Left Head Touched	0.416	0.474	0.890	NA
	Left Head Tilted 15°	0.454	0.481	0.935	NA
	Right Head Touched	0.337	0.459	0.796	NA
	Right Head Tilted 15°	0.365	0.220	0.585	NA
Body Hotspot	Front side	0.473	0.713	1.186	NA
	Rear side	0.545	0.325	0.870	NA
	Top side	0.353	0.680	1.033	NA
	Right side	0.028	0.000	0.028	NA

Note: Simultaneous Tx Combination of UMTS Band V and Wi-Fi

MAX.ΣSAR_{1g} = 1.312W/kg < 1.6 W/kg, so the Simultaneous SAR is not required for Wi-Fi and GSM&UMTS antenna.

Test Position		Scaled SAR _{Max}		Σ _{1-g} SAR	SPLSP
		GSM850	BT		
Head	Left Head Touched	0.592	0.093	0.685	NA
	Left Head Tilted 15°	0.580	0.093	0.673	NA
	Right Head Touched	0.376	0.093	0.469	NA
	Right Head Tilted 15°	0.575	0.093	0.668	NA
Body Hotspot	Front side	0.582	0.093	0.675	NA
	Rear side	0.645	0.093	0.738	NA
	Top side	0.342	0.093	0.435	NA
	Right side	0.136	0.093	0.229	NA

Note: Simultaneous Tx Combination of GSM850 and BT

Test Position		Scaled SAR _{Max}		Σ _{1-g} SAR	SPLSP
		GSM1900	BT		
Head	Left Head Touched	0.519	0.093	0.612	NA
	Left Head Tilted 15°	0.445	0.093	0.538	NA
	Right Head Touched	0.544	0.093	0.637	NA
	Right Head Tilted 15°	0.588	0.093	0.681	NA
Body Hotspot	Front side	0.383	0.093	0.476	NA
	Rear side	0.500	0.093	0.593	NA
	Top side	0.416	0.093	0.509	NA
	Right side	0.590	0.093	0.683	NA

Note: Simultaneous Tx Combination of GSM1900 and BT

Test Position		Scaled SAR _{Max}		Σ _{1-g} SAR	SPLSP
		UMTS Band II	BT		
Head	Left Head Touched	0.412	0.093	0.505	NA
	Left Head Tilted 15°	0.320	0.093	0.413	NA
	Right Head Touched	0.438	0.093	0.531	NA
	Right Head Tilted 15°	0.365	0.093	0.458	NA
Body Hotspot	Front side	0.410	0.093	0.503	NA
	Rear side	0.658	0.093	0.751	NA
	Top side	0.632	0.093	0.725	NA
	Right side	0.368	0.093	0.461	NA

Note: Simultaneous Tx Combination of UMTS Band II and BT

Test Position		Scaled SAR _{Max}		Σ _{1-g} SAR	SPLSP
		UMTS Band V	BT		
Head	Left Head Touched	0.416	0.093	0.509	NA
	Left Head Tilted 15°	0.454	0.093	0.547	NA
	Right Head Touched	0.337	0.093	0.430	NA
	Right Head Tilted 15°	0.365	0.093	0.458	NA
Body Hotspot	Front side	0.473	0.093	0.566	NA
	Rear side	0.545	0.093	0.638	NA
	Top side	0.353	0.093	0.446	NA
	Right side	0.028	0.093	0.121	NA

Note: Simultaneous Tx Combination of UMTS Band V and BT

MAX.ΣSAR_{1g} = 0.751W/kg < 1.6 W/kg, so the Simultaneous SAR is not required for BT and GSM&UMTS antenna.

11 Measurement uncertainty evaluation

11.1 Measurement uncertainty evaluation for SAR test

The following table includes the uncertainty table of the IEEE 1528. The values are determined by Satimo. The breakdown of the individual uncertainties is as follows:

Measurement Uncertainty evaluation for SAR test								
Uncertainty Component	Tol. (±%)	Prob. Dist.	Div.	C_i (1g)	C_i (10g)	$1g U_i$ (±%)	$10g U_i$ (±%)	V_i
measurement system								
Probe Calibration	5.8	N	1	1	1	5.8	5.8	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	$(1-C_p)^{1/2}$	$(1-C_p)^{1/2}$	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	$\sqrt{C_p}$	$\sqrt{C_p}$	2.41	2.41	∞
Boundary Effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
system Detection Limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3	N	1	1	1	3.00	3.00	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF Ambient Conditions-Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF Ambient Conditions-Reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe Positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and Integration Algorithms for Max.SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related								
Test Sample Positioning	2.6	N	1	1	1	2.60	2.60	11
Device Holder Uncertainty	3	N	1	1	1	3.00	3.00	7
Output Power Variation-SAR drift measurement	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (shape and thickness tolerances)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation (in permittivity and conductivity)	2	N	1	1	0.84	2.00	1.68	∞
Liquid conductivity (meas.)	2.5	N	1	0.64	0.43	1.60	1.08	5
Liquid conductivity (target.)	5	R	$\sqrt{3}$	0.64	0.43	1.85	1.24	5
Liquid Permittivity (meas.)	2.5	N	1	0.60	0.49	1.50	1.23	∞
Liquid Permittivity (target.)	5	R	$\sqrt{3}$	0.60	0.49	1.73	1.42	∞
Combined Standard Uncertainly		Rss				10.63	10.54	
Expanded Uncertainty{95% CONFIDENCE INTERVAL}		k				21.26	21.08	

11.2 Measurement uncertainty evaluation for system check

The following table includes the uncertainty table of the IEEE 1528. The values are determined by Satimo. The breakdown of the individual uncertainties is as follows:

Uncertainty For System Performance Check								
Uncertainty Component	Tol. (±%)	Prob. Dist.	Div.	C_i 1g	C_i 10g	$1g$ $U_i(\pm\%)$	$10g$ $U_i(\pm\%)$	V_i
measurement system								
Probe Calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	$(1-C_p)^{1/2}$	$(1-C_p)^{1/2}$	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	$\sqrt{C_p}$	$\sqrt{C_p}$	2.41	2.41	∞
Boundary Effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
system detection Limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0	N	1	1	1	0.00	0.00	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions – Reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioned Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of experimental source from numerical source	4	N	1	1	1	4.00	4.00	∞
Input power and SAR drift measurement	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Dipole axis to liquid Distance	2	R	$\sqrt{3}$	1	1	1.16	1.16	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (shape and thickness tolerances)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation (in permittivity and conductivity)	2	N	1	1	0.84	2.00	1.68	∞
Liquid conductivity (meas.)	2.5	N	1	0.64	0.43	1.60	1.08	5
Liquid conductivity (target.)	5	R	$\sqrt{3}$	0.64	0.43	1.85	1.24	5
Liquid Permittivity (meas.)	2.5	N	1	0.60	0.49	1.50	1.23	∞
Liquid Permittivity (target.)	5	R	$\sqrt{3}$	0.60	0.49	1.73	1.41	∞
Combined Standard Uncertainty		Rss				10.28	9.98	
Expanded Uncertainty (95% Confidence interval)		k				20.57	19.95	

12 Test equipment and ancillaries used for tests

To simplify the identification of the test equipment and/or ancillaries which were used, the reporting of the relevant test cases only refer to the test item number as specified in the table below.

	Manufacturer	Device Type	Type(Model)	Serial number	calibration	
					Last Cal.	Due Date
<input checked="" type="checkbox"/>	SATIMO	COMOSAR DOSIMETRIC E FIELD PROBE	SSE5	SN 09/13 EP170	2016-07-25	2017-07-24
<input checked="" type="checkbox"/>	SATIMO	COMOSAR 835 MHz REFERENCE DIPOLE	SID835	SN 14/13 DIP0G835-235	2016-07-25	2017-07-24
<input type="checkbox"/>	SATIMO	COMOSAR 900 MHz REFERENCE DIPOLE	SID900	SN 14/13 DIP0G900-231	2016-07-25	2017-07-24
<input type="checkbox"/>	SATIMO	COMOSAR 1800 MHz REFERENCE DIPOLE	SID1800	SN 14/13 DIP1G800-232	2016-07-25	2017-07-24
<input checked="" type="checkbox"/>	SATIMO	COMOSAR 1900 MHz REFERENCE DIPOLE	SID1900	SN 14/13 DIP1G900-236	2016-07-25	2017-07-24
<input type="checkbox"/>	SATIMO	COMOSAR 2000 MHz REFERENCE DIPOLE	SID2000	SN 14/13 DIP2G000-237	2016-07-25	2017-07-24
<input checked="" type="checkbox"/>	SATIMO	COMOSAR 2450 MHz REFERENCE DIPOLE	SID2450	SN 14/13 DIP2G450-238	2016-07-25	2017-07-24
<input type="checkbox"/>	SATIMO	COMOSAR 2600 MHz REFERENCE DIPOLE	SID2600	SN 28/14 DIP2G600-327	2016-07-25	2017-07-24
<input checked="" type="checkbox"/>	SATIMO	Software	OPENSAR	N/A	N/A	N/A
<input checked="" type="checkbox"/>	SATIMO	Phantom	COMOSAR IEEE SAM PHANTOM	SN 14/13 SAM99	N/A	N/A
<input checked="" type="checkbox"/>	R & S	Universal Radio Communication Tester	CMU 200	117528	2016-08-19	2017-08-18
<input checked="" type="checkbox"/>	HP	Network Analyser	8753D	3410A08889	2016-08-19	2017-08-18
<input checked="" type="checkbox"/>	HP	Signal Generator	E4421B	GB39340770	2016-08-19	2017-08-18
<input checked="" type="checkbox"/>	Keithley	Multimeter	Keithley 2000	4014539	2016-08-19	2017-08-18
<input checked="" type="checkbox"/>	SATIMO	Amplifier	Power Amplifier	MODU-023-A-0004	2015-10-13	2016-10-12
<input checked="" type="checkbox"/>	Agilent	Power Meter	E4418B	GB43312909	2015-10-13	2016-10-12
<input checked="" type="checkbox"/>	Agilent	Power Meter Sensor	E4412A	MY41500046	2015-10-13	2016-10-12
<input checked="" type="checkbox"/>	Agilent	Power Meter	E4417A	GB41291826	2015-10-13	2016-10-12
<input checked="" type="checkbox"/>	Agilent	Power Meter Sensor	8481H	MY41091215	2015-10-13	2016-10-12
<input checked="" type="checkbox"/>	SATIMO	DAE	SUPR72	SN 42/13	2016-07-25	2017-07-24

Annex A: System performance verification

(Please See the SAR Measurement Plots of annex A.)

Annex B: Measurement results

(Please See the SAR Measurement Plots of annex B.)

Annex C: Calibration reports

(Please See the Calibration reports of annex C.)

Annex D: Photo documentation

Photo 1: Measurement System OPENSAR	Photo 2: Front view
	
Photo 3: Rear View	Photo 4: Left Head Touched
	

Photo 5: Left Head Tilted 15°	Photo 6: Right Head Touched
	
Photo 7: Right Head Tilted 15°	Photo 8: Towards Phantom 0mm
	

Photo 9: Towards Ground 0mm	Photo 10: Top Side 0mm
 A photograph showing a black tablet mounted on a stand, facing a white wall. To the left of the tablet are wooden shelves holding several white plastic jugs. A yellow and black device is visible on the right.	 A photograph showing a black tablet mounted on a stand, facing a white wall. To the left of the tablet are wooden shelves holding several white plastic jugs. A blue and yellow box labeled 'OWI' is visible on the left. A white device is mounted on the wall to the right of the tablet.
Photo 11: Left Side 0mm	Photo 12: Right Side 0mm
 A photograph showing a black tablet mounted on a stand, facing a white wall. To the left of the tablet are wooden shelves holding several white plastic jugs. A yellow and black device is visible on the right.	 A photograph showing a black tablet mounted on a stand, facing a white wall. To the left of the tablet are wooden shelves holding several white plastic jugs. A white device is mounted on the wall to the right of the tablet.

Photo 13: 850MHz Liquid Depth \geq 15.0cm	Photo 14: 1800~1900MHz Liquid Depth \geq 15.0cm
Photo 15: 2450MHz Liquid Depth \geq 15.0cm	Photo 16: N/A
	N/A

End