

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	REMOTE CONTROL
Model Name	AG-01, AG-01W, AG-01P, AG-01D, AG-01DW, AG-01DP, AG-02, AG-02W, AG-02P, AG-02D, AG-02DW, AG-02DP, AG-03, AG-03W, AG-03P, AG-03S, AG-07, AG-07W, AG-07P, AG-07D, AG-07DW, AG-07DP, 6060, 6075
FCC ID	2AMZPAG01CDLWP

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

According to the follow transmitter output power (P_t) formula :

$$P_t = (E \times d)^2 / (30 \times g_t)$$

P_t =transmitter output power in watts

g_t =numeric gain of the transmitting antenna (unitless)

E=electric field strength in V/m

d=measurement distance in meters (m)

$$P_t = -6.29\text{dBm} = 0.235\text{mW}$$

The result for RF exposure evaluation

$$\text{SAR} = (0.235\text{mW} / 5\text{mm}) \cdot [\sqrt{2.44(\text{GHz})}] = 0.073 < 3.0 \text{ for 1-g SAR}$$

4. CONCLUSION

The SAR evaluation is not required.