specification

RA	Н	S	
NU		N	/
	-		

customer name	Ai small electricity
product type	coil
Top wisdom material number	TX-DZ43.505.3006-K6.5-L40 Open the double groove
Customer material number	

 $[\Box \lor \lor \lor$ New version release, \Box version revision] [This specification contains 7 pages of the directory] [RoH S CompliantParts]

authorized strength	examine and verify	ratify
The clock to establish	/	Ma Xiangping

Guangdong Dingzhi Electronic Technology Co., LTD

Factory Address: 1st Floor, No.1231, Yingbin Avenue, Longmen County, Huizhou City, Guangdong Province Tel.: 13147097490

This acceptance must be returned within 30 days of receipt by the customer, which shall be deemed to be executed according to the standard of this acceptance.

[Customer Approval] Date:

Admission status: \Box fully acknowledged \Box conditional recognition \Box refused to admit

ratify	examine and verify	recheck	check up
explain:		1	

specification

custo name	customer name				Ai small electricity	Customer material number		
Top w mater numbe		TX-DZ43.50 double groov	5.3006-K6.5-L40 open ve	Specificati on number	20240	8024001		
			Issue /	Revision Recon	rds			
editio n	av da	vailability ate	C	hange the conten	approval			
01	20	924/8/24		New specificatio	ons issued	Ma Xiangping		
				1				
	auth stre	orized ngth	examin	e and verify	ratify			

The clock to	1	Ma	
establish		Xiangping	

specification

customer name		Ai small electric	city	Customer material number					
Top wisdom material number	TX-DZ43 double gi	.505.3006-K6.5-L40 open roove	1	Specificati on number	20240802	24001	editio	n	01
 , outline dim 	ension						(unit	:mm)	
							A 5	.3±1.5	
							в 20	.5±1.5	
•	11			11 0		(C 38	.5±1.5	
1		I.I.					D 43	.5±1.5	
1			,				E 43	.0±1.5	
			/		1		F 40	.0±2.0	
			(0	1		Н 1	.7±0.3	
		//		0	A.		I 0.6		(magneti hickness
,		H		V	背双面胶		ne diameter: (neled wire).08 * (24	+* 2P)
	C C					(2) N	umber of wind	ling coil: [·]	10TS
-	D						/hether the sta ses: yes	arting and	d tail line
						(4) Co tape	oil wrap 4mm w	de high te	mperature
							he coil and the		
						(6) M glue	agnetic film b	ack 42 ro	und white
, electrical c	haracter:								
parameter		specifications	te	est condition	measurin g and test instrume nts				
L0	6.5±	:10%µH		0KHz/1V	■ TH181	6B			
Q	>30	min		DKHz/1V	■ TH181				
DCR •, temperatur	<95r	nt7	L.	⊉25℃	■ CH-502	2 BC			
service	-40°C~125°C								
service temperatur e	~+0 C~120 C	-							
, bill of mate	rial:								
order	name	material		supplier	remar				
number	of a part	specificat	tion		ks				
1	magnet ic sheet	43.5*5.3*0.6T Ope the double groove			PC40 fie zinc	erce			

2	copper line	0.08	3* (24*2P)	varnis hed wire			
3	High temperat ure tape		4MM	Environment al protection tape			
4	glue		42 Round white glue	Environment al rubber paper			
5	tin		107H	Thousand island environme l protect tin			
6	glue		Yellow gum	Environment al glue			
authorize	authorized strength		examine and verify			rati	fy
The clock to establish		/			Ma Xiangping		