

# **FCC Test Report**

Report No.: AGC09477240908FR02

FCC ID : 2AMZY-SHOWOFF

**APPLICATION PURPOSE**: Original Equipment

**PRODUCT DESIGNATION**: ShowOff Wireless earbuds with LCD display

**BRAND NAME** : Origaudio

**MODEL NAME** : 98440

**APPLICANT**: HandStandsPromo LLC

**DATE OF ISSUE** : Sep. 19, 2024

**STANDARD(S)** : FCC Part 15 Subpart C §15.247

**REPORT VERSION**: V1.0

Attestation of Global Conclusive (Shenzhen) Co., Ltd



Page 2 of 76


# **Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 19, 2024	Valid	Initial Release



## **Table of Contents**

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Test Frequency List	6
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Receiver Input Bandwidth	7
2.6 Equally Average Use of Frequencies And Behaviour	7
2.7 Pseudorandom Frequency Hopping Sequence	8
2.8 Special Accessories	g
2.9 Equipment Modifications	g
2.10 Antenna Requirement	g
3. Test Environment	10
3.1 Address of The Test Laboratory	10
3.2 Test Facility	10
3.3 Environmental Conditions	11
3.4 Measurement Uncertainty	11
3.5 List of Equipment Used	12
4.System Test Configuration	14
4.1 EUT Configuration	14
4.2 EUT Exercise	14
4.3 Configuration of Tested System	14
4.4 Equipment Used in Tested System	14
4.5 Summary of Test Results	15
5. Description of Test Modes	16
6. RF Output Power Measurement	17
6.1 Provisions Applicable	17
6.2 Measurement Procedure	17
6.3 Measurement Setup (Block Diagram of Configuration)	17
6.4 Measurement Result	18
7. 20dB Bandwidth and 99% Occupied Bandwidth Measurement	24
7.1 Provisions Applicable	24
7.2 Measurement Procedure	24
7.3 Measurement Setup (Block Diagram of Configuration)	24
7.4 Measurement Results	25
8. Conducted Band Edge and Out-of-Band Emissions	30
8.1 Provisions Applicable	30
8.2 Measurement Procedure	30
8.3 Measurement Setup (Block Diagram of Configuration)	30
8.4 Measurement Results	31





9. Radiated Spurious Emission	51
9.1 Measurement Limit	51
9.2 Measurement Procedure	51
9.3 Measurement Setup (Block Diagram of Configuration)	54
9.4 Measurement Result	55
10. Number of Hopping Frequency Measurement	64
10.1 Provisions Applicable	64
10.2 Measurement Procedure	64
10.3 Measurement Setup (Block Diagram of Configuration)	64
10.4 Measurement Result	64
11. Time of Occupancy (Dwell Time) Measurement	66
11.1 Provisions Applicable	66
11.2 Measurement Procedure	66
11.3 Measurement Setup (Block Diagram of Configuration)	66
11.4 Measurement Result	66
12. Frequency Separation Measurement	70
12.1 Provisions Applicable	70
12.2 Measurement Procedure	70
12.3 Measurement Setup (Block Diagram of Configuration)	70
12.4 Measurement Result	70
13. AC Power Line Conducted Emission Test	72
13.1 Measurement Limit	72
13.2 Measurement Setup (Block Diagram of Configuration)	72
13.3 Preliminary Procedure of Line Conducted Emission Test	73
13.4 Final Procedure of Line Conducted Emission Test	73
13.5 Measurement Results	73
Appendix I: Photographs of Test Setup	76
Appendix II: Photographs of Test EUT	76



Report No.: AGC09477240908FR02 Page 5 of 76

## 1. General Information

Applicant	HandStandsPromo LLC
Address	1770 South 5350 West Suite 100, Salt Lake City, Utah 84104, United States
Manufacturer	Amitec Industrial Limited
Address	1706, Rongchao Building A, Haixiu Road, Bao'An, Shenzhen City, Guangdong Province, China
Factory	Amitec Industrial Limited
Address	1706, Rongchao Building A, Haixiu Road, Bao'An, Shenzhen City, Guangdong Province, China
Product Designation	ShowOff Wireless earbuds with LCD display
Brand Name	Origaudio
Test Model	98440
Series Model(s)	N/A
Difference Description	N/A
Date of receipt of test item	Sep. 11, 2024
Date of Test	Sep. 11, 2024 - Sep. 19, 2024
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-BR_EDR-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Reviewed By

Cici Li
(Project Engineer)

Calvin Liu
(Reviewer)

Max Zhang
(Authorized Officer)

Sep. 19, 2024

Sep. 19, 2024



Page 6 of 76

## 2. Product Information

## 2.1 Product Technical Description

Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.4
Modulation Type	BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK
Number of channels	79 Channels
Channel Separation	1 MHz
Maximum Transmitter Power	2.125dBm
Hardware Version	V1.0
Software Version	V1.3
Antenna Designation	Chip Antenna
Antenna Gain	1.7dBi
Power Supply	DC 3.7V by battery or DC 5V by adapter

#### Note:

The EUT comprises left and right channel headsets, both are the same and have been tested, only the test data of right earphone recorded in this report.

## 2.2 Test Frequency List

Frequency Band	Channel Number	Frequency				
	0	2402 MHz				
	1	2403 MHz				
	:	:				
2400~2483.5MHz	39	2441MHz				
	:	:				
	77	2479 MHz				
	78	2480 MHz				
Note: f = 2402 + 1k MHz, k = 0,, 78; "f "is the operating frequency (MHz); "k" is the operating channel.						



Page 7 of 76

### 2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: 2AMZY-SHOWOFF, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

### 2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity Document Title			
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations		
2	FCC 47 CFR Part 15 Radio Frequency Devices			
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices		
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules		

#### 2.5 Receiver Input Bandwidth

The input bandwidth of the receiver is 1.3MHz, in every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally, the type of connection (e.g. single of multi slot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also, the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

#### 2.6 Equally Average Use of Frequencies and Behaviour.

The generation of the hopping sequence in connection mode depends essentially on two input values:

- 1. LAP/UAP of the master of the connection.
- 2. Internal master clock.

The LAP (lower address part) are the 24 LSB's of the 48 BD\_ADDRESS. The BD\_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24MSB's of the 48BD ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior action with other units only offset is used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30).

In most case it is implemented as 28 bits counter. For the deriving of the hopping sequence the entire. LAP (24 bits),4LSB's(4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended. The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer (and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always differ from the first one.




Report No.: AGC09477240908FR02 Page 8 of 76

# 2.7 Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 29 1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of The PRBS Sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.



Page 9 of 76

### 2.8 Special Accessories

Not available for this EUT intended for grant.

### 2.9 Equipment Modifications

Not available for this EUT intended for grant.

# 2.10 Antenna Requirement

# Standard Requirement

## 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

#### **EUT Antenna:**

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 1.7dBi.



Page 10 of 76

#### 3. Test Environment

## 3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

## CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

### A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

## FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

## IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 11 of 76

#### 3.3 Environmental Conditions

	Normal Conditions		
Temperature range (°C)	15 - 35		
Relative humidity range	20 % - 75 %		
Pressure range (kPa)	86 - 106		
Power supply	DC 3.7V by battery or DC 5V by adapter		

# 3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	U <sub>c</sub> = ±2 %
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$



3.5 List of Equipment Used

Report No.: AGC09477240908FR02 Page 12 of 76

• R	RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
$\boxtimes$	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024-05-24	2025-05-23	
$\boxtimes$	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2024-02-01	2025-01-31	
$\boxtimes$	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2024-02-01	2025-01-31	
$\boxtimes$	AGC-ER-A001	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-09-21	2025-09-20	
	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2024-07-24	2026-07-23	
$\boxtimes$	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A	
$\boxtimes$	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A	

• F	Radiated Spurious Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31	
	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23	
$\boxtimes$	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27	
$\boxtimes$	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04	
$\boxtimes$	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10	
$\boxtimes$	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30	
$\boxtimes$	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23	
$\boxtimes$	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23	
$\boxtimes$	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22	
$\boxtimes$	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	

• A	AC Power Line Conducted Emission							
I I sed I Equipment No. 1 Lest Equipment   Manufacturer   Model No. 1 Serial No. 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1							Next Cal. Date (YY-MM-DD)	
	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27	
	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2025-06-08	
	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27	



Report No.: AGC09477240908FR02 Page 13 of 76

Test Software						
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information	
$\boxtimes$	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71	
$\boxtimes$	AGC-EM-S003	RE Test System	FARA	EZ-EMC	VRA-03A	
$\boxtimes$	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6	
$\boxtimes$	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0	



Page 14 of 76

# 4. System Test Configuration

## 4.1 EUT Configuration


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

#### 4.2 EUT Exercise


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

## 4.3 Configuration of Tested System

Radiated Emission Configure:



Conducted Emission Configure:



#### 4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Control Box	N/A	USB-TTL		
2	Adapter	Huawei	HW-200440C00		

☐ Test Accessories Come From The Manufacturer


No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1		-		1	



Page 15 of 76

# 4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(1)	RF Output Power	Pass
3	§15.247 (a)(1)	20 dB Bandwidth	Pass
4	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	
5	§15.209	Radiated Spurious Emission	Pass
6	§15.247 (a)(1)(iii) Number of Hopping Frequen		Pass
7	§15.247 (a)(1)(iii) Time of Occupancy		Pass
8	§15.247 (a)(1)	Frequency Separation	Pass
9	§15.207 AC Power Line Conducted Emission		Pass






# 5. Description of Test Modes

Summary table of Test Cases				
Test Item	Data Rate / Modulation			
rest item	Bluetooth – BR_EDR (GFSK/π /4-DQPSK/8DPSK)			
Radiated & Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps (Battery powered or AC/DC adapter) Mode 2: Bluetooth Tx CH39_2441 MHz_1Mbps (Battery powered or AC/DC adapter) Mode 3: Bluetooth Tx CH78_2480 MHz_1Mbps (Battery powered or AC/DC adapter) Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps (Battery powered or AC/DC adapter) Mode 5: Bluetooth Tx CH39_2441 MHz_2Mbps (Battery powered or AC/DC adapter) Mode 6: Bluetooth Tx CH78_2480 MHz_2Mbps (Battery powered or AC/DC adapter) Mode 7: Bluetooth Tx CH00_2402 MHz_3Mbps (Battery powered or AC/DC adapter) Mode 8: Bluetooth Tx CH39_2441 MHz_3Mbps (Battery powered or AC/DC adapter) Mode 9: Bluetooth Tx CH78_2480 MHz_3Mbps (Battery powered or AC/DC adapter) Mode10: Bluetooth Tx Hopping-1Mbps (Battery powered or AC/DC adapter) Mode11: Bluetooth Tx Hopping-2Mbps (Battery powered or AC/DC adapter) Mode12: Bluetooth Tx Hopping-3Mbps (Battery powered or AC/DC adapter)			
AC Conducted Emission	Mode 1: Bluetooth Link + Battery + USB Cable (Charging from AC Adapter)			

#### Note:

- Only the result of the worst case was recorded in the report, if no other cases.
- 2. The battery is full-charged during the test.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.





Page 17 of 76

## 6. RF Output Power Measurement

## 6.1 Provisions Applicable

The maximum out power permissible output power is 1 Watt for all frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.

The maximum out power permissible output power is 0.125 watts for all other frequency hopping systems in the 2400-2483.5 MHz band.

#### 6.2 Measurement Procedure


- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 3. RBW > 20 dB bandwidth of the emission being measured.
- 4. VBW ≥RBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

For Average power test:

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required

#### 6.3 Measurement Setup (Block Diagram of Configuration)


For Average power test setup






Page 18 of 76

# 



## 6.4 Measurement Result

Test Data of Conducted Output Power					
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail	
	2402	-0.533	≤21	Pass	
GFSK	2441	-0.418	≤21	Pass	
	2480	-0.551	≤21	Pass	
	2402	0.978	≤21	Pass	
π /4-DQPSK	2441	1.431	≤21	Pass	
	2480	1.413	≤21	Pass	
	2402	1.694	≤21	Pass	
8DPSK	2441	2.098	≤21	Pass	
	2480	2.125	≤21	Pass	



0 Hz



**Test Graphs of Conducted Output Power** 11:57:15 AM Sep 13, 2024 Avg Type: Log-Pwr Avg|Hold: 100/100 Frequency TYPE M WWW DET P NNN Center Freq 2.402000000 GHz Trig: Free Run #Atten: 40 dB PNO: Fast ↔ IFGain:Low **Auto Tune** Mkr1 2.402 103 GHz -0.533 dBm 10 dB/div Ref 30.00 dBm Center Freq 2.402000000 GHz Start Freq 2.399500000 GHz Stop Freq 2.404500000 GHz **CF Step** 500.000 kHz Man <u>Auto</u> Freq Offset 0 Hz Center 2.402000 GHz #Res BW 1.5 MHz Span 5.000 MHz Sweep 1.066 ms (1000 pts) **#VBW 5.0 MHz** Test\_Graph\_BR\_ANT1\_2402\_1Mbps\_Peak Power Center Freq 2.441000000 GHz Frequency Avg Type: Log-Pwr Avg|Hold: 100/100 Trig: Free Run #Atten: 40 dB PNO: Fast ↔ IFGain:Low **Auto Tune** Mkr1 2.440 907 GHz -0.418 dBm Ref 30.00 dBm 10 dB/div Center Freq 2.441000000 GHz Start Freq 2.438500000 GHz Stop Freq 2 443500000 GHz CF Step 500.000 kHz <u>Auto</u> Freq Offset

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_BR\_ANT1\_2441\_1Mbps\_Peak Power

**#VBW 5.0 MHz** 

Span 5.000 MHz Sweep 1.066 ms (1000 pts)

Center 2.441000 GHz #Res BW 1.5 MHz




<u>Auto</u>

Span 5.000 MHz Sweep 1.066 ms (1000 pts) Mar

Freq Offset





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test\_Graph\_EDR\_ANT1\_2402\_2Mbps\_Peak Power

#VBW 5.0 MHz

Center 2.402000 GHz #Res BW 1.5 MHz








Test\_Graph\_EDR\_ANT1\_2480\_2Mbps\_Peak Power


#VBW 5.0 MHz

Span 5.000 MHz Sweep 1.066 ms (1000 pts)

Center 2.480000 GHz #Res BW 1.5 MHz









Test\_Graph\_EDR\_ANT1\_2441\_3Mbps\_Peak Power

#VBW 5.0 MHz









Page 24 of 76

# 7. 20dB Bandwidth and 99% Occupied Bandwidth Measurement

# 7.1 Provisions Applicable


There is no corresponding limit requirement for this test item.


#### 7.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 6.9.2 (20dB BW).

- The 20dB bandwidth spectrum analyzer setting reference is as follows:
- 1. Set RBW ≥ 1% to 5% of the 20dB bandwidth
- 2. VBW = Approximately three times RBW
- 3. Span = Approximately 2 to 5 times the 20dB bandwidth, centered on a hopping channel
- 4. Detector = Peak
- 5. Trace mode = Max hold
- 6. Sweep = Auto couple
- 7. Allow the trace to stabilize
- 8. Measure the maximum width of the emission that is constrained by the frequencies associated
- 9. with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20
- 10. dB relative to the maximum level in the fundamental emission.
- The 99% bandwidth spectrum analyzer setting reference is as follows:
- 1. Span = 1.5 times to 5 times the OBW
- 2. Set RBW = 1% to 5% the OBW
- 3. VBW ≥ 3 × RBW
- 4. Detector = Peak
- 5. Trace mode = Max hold
- 6. Sweep = Auto couple
- 7. Allow the trace was allowed to stabilize

## 7.3 Measurement Setup (Block Diagram of Configuration)









#### 7.4 Measurement Results


Test Data of Occupied Bandwidth and -20dB Bandwidth					
Test Mode	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)	-20dB Bandwidth (MHz)	Limits	Pass or Fail
	2402	0.838	0.949	N/A	Pass
GFSK	2441	0.839	0.949	N/A	Pass
	2480	0.838	0.951	N/A	Pass
	2402	1.162	1.314	N/A	Pass
π /4-DQPSK	2441	1.163	1.313	N/A	Pass
	2480	1.162	1.310	N/A	Pass
	2402	1.166	1.300	N/A	Pass
8DPSK	2441	1.165	1.300	N/A	Pass
	2480	1.166	1.301	N/A	Pass


Test Graphs of Occupied Bandwidth and -20 Bandwidth































Page 30 of 76

# 8. Conducted Band Edge and Out-of-Band Emissions

# 8.1 Provisions Applicable


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.


#### **8.2 Measurement Procedure**

The testing follows the ANSI C63.10 Section 6.10.4 and 7.8.8:

- Reference level measurement
- 1. Span = Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Sweep time = Auto couple
- Trace mode = Max hold
- 7. Allow the trace to stabilize. Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.
- Emission level measurement
- 1. Span = Wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Sweep time = Auto couple
- 6. Trace mode = Max hold
- 7. Trace was allowed to stabilize
- Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

#### 8.3 Measurement Setup (Block Diagram of Configuration)










#### 8.4 Measurement Results

Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands










Test\_Graph\_BR\_ANT1\_2441\_1Mbps\_Reference Level

#VBW 300 kHz

Span 3.000 MHz Sweep 2.000 ms (30000 pts)


Center 2.441000 GHz #Res BW 100 kHz



Freq Offset

Span 22.52 GHz Sweep 2.152 s (30000 pts)






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_BR\_ANT1\_2441\_1Mbps\_Higher Band Emissions

#VBW 300 kHz


Center 13.74 GHz #Res BW 100 kHz








Test\_Graph\_BR\_ANT1\_2480\_1Mbps\_Lower Band Emissions








Test\_Graph\_EDR\_ANT1\_2402\_2Mbps\_Reference Level


#VBW 300 kHz


Span 3.000 MHz Sweep 2.000 ms (30000 pts)


Center 2.402000 GHz #Res BW 100 kHz
























Test\_Graph\_EDR\_ANT1\_2480\_2Mbps\_Reference Level


#VBW 300 kHz


Span 3.000 MHz Sweep 2.000 ms (30000 pts)


Center 2.480000 GHz #Res BW 100 kHz

















Test\_Graph\_EDR\_ANT1\_2402\_3Mbps\_Lower Band Emissions


#VBW 300 kHz



Freq Offset

Span 3.000 MHz Sweep 2.000 ms (30000 pts)






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_EDR\_ANT1\_2441\_3Mbps\_Reference Level


#VBW 300 kHz


Center 2.441000 GHz #Res BW 100 kHz


















Test\_Graph\_EDR\_ANT1\_2480\_3Mbps\_Lower Band Emissions





















Test\_Graph\_BR\_HOP\_ANT1\_NA\_1Mbps\_Higher Band Edge Emissions







Test\_Graph\_EDR\_ANT1\_2480\_2Mbps\_Higher Band Edge Emissions









Test\_Graph\_EDR\_HOP\_ANT1\_NA\_2Mbps\_Higher Band Edge Emissions







Test\_Graph\_EDR\_ANT1\_2480\_3Mbps\_Higher Band Edge Emissions



2.500000000 GHz

**CF Step** 

Mar

2.500000 MHz


Freq Offset

<u>Auto</u>

Span 25.00 MHz

Sweep 4.000 ms (30000 pts)





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_EDR\_HOP\_ANT1\_NA\_3Mbps\_Higher Band Edge Emissions

#VBW 300 kHz

Center 2.48750 GHz #Res BW 100 kHz



Report No.: AGC09477240908FR02

Page 51 of 76

## 9. Radiated Spurious Emission

#### 9.1 Measurement Limit

15.209 Limit in the below table has to be followed

Frequencies	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

#### 9.2 Measurement Procedure

- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average



Report No.: AGC09477240908FR02 Page 52 of 76

absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting		
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP		
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP		
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP		
Start ~Stop Frequency	1GHz~26.5GHz		
Start ~Stop Frequency	1MHz/3MHz for Peak, 1MHz/3MHz for Average		

Receiver Parameter	Setting		
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP		
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP		
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP		



Report No.: AGC09477240908FR02

Page 53 of 76

#### Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

#### Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize


#### Average Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW ≥ [3 × RBW]
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- 8. The applicable correction factor is [10\*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




## 9.3 Measurement Setup (Block Diagram of Configuration)


### Radiated Emission Test Setup 9KHz-30MHz



## Radiated Emission Test Setup 30MHz-1000MHz



### Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Report No.: AGC09477240908FR02


Page 55 of 76

#### 9.4 Measurement Result


#### **Radiated Emission Below 30MHz**

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

	Radiated Emission Test Results at 30MHz-1GHz						
EUT Name	98440						
Temperature	22.9℃	Relative Humidity	58.3%				
Pressure	960hPa	Test Voltage	DC 3.7V by battery				
Test Mode	Mode 9	Antenna Polarity	Horizontal				




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		41.4215	5.73	13.80	19.53	40.00	-20.47	peak
2		114.9168	5.04	16.35	21.39	43.50	-22.11	peak
3		444.8514	5.25	24.93	30.18	46.00	-15.82	peak
4		519.0648	5.39	25.05	30.44	46.00	-15.56	peak
5		618.5368	5.15	25.19	30.34	46.00	-15.66	peak
6	*	896.9964	5.96	31.42	37.38	46.00	-8.62	peak





Radiated Emission Test Results at 30MHz-1GHz						
EUT Name ShowOff Wireless earbuds with LCD display Model Name 98440						
Temperature	22.9℃	Relative Humidity	58.3%			
Pressure	960hPa	Test Voltage	DC 3.7V by battery			
Test Mode	Mode 9	Antenna Polarity	Vertical			



## **RESULT: Pass**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The mode 9 is the worst case and recorded in the report.



Report No.: AGC09477240908FR02

Page 57 of 76

### **Radiated Emissions Test Results Above 1GHz**

EUT Name	ShowOff Wireless earbuds with LCD display	Model Name	98440
Temperature	22.9℃	Relative Humidity	58.3%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 7	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	47.26	0.08	47.34	74	-26.66	peak
4804.000	38.41	0.08	38.49	54	-15.51	AVG
7206.000	42.34	2.21	44.55	74	-29.45	peak
7206.000	31.26	2.21	33.47	54	-20.53	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT Name	ShowOff Wireless earbuds with LCD display	Model Name	98440
Temperature	22.9℃	Relative Humidity	58.3%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 7	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4804.000	47.94	0.08	48.02	74	-25.98	peak
4804.000	38.52	0.08	38.6	54	-15.4	AVG
7206.000	41.84	2.21	44.05	74	-29.95	peak
7206.000	31.55	2.21	33.76	54	-20.24	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

### **RESULT: Pass**



Report No.: AGC09477240908FR02 Page 58 of 76

### **Radiated Emissions Test Results for Above 1GHz**

EUT Name	ShowOff Wireless earbuds with LCD display	Model Name	98440
Temperature	22.9℃	Relative Humidity	58.3%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 8	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4882.000	46.28	0.14	46.42	74	-27.58	peak
4882.000	37.48	0.14	37.62	54	-16.38	AVG
7323.000	42.31	2.36	44.67	74	-29.33	peak
7323.000	31.58	2.36	33.94	54	-20.06	AVG
Remark:						

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	ShowOff Wireless earbuds with LCD display	Model Name	98440
Temperature	22.9℃	Relative Humidity	58.3%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 8	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4882.000	45.34	0.14	45.48	74	-28.52	peak
4882.000	37.52	0.14	37.66	54	-16.34	AVG
7323.000	40.29	2.36	42.65	74	-31.35	peak
7323.000	32.85	2.36	35.21	54	-18.79	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

### **RESULT: Pass**



Report No.: AGC09477240908FR02 Page 59 of 76

#### **Radiated Emissions Test Results for Above 1GHz**

EUT Name	ShowOff Wireless earbuds with LCD display	Model Name	98440
Temperature	22.9℃	Relative Humidity	58.3%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 9	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	48.62	0.22	48.84	74	-25.16	peak
4960.000	37.18	0.22	37.4	54	-16.6	AVG
7440.000	41.37	2.64	44.01	74	-29.99	peak
7440.000	30.69	2.64	33.33	54	-20.67	AVG
Remark:	Remark:					

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	ShowOff Wireless earbuds with LCD display	Model Name	98440
Temperature	22.9℃	Relative Humidity	58.3%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 9	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	46.86	0.22	47.08	74	-26.92	peak
4960.000	37.92	0.22	38.14	54	-15.86	AVG
7440.000	40.25	2.64	42.89	74	-31.11	peak
7440.000	31.43	2.64	34.07	54	-19.93	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

#### **RESULT: Pass**


#### Note:


- The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.



EUT Name	ShowOff Wireless earbuds with LCD display	Model Name	98440
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 7	Antenna Polarity	Horizontal

Test Graph for Peak Measurement






### **RESULT: Pass**



EUT Name	ShowOff Wireless earbuds with LCD display	Model Name	98440
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 7	Antenna Polarity	Vertical

Test Graph for Peak Measurement







### **RESULT: Pass**




EUT Name	ShowOff Wireless earbuds with LCD display	Model Name	98440
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 9	Antenna Polarity	Horizontal

Test Graph for Peak Measurement






### **RESULT: Pass**






EUT Name	ShowOff Wireless earbuds with LCD display	Model Name	98440
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 9	Antenna Polarity	Vertical

Test Graph for Peak Measurement





### **RESULT: Pass**

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



Report No.: AGC09477240908FR02 Page 64 of 76

10. Number of Hopping Frequency Measurement

### 10.1 Provisions Applicable


This frequency hopping system must employ a minimum of 15 hopping channels.

#### **10.2 Measurement Procedure**

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:


- 1. Span = The frequency band of operation. Depending on the number of channels the device
- 2. supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- 4. VBW ≥ RBW
- 5. Sweep time = Auto couple
- 6. Detector = Peak
- 7. Trace mode = Max hold
- 8. Allow the trace to stabilize

### 10.3 Measurement Setup (Block Diagram of Configuration)




#### 10.4 Measurement Result

Test Data of Number of Hopping Frequency					
Test Mode Number of Hopping Frequency Limits Pass or Fail					
8DPSK Hopping	79	>=15	Pass		







Note: All mode rates are tested and evaluated, 8DPSK modulated 3DH5 mode is the worst case and documented in the report.



Report No.: AGC09477240908FR02

Page 66 of 76

## 11. Time of Occupancy (Dwell Time) Measurement

### 11.1 Provisions Applicable


The maximum permissible time of occupancy is 400ms within a period of 400ms multiplied by the number of hopping channels employed.

#### 11.2 Measurement Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:


- 1. Span = Zero span, centered on a hopping channel.
- 2. RBW shall be ≤ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
- 3. VBW ≥ RBW
- 4. Sweep time = As necessary to capture the entire dwell time per hopping channel
- 5. Detector = Peak
- 6. Trace mode = Free Run
- 7. Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time. An oscilloscope may be used instead of a spectrum analyzer. The EUT shall show compliance with the appropriate regulatory limit for the number of hopping channels. A plot of the data shall be included in the test report.

### 11.3 Measurement Setup (Block Diagram of Configuration)



#### 11.4 Measurement Result

	Test Data of Dwell Time						
Channel	Time of Pulse for 3DH5 (ms)	Number of hops in the period specified in the requirements	Dwell Time (ms)	Limit (ms)	Pass or Fail		
2402	2.906	22.0*4	255.728	400	Pass		
2441	2.905	19.0*4	220.780	400	Pass		
2480	2.906	33.0*4	383.592	400	Pass		






**Test Graphs of Dwell Time** 12:57:14 PM Sep 13, 2024 Frequency Avg Type: Log-Pwr Center Freq 2.402000000 GHz Trig: Free Run #Atten: 40 dB TYPE WWW PNO: Fast IFGain:Low **Auto Tune** 10 dB/div Ref 30.00 dBm Center Freq 2.402000000 GHz Start Freq 2.402000000 GHz Stop Freq 2.402000000 GHz **CF Step** 1.000000 MHz <u>Auto</u> Freq Offset 0 Hz Center 2.402000000 GHz Res BW 1.0 MHz Span 0 Hz Sweep 7.902 s (30000 pts)

**#VBW** 3.0 MHz


# Test\_Graph\_EDR\_HOP\_ANT1\_NA\_3Mbps\_2402\_Number of Busrt ON RL RF 50 Ω ACC Center Freq 2.402000000 GHz PNO: Fast → IFGain:Low Trig Delay-2.000 ms Trig: Video #Atten: 40 dB Frequency Avg Type: Log-Pwr **Auto Tune** ΔMkr1 2.906 ms -0.21 dB Ref 30.00 dBm 10 dB/div Center Freq 2.402000000 GHz Start Freq 1Δ2 2.402000000 GHz Stop Freq 2 402000000 GHz CF Step 1.000000 MHz <u>Auto</u> Freq Offset 0 Hz Center 2.402000000 GHz Res BW 1.0 MHz Span 0 Hz Sweep 8.000 ms (30000 pts) #VBW 3.0 MHz Test\_Graph\_EDR\_HOP\_ANT1\_NA\_3Mbps\_2402\_Time per Burst


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Web: http://www.agccert.com/
















Note: All mode rates are tested and evaluated, 8DPSK modulated 3DH5 mode is the worst case and documented in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_EDR\_HOP\_ANT1\_NA\_3Mbps\_2480\_Time per Burst