



## (i) Certified

Input: DC5.0V/2.0A, 9.0V/1.67A

Output: 5W/7.5W/10W

Rated Frequency: 112.50~183.33kHz

Transmission distance: 0~8mm (3mm optimal)

Efficiency:  $\geq 75\%$ 

CAUTION: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the product.NOTE: This equipment has been tested and found to comply with the limits for a wireless power charger, pursuant to Part 18 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged

to try to correct the interference by one or more of the following measures: Reorient or relocate the receiving antenna.

Increase the separation between the equipment and receiver. Connect the equipment into an outlet on a circuit different from that to which the receiver is connected. Consult the dealer or an experienced radio/TV technician for help.

www.NumiProducts.com Salt Lake City, Utah \*2019 Instruction Manual smart dock plus™ **O** numi

## **How To Use:**



Clean surface you wish to place the Smart Dock Plus on.



Remove protective liner from Flex Grip base and place Smart Dock Plus on surface. Ensure that Flex Grip base is in full contact with surface.



Phone can be placed flat or in landscape viewing angle for hands-free navigation use.

**How To Clean:** 

Air Core can be removed for cleaning. To renew grip simply wipe with damp cloth and

allow to dry.



To charge in landscape position, slide Air Core out of front and insert into rear slots with cable facing down. Adjust height of Air Core to cover center of phone for optimal connection.



Connect USB cord to powered USB port or 12v adapter. Air Core will briefly flash red to indicate it is ready to charge.



Remove liner from top of Air-Core and place your phone. Air Core will briefly flash blue to indicate your device is charging.

Removing Smart
Dock Plus:

To remove, simply peel off dash slowly from a corner or edge.





Use QC 3.0 or better power supply for maximum performance

Product is meant to securely hold your phone on curved or inclined surfaces commonly found on vehicle dashboards, but not on extreme inclines or vertical surfaces.

Grip surfaces contain no adhesive and leave no residue. They are tested to withstand temperatures & UV exposure commonly found in cars.

Do not clean product with chemicals or spray with vehicle interior treatments. Air Core is not waterproof and should not be submerged or placed under running water. Permanent damage may occur.