

Page: 1 of 28

FCC Test Report

Application No.: HKEM1807000581HS

Applicant: Neuro Tennis, Inc.

Address: 1000 Wilson Blvd. Ste 1800 ArlingtonVirginia 22209 United States

Product Information:

Product Description: Neuro Tennis Electronic

Model No.: NT 200

Product Class: Low Power Communication Device –Tranceiver (2.4 GHz)

FCC ID: 2AMZZNT200

Requirement: CFR 47 FCC PART 15 SUBPART C, 2018

Intentional Radiators (Section 15.249)

Date of Receipt: 2018-07-19

Date of Test: 2018-07-26 to 2018-08-01

Date of Issue: 2018-08-01

Test Result : PASS*

In the configuration tested, the EUT complied with the requirements for the relevant clauses of Federal Communications Commission Rules as specified above.

Authorized Signature:

Ivan Toa

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevants tandards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspxand-for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documenta.aspx. Attention is drawn to the limits of adaptive, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exone rate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Page: 2 of 28

2 Test Summary

Test	Test Requirement	Test Method	Result
Conducted Emission (150KHz to 30MHz)	FCC PART 15, SUBPART C: 2018	ANSI C63.10:2013	N/A
Radiated Emission (9kHz to 1GHz)	FCC PART 15, SUBPART C: 2018	ANSI C63.10:2013	PASS
Radiated Emission above 1 GHz	FCC PART 15, SUBPART C: 2018	ANSI C63.10:2013	PASS
Restricted-band band- edge measurements (Radiated Emission)	FCC PART 15, SUBPART C: 2018	ANSI C63.10:2013	PASS
20dB bandwidth	FCC PART 15, SUBPART C: 2018	ANSI C63.10:2013	PASS

Remark:

This device is battery operated only.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any hoter of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exoneate paties to a transaction of comments. This document annot be reproduced except in full, without prior written approval of the Company. Any unautho tized alteration, to reprove falsification of the content or appearance of this document is unlawful and o flenders may be prosecuted to the fullest extent of the law.



Page: 3 of 28

3 Contents

		Page
1	COVER PAGE	1
2	TEST SUMMARY	2
_	TLOT GOMINIANT	······
3	CONTENTS	3
4	GENERAL INFORMATION	4
	4.1 GENERAL DESCRIPTION OF EUT	4
	4.2 DETAILS OF EUT	
	4.3 CONDITIONS OF EUT	
	4.4 DESCRIPTION OF SUPPORT UNITS	
	4.5STANDARDS APPLICABLE FOR TESTING	
	4.6 TEST LOCATION	
	4.7 TEST FACILITY	
	4.8 DEVIATION FROM STANDARDS	
	4.9 ABNORMALITIES FROM STANDARD CONDITIONS	
	4.10 DECLARATION OF FAMILY GROUPING	
	4.11 Abbreviations	
	4.12 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	
5	EQUIPMENTS USED DURING TEST	7
6	TEST RESULTS	8
	6.1 RADIATED EMISSIONS, 9KHZ TO 1GHZ	8
	6.2.1 EUT Operation	
	6.2.2 Test Setup and Procedure	
	6.2.3 Measurement Data	
	6.3 RADIATED EMISSIONS ABOVE 1 GHZ	
	6.3.1 EUT Operation	
	6.3.2 Test Setup and Procedure	
	6.3.3 Measurement Data	
	6.4 RESTRICTED-BAND BAND-EDGE MEASUREMENTS (RADIATED EMISSION)	
6.	.5 20 DB BANDWIDTH	24
7	PHOTOGRAPHS	28
	7.1 EUT CONSTRUCTIONAL DETAILS	28

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any hoter of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exoneate paties to a transaction of comments. This document annot be expreduced except in full, without prior written approval of the Company. Any unautho fized alteration, to no error as all fication of the content or appearance of this document is unlawful and o fiendes may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Page: 4 of 28

4 General Information

4.1 General Description of EUT

Product Description: Neuro Tennis Electronic

Model No.: NT 200

Serial No.:

4.2 Details of EUT

Power Supply: AC120V ~ 60Hz to DC 5.25V (Adaptor no.: GEO061U-0510) for battery

charging

DC 3.7V (Rechargeable battery x 1)

Operating Frequency 2405-2475MHz for Zigbee modes

2402-2480MHz for Bluetooth modes

Antenna Type: Unreplaceble onboard chip antenna

Antenna gain: Antenna 1: 1.5dBi for Zigbee

Antenna 1: 0dBi for Bluetooth

Modulation Type: GFSK

Zigbee modes: Test frequency tested are the lowest channel: 1 channel (2405MHz), middle channel: 2 channel (2440MHz) and highest channel: 3 channel (2475MHz)

Bluetooth modes: Test frequency tested are the lowest channel: 1 channel (2402MHz), middle channel: 2 channel (2441MHz) and highest channel: 3 channel (2480MHz)

Channel configuration method:

- 1. Power on the button to enter test mode.
- 2. Press the button to change the channel from low to high frequency mode.

4.3 Conditions of EUT

Good condition

4.4 Description of Support Units

1. All field strength measures in this test report were done by the sample which set the frequency fixed with continuous transmission

4.5Standards Applicable for Testing

CFR 47, FCC Part 15, 2018 ANSI C63.10:2013

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction is sues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the firme of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exone ate paties to a transaction of comments. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, to grey or falsification of the content or appearance of this document is unlawful and of fenders may be prosecuted to the fullest extent of the law.

Un less o therwise stated the results shown in this testrep or trefer only to the sam ple(s) tested and such sam ple(s) are retained for 30 days only.



Page: 5 of 28

4.6 Test Location

All tests were performed at:

SGS IECC Limited (Member of the SGS Group (SGS SA))

16-B, Yip Wo Street, On Lok Cheun, Fanling, Hong Kong.

Tel: +852 2305 2570 Fax: +852 2756 4480

No tests were sub-contracted

4.7 Test Facility

The test facility is recognized or accredited by the following organizations:

HOKLAS (Lab Code: 125)

SGS IECC Limited has been accepted by HKAS Executive, on the recommendation of the Accreditation Advisory Board, as a HOKLAS Accredited Laboratory, this laboratory meets the requirements of ISO/IEC 17025:2005 an it has been accredited for performing specific test as listed in the scope of accreditation within the test category of Electrical and Electronic Products.

FCC Recognized Accredited Test Firm(CAB Registration No.: 446297)

SGS IECC Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: **HK0010**, Test Firm Registration Number: **446297**.

Industry Canada (Registration No.: 5193A-2)

The 3m Alternative Semi-anechoic chamber of SGS IECC Limited has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. **5193A-2.**

4.8 Deviation from Standards

None.

4.9 Abnormalities from Standard Conditions

None.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions/aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documentaspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate paties to a transaction of comments. This document annot be reproduced except in full, without prior written approval of the Company. Any unautho tized alteration, to grey or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 6 of 28

4.10 Declaration of Family Grouping

None.

4.11 Abbreviations

N/A: Not Applicable

EUT: Equipment Under Test

4.12 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radiated disturbance 9 kHz - 30MHz	4.16
2	Radiated disturbance 30MHz – 1GHz	5.90
3	Radiated disturbance 1GHz – 18GHz	4.96
4	Conducted Emissions	3.00

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any hoter of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exoneate paties to a transaction of comments. This document annot be reproduced except in full, without prior written approval of the Company. Any unautho tized alteration, to reprove falsification of the content or appearance of this document is unlawful and o flenders may be prosecuted to the fullest extent of the law.



Page: 7 of 28

5 Equipments Used during Test

Equipment	Manufacturer	Model / Serial No.	Cal. Due Date
EMI Test Receiver 9kHz to 3.6GHz	Rohde & Schwarz	ESR3 / 102326	2018/08/15
Antenna	Schaffner	CBL6111C / 2791	2018/10/26
Loop Antenna	Rohde & Schwarz	HFH2-Z2 / 871336/48	2019/01/22
Antenna	Schwarzbeck	BBA9106 / TE039A	2020/01/29
Antenna	Schwarzbeck	UHALP9107 / TE039B	2020/01/29
Antenna Mast System	Schwarzbeck	AM9104 / -	
Turntable with Controller	Drehtisch	DT312 / -	
Spectrum Analyzer	Rohde & Schwarz	FSP30 / 101474	2019/05/22
Horn Antenna	Schwarzbeck	BBHA9120D / 9120D-1070	2020/01/29
Horn Antenna	Schwarzbeck	BBHA9170 / 9170-492	2019/10/16
Preamplifier	Schwarzbeck	BBV9718 / 9718-223	2019/01/28
Preamplifier	Schwarzbeck	BBV9719 / 9719-019	2018/12/20
Highpass Filter	Wainwright	WHNX3.5/26.5G-6SS / nil	2018/12/18
Band Reject Filter	Wainwright	WRCJV 2400/2500- 2100/2800-40/3SS / nil	2018/12/18
RF cable	HUBER+SUHNER	SF104-26.5/2	2018/12/26

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any hoter of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exoneate paties to a transaction of comments. This document annot be expreduced except in full, without prior written approval of the Company. Any unautho fized alteration, to no error as all fication of the content or appearance of this document is unlawful and o fiendes may be prosecuted to the fullest extent of the law.



Page: 8 of 28

6 Test Results

6.1 Radiated Emissions, 9kHz to 1GHz

Test Requirement: FCC Part15 Subpart C Section 15.209 and 15.249(d)

Test Method: ANSI C63.10

Test Date: 2018-07-26 to 2018-07-31

Frequency Range: The lowest frequency generated by EUT, 12MHz to 1GHz

Measurement Distance: 3m

Detector: Peak for pre-scan

(200Hz resolution bandwidth and 1kHz video bandwidth for measurement

between 9kHz - 150kHz)

(9kHz resolution bandwidth and 100kHz video bandwidth for

measurement between 150kHz - 30MHz)

120kHz resolution bandwidth and 1MHz video bandwidth for

measurement between 30MHz to 1GHz)

Quasi-Peak if maximised peak within 6dB of limit

Limit:

Frequency range MHz	Quasi-peak limits dB (μV/m)
0.009 - 0.490	-72.4 – 20logF(MHz)
0.490 - 1.705	-12.4 – 20logF(MHz)
1.705 – 30.0	-10.5
30 to 88	40
88 to 216	43.5
216 to 960	46
Above 960	54

Note: 1) At transitional frequencies the lower limit applies.

2) F is the frequency of the spurious emission measured in MHz.

3) Limit from 0.009 - 30 MHz is converted from measuring distance 300m or 30m to 3m with the formulat provided in FCC Part 15, section 15.31(f)(2)

6.2.1 EUT Operation

Operating Environment:

Temperature: 24 °C Humidity: 59 %

EUT Operation: Pre-test with Peak detector with the following mode(s):

Transmission in continuous transmitting mode
 Test in lowest, middle and high frequency

Final test with Quasi-Peak detector with the following mode(s):

1: Transmission in continous transmitting mode

2. Test in lowest, middle and high frequency


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions/aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documentaspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate paties to a transaction of comments. This document annot be reproduced except in full, without prior written approval of the Company. Any unautho tized alteration, to grey or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Un less o therwise stated the results shown in this testrep or trefer only to the sam ple(s) tested and such sam ple(s) are retained for 30 days only.



Page: 9 of 28

6.2.2 Test Setup and Procedure



- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the Y axis positioning which it is worse case.
- 1. Repeat above procedures until all frequencies measured was complete.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions/aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documentaspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate paties to a transaction of comments. This document annot be reproduced except in full, without prior written approval of the Company. Any unautho tized alteration, to grey or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Page: 10 of 28

6.2.3 Measurement Data

Test results:

For Zigbee modes

(1) Operation Frequency: 2405MHz

	ı					
Гиализапан	A mata mana	Correction	Receiver	Emission	Limit	Over Limit
Frequency	Antenna	Factor	QP Reading	Level	(dBµV/m)	Over Limit
(MHz)	Polarization		ŭ		(0.2 μ. 1 /)	(dB)
, ,		(dB/m)	(dBμV)	(dBμV/m)		, ,
21 010						
31.810	Н	18.1	9.0	27.1	40	-12.9
57.150	V	10.2	6.6	16.8	40	-23.2
37.130	V	10.2	0.0	10.0	40	-23.2
141.350	Н	11.1	7.4	18.5	43.5	-25.0
287.650	V	12.7	7.7	20.4	46	-25.6
207.000	V	12.7	1.1	20.4	40	-25.0
413.490	Н	15.9	6.6	22.5	46	-23.5
722.870	V	19.6	8.2	27.8	46	-18.2

(2) Operation Frequency: 2440MHz

Frequency (MHz)	Antenna Polarization	Correction Factor (dB/m)	Receiver QP Reading (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Over Limit (dB)
32.020	V	18.0	9.1	27.1	40	-12.9
62.220	V	9.5	6.8	16.3	40	-23.7
123.050	V	10.9	7.2	18.1	43.5	-25.4
295.560	Н	13.0	6.4	19.4	46	-26.6
439.620	V	16.5	7.8	24.3	46	-21.7
720.820	Н	19.6	8.2	27.8	46	-18.2

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any hoter of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exoneate paties to a transaction of comments. This document annot be reproduced except in full, without prior written approval of the Company. Any unautho tized alteration, to reprove falsification of the content or appearance of this document is unlawful and o flenders may be prosecuted to the fullest extent of the law.



Page: 11 of 28

(3) Operation Frequency: 2475MHz

Frequency (MHz)	Antenna Polarization	Correction Factor (dB/m)	Receiver QP Reading (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Over Limit (dB)
31.630	V	18.2	9.1	27.3	40	-12.7
63.110	Н	9.4	6.6	16.0	40	-24.0
129.940	V	11.0	7.4	18.4	43.5	-25.1
238.970	V	10.6	8.1	18.7	46	-27.3
431.890	Н	16.4	7.2	23.6	46	-22.4
728.100	V	19.7	10.1	29.8	46	-16.2

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any hoter of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exoneate paties to a transaction of comments. This document annot be expreduced except in full, without prior written approval of the Company. Any unautho fized alteration, to no error as all fication of the content or appearance of this document is unlawful and o fiendes may be prosecuted to the fullest extent of the law.



Page: 12 of 28

For Bluetooth modes

(1) Operation Frequency: 2402MHz

Frequency (MHz)	Antenna Polarization	Correction Factor (dB/m)	Receiver QP Reading (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Over Limit (dB)
30.170	V	18.9	7.5	26.4	40	-13.6
59.380	Н	9.8	6.7	16.5	40	-23.5
139.730	Н	11.1	7.4	18.5	43.5	-25.0
272.260	V	12.1	7.5	19.6	46	-26.4
439.230	Н	16.5	7.7	24.2	46	-21.8
727.480	Н	19.7	10.1	29.8	46	-16.2

(2) Operation Frequency: 2441MHz

Frequency	Antenna	Correction	Receiver	Emission	Limit	Over Limit
		Factor	QP Reading	Level	(dBµV/m)	
(MHz)	Polarization	(dB/m)	(dBµV)	(dBµV/m)		(dB)
31.640	Н	18.2	9.0	27.2	40	-12.8
66.020	Н	9.1	6.9	16.0	40	-24.0
00.020	П	9.1	0.9	10.0	40	-24.0
135.450	Н	11.1	7.4	18.5	43.5	-25.0
283.850	V	12.6	7.6	20.2	46	-25.8
	•					
450.560	Н	17.0	6.7	23.7	46	-22.3
727.690	Н	19.7	10.1	29.8	46	-16.2

(3) Operation Frequency: 2480MHz

Frequency (MHz)	Antenna Polarization	Correction Factor (dB/m)	Receiver QP Reading (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Over Limit (dB)
30.550	V	18.7	7.5	26.2	40	-13.8
63.570	Н	9.4	7.1	16.5	40	-23.5
139.180	V	11.1	7.4	18.5	43.5	-25.0
287.210	V	12.7	7.7	20.4	46	-25.6
494.720	V	17.5	6.8	24.3	46	-21.7
724.740	V	19.6	8.2	27.8	46	-18.2

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any hoter of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exoneate paties to a transaction of comments. This document annot be reproduced except in full, without prior written approval of the Company. Any unautho tized alteration, to reprove falsification of the content or appearance of this document is unlawful and o flenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Page: 13 of 28

Note:

- 1) All readings are Quasi-Peak values.
- 2) Correction Factor = Antenna Factor + Cable Loss.
- 3) The above results were the worst case results with the EUT positioned in all 3 axis during the test. The EUT was positioned vertically and horizontally on the table for vertical and horizontal measurement respectively.
- 4) Other emissions more than 20dB below the limit are not shown on the above table and only worst six emissions below 1GHz are listed.

This document is issued by the Company subject to its General Conditions of Sewice printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-a



Page: 14 of 28

6.3 Radiated Emissions above 1 GHz

Test Requirement: FCC Part15 Subpart C Section 15.209 & 15.249(a) & (d)

Test Method: ANSI C63.10

Test Date: 2018-07-26 to 2018-08-01

Frequency Range: 1GHz – 26GHz

Measurement Distance: 3m

Detector: Peak for pre-scan (1MHz resolution bandwidth, 1MHz video bandwidth)

Average and Peak detector for final test

Limit:

Fundamental Frequency:

Frequency range MHz	Limits (Peak) dB (μV/m)	Limits (Average) dB (μV/m)
2400 to 2483.5	114	94

Spurious Emission:

Frequency range	Limits (Peak)	Limits (Average)
MHz	dB (μV/m)	dB (μV/m)
Over 1000	74	54

6.3.1 EUT Operation

Operating Environment:

Temperature: 24 °C Humidity: 59 %

EUT Operation: Pre-test with Peak detector with the following mode(s):

1: Transmission in continous transmitting mode

2. Test in lowest, middle and high frequency

Final test with Peak and Avearge detector with the following mode(s):

1: Transmission in continous transmitting mode


2. Test in lowest, middle and high frequency

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions/aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documentaspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate paties to a transaction of comments. This document annot be reproduced except in full, without prior written approval of the Company. Any unautho tized alteration, to grey or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 15 of 28

6.3.2 Test Setup and Procedure



- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the Y axis positioning which it is worse case.
- 1. Repeat above procedures until all frequencies measured was complete.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions/aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documentaspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate paties to a transaction of comments. This document annot be reproduced except in full, without prior written approval of the Company. Any unautho tized alteration, to grey or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Un less o therwise stated the results shown in this testrep or trefer only to the sam ple(s) tested and such sam ple(s) are retained for 30 days only.



Page: 16 of 28


6.3.3 Measurement Data

An initial pre-scan was performed in the 3m chamber using the spectrum analyser in peak detection mode. The EUT was measured with 3 orthogonal polarities and frequencies of average emissions from the EUT were measured as follows:

Emission at the fundemental frequency for the pulse modulated device was measured with the peak detector function of the test receiver and was properly adjusted for the duty cycle correction factor as pulse desensitization to calculate the average emission value.

For Zigbee modes

<u>Time Domain Plots (Fundamental frequency of Transmitter):</u>



Date: 27.JUL.2018 10:00:10


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documentaspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exone ate paties to a transaction of comments. This document cannot be reproduced except in full, without prior written approach of the Company. Any unauthotized alteration, to gery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 17 of 28

For Bluetooth modes

Time Domain Plots (Fundamental frequency of Transmitter):



Date: 1.AUG.2018 14:57:41

According to above plot, the duty cycle of the this device is 100%, plused operation according to C63.10 clause 7.5 is not employed and the average correction calculation is not applied on this report.

Hence, the average measurement is used below setting:

Dectector = peak

 $RBW = \ge 1MHz$

 $VBW = \ge 1Hz$

This document is issued by the Company subject to its General Conditions of Sewice printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-a

Unless otherwise stated the results shown in this testreport refer only to the sam ple(s) tested and such sam ple(s) are retained for 30 days only.



Page: 18 of 28

Test results:

For Zigbee modes

(1) Fundmental Frequency

Frequency	Antenna	Emission Level (dBμV/m)		Limit (d	Remark	
(MHz)	Polarization	Peak	Average	Peak	Average	rioman
2405.0	Н	96.49	60.63	114	94	Pass
2405.0	V	93.50	59.23	114	94	Pass
2440.0	Н	95.34	60.70	114	94	Pass
2440.0	V	91.85	60.08	114	94	Pass
2475.0	Н	94.01	60.13	114	94	Pass
2475.0	V	90.06	59.30	114	94	Pass

(2) Spurious Emission

Operation Frequency: 2405.0 MHz

Frequency	Antenna	Emission Level (dBμV/m)		Limit (d	BμV/m)	Remark
(MHz)	Polarization	Peak	Average	Peak	Average	Hemaik
4811	Н	45.32	23.58	74	54	Pass
6011	Н	42.19	24.82	74	54	Pass
7214	V	51.31	30.22	74	54	Pass
8641	V	49.82	32.22	74	54	Pass
9618	Н	57.01	33.62	74	54	Pass
12033	V	52.40	36.73	74	54	Pass

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any hoter of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exoneate paties to a transaction of comments. This document annot be reproduced except in full, without prior written approval of the Company. Any unautho tized alteration, to reprove falsification of the content or appearance of this document is unlawful and o flenders may be prosecuted to the fullest extent of the law.



Page: 19 of 28

Operation Frequency: 2440.0 MHz

Frequency	Antenna	Emission Level (dBµV/m)		Limit (c	Remark	
(MHz)	Polarization	Peak	Average	Peak	Average	Hemark
4879	V	45.82	24.21	74	54	Pass
6225	Н	44.27	26.33	74	54	Pass
7322	V	53.19	31.00	74	54	Pass
8500	V	48.74	31.96	74	54	Pass
9762	Н	58.89	35.56	74	54	Pass
12198	V	53.24	36.45	74	54	Pass

Operation Frequency: 2475.0 MHz

Frequency	Antenna	Emission Level (dBμV/m)		Limit (c	Remark	
(MHz)	Polarization	Peak	Average	Peak	Average	Heman
4949	Н	48.92	25.73	74	54	Pass
5455	Н	43.09	24.33	74	54	Pass
7423	Н	55.07	31.53	74	54	Pass
8596	Н	48.20	32.52	74	54	Pass
9898	Н	60.16	35.09	74	54	Pass
12374	Н	52.85	36.66	74	54	Pass

For Bluetooth modes

(3) Fundmental Frequency

` '						
Frequency	Antenna	Emission Le	Emission Level (dBμV/m)		Limit (dBµV/m)	
(MHz)	Polarization	Peak	Average	Peak	Average	Remark
2402.0	Н	95.83	72.06	114	94	Pass
2402.0	V	95.17	72.15	114	94	Pass
2441.0	Н	95.88	71.48	114	94	Pass
2441.0	V	94.05	71.22	114	94	Pass
2480.0	Н	95.35	70.58	114	94	Pass
2480.0	V	94.44	70.25	114	94	Pass

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any hoter of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exoneate paties to a transaction of comments. This document annot be reproduced except in full, without prior written approval of the Company. Any unautho tized alteration, to reprove falsification of the content or appearance of this document is unlawful and o flenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Page: 20 of 28

(4) Spurious Emission

Operation Frequency: 2402.0 MHz

Frequency	Antenna	Emission Level (dBμV/m)		Limit (d	Remark	
(MHz)	Polarization	Peak	Average	Peak	Average	nemark
4800	Н	38.86	22.02	74	54	Pass
5470	V	42.99	23.81	74	54	Pass
7204	V	46.66	29.53	74	54	Pass
8311	V	47.14	31.69	74	54	Pass
9607	V	48.05	31.48	74	54	Pass
10452	V	54.04	35.61	74	54	Pass

Operation Frequency: 2441.0 MHz

Frequency	Antenna	Emission Level (dBμV/m)		Limit (d	Remark	
(MHz)	Polarization	Peak	Average	Peak	Average	Homan
3873	Н	39.69	19.44	74	54	Pass
4882	V	42.17	23.42	74	54	Pass
7219	V	46.03	25.74	74	54	Pass
8026	Н	47.04	31.49	74	54	Pass
9767	V	49.44	32.67	74	54	Pass
10518	V	52.43	35.11	74	54	Pass

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-end-Conditions/



Page: 21 of 28

Operation Frequency: 2480.0 MHz

Frequency	Antenna	Emission Level (dBμV/m)		Limit (dBµV/m)		Remark
(MHz)	Polarization	Peak	Average	Peak	Average	rieman
4965	V	40.60	25.53	74	54	Pass
5464	Н	41.62	23.97	74	54	Pass
7442	V	47.23	31.50	74	54	Pass
8586	V	48.08	31.87	74	54	Pass
9911	V	49.20	32.45	74	54	Pass
10430	Н	52.22	34.94	74	54	Pass

Note:

- 1) The above results were the worst case results with the EUT positioned in all 3 axis during the test. The EUT was positioned vertically and horizontally on the table for vertical and horizontal measurement respectively.
- 2) Other emissions more than 20dB below the limit are not shown on the above table and only worst six emissions below 1GHz are listed.
- 3) There is not any other emission which falls in restricted bands which set out in Section 15.205 Restricted bands can be detected and reported.

This document is issued by the Company subject to its General Conditions of Sewice printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-a



Page: 22 of 28

6.4 Restricted-band band-edge measurements (Radiated Emission)

Test Requirement: FCC Part15 Subpart C Section 15.215, 15.249(d)

Test Method: ANSI C63.10

Measurement Distance: 3m

Detector: (1MHz resolution bandwidth, 3MHz video bandwidth)

Average and Peak detector

Limit: Emissions radiated outside of the specified frequency bands, except for

harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general field strength limits listed in RSS-Gen,

whichever is less stringent.

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.0	Quasi-peak Value
88MHz-216MHz	43.5	Quasi-peak Value
216MHz-960MHz	46.0	Quasi-peak Value
960MHz-1GHz	54.0	Quasi-peak Value
A1 4011	54.0	Average Value
Above 1GHz	74.0	Peak Value

Test Date: 2018-07-26 to 2018-07-31

EUT Operation: 1: Transmission with GFSK

Result: Pass

This document is issued by the Company subject to its General Conditions of Sewice printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-a



Page: 23 of 28

Test results: (Worst case: Transmissin with GFSK)

For Zigbee modes

Operation frequency: 2405.0 MHz

Frequency	Antenna	Emission Level (dBμV/m)		Limit (d	Remark	
(MHz)	Polarization	Peak Average		Peak Average		Homan
2400.0	Н	36.60	12.67	74	54	Pass

Operation frequency: 2475.0 MHz

Frequency	Antenna	Emission Level (dBμV/m)		Limit (dBµV/m)		Remark
(MHz)	Polarization	Peak	Average	Peak	Average	riomani
2483.5	Н	30.25	14.83	74	54	Pass

For Bluetooth modes

Operation frequency: 2402.0 MHz

Frequency	Antenna	Emission Level (dBµV/m)		Limit (dBµV/m)		Remark
(MHz)	Polarization	Peak	Average	Peak	Average	rioman
2400.0	Н	56.10	20.70	74	54	Pass

Operation frequency: 2480.0 MHz

Frequency	Antenna	Emission Level (dBμV/m)		Limit (dBµV/m)		Remark
(MHz)	Polarization	Peak	Average	Peak	Average	Homan
2483.5	V	49.71	20.04	74	54	Pass

According to above bandedge measurement, emissions radiated outside of the specified frequency bands, (2400-2483.5)MHz except for harmonics, are below general field strength limits under 15.209 It is deemed to comply with section 15.215 and 15.249(d)

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exoneate parties to a transaction from exercising all their rights and ob ligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unautho fized alteration, to gery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Un less otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Page: 24 of 28

6.5 20 dB Bandwidth

Test Requirement: FCC Part15 Subpart C Section 15.215

Test Method: ANSI C63.10:2013

Test Date: 2018-07-27 to 2018-08-01


EUT Operation: 1: Transmission with GFSK

Result: Pass

Test Plot: (Worst case: Transmission with GFSK)

For Zigbee modes

Operation frequency: 2405.0 MHz



Date: 27.JUL.2018 10:04:53

According to above plot, 20dB bandwidth falls in assigned band (2400-2483.5)MHz. It is deemed to comply with section 15.215


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documentaspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exone ate paties to a transaction of comments. This document cannot be reproduced except in full, without prior written approach of the Company. Any unauthotized alteration, to gery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Un less o therwise stated the results shown in this testrep or trefer only to the sam ple(s) tested and such sam ple(s) are retained for 30 days only.



Page: 25 of 28

Operation frequency: 2475.0 MHz



Date: 27.JUL.2018 10:07:46

According to above plot, 20dB bandwidth falls in assigned band (2400-2483.5)MHz. It is deemed to comply with section 15.215


This document is issued by the Company subject to its General Conditions of Sewice printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-a



Page: 26 of 28

For Bluetooth modes

Operation frequency: 2402.0 MHz



Date: 1.AUG.2018 15:16:42


According to above plot, 20dB bandwidth falls in assigned band (2400-2483.5)MHz. It is deemed to comply with section 15.215

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documentaspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exone ate paties to a transaction of comments. This document cannot be reproduced except in full, without prior written approach of the Company. Any unauthotized alteration, to gery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 27 of 28

Operation frequency: 2480.0 MHz



Date: 1.AUG.2018 15:18:19

According to above plot, 20dB bandwidth falls in assigned band (2400-2483.5)MHz. It is deemed to comply with section 15.215

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documentaspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exone ate paties to a transaction of comments. This document cannot be reproduced except in full, without prior written approach of the Company. Any unauthotized alteration, to gery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 28 of 28

7 Photographs

7.1 EUT Constructional Details



- END OF REPORT --

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any hoter of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exoneate paties to a transaction of comments. This document annot be reproduced except in full, without prior written approval of the Company. Any unautho tized alteration, to reprove falsification of the content or appearance of this document is unlawful and o flenders may be prosecuted to the fullest extent of the law.