Beijing Roborock Technology Co., Ltd.

Request for Modular/Limited Modular Approval

| Date: May 24, 2021 | | | | |
|--|--|---|---------------|-----------|
| Subject: Manufacturer's Declaration for □ - 1 □ - 1 | Modular Approval Limited Modular Approval | □ - Split Modula□ - Limited Spli | | pproval |
| Confidentiality Request for: 2AN2O-RSV | W06 | | | |
| | quirements – FCC Part 15.212(a | | | |
| For Items Marked "NO(*)", the Limited | | Filled Out on the Fol | | |
| Modular Approva | | 414-41 | Require | ment Met |
| 1. The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i) | | □ - YES | ⊠ - NO(*) | |
| Details: the module doesn't have its own RF shielding. | | | | |
| 2. The modular transmitter must have buffered modu ensure that the module will comply with FCC requ over-modulation. 15.212(a)(1)(ii) | | | 🖾 - YES | □ - NO(*) |
| Details: Data to the modulation circuit is buffered as described in the operational description provided with the application. | | | | lication. |
| 3. The modular transmitter must have its own power ensure that the module will comply with FCC requ supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device into which the module will be a supplying circuitry in the device will be a supplying circuitry in the supplying circuitry in the supply in the supplying circuitry in the supplying circuitry in the supplying circuitry in the supply in the supplying circuitry in the supplying circuitry in the supply in the suppl | irements regardless of the design | of the power | ⊠ - YES | ☐ - NO(*) |
| Details: The module contains its own power supply regulation. Please refer to schematic filed with this application. | | | | |
| 4. The modular transmitter must comply with the ante 15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929 attached or employ a "unique" antenna coupler (a antenna, including the cable). The "professional in to modules but can apply to limited modular appro | (b). The antenna must either be pout all connections between the modustallation" provision of § 15.203 | ermanently lule and the is not applicable | □ - YES | ⊠ - NO(*) |
| Details: EUT used a permanently attached PCB a approved with this device may be found in user's | | | of antennas t | ested and |
| 5. The modular transmitter must be tested in a standarinside another device during testing. This is intend complying with Part 15 emission limits regardless. Unless the transmitter module will be battery power requirements found in Section 15.207. AC or DC pthe module must not contain ferrites, unless they w 15.27(a)). The length of these lines shall be length least 10 centimeters to insure that there is no coupl equipment. Any accessories, peripherals, or supportshall be unmodified or commercially available (see | ed to demonstrate that the module of the device into which it is even ered, it must comply with the AC power lines and data input/output will be marketed with the module (typical of actual use or, if that lending between the case of the modurt equipment connected to the modurt equipment connected to the modure. | e is capable of atually installed. line conducted lines connected to see Section agth is unknown, at le and supporting dule during testing | □ - YES | ⊠ - NO(*) |
| Details: The modular transmitter has been perfortesting as a stand-alone and then confirmed the c in the test set photo. | | | | |

Beijing Roborock Technology Co., Ltd.

| | Modular Approval Requirement | Require | ment Met |
|----|---|------------------|-----------|
| 6. | The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). | Require | ment Met |
| | If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. | □ - YES | ⊠ - NO(*) |
| | If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi) | | |
| | Details: Since there is no space which indicates FCC ID on this module, FCC ID is indicated in a manual and Packing. | | king. |
| 7. | The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii) | ⊠ - YES | □ - NO(*) |
| | Details: The module complies with FCC Part 15C requirements. Instructions to the OEM installer ar installation manual filed with this application. | re provided in | the |
| 8. | The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii) | ⊠ - YES | □ - NO(*) |
| | Details: The module meets Portable exclusion levels as shown in the RF exposure information filed w | vith this applic | cation. |

Beijing Roborock Technology Co., Ltd.

Limited Module Description – When Applicable

* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: Yes, all these requirements will show in the manual and operation description.

| Software Considerations - KDB 594280 / KDB 442812 (One of the following 2 items must be applied) | | | |
|--|---|---|---------|
| Requirement | | Requirement Met | |
| 1. | For <u>non-Software Defined Radio</u> transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280. | □ - Provided in Separate Cover Letter | □ - N/A |
| | Details: The firmware of the device can not be modified or adjusted by the end user as | described in operation descr | iption. |
| 2. | For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812. | ☐ - Provided in Separate Cover Letter | □ - N/A |
| | Details: <example -n="" a=""></example> | | |

| Split Modular Requirements | | | |
|---|--|---------|--|
| Requirement | Provided in Manual | | |
| For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained. | ☐ - Provided in Separate Cover Letter | ⊠ - N/A | |
| Details: <example a="" n="" –=""></example> | | | |

| | OFM Into and in 184 | musl Cuidones - VDD 00/2/0 D02 Castian 2 | | | |
|--|--|--|--|--|--|
| OEM Integration Manual Guidance – KDB 996369 D03 Section 2 | | | | | |
| Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures | | | | | |
| fo | r third-parties to use | and/or integrate the module into a host device. | | | |
| Requirement | | | | | |
| | | ⊠ - No, | | | |
| | | If No, and LMA applies, the applicant ca | | | |
| T- 41:: d-1- : d-1 f | | | make the following detailed info public. However there still needs to be basic integration instructions for a users manual and the | | |
| Is this module intended for sale to third parties? | ☐ - YES | information below must still be inclu | information below must still be included in the operational | | |
| | | description. <u>If the applicant wishes to k</u> this will require a separate statement or | | | |
| | | module is not for sale to third partie | | | |
| т. | | instructions are internal confidence in the conf | ential documents. | | |
| | | the manual – See KDB 996369 D03, Section 2 owing information to be in the installation manual. | Modular transmitter | | |
| applicants should include inforr | nation in their instruc | tions for all these items indicating clearly when the | ey are not applicable. For | | |
| | | ndicate "Not Applicable". Also if a module is limit | | | |
| | | he user instructions may not need to be detailed an otion, but this should include a cover letter as cited | | | |
| List of applicable FCC rules. | KDB 996369 D03, Se | ection 2.2 | | | |
| | s related to the transmit | | - | | |
| Summarize the specific opera a. Conditions su | | KDB 996369 D03, Section 2.3 s, cable loss, reduction of power for point to point | | | |
| systems, profe | essional installation inf | 0 | | | |
| 3. Limited Module Procedures. | | | | | |
| a. Describe alter limiting condi | | rantee uses to verify the host meets the necessary | | | |
| b. When RF exp | osure evaluation is nec | essary, state how control will be maintained such | ☐ - All Items shown to | | |
| that complian | ce is ensured, such as C | Class II for new hosts, etc. | the left are provided in the Modular Integration | | |
| 4. Trace antenna designs. KDE | | | Guide (or UM) for Full | | |
| | | enna, connectors, isolation requirements, tests for est procedures for ensuring compliance. If | Modular Approval (MA) or LMA. | | |
| confidential, t | he method used to keep | confidential must be identified and information | of LWA. | | |
| provided in th 5. RF exposure considerations. | e operational description | on. | ☐ - An LMA applies | | |
| | | s that allow host manufacturers to use the module. | and is approved ONLY | | |
| Two types of | instructions are necessa | ary: first to the host manufacturer to define | for use by the grantee in their own products, and | | |
| | obile, portable – xx cm le end user in the host p | from body) and second additional text needed to be | not intended for sale to | | |
| 6. Antennas. KDB 996369 D03 | | roduct manuals. | - 3 rd parties as provided in a separate cover letter. | | |
| | | ication and all applicable professional installer | Therefore the | | |
| | | tenna list shall also identify the antenna types that "omni-directional" is not considered a type) | information shown to the | | |
| 7. Label and compliance inform | nation. KDB 996369 D | 03, Section 2.8 | left is found in the theory of operation. | | |
| | | need to provide a physical or e-label stating | theory or operation. | | |
| | C ID: " with their finished additional testing rec | quirements. KDB 996369 D03, Section 2.9 | | | |
| a. Test modes that should be taken into consideration by host integrators including | | | | | |
| | | ne and simultaneous configurations. gure test modes for evaluation | | | |
| 9. Additional testing, Part 15 Su | | | - | | |
| | | | | | |
| Sincerely, | | | | | |
| A L | uby Hu | | | | |
| By: | | Ruby Hu | | | |
| (Sig | gnature/Title ¹) | (Print name) | • | | |

¹ - Must be signed by applicant contact given for applicant on the FCC site, or by the authorized agent if an appropriate authorized agent letter has been provided. Letters should be placed on appropriate letterhead.