

## FCC TEST REPORT

For

HOYOTOP Technology(Shenzhen)Co.,Ltd

Mobile Business MINI Projector

Model No.: S100

Prepared for : HOYOTOP Technology(Shenzhen)Co.,Ltd  
Address : 9F, Building A, Jingang tech Park, Qiaotou village, Fuyong Town,  
Bao'an, Shenzhen, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an  
District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : November 19, 2016  
Number of tested samples : 1  
Serial number : Prototype  
Date of Test : October 09, 2017~October 23, 2017  
Date of Report : October 23, 2017

**FCC TEST REPORT**  
**FCC CFR 47 PART 15 C(15.247): 2016**

**Report Reference No.** ..... : **LCS1611192238E**

Date of Issue ..... : October 23, 2017

**Testing Laboratory Name**..... : **Shenzhen LCS Compliance Testing Laboratory Ltd.**

Address ..... : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,  
 Bao'an District, Shenzhen, Guangdong, China

Testing Location/ Procedure ..... : Full application of Harmonised standards   
 Partial application of Harmonised standards   
 Other standard testing method

**Applicant's Name**..... : **HOYOTOP Technology(Shenzhen)Co.,Ltd**

Address ..... : 9F, Building A, Jingang tech Park, Qiaotou village, Fuyong Town,  
 Bao'an, Shenzhen, China

**Test Specification**

Standard..... : FCC CFR 47 PART 15 C(15.247): 2016

**Test Report Form No.** ..... : LCSEMC-1.0

TRF Originator ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF ..... : Dated 2011-03

**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**EUT Description.** ..... : **Mobile Business MINI Projector**

Trade Mark..... : HOYOTOP

Model/ Type reference ..... : S100

Ratings ..... : DC 12.6V by battery(2000mAh);  
 Charging parameter: DC 12.0V, 2.0A

Result ..... : **Positive**

**Compiled by:**



Linda He/ File administrators

**Supervised by:**



Dick Su/ Technique principal

**Approved by:**



Gavin Liang/ Manager

### FCC -- TEST REPORT

<b>Test Report No. :</b> LCS1611192238E	<u>October 23, 2017</u> Date of issue
---	--

EUT.....	: Mobile Business MINI Projector
Type / Model.....	: S100
<b>Applicant.....</b>	<b>: HOYOTOP Technology(Shenzhen)Co.,Ltd</b>
Address.....	: 9F, Building A, Jingang tech Park, Qiaotou village, Fuyong Town, Bao'an, Shenzhen, China
Telephone.....	: 0755-29309235
Fax.....	: 0755-29309235
<b>Manufacturer.....</b>	<b>: HOYOTOP Technology(Shenzhen)Co.,Ltd</b>
Address.....	: 9F, Building A, Jingang tech Park, Qiaotou village, Fuyong Town, Bao'an, Shenzhen, China
Telephone.....	: 0755-29309235
Fax.....	: 0755-29309235
<b>Factory.....</b>	<b>: HOYOTOP Technology(Shenzhen)Co.,Ltd</b>
Address.....	: 9F, Building A, Jingang tech Park, Qiaotou village, Fuyong Town, Bao'an, Shenzhen, China
Telephone.....	: 0755-29309235
Fax.....	: 0755-29309235

<b>Test Result</b>	<b>Positive</b>
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

**Revision History**

Revision	Issue Date	Revisions	Revised By
000	October 23, 2017	Initial Issue	Gavin Liang

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION.....</b>	<b>6</b>
1.1. DESCRIPTION OF DEVICE (EUT).....	6
1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS.....	6
1.3. EXTERNAL I/O CABLE.....	6
1.4. DESCRIPTION OF TEST FACILITY.....	7
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	7
1.6. MEASUREMENT UNCERTAINTY.....	7
1.7. DESCRIPTION OF TEST MODES.....	8
<b>2. TEST METHODOLOGY.....</b>	<b>9</b>
2.1. EUT CONFIGURATION.....	9
2.2. EUT EXERCISE.....	9
2.3. GENERAL TEST PROCEDURES.....	9
<b>3. SYSTEM TEST CONFIGURATION.....</b>	<b>10</b>
3.1. JUSTIFICATION.....	10
3.2. EUT EXERCISE SOFTWARE.....	10
3.3. SPECIAL ACCESSORIES.....	10
3.4. BLOCK DIAGRAM/SCHEMATICS.....	10
3.5. EQUIPMENT MODIFICATIONS.....	10
3.6. TEST SETUP.....	10
<b>4. SUMMARY OF TEST RESULTS.....</b>	<b>11</b>
<b>5. TEST RESULT.....</b>	<b>12</b>
5.1. ON TIME AND DUTY CYCLE.....	12
5.2. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT.....	14
5.3. POWER SPECTRAL DENSITY MEASUREMENT.....	16
5.4. 6 DB SPECTRUM BANDWIDTH MEASUREMENT.....	20
5.5. RADIATED EMISSIONS MEASUREMENT.....	24
5.6. CONDUCTED SPURIOUS EMISSIONS AND BAND EDGES TEST.....	37
5.7. POWER LINE CONDUCTED EMISSIONS.....	46
5.8. BAND-EDGE MEASUREMENTS FOR RADIATED EMISSIONS.....	49
5.9. ANTENNA REQUIREMENTS.....	56
<b>6. LIST OF MEASURING EQUIPMENTS.....</b>	<b>58</b>
<b>7. TEST SETUP PHOTOGRAPHS OF EUT.....</b>	<b>59</b>
PLEASE REFER TO TEST SETUP PHOTOGRAPHS OF EUT.....	59
<b>8. EXTERIOR PHOTOGRAPHS OF THE EUT.....</b>	<b>59</b>
PLEASE REFER TO EXTERIOR PHOTOGRAPHS OF EUT.....	59
<b>9. INTERIOR PHOTOGRAPHS OF THE EUT.....</b>	<b>59</b>
PLEASE REFER TO INTERIOR PHOTOGRAPHS OF EUT.....	59

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

EUT	: Mobile Business MINI Projector
Model Number	: S100
Model Declaration	: /
Test Model	: S100
Power Supply	: DC 12.6V by battery(2000mAh); Charging parameter: DC 12.0V, 2.0A
Frequency Range	: 2412.00~2462.00MHz
Channel Number	: 11 Channels for WIFI 20MHz Bandwidth(802.11b/g/n(HT20)); 7 Channels for WIFI 40MHz Bandwidth(802.11n(HT40))
Modulation Technology	: IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK); IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK); IEEE 802.11n: OFDM(64QAM, 16QAM,QPSK,BPSK);
Data Rates	: IEEE 802.11b: 1-11Mbps; IEEE 802.11g: 6-54Mbps; IEEE 802.11n HT20: MCS0-MCS7; IEEE 802.11n HT40: MCS8-MCS15
Antenna Type And Gain	: PIFA antenna, 3.0dBi

### 1.2. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
Shenzhen TDS Electrionc Co., Ltd	AC/DC Adapter	TDTA36U-120300	--	VoC

### 1.3. External I/O Cable

I/O Port Description	Quantity	Cable
DC	1	N/A
TF	1	N/A
USB	2	1.0m, Shielded
HDMI	1	1.2m, Shielded
RJ45	1	0.8m, Unshielded

### 1.4. Description of Test Facility

CNAS Registration Number. is L4595.  
 FCC Registration Number. is CN5024.  
 Industry Canada Registration Number. is 9642A-1.  
 ESMD Registration Number. is ARCB0108.  
 UL Registration Number. is 100571-492.  
 TUV SUD Registration Number. is SCN1081.  
 TUV RH Registration Number. is UA 50296516-001  
 NVLAP Registration Code is 600167-0

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

### 1.5. Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

### 1.6. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	±3.10dB	(1)
	30MHz~200MHz	±2.96dB	(1)
	200MHz~1000MHz	±3.10dB	(1)
	1GHz~26.5GHz	±3.80dB	(1)
	26.5GHz~40GHz	±3.90dB	(1)
Conduction Uncertainty	150kHz~30MHz	±1.63dB	(1)
Power disturbance	30MHz~300MHz	±1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 1.7. Description Of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.

Worst-case mode and channel used for 150kHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, that was determined to be 802.11b mode(High Channel).

Worst-case mode and channel used for 9kHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be 802.11b mode(High Channel).

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case datarates used during the testing are as follows:

802.11b Mode: 1 Mbps, DSSS.

802.11g Mode: 6 Mbps, OFDM.

802.11n Mode HT20: MCS0, OFDM.

802.11n Mode HT40: MCS15, OFDM.

### Channel List & Frequency

#### IEEE 802.11b/g/n(HT20)

Frequency Band	Channel No.	Frequency(MHz)	Channel No.	Frequency(MHz)
2412~2462MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	--	--

#### IEEE 802.11n(HT40)

Frequency Band	Channel No.	Frequency(MHz)	Channel No.	Frequency(MHz)
2422~2452MHz	1	/	7	2442
	2	/	8	2447
	3	2422	9	2452
	4	2427	10	/
	5	2432	11	/
	6	2437	--	--



## 2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd..

### 2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure KDB558074 D01 DTS Meas. Guidance v03r05 and KDB 6622911 are required to be used for this kind of FCC 15.247 digital modulation device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

### 2.3. General Test Procedures

#### 2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013

### 3. SYSTEM TEST CONFIGURATION

#### 3.1. Justification

The system was configured for testing in a continuous transmit condition.

#### 3.2. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software (Realtek\_RF\_MP\_Tool) provided by application.

#### 3.3. Special Accessories

Manufacturer	Description	Model	Serial Number	Certificate
Lenovo	PC	B470	--	DOC
Lenovo	AC/DC ADAPTER	ADP-90DDB	--	DOC

#### 3.4. Block Diagram/Schematics

Please refer to the related document

#### 3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

#### 3.6. Test Setup

Please refer to the test setup photo.

#### 4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart C		
FCC Rules	Description of Test	Result
§15.247(b)	Maximum Conducted Output Power	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	6dB Bandwidth	Compliant
§15.247(a)	Occupied Bandwidth	Compliant
§15.209, §15.247(d)	Radiated and Conducted Spurious Emissions	Compliant
§15.205	Emissions at Restricted Band	Compliant
§15.207(a)	Conducted Emissions	Compliant
§15.203	Antenna Requirements	Compliant
§15.247(i)§2.1093	RF Exposure	Compliant

## 5. TEST RESULT

### 5.1. On Time and Duty Cycle

#### 5.1.1. Standard Applicable

None; for reporting purpose only.


#### 5.1.2. Measuring Instruments and Setting

Please refer to section 6 of equipments list in this report. The following table is the setting of the spectrum analyse.

#### 5.1.3. Test Procedures

1. Set the centre frequency of the spectrum analyse to the transmitting frequency;
2. Set the span=0MHz, RBW=8MHz, VBW=50MHz, Sweep time=5ms;
3. Detector = peak;
4. Trace mode = Single hold.

#### 5.1.4. Test Setup Layout





#### 5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 5.1.6. Test result



Mode	On Time B (ms)	Period (ms)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW(KHz)
IEEE 802.11b	5.0	5.0	1	100	0.00	0.01
IEEE 802.11g	5.0	5.0	1	100	0.00	0.01
IEEE 802.11n(HT20)	5.0	5.0	1	100	0.00	0.01
IEEE 802.11n(HT40)	5.0	5.0	1	100	0.00	0.01

### Test plot of On Time and Duty Cycle



### IEEE 802.11b

### IEEE 802.11g



### IEEE 802.11n(HT20)

### IEEE 802.11n(HT40)

## 5.2. Maximum Conducted Output Power Measurement

### 5.2.1. Standard Applicable

According to §15.247(b): For systems using digital modulation in the 2400-2483.5 MHz and 5725-5850 MHz band, the limit for maximum peak conducted output power is 30dBm. The limit has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter peak output power.

### 5.2.2. Measuring Instruments and Setting

Please refer to section 6 of equipments list in this report. The following table is the setting of the power meter.

### 5.2.3. Test Procedures

According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power, 9.1.2 the maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

According to KDB558074 D01 DTS Measurement Guidance Section 9.2 Maximum average conducted output power, 9.2.3.1 Method AVGPM (Measurement using an RF average power meter)

(a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.


- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
- 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

(b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.

(c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

(d) Adjust the measurement in dBm by adding  $10\log(1/x)$ , where x is the duty cycle to the measurement result.

### 5.2.4. Test Setup Layout



### 5.2.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

## 5.2.6. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	60%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b/g/n

Peak Power					
Mode	Channel	Frequency (MHz)	Conducted Power (Peak, dBm)	Max. Limit (dBm)	Result
IEEE 802.11b	1	2412	15.73	30	Complies
	6	2437	15.58	30	Complies
	11	2462	15.54	30	Complies
IEEE 802.11g	1	2412	16.95	30	Complies
	6	2437	16.64	30	Complies
	11	2462	16.48	30	Complies
IEEE 802.11n (HT20)	1	2412	16.96	30	Complies
	6	2437	16.82	30	Complies
	11	2462	16.97	30	Complies
IEEE 802.11n (HT40)	3	2422	17.04	30	Complies
	6	2437	17.01	30	Complies
	9	2452	17.03	30	Complies

**Remark:**

1. Measured output power at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 135Mbps at IEEE 802.11n HT40

## 5.3. Power Spectral Density Measurement

### 5.3.1. Standard Applicable

According to §15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


### 5.3.2. Measuring Instruments and Setting

Please refer to section 6 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

### 5.3.3. Test Procedures

1. The transmitter was connected directly to a Spectrum Analyzer through a directional coupler.
2. The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
3. Set the RBW = 3 kHz~100kHz.
4. Set the VBW  $\geq 3 \times$  RBW
5. Set the span to 1.5 times the DTS channel bandwidth.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum power level in any 3 kHz band segment within the fundamental EBW.

### 5.3.4. Test Setup Layout



### 5.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



## 5.3.6. Test Result of Power Spectral Density

Temperature	25°C	Humidity	60%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b/g/n


Test Mode	Channel	Frequency (MHz)	Measured Peak Power Spectral Density (dBm/100KHz)	Limits (dBm/3KHz)	Verdict
IEEE 802.11b	1	2412	2.840	8	PASS
	6	2437	2.734		
	11	2462	2.417		
IEEE 802.11g	1	2412	-4.056	8	PASS
	6	2437	-4.360		
	11	2462	-4.156		
IEEE 802.11n HT20	1	2412	-4.005	8	PASS
	6	2437	-4.125		
	11	2462	-4.163		
IEEE 802.11n HT40	3	2422	-7.302	8	PASS
	6	2437	-7.371		
	9	2452	-7.152		

**Remark:**


1. Measured output power at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 135Mbps at IEEE 802.11n HT40
4. please refer to following plots;

Test plot of Power Spectral Density


IEEE 802.11b




IEEE 802.11g




Low channel




Low channel



Middle channel



Middle channel




High channel


High channel

Test plot of Power Spectral Density


IEEE 802.11n HT20




IEEE 802.11n HT40




Low channel




Low channel



Middle channel



Middle channel



High channel

High channel

## 5.4. 6 dB Spectrum Bandwidth Measurement

### 5.4.1. Standard Applicable

According to §15.247(a)(2): For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

### 5.4.2. Measuring Instruments and Setting


Please refer to section 6 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> RBW
Detector	Peak
Trace	Max Hold
Sweep Time	100ms

### 5.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth and the video bandwidth were set according to KDB558074.
3. Measured the spectrum width with power higher than 6dB below carrier.

### 5.4.4. Test Setup Layout



### 5.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

## 5.4.6. Test Result of 6dB Spectrum Bandwidth

Temperature	25°C	Humidity	60%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b/g/n

Test Mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limits (MHz)	Verdict
IEEE 802.11b	1	2412	9.151	0.500	PASS
	6	2437	9.153		
	11	2462	9.151		
IEEE 802.11g	1	2412	16.37	0.500	PASS
	6	2437	16.40		
	11	2462	16.44		
IEEE 802.11n HT20	1	2412	17.62	0.500	PASS
	6	2437	17.66		
	11	2462	17.62		
IEEE 802.11n HT40	3	2422	36.30	0.500	PASS
	6	2437	36.06		
	9	2452	36.10		



**Remark:**

1. Measured output power at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 135Mbps at IEEE 802.11n HT40
4. please refer to following plots;

Test plot of 6 dB Bandwidth



IEEE 802.11b

IEEE 802.11g





Low channel

Low channel



Middle channel

Middle channel





High channel

High channel

Test plot of 6 dB Bandwidth



IEEE 802.11n HT20

IEEE 802.11n HT40





Low channel

Low channel



Middle channel

Middle channel



High channel

High channel

## 5.5. Radiated Emissions Measurement

### 5.5.1. Standard Applicable

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3



### 5.5.2. Measuring Instruments and Setting

Please refer to section 6 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

### 5.5.3. Test Procedures

#### 1) Sequence of testing 9 kHz to 30 MHz

##### **Setup:**

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions.

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

##### **Premeasurement:**

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna height is 0.8 meter.

--- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

##### **Final measurement:**

--- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

### 3) Sequence of testing 1 GHz to 18 GHz

#### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

#### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

#### 4) Sequence of testing above 18 GHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.


##### Premeasurement:

- The antenna is moved spherical over the EUT in different polarisations of the antenna.

##### Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

5.5.4. Test Setup Layout



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$  (dB);  
Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

5.5.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.5.6. Results of Radiated Emissions (9kHz~30MHz)

Temperature	25°C	Humidity	60%
Test Engineer	Jayden Zhuo	Configurations	802.11b/g/n

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = 40 log (specific distance / test distance) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

5.5.7. Results of Radiated Emissions (30MHz~1GHz)

Temperature	25°C	Humidity	60%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b (High CH)


Test result for IEEE 802.11b (High Channel)



Env./Ins: 24°C / 56%  
 pol: VERTICAL

	Freq MHz	Reading dBuV	CabLos dB	Antfac dB/m	Measured dBuV/m	Limit dBuV/m	Over dB	Remark
1	70.74	25.64	0.55	8.52	34.71	40.00	-5.29	QP
2	139.61	27.38	0.75	8.22	36.35	43.50	-7.15	QP
3	212.36	26.29	0.93	10.96	38.18	43.50	-5.32	QP
4	257.95	24.46	1.01	12.05	37.52	46.00	-8.48	QP
5	622.67	17.03	1.49	18.53	37.05	46.00	-8.95	QP
6	742.95	15.56	1.78	19.35	36.69	46.00	-9.31	QP

Note: 1. All readings are Quasi-peak values.  
 2. Measured= Reading + Antenna Factor + Cable Loss  
 3. The emission that at 20db blow the official limit are not reported



Env./Ins: 24°C/56%  
 pol: HORIZONTAL

	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	170.65	28.00	0.80	9.02	37.82	43.50	-5.68	QP
2	212.36	27.45	0.93	10.96	39.34	43.50	-4.16	QP
3	253.10	25.71	0.90	12.06	38.67	46.00	-7.33	QP
4	480.08	20.87	1.31	16.07	38.25	46.00	-7.75	QP
5	600.36	18.64	1.43	18.45	38.52	46.00	-7.48	QP
6	742.95	20.48	1.78	19.35	41.61	46.00	-4.39	QP

Note: 1. All readings are Quasi-peak values.  
 2. Measured= Reading + Antenna Factor + Cable Loss  
 3. The emission that are 20db below the official limit are not reported

Note:

- 1). Pre-scan all mode and recorded the worst case results in this report (IEEE 802.11b (High Channel)).  
 Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 2). Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



## 5.5.8. Results for Radiated Emissions (Above 1GHz)

IEEE 802.11b

## Channel 1 / 2412MHz

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4824.00	57.10	33.06	35.04	3.94	59.06	74	-14.94	Peak	Horizontal
4824.00	43.26	33.06	35.04	3.94	45.22	54	-8.78	Average	Horizontal
4824.00	55.80	33.06	35.04	3.94	57.76	74	-16.24	Peak	Vertical
4824.00	41.46	33.06	35.04	3.94	43.42	54	-10.58	Average	Vertical

## Channel 6 / 2437MHz

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4874.00	57.98	33.16	35.15	3.96	59.95	74	-14.05	Peak	Horizontal
4874.00	43.26	33.16	35.15	3.96	45.23	54	-8.77	Average	Horizontal
4874.00	55.69	33.16	35.15	3.96	57.66	74	-16.34	Peak	Vertical
4874.00	41.11	33.16	35.15	3.96	43.08	54	-10.92	Average	Vertical

## Channel 11 / 2462MHz

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4924.00	57.05	33.26	35.14	3.98	59.15	74	-14.85	Peak	Horizontal
4924.00	43.34	33.26	35.14	3.98	45.44	54	-8.56	Average	Horizontal
4924.00	55.69	33.26	35.14	3.98	57.79	74	-16.21	Peak	Vertical
4924.00	40.96	33.26	35.14	3.98	43.06	54	-10.94	Average	Vertical

IEEE 802.11g

Channel 1 / 2412MHz

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4824.00	56.83	33.06	35.04	3.94	58.79	74	-15.21	Peak	Horizontal
4824.00	41.29	33.06	35.04	3.94	43.25	54	-10.75	Average	Horizontal
4824.00	55.18	33.06	35.04	3.94	57.14	74	-16.86	Peak	Vertical
4824.00	40.82	33.06	35.04	3.94	42.78	54	-11.22	Average	Vertical

Channel 6 / 2437MHz

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4874.00	56.50	33.16	35.15	3.96	58.47	74	-15.53	Peak	Horizontal
4874.00	41.26	33.16	35.15	3.96	43.23	54	-10.77	Average	Horizontal
4874.00	55.25	33.16	35.15	3.96	57.22	74	-16.78	Peak	Vertical
4874.00	40.07	33.16	35.15	3.96	42.04	54	-11.96	Average	Vertical

Channel 11 / 2462MHz

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4924.00	56.26	33.26	35.14	3.98	58.36	74	-15.64	Peak	Horizontal
4924.00	40.92	33.26	35.14	3.98	43.02	54	-10.98	Average	Horizontal
4924.00	55.65	33.26	35.14	3.98	57.75	74	-16.25	Peak	Vertical
4924.00	40.01	33.26	35.14	3.98	42.11	54	-11.89	Average	Vertical

IEEE 802.11n HT20

Channel 1 / 2412MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	55.29	33.06	35.04	3.94	57.25	74	-16.75	Peak	Horizontal
4824.00	41.10	33.06	35.04	3.94	43.06	54	-10.94	Average	Horizontal
4824.00	54.48	33.06	35.04	3.94	56.44	74	-17.56	Peak	Vertical
4824.00	40.75	33.06	35.04	3.94	42.71	54	-11.29	Average	Vertical

Channel 6 / 2437MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	55.30	33.16	35.15	3.96	57.27	74	-16.73	Peak	Horizontal
4874.00	41.91	33.16	35.15	3.96	43.88	54	-10.12	Average	Horizontal
4874.00	54.59	33.16	35.15	3.96	56.56	74	-17.44	Peak	Vertical
4874.00	40.11	33.16	35.15	3.96	42.08	54	-11.92	Average	Vertical

Channel 11 / 2462MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	55.02	33.26	35.14	3.98	57.12	74	-16.88	Peak	Horizontal
4924.00	41.34	33.26	35.14	3.98	43.44	54	-10.56	Average	Horizontal
4924.00	54.69	33.26	35.14	3.98	56.79	74	-17.21	Peak	Vertical
4924.00	40.29	33.26	35.14	3.98	42.39	54	-11.61	Average	Vertical

IEEE 802.11n HT40

Channel 3 / 2422MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4844.00	55.05	33.06	35.04	3.94	57.01	74	-16.99	Peak	Horizontal
4844.00	41.77	33.06	35.04	3.94	43.73	54	-10.27	Average	Horizontal
4844.00	53.29	33.06	35.04	3.94	55.25	74	-18.75	Peak	Vertical
4844.00	39.50	33.06	35.04	3.94	41.46	54	-12.54	Average	Vertical

Channel 6 / 2437MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	55.18	33.16	35.15	3.96	57.15	74	-16.85	Peak	Horizontal
4874.00	41.47	33.16	35.15	3.96	43.44	54	-10.56	Average	Horizontal
4874.00	53.31	33.16	35.15	3.96	55.28	74	-18.72	Peak	Vertical
4874.00	39.34	33.16	35.15	3.96	41.31	54	-12.69	Average	Vertical

Channel 9 / 2452MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4904.00	54.98	33.26	35.14	3.98	57.08	74	-16.92	Peak	Horizontal
4904.00	41.02	33.26	35.14	3.98	43.12	54	-10.88	Average	Horizontal
4904.00	53.36	33.26	35.14	3.98	55.46	74	-18.54	Peak	Vertical
4904.00	39.59	33.26	35.14	3.98	41.69	54	-12.31	Average	Vertical

**Remark:**

1. Measuring frequencies from 9k~10th harmonic or 26.5GHz (which is less), No emission found between lowest internal used/generated frequency to 30MHz.
2. Radiated emissions measured in frequency range from 9k~10th harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 135Mbps at IEEE 802.11n HT40

## 5.6. Conducted Spurious Emissions and Band Edges Test

### 5.6.1. Standard Applicable

According to §15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 5.6.2. Measuring Instruments and Setting

Please refer to section 6 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Detector	Peak
Attenuation	Auto
RB / VB (Emission in restricted band)	100KHz/300KHz
RB / VB (Emission in non-restricted band)	100KHz/300KHz

### 5.6.3. Test Procedures

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz

The spectrum from 9kHz to 26.5GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

### 5.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 5.4.4.

### 5.6.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

### 5.6.6. Test Results of Conducted Spurious Emissions

Temperature	25°C	Humidity	60%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b/g/n



Test Mode	Channel	Frequency (MHz)	Spurious RF Conducted Emission (dBc)	Limits (dBc)	Verdict
IEEE 802.11b	1	2412	<-20	-20	PASS
	6	2437	<-20		
	11	2462	<-20		
IEEE 802.11g	1	2412	<-20	-20	PASS
	6	2437	<-20		
	11	2462	<-20		
IEEE 802.11n HT20	1	2412	<-20	-20	PASS
	6	2437	<-20		
	11	2462	<-20		
IEEE 802.11n HT20	3	2402	<-20	-20	PASS
	6	2440	<-20		
	9	2480	<-20		

**Remark:**

5. Measured output power at difference data rate for each mode and recorded worst case for each mode.
6. Test results including cable loss;
7. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 135Mbps at IEEE 802.11n HT20;
8. “---“means that the fundamental frequency not for 15.209 limits requirement.
9. please refer to following plots;



Test plot of Conducted Spurious Emission

IEEE 802.11b





Low channel Reference

Low channel



Middle channel Reference

Middle channel





High channel Reference

High channel



Test plot of Conducted Spurious Emission

IEEE 802.11g





Low channel Reference

Low channel



Middle channel Reference

Middle channel




High channel Reference


High channel




Test plot of Conducted Spurious Emission  
IEEE 802.11n(HT20)




Low channel Reference




Low channel




Middle channel Reference



Middle channel




High channel Reference




High channel


Test plot of Conducted Spurious Emission  
IEEE 802.11n(HT40)




Low channel Reference




Low channel




Middle channel Reference



Middle channel




High channel Reference




High channel

5.6.7. Test Results of Band Edges Test


Test plot of Band Edges Test




IEEE 802.11b-Low channel Reference




IEEE 802.11b-Low channel




IEEE 802.11b-High channel Reference



IEEE 802.11b-High channel





IEEE 802.11g-Low channel Reference



IEEE 802.11g-Low channel





Test plot of Band Edges Test





IEEE 802.11g-High channel Reference

IEEE 802.11g-High channel



IEEE 802.11n(HT20)-Low channel Reference



IEEE 802.11n(HT20)-Low channel



IEEE 802.11n(HT20)-High channel Reference



IEEE 802.11n(HT20)-High channel

Test plot of Band Edges Test



IEEE 802.11n(HT40)-Low channel Reference

IEEE 802.11n(HT40)-Low channel



IEEE 802.11n(HT40)-High channel Reference

IEEE 802.11n(HT40)-High channel


### 5.7. Power line conducted emissions

#### 5.7.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dBµV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

#### 5.7.2 Block Diagram of Test Setup




#### 5.7.3 Test Results

**PASS.**

The test data please refer to following page.




Test result for IEEE 802.11b(AC 120V)



Env. Ins: 24\*/56%  
 Pol: LINE

	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB
1	0.17	29.47	9.59	0.02	10.00	49.08	65.16	-16.08	QP
2	0.17	13.35	9.59	0.02	10.00	32.96	55.16	-22.20	Average
3	0.20	27.65	9.63	0.02	10.00	47.30	63.71	-16.41	QP
4	0.20	8.32	9.63	0.02	10.00	27.97	53.71	-25.74	Average
5	0.25	22.89	9.63	0.03	10.00	42.55	61.78	-19.23	QP
6	0.25	8.20	9.63	0.03	10.00	27.86	51.77	-23.91	Average
7	3.96	17.31	9.65	0.06	10.00	37.02	56.00	-18.98	QP
8	3.96	3.63	9.65	0.06	10.00	23.34	46.00	-22.66	Average
9	8.19	18.63	9.68	0.07	10.00	38.38	60.00	-21.62	QP
10	8.19	6.84	9.68	0.07	10.00	26.59	50.00	-23.41	Average
11	11.20	20.07	9.70	0.09	10.00	39.86	60.00	-20.14	QP
12	11.20	8.76	9.70	0.09	10.00	28.55	50.00	-21.45	Average

Remarks: 1. Measured = Reading +Cable Loss +Aux2 Fac.  
 2. The emission levels that are 20dB below the official limit are not reported.




Env. Ins: 24\*/56%  
 Pol: NEUTRAL

	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB
1	0.17	31.80	9.65	0.02	10.00	51.47	64.94	-13.47	QP
2	0.17	10.27	9.65	0.02	10.00	29.94	54.94	-25.00	Average
3	0.22	27.00	9.59	0.03	10.00	46.62	62.74	-16.12	QP
4	0.22	10.75	9.59	0.03	10.00	30.37	52.74	-22.37	Average
5	0.25	23.46	9.60	0.03	10.00	43.09	61.91	-18.82	QP
6	0.25	9.43	9.60	0.03	10.00	29.06	51.90	-22.84	Average
7	4.05	16.73	9.65	0.06	10.00	36.44	56.00	-19.56	QP
8	4.05	1.28	9.65	0.06	10.00	20.99	46.00	-25.01	Average
9	8.15	19.21	9.70	0.07	10.00	38.98	60.00	-21.02	QP
10	8.15	5.05	9.70	0.07	10.00	24.82	50.00	-25.18	Average
11	11.32	17.67	9.73	0.09	10.00	37.49	60.00	-22.51	QP
12	11.32	7.51	9.73	0.09	10.00	27.33	50.00	-22.67	Average

Remarks: 1. Measured = Reading +Cable Loss +Aux2 Fac.  
 2. The emission levels that are 20dB below the official limit are not reported.


Test result for IEEE 802.11b(AC 240V)



Env. Ins: 24\*/56%  
 Pol: NEUTRAL

	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB
1	0.15	33.99	9.69	0.02	10.00	53.70	65.78	-12.08	QP
2	0.15	17.54	9.69	0.02	10.00	37.25	55.77	-18.52	Average
3	0.21	28.53	9.59	0.03	10.00	48.15	63.18	-15.03	QP
4	0.21	11.63	9.59	0.03	10.00	31.25	53.18	-21.93	Average
5	0.60	14.75	9.63	0.04	10.00	34.42	56.00	-21.58	QP
6	0.60	5.68	9.63	0.04	10.00	25.35	46.00	-20.65	Average
7	4.16	14.29	9.65	0.06	10.00	34.00	56.00	-22.00	QP
8	4.16	-0.99	9.65	0.06	10.00	18.72	46.00	-27.28	Average
9	8.19	17.06	9.70	0.07	10.00	36.83	60.00	-23.17	QP
10	8.19	4.75	9.70	0.07	10.00	24.52	50.00	-25.48	Average
11	11.20	16.22	9.73	0.09	10.00	36.04	60.00	-23.96	QP
12	11.20	6.87	9.73	0.09	10.00	26.69	50.00	-23.31	Average

Remarks: 1. Measured = Reading +Cable Loss +Aux2 Fac.  
 2. The emission levels that are 20dB below the official limit are not reported.



Env. Ins: 24\*/56%  
 Pol: LINE

	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB
1	0.16	33.71	9.58	0.02	10.00	53.31	65.56	-12.25	QP
2	0.16	14.63	9.58	0.02	10.00	34.23	55.55	-21.32	Average
3	0.21	27.23	9.63	0.03	10.00	46.89	63.05	-16.16	QP
4	0.21	11.85	9.63	0.03	10.00	31.51	53.05	-21.54	Average
5	0.25	24.38	9.63	0.03	10.00	44.04	61.91	-17.87	QP
6	0.25	7.88	9.63	0.03	10.00	27.54	51.90	-24.36	Average
7	4.18	15.78	9.65	0.06	10.00	35.49	56.00	-20.51	QP
8	4.18	1.84	9.65	0.06	10.00	21.55	46.00	-24.45	Average
9	8.28	15.80	9.68	0.07	10.00	35.55	60.00	-24.45	QP
10	8.28	3.86	9.68	0.07	10.00	23.61	50.00	-26.39	Average
11	11.08	15.37	9.70	0.09	10.00	35.16	60.00	-24.84	QP
12	11.08	6.97	9.70	0.09	10.00	26.76	50.00	-23.24	Average

Remarks: 1. Measured = Reading +Cable Loss +Aux2 Fac.  
 2. The emission levels that are 20dB below the official limit are not reported.

\*\*\*Note: Pre-scan all mode and recorded the worst case MHz results in this report (IEEE 802.11b).




## 5.8. Band-edge measurements for radiated emissions

### 5.8.1 Standard Applicable

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 5.8.2. Test Setup Layout



### 5.8.3. Measuring Instruments and Setting

Please refer to section 6 of equipment list in this report. The following table is the setting of Spectrum Analyzer.

### 5.8.4. Test Procedures

According to KDB 558074 D01 V03 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=1/B for Peak detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).

7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies  $\leq 30$  MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies  $> 1000$  MHz).
9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

Where:

E = electric field strength in dB $\mu$ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
12. Compare the resultant electric field strength level to the applicable regulatory limit.
13. Perform radiated spurious emission test duress until all measured frequencies were complete.

## 5.8.5 Test Results

IEEE 802.11b						
Freq. MHz	Reading Level dBm	Antenna Gain dBi	Measured E dBuV/m	Limit dBuV/m	Margin dB	Remark
2310.000	-51.091	3.0	47.209	74	-26.791	Peak
2310.000	-59.960	3.0	38.340	54	-15.660	Average
2390.000	-49.331	3.0	48.969	74	-25.031	Peak
2390.000	-58.691	3.0	39.609	54	-14.391	Average
2483.500	-50.256	3.0	48.044	74	-25.956	Peak
2483.500	-59.036	3.0	39.264	54	-14.736	Average
2500.000	-50.899	3.0	47.401	74	-26.599	Peak
2500.000	-59.165	3.0	39.135	54	-14.865	Average

IEEE 802.11g						
Freq. MHz	Reading Level dBm	Antenna Gain dBi	Measured E dBuV/m	Limit dBuV/m	Margin dB	Remark
2310.000	-51.113	3.0	47.187	74	-26.813	Peak
2310.000	-59.828	3.0	38.472	54	-15.528	Average
2390.000	-46.861	3.0	51.439	74	-22.561	Peak
2390.000	-55.649	3.0	42.651	54	-11.349	Average
2483.500	-46.296	3.0	52.004	74	-21.996	Peak
2483.500	-56.845	3.0	41.455	54	-12.545	Average
2500.000	-48.296	3.0	50.004	74	-23.996	Peak
2500.000	-57.587	3.0	40.713	54	-13.287	Average


IEEE 802.11n(HT20)						
Freq. MHz	Reading Level dBm	Antenna Gain dBi	Measured E dBuV/m	Limit dBuV/m	Margin dB	Remark
2310.000	-49.593	3.0	48.707	74	-25.293	Peak
2310.000	-60.166	3.0	38.134	54	-15.866	Average
2390.000	-44.346	3.0	53.954	74	-20.046	Peak
2390.000	-56.514	3.0	41.786	54	-12.214	Average
2483.500	-47.000	3.0	51.300	74	-22.700	Peak
2483.500	-56.868	3.0	41.432	54	-12.568	Average
2500.000	-47.940	3.0	50.360	74	-23.640	Peak
2500.000	-57.805	3.0	40.495	54	-13.505	Average

IEEE 802.11n(HT40)						
Freq. MHz	Reading Level dBm	Antenna Gain dBi	Measured E dBuV/m	Limit dBuV/m	Margin dB	Remark
2310.000	-50.843	3.0	47.457	74	-26.543	Peak
2310.000	-60.564	3.0	37.736	54	-16.264	Average
2390.000	-40.370	3.0	57.930	74	-16.070	Peak
2390.000	-55.183	3.0	43.117	54	-10.883	Average
2483.500	-36.647	3.0	61.653	74	-12.347	Peak
2483.500	-57.164	3.0	41.136	54	-12.864	Average
2500.000	-47.317	3.0	50.983	74	-23.017	Peak
2500.000	-57.530	3.0	40.770	54	-13.230	Average


**Remark:**

1. Measured output power at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20;
4. “---“means that the fundamental frequency not for 15.209 limits requirement.
5. please refer to following plots;


Test plot of Restricted Bands




IEEE 802.11b-Low channel(Peak)




IEEE 802.11b-Low channel(Average)




IEEE 802.11b-High channel(Peak)



IEEE 802.11b-High channel(Average)





IEEE 802.11g-Low channel(Peak)





IEEE 802.11g-Low channel(Average)

Test plot of Restricted Bands





IEEE 802.11g-High channel(Peak)

IEEE 802.11g-High channel(Average)



IEEE 802.11n(HT20)-Low channel(Peak)


IEEE 802.11n(HT20)-Low channel(Average)



IEEE 802.11n(HT20)-High channel(Peak)


IEEE 802.11n(HT20)-High channel(Average)

Test plot of Restricted Bands



IEEE 802.11n(HT40)-Low channel(Peak)

IEEE 802.11n(HT40)-Low channel(Average)



IEEE 802.11n(HT40)-High channel(Peak)

IEEE 802.11n(HT40)-High channel(Average)

## 5.9. Antenna Requirements

### 5.9.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### 5.9.2 Antenna Connected Construction

#### 5.9.2.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 5.9.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting is 3.0dBi, and the antenna is an PIFA antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.

#### 5.9.2.3. Results: Compliance.

### Measurement

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

Conducted power refers ANSI C63.10:2013 Output power test procedure for DTS devices.

Radiated power refers to ANSI C63.10:2013 Radiated emissions tests.

### Measurement parameters

Measurement parameter	
Detector:	Peak
Sweep Time:	Auto
Resolution bandwidth:	1MHz
Video bandwidth:	3MHz
Trace-Mode:	Max hold



**Limits**

FCC	IC
Antenna Gain	
6 dBi	

Note: The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For WLAN devices, the DSSS mode is used;

Tnom	Vnom	Lowest Channel 2412 MHz	Middle Channel 2437 MHz	Highest Channel 2462 MHz
Conducted power [dBm] Measured with DSSS modulation		5.36	5.44	5.27
Radiated power [dBm] Measured with DSSS modulation		8.19	8.10	8.18
Gain [dBi] Calculated		2.83	2.66	2.91
Measurement uncertainty			± 1.6 dB (cond.) / ± 3.8 dB (rad.)	

Result: -/-

## 6. LIST OF MEASURING EQUIPMENTS

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Power Meter	R&S	NRVS	100444	2017-06-17	2018-06-16
2	Power Sensor	R&S	NRV-Z81	100458	2017-06-17	2018-06-16
3	Power Sensor	R&S	NRV-Z32	10057	2017-06-17	2018-06-16
4	EPM Series Power Meter	Agilent	E4419B	MY45104493	2017-06-17	2018-06-16
5	E-SERIES AVG POWER SENSOR	Agilent	E9301H	MY41495234	2017-06-17	2018-06-16
6	ESA-E SERIES SPECTRUM ANALYZER	Agilent	E4407B	MY41440754	2016-11-18	2017-11-17
7	MXA Signal Analyzer	Agilent	N9020A	MY49100040	2017-06-17	2018-06-16
8	SPECTRUM ANALYZER	R&S	FSP	100503	2017-06-17	2018-06-16
9	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2017-06-17	2018-06-16
10	Positioning Controller	MF	MF-7082	/	2017-06-17	2018-06-16
11	EMI Test Software	AUDIX	E3	N/A	2017-06-17	2018-06-16
12	EMI Test Receiver	ROHDE & SCHWARZ	ESR 7	101181	2017-06-17	2018-06-16
13	AMPLIFIER	QuieTek	QTK-A2525G	CHM10809065	2016-11-18	2017-11-17
14	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2017-06-23	2018-06-22
15	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2017-05-02	2018-05-01
16	Horn Antenna	EMCO	3115	6741	2017-06-23	2018-06-22
17	Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	2017-06-23	2018-06-22
18	RF Cable-R03m	Jye Bao	RG142	CB021	2017-06-17	2018-06-16
19	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2017-06-17	2018-06-16
20	TEST RECEIVER	R&S	ESCI	101142	2017-06-17	2018-06-16
21	RF Cable-CON	UTIFLEX	3102-26886-4	CB049	2017-06-17	2018-06-16
22	10dB Attenuator	SCHWARZBECK	MTS-IMP136	261115-001-003 2	2017-06-17	2018-06-16
23	Artificial Mains	R&S	ENV216	101288	2017-06-17	2018-06-16

**7. TEST SETUP PHOTOGRAPHS OF EUT**

Please Refer To Test Setup Photographs Of EUT

**8. EXTERIOR PHOTOGRAPHS OF THE EUT**

Please Refer To Exterior Photographs Of EUT

**9. INTERIOR PHOTOGRAPHS OF THE EUT**

Please Refer To Interior Photographs Of EUT

-----THE END OF REPORT-----