



TEST REPORT

Applicant Name : Address :

Report Number :

FCC ID:

M5Stack Technology Co.,Ltd 5F, Tangwei Stock Commercial Building, Youli Road, Bao'an District, Shenzhen, China RA230410-18058E-MPE 2AN3WM5CM4STACK

Test Standard (s)

FCC PART 1.1307 and FCC Part 2.1091

Sample Description

M5CM4Stack			
CM4Stack			
MSSTACK			
2023-04-10			
2023-05-22			

Test Result:

Pass*

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Lipa. Wu

Lipa Wu EMC Engineer

Approved By:

Candry . Li

Candy Li EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "*.

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: +86 755-26503290 Fax: +86 755-26503290 Web: www.atc-lab.com

Version 47: 2023-01-30

FCC-MPE

Shenzhen Accurate Technology Co., Ltd.

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
FCC §1.1307 & §2.1091- RF EXPOSURE	4
TEST RESULT:	5

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230410-18058E-MPE	Original Report	2023-05-22

FCC §1.1307 & §2.1091- RF EXPOSURE

Applicable Standard

According to KDB 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.4 – MPE-Based Exemption:

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

Table to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R ² .
1.34-30	3,450 R ² /f ² .
30-300	3.83 R ² .
300-1,500	0.0128 R ² f.
1,500-100,000	19.2R ² .

f = frequency in MHz;

R = minimum separation distance from the body of a nearby person (appropriate units, e.g., m);

Test Result:

For worst case:

Mode	Frequency Range	Output Power*		Antenna Gain*		ERP		Evaluation Distance	ERP Limit
1,10uc	(MHz)	(dBm)	(mW)	(dBi)	(dBd)	(dBm)	(mW)	(cm)	(mW)
BT	2402-2480	7.0	5.01	3.5	1.35	8.35	6.84	20	768
BLE	2402-2480	5.0	3.16	3.5	1.35	6.35	4.32	20	768
2.4G WIFI	2412-2462	15.5	35.48	3.5	1.35	16.85	48.42	20	768
5G WIFI	5150-5250	17.0	50.12	2.5	0.35	17.35	54.33	20	768
5G WIFI	5250-5350	17.5	56.23	2.5	0.35	17.85	60.95	20	768
5G WIFI	5470-5725	18.5	70.79	2.5	0.35	18.85	76.74	20	768
5G WIFI	5725-5850	18.0	63.10	2.5	0.35	18.35	68.39	20	768

Note 1: Please refer to the FCC ID: 2ABCB-RPIRM0 for the output power and antenna gain, which was provided by the applicant. Note 2: 0dBd=2.15dBi.

Note 3: BT/BLE/2.4G WIFI/5G WIFI can not transmit simultaneously

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

*****END OF REPORT*****