



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247

TEST REPORT

For

M5Stack Technology Co., Ltd

106, 1st Floor, Building 1, Bright Technology Park, 88 Zhuguang North Road, Xili Taoyuan Street, Nanshan District, Shenzhen, Guangdong, China

FCC ID: 2AN3WM5COREINK

| | |
|--|---|
| Report Type: Original Report | Product Type: CoreInk |
| Test Engineer: | CK Huang <i>CK Huang</i> |
| Report Number: | RSHD200901001-00A |
| Report Date: | 2020-09-21 |
| Reviewed By: | Oscar Ye EMC Manager <i>Oscar.Ye</i> |
| Prepared By: | Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn |

TABLE OF CONTENTS

GENERAL INFORMATION.....4

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)4

 OBJECTIVE4

 RELATED SUBMITTAL(S)/GRANT(S).....4

 TEST METHODOLOGY4

 MEASUREMENT UNCERTAINTY5

 TEST FACILITY5

SYSTEM TEST CONFIGURATION6

 DESCRIPTION OF TEST CONFIGURATION6

 EQUIPMENT MODIFICATIONS6

 EUT EXERCISE SOFTWARE7

 SUPPORT EQUIPMENT LIST AND DETAILS11

 EXTERNAL I/O CABLE.....11

 BLOCK DIAGRAM OF TEST SETUP11

SUMMARY OF TEST RESULTS13

TEST EQUIPMENT LIST14

FCC §15.247 (I) & §1.1310 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)15

 APPLICABLE STANDARD15

 CALCULATED FORMULARY:.....15

 CALCULATED DATA:.....15

FCC §15.203 - ANTENNA REQUIREMENT.....16

 APPLICABLE STANDARD16

 ANTENNA CONNECTOR CONSTRUCTION16

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS17

 APPLICABLE STANDARD17

 EUT SETUP17

 EMI TEST RECEIVER SETUP.....17

 TEST PROCEDURE18

 FACTOR & OVER LIMIT CALCULATION.....18

 TEST RESULTS SUMMARY18

 TEST DATA18

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....23

 APPLICABLE STANDARD23

 EUT SETUP23

 EMI TEST RECEIVER SETUP.....24

 TEST PROCEDURE24

 CORRECTED AMPLITUDE & MARGIN CALCULATION24

 TEST RESULTS SUMMARY24

 TEST DATA25

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....55

 APPLICABLE STANDARD55

 TEST PROCEDURE55

 TEST DATA55

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....65

 APPLICABLE STANDARD65

| | |
|--|-----------|
| TEST PROCEDURE | 65 |
| TEST DATA | 66 |
| FCC §15.247(d) – BAND EDGE..... | 69 |
| APPLICABLE STANDARD | 69 |
| TEST PROCEDURE | 69 |
| TEST DATA | 69 |
| FCC §15.247(e) - POWER SPECTRAL DENSITY | 75 |
| APPLICABLE STANDARD | 75 |
| TEST PROCEDURE | 75 |
| TEST DATA | 75 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

| | |
|---------------------------|--|
| Applicant: | M5Stack Technology Co., Ltd |
| Product Type: | CoreInk |
| Tested Model: | CoreInk |
| Power Supply: | DC 3.7 V from battery or DC 5.0 V |
| RF Function: | 2.4G Wi-Fi, BLE(1Mbps) |
| Operating Band/Frequency: | 2.4G Wi-Fi: 2412-2462 MHz BLE(1Mbps): 2402-2480 MHz |
| Channel Number: | 2.4G Wi-Fi: 11, BLE(1Mbps): 40 |
| Channel Separation: | 2.4G Wi-Fi: 5 MHz, BLE(1Mbps): 2 MHz |
| Modulation Type: | Wi-Fi: OFDM,DSSS; BLE(1Mbps): GFSK |
| Antenna Type: | Wi-Fi/BLE: PIFA Antenna |
| Maximum Antenna Gain: | Wi-Fi/BLE: 2.0 dBi |

**All measurement and test data in this report was gathered from production sample serial number: 20200901001. (Assigned by the BACL. The EUT supplied by the applicant was received on 2020-09-01)*

Objective

This report is prepared on behalf of *M5Stack Technology Co., Ltd* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS submissions with FCC ID: 2AN3WM5COREINK.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

| Item | | Uncertainty |
|------------------------------------|-------------|-------------|
| AC Power Lines Conducted Emissions | | 3.19dB |
| RF conducted test with spectrum | | 0.9dB |
| RF Output Power with Power meter | | 0.5dB |
| Radiated emission | 30MHz~1GHz | 6.11dB |
| | 1GHz~6GHz | 4.45dB |
| | 6GHz~18GHz | 5.23dB |
| | 18GHz~40GHz | 5.65dB |
| Occupied Bandwidth | | 0.5kHz |
| Temperature | | 1.0°C |
| Humidity | | 6% |

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Test channel list is as below:

For 802.11b, 802.11g and 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11;

For 802.11n-HT40 mode, EUT was tested with Channel 3, 6 and 9;

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1 | 2412 | 7 | 2442 |
| 2 | 2417 | 8 | 2447 |
| 3 | 2422 | 9 | 2452 |
| 4 | 2427 | 10 | 2457 |
| 5 | 2432 | 11 | 2462 |
| 6 | 2437 | / | / |

For BLE mode, EUT was tested with channel 0, 19 and 39.

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 0 | 2402 | 20 | 2442 |
| 1 | 2404 | ... | ... |
| ... | ... | ... | ... |
| ... | ... | ... | ... |
| 18 | 2438 | 38 | 2478 |
| 19 | 2440 | 39 | 2480 |

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software


RF test software: EspRFtestTool

Pre-scan with all the data rates, and the worst case was performed as below:


| Mode | Data Rate | Power Level |
|--------------|-----------|-------------|
| 802.11b | 1 Mbps | 5 |
| 802.11g | 6 Mbps | 6 |
| 802.11n-HT20 | MCS0 | 5 |
| 802.11n-HT40 | MCS0 | 10 |
| BLE | 1Mbps | 6 |

Duty Cycle:


802.11b Mode Middle Channel




802.11g Mode Middle Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT40 Mode Middle Channel



BLE Mode Middle Channel-1



BLE Mode Middle Channel-2



| Mode | Duty Cycle (%) | T(ms) | 1/T(kHz) | 10log(1/x) |
|--------------|----------------|--------|----------|------------|
| 802.11b | 100.00 | / | / | 0.00 |
| 802.11g | 100.00 | / | / | 0.00 |
| 802.11n-HT20 | 100.00 | / | / | 0.00 |
| 802.11n-HT40 | 100.00 | / | / | 0.00 |
| BLE | 88.11 | 10.677 | 0.09 | 0.55 |

Note: “x” means the Duty Cycle.

Support Equipment List and Details


| Manufacturer | Description | Model | Serial Number |
|--------------------|-------------|------------|---------------|
| DELL | Notebook | GX620 | D65874152 |
| DELL | Adapter | LA65NS0-00 | DF263 |
| M5Stack Technology | Sensor | unknown | unknown |

External I/O Cable


| Cable Description | Shielding Type | Length (m) | From Port | To |
|-------------------|----------------|------------|-----------|--------|
| USB Cable | Un-shielding | 1.0 | Notebook | EUT |
| Data cable | Un-shielding | 0.1 | EUT | Sensor |

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|--------------------------------|------------------------------------|---------------|
| §15.247 (I), §1.1310 & §2.1091 | MAXIMUM PERMISSIBLE EXPOSURE (MPE) | Compliant |
| §15.203 | Antenna Requirement | Compliant |
| §15.207 (a) | AC Line Conducted Emissions | Compliant |
| §15.247(d) | Spurious Emissions at Antenna Port | Compliant |
| §15.205, §15.209, §15.247(d) | Spurious Emissions | Compliant |
| §15.247 (a)(2) | 6 dB Emission Bandwidth | Compliant |
| §15.247(b)(3) | Maximum Conducted Output Power | Compliant |
| §15.247(d) | Band Edge | Compliant |
| §15.247(e) | Power Spectral Density | Compliant |

TEST EQUIPMENT LIST

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--|--------------------|-----------|------------------------|------------------|----------------------|
| Radiated Emission Test (Chamber 1#) | | | | | |
| Rohde & Schwarz | EMI Test Receiver | ESCI | 100195 | 2019-12-14 | 2020-12-13 |
| Sunol Sciences | Broadband Antenna | JB3 | A090413-1 | 2017-12-26 | 2020-12-25 |
| Sonoma Instrument | Pre-amplifier | 310N | 171205 | 2020-08-14 | 2021-08-13 |
| Rohde & Schwarz | Auto test Software | EMC32 | 100361 | / | / |
| MICRO-COAX | Coaxial Cable | Cable-8 | 008 | 2020-08-15 | 2021-08-14 |
| MICRO-COAX | Coaxial Cable | Cable-9 | 009 | 2020-08-15 | 2021-08-14 |
| MICRO-COAX | Coaxial Cable | Cable-10 | 010 | 2020-08-15 | 2021-08-14 |
| Radiated Emission Test (Chamber 2#) | | | | | |
| Rohde & Schwarz | EMI Test Receiver | ESU40 | 100207 | 2020-04-01 | 2021-03-31 |
| ETS-LINDGREN | Horn Antenna | 3115 | 6229 | 2020-01-10 | 2023-01-09 |
| ETS-LINDGREN | Horn Antenna | 3116 | 00084159 | 2019-10-18 | 2022-10-17 |
| A.H.Systems,inc | Amplifier | PAM-0118P | 512 | 2020-02-20 | 2021-02-19 |
| EM Electronics Corporation | Amplifier | EM18G40G | 060726 | 2020-03-22 | 2021-03-21 |
| MICRO-TRONICS | Band Reject Filter | BRM50702 | G024 | 2020-08-05 | 2021-08-04 |
| Narda | Attenuator | 10dB | 010 | 2020-08-15 | 2021-08-14 |
| Rohde & Schwarz | Auto test Software | EMC32 | 100361 | / | / |
| MICRO-COAX | Coaxial Cable | Cable-6 | 006 | 2019-12-12 | 2020-12-11 |
| MICRO-COAX | Coaxial Cable | Cable-11 | 011 | 2020-08-15 | 2021-08-14 |
| MICRO-COAX | Coaxial Cable | Cable-12 | 012 | 2020-08-15 | 2021-08-14 |
| MICRO-COAX | Coaxial Cable | Cable-13 | 013 | 2020-08-15 | 2021-08-14 |
| RF Conducted Test | | | | | |
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 836131/009 | 2019-12-14 | 2020-12-13 |
| Narda | Attenuator | 10dB | 010 | 2020-08-15 | 2021-08-14 |
| Agilent | Power Meter | N1912A | MY5000492 | 2019-11-18 | 2020-11-17 |
| Agilent | Power Sensor | N1921A | MY54210024 | 2019-11-18 | 2020-11-17 |
| M5Stack Technology | RF Cable | 01 | M5Stack Technology C01 | Each Time | / |
| Conducted Emission Test | | | | | |
| Rohde & Schwarz | EMI Test Receiver | ESR | 1316.3003K03-101746-zn | 2019-12-14 | 2020-12-13 |
| Rohde & Schwarz | LISN | ENV216 | 3560655016 | 2019-11-30 | 2020-11-29 |
| Audix | Test Software | e3 | V9 | -- | -- |
| Rohde & Schwarz | Pulse limiter | ESH3-Z2 | 0357.8810.54 | 2020-08-10 | 2021-08-09 |
| MICRO-COAX | Coaxial Cable | Cable-15 | 015 | 2020-08-15 | 2021-08-14 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (I) & §1.1310 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1310, 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

| Limits for General Population/Uncontrolled Exposure | | | | |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minutes) |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | | f/1500 | 30 |
| 1500-100,000 | / | | 1.0 | 30 |

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

| Mode | Frequency Range (MHz) | Maximum Antenna Gain | | Tune-up Conducted Power | | Evaluation Distance (cm) | Power Density (mW/cm ²) | MPE Limit (mW/cm ²) |
|--------------|-----------------------|----------------------|-----------|-------------------------|--------|--------------------------|-------------------------------------|---------------------------------|
| | | (dBi) | (numeric) | (dBm) | (mW) | | | |
| 802.11b | 2412-2462 | 2.00 | 1.58 | 25.50 | 354.81 | 20 | 0.1115 | 1.0 |
| 802.11g | | 2.00 | 1.58 | 24.00 | 251.19 | 20 | 0.0789 | 1.0 |
| 802.11n-HT20 | | 2.00 | 1.58 | 24.00 | 251.19 | 20 | 0.0789 | 1.0 |
| 802.11n-HT40 | 2422-2452 | 2.00 | 1.58 | 23.50 | 223.87 | 20 | 0.0704 | 1.0 |
| BLE | 2402-2480 | 2.00 | 1.58 | 5.50 | 3.55 | 20 | 0.0011 | 1.0 |
| BT | 2402-2480 | 2.00 | 1.58 | 9.50 | 8.91 | 20 | 0.0028 | 1.0 |

Note: 1. For the above tune up power were declared by the manufacturer.

2. Wi-Fi and BT/BLE can't transmit simultaneously.

Result: The device meet FCC MPE at 20 cm distance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an internal PIFA antenna for WIFI&BLE, which the antenna gain is 2.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Attenuator. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Attenuator (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data

Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 24.6 °C |
| Relative Humidity: | 51 % |
| ATM Pressure: | 101.5 kPa |


The testing was performed by CK Huang 2020-09-09.

Test Result: Compliant.

For Wi-Fi Mode:

EUT operation mode: Transmitting in 802.11b mode low channel (worst case)


AC 120V/60 Hz, Line



| | Freq | Read Level | Factor | Level | Limit Line | Over Limit | Remark |
|----|--------|------------|--------|-------|------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | |
| 1 | 0.573 | 12.90 | 19.75 | 32.65 | 46.00 | -13.35 | Average |
| 2 | 0.573 | 17.30 | 19.75 | 37.05 | 56.00 | -18.95 | QP |
| 3 | 0.763 | 1.80 | 19.72 | 21.52 | 46.00 | -24.48 | Average |
| 4 | 0.763 | 5.40 | 19.72 | 25.12 | 56.00 | -30.88 | QP |
| 5 | 1.153 | 3.00 | 19.81 | 22.81 | 46.00 | -23.19 | Average |
| 6 | 1.153 | 6.80 | 19.81 | 26.61 | 56.00 | -29.39 | QP |
| 7 | 1.216 | 3.30 | 19.81 | 23.11 | 46.00 | -22.89 | Average |
| 8 | 1.216 | 8.60 | 19.81 | 28.41 | 56.00 | -27.59 | QP |
| 9 | 1.619 | -1.00 | 19.84 | 18.84 | 46.00 | -27.16 | Average |
| 10 | 1.619 | 2.50 | 19.84 | 22.34 | 56.00 | -33.66 | QP |
| 11 | 20.486 | -2.80 | 19.93 | 17.13 | 50.00 | -32.87 | Average |
| 12 | 20.486 | -0.10 | 19.93 | 19.83 | 60.00 | -40.17 | QP |

AC 120V/60 Hz, Neutral

Date: 2020-09-09




| | Freq | Read Level | Factor | Level | Limit Line | Over Limit | Remark |
|----|-------|------------|--------|-------|------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | |
| 1 | 0.173 | -0.60 | 19.83 | 19.23 | 54.81 | -35.58 | Average |
| 2 | 0.173 | 11.70 | 19.83 | 31.53 | 64.81 | -33.28 | QP |
| 3 | 0.226 | -1.70 | 19.82 | 18.12 | 52.61 | -34.49 | Average |
| 4 | 0.226 | 9.10 | 19.82 | 28.92 | 62.61 | -33.69 | QP |
| 5 | 0.285 | -3.90 | 19.82 | 15.92 | 50.68 | -34.76 | Average |
| 6 | 0.285 | 4.30 | 19.82 | 24.12 | 60.68 | -36.56 | QP |
| 7 | 0.585 | 1.80 | 19.75 | 21.55 | 46.00 | -24.45 | Average |
| 8 | 0.585 | 10.10 | 19.75 | 29.85 | 56.00 | -26.15 | QP |
| 9 | 1.016 | -2.80 | 19.82 | 17.02 | 46.00 | -28.98 | Average |
| 10 | 1.016 | 0.80 | 19.82 | 20.62 | 56.00 | -35.38 | QP |
| 11 | 1.282 | 2.60 | 19.82 | 22.42 | 46.00 | -23.58 | Average |
| 12 | 1.282 | 10.10 | 19.82 | 29.92 | 56.00 | -26.08 | QP |

For BLE Mode:

EUT operation mode: Transmitting in high channel (worst case)


AC 120V/60 Hz, Line



| | Read Freq | Read Level | Read Factor | Limit Level | Limit Line | Over Limit | Remark |
|----|-----------|------------|-------------|-------------|------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | |
| 1 | 0.582 | 12.60 | 19.75 | 32.35 | 46.00 | -13.65 | Average |
| 2 | 0.582 | 17.40 | 19.75 | 37.15 | 56.00 | -18.85 | QP |
| 3 | 0.792 | 2.51 | 19.70 | 22.21 | 46.00 | -23.79 | Average |
| 4 | 0.792 | 5.61 | 19.70 | 25.31 | 56.00 | -30.69 | QP |
| 5 | 1.172 | 2.10 | 19.81 | 21.91 | 46.00 | -24.09 | Average |
| 6 | 1.172 | 5.50 | 19.81 | 25.31 | 56.00 | -30.69 | QP |
| 7 | 1.276 | 3.00 | 19.82 | 22.82 | 46.00 | -23.18 | Average |
| 8 | 1.276 | 7.90 | 19.82 | 27.72 | 56.00 | -28.28 | QP |
| 9 | 1.707 | -0.70 | 19.84 | 19.14 | 46.00 | -26.86 | Average |
| 10 | 1.707 | 2.90 | 19.84 | 22.74 | 56.00 | -33.26 | QP |
| 11 | 20.270 | -2.30 | 19.94 | 17.64 | 50.00 | -32.36 | Average |
| 12 | 20.270 | 0.80 | 19.94 | 20.74 | 60.00 | -39.26 | QP |

AC 120V/60 Hz, Neutral

Date: 2020-09-09



| | Read Freq | Read Level | Factor | Level | Limit Line | Over Limit | Remark |
|----|-----------|------------|--------|-------|------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | |
| 1 | 0.155 | 0.40 | 19.82 | 20.22 | 55.74 | -35.52 | Average |
| 2 | 0.155 | 12.00 | 19.82 | 31.82 | 65.74 | -33.92 | QP |
| 3 | 0.238 | -2.40 | 19.82 | 17.42 | 52.17 | -34.75 | Average |
| 4 | 0.238 | 7.30 | 19.82 | 27.12 | 62.17 | -35.05 | QP |
| 5 | 0.317 | -1.80 | 19.82 | 18.02 | 49.79 | -31.77 | Average |
| 6 | 0.317 | 3.20 | 19.82 | 23.02 | 59.79 | -36.77 | QP |
| 7 | 0.555 | -1.00 | 19.75 | 18.75 | 46.00 | -27.25 | Average |
| 8 | 0.555 | 5.10 | 19.75 | 24.85 | 56.00 | -31.15 | QP |
| 9 | 0.817 | -3.19 | 19.70 | 16.51 | 46.00 | -29.49 | Average |
| 10 | 0.817 | 1.11 | 19.70 | 20.81 | 56.00 | -35.19 | QP |
| 11 | 1.289 | 1.40 | 19.82 | 21.22 | 46.00 | -24.78 | Average |
| 12 | 1.289 | 5.80 | 19.82 | 25.62 | 56.00 | -30.38 | QP |


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

| Frequency Range | RBW | Video B/W | IF B/W | Detector |
|-------------------|---------|-----------|---------|----------|
| 30 MHz – 1000 MHz | 120 kHz | 300 kHz | 120 kHz | QP |
| Above 1GHz | 1MHz | 3 MHz | / | PK |
| | 1MHz | 3 MHz | / | Ave. |

Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection mode for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V /m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V /m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

| | |
|---------------------------|-----------------|
| Temperature: | 24.1~25.5 °C |
| Relative Humidity: | 50~52 % |
| ATM Pressure: | 101.1~101.5 kPa |

The testing was performed by CK Huang from 2020-09-14 to 2020-09-16.

Test Result: Compliant.


EUT operation mode: Transmitting

For Wi-Fi Mode:

Spurious Emission Test:

30MHz-1GHz:

Pre-Scan with 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case **low channel of 802.11b Mode in Y-axis of orientation** was recorded



| Frequency (MHz) | Corrected Amplitude | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | Quasi-peak (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 44.53 | 30.99 | 100.0 | V | 89.0 | -14.3 | 40.00 | 9.01 |
| 66.06 | 15.64 | 100.0 | V | 57.0 | -18.0 | 40.00 | 24.36 |
| 79.53 | 15.22 | 100.0 | V | 21.0 | -18.2 | 40.00 | 24.78 |
| 87.05 | 15.45 | 100.0 | V | 158.0 | -18.0 | 40.00 | 24.55 |
| 142.93 | 16.13 | 100.0 | H | 182.0 | -12.5 | 43.50 | 27.37 |
| 205.36 | 15.80 | 100.0 | V | 195.0 | -12.7 | 43.50 | 27.70 |

1GHz-18GHz:

802.11b Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
 Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

Low Channel: 2412MHz


Full Spectrum



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBµV/m) | Average (dBµV/m) | Height (cm) | Polar (H/V) | | | | |
| 1402.90 | --- | 23.48 | 150.0 | H | 356.0 | -16.9 | 54.00 | 30.52 |
| 1402.90 | 32.23 | --- | 150.0 | H | 356.0 | -16.9 | 74.00 | 41.77 |
| 4824.00 | 49.70 | --- | 150.0 | V | 160.0 | -5.5 | 74.00 | 24.30 |
| 4824.00 | --- | 42.57 | 150.0 | V | 160.0 | -5.5 | 54.00 | 11.43 |
| 8656.80 | --- | 38.65 | 150.0 | V | 84.0 | 1.5 | 54.00 | 15.35 |
| 8656.80 | 48.06 | --- | 150.0 | V | 84.0 | 1.5 | 74.00 | 25.94 |
| 11432.90 | --- | 39.79 | 150.0 | V | 122.0 | 2.8 | 54.00 | 14.21 |
| 11432.90 | 48.59 | --- | 150.0 | V | 122.0 | 2.8 | 74.00 | 25.41 |
| 13998.20 | --- | 41.90 | 150.0 | H | 288.0 | 6.1 | 54.00 | 12.10 |
| 13998.20 | 51.63 | --- | 150.0 | H | 288.0 | 6.1 | 74.00 | 22.37 |
| 17668.50 | 54.83 | --- | 150.0 | V | 283.0 | 8.9 | 74.00 | 19.17 |
| 17668.50 | --- | 48.01 | 150.0 | V | 283.0 | 8.9 | 54.00 | 5.99 |

Middle Channel: 2437MHz


Full Spectrum



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBμV/m) | Average (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 1545.70 | --- | 25.22 | 150.0 | V | 311.0 | -16.2 | 54.00 | 28.78 |
| 1545.70 | 38.81 | --- | 150.0 | V | 311.0 | -16.2 | 74.00 | 35.19 |
| 3499.00 | --- | 32.11 | 150.0 | V | 105.0 | -8.8 | 54.00 | 21.89 |
| 3499.00 | 39.70 | --- | 150.0 | V | 105.0 | -8.8 | 74.00 | 34.30 |
| 4874.00 | 54.81 | --- | 150.0 | V | 341.0 | -5.4 | 74.00 | 19.19 |
| 4874.00 | --- | 44.82 | 150.0 | V | 341.0 | -5.4 | 54.00 | 9.18 |
| 7709.90 | --- | 37.76 | 150.0 | H | 133.0 | 1.4 | 54.00 | 16.24 |
| 7709.90 | 47.36 | --- | 150.0 | H | 133.0 | 1.4 | 74.00 | 26.64 |
| 12344.10 | --- | 40.38 | 150.0 | V | 0.0 | 3.2 | 54.00 | 13.62 |
| 12344.10 | 49.80 | --- | 150.0 | V | 0.0 | 3.2 | 74.00 | 24.20 |
| 17328.50 | --- | 47.02 | 150.0 | V | 222.0 | 8.3 | 54.00 | 6.98 |
| 17328.50 | 56.08 | --- | 150.0 | V | 222.0 | 8.3 | 74.00 | 17.92 |

High Channel: 2462MHz

Full Spectrum



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBμV/m) | Average (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 1312.80 | 31.54 | --- | 150.0 | V | 319.0 | -17.4 | 74.00 | 42.46 |
| 1312.80 | --- | 22.73 | 150.0 | V | 319.0 | -17.4 | 54.00 | 31.27 |
| 3553.40 | --- | 29.68 | 150.0 | H | 50.0 | -8.6 | 54.00 | 24.32 |
| 3553.40 | 38.32 | --- | 150.0 | H | 50.0 | -8.6 | 74.00 | 35.68 |
| 4924.00 | --- | 41.58 | 150.0 | V | 186.0 | -5.3 | 54.00 | 12.42 |
| 4924.00 | 49.94 | --- | 150.0 | V | 186.0 | -5.3 | 74.00 | 24.06 |
| 8087.30 | 46.83 | --- | 150.0 | V | 342.0 | 1.7 | 74.00 | 27.17 |
| 8087.30 | --- | 38.01 | 150.0 | V | 342.0 | 1.7 | 54.00 | 15.99 |
| 14139.30 | --- | 42.03 | 150.0 | H | 103.0 | 6.2 | 54.00 | 11.97 |
| 14139.30 | 50.22 | --- | 150.0 | H | 103.0 | 6.2 | 74.00 | 23.78 |
| 17532.50 | --- | 45.37 | 150.0 | V | 135.0 | 8.9 | 54.00 | 8.63 |
| 17532.50 | 50.84 | --- | 150.0 | V | 135.0 | 8.9 | 74.00 | 23.16 |

802.11g Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
 Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

Low Channel: 2412MHz


Full Spectrum



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBµV/m) | Average (dBµV/m) | Height (cm) | Polar (H/V) | | | | |
| 1416.50 | --- | 23.35 | 150.0 | H | 157.0 | -16.8 | 54.00 | 30.65 |
| 1416.50 | 32.68 | --- | 150.0 | V | 276.0 | -16.8 | 74.00 | 41.32 |
| 4824.00 | --- | 41.64 | 150.0 | V | 209.0 | -5.5 | 54.00 | 12.36 |
| 4824.00 | 49.43 | --- | 150.0 | V | 209.0 | -5.5 | 74.00 | 24.57 |
| 7184.60 | --- | 37.91 | 150.0 | V | 69.0 | 0.3 | 54.00 | 16.09 |
| 7184.60 | 47.63 | --- | 150.0 | V | 69.0 | 0.3 | 74.00 | 26.37 |
| 10640.70 | --- | 39.40 | 150.0 | H | 297.0 | 2.5 | 54.00 | 14.60 |
| 10640.70 | 48.46 | --- | 150.0 | V | 31.0 | 2.5 | 74.00 | 25.54 |
| 14219.20 | --- | 42.09 | 150.0 | V | 43.0 | 6.3 | 54.00 | 11.91 |
| 14219.20 | 51.88 | --- | 150.0 | H | 130.0 | 6.3 | 74.00 | 22.12 |
| 17685.50 | 53.94 | --- | 150.0 | H | 272.0 | 8.9 | 74.00 | 20.06 |
| 17685.50 | --- | 47.62 | 150.0 | H | 272.0 | 8.9 | 54.00 | 6.38 |

Middle Channel: 2437MHz


Full Spectrum



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBμV/m) | Average (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 1329.80 | --- | 24.60 | 150.0 | V | 44.0 | -17.3 | 54.00 | 29.40 |
| 1329.80 | 34.19 | --- | 150.0 | V | 44.0 | -17.3 | 74.00 | 39.81 |
| 3915.50 | --- | 31.78 | 150.0 | H | 181.0 | -7.3 | 54.00 | 22.22 |
| 3915.50 | 41.62 | --- | 150.0 | H | 181.0 | -7.3 | 74.00 | 32.38 |
| 4874.00 | --- | 43.04 | 150.0 | V | 185.0 | -5.4 | 54.00 | 10.96 |
| 4874.00 | 50.78 | --- | 150.0 | V | 185.0 | -5.4 | 74.00 | 23.22 |
| 12158.80 | --- | 39.45 | 150.0 | V | 0.0 | 3.5 | 54.00 | 14.55 |
| 12158.80 | 49.62 | --- | 150.0 | V | 0.0 | 3.5 | 74.00 | 24.38 |
| 14610.20 | --- | 42.55 | 150.0 | V | 3.0 | 6.2 | 54.00 | 11.45 |
| 14610.20 | 52.20 | --- | 150.0 | H | 36.0 | 6.2 | 74.00 | 21.80 |
| 17678.70 | 53.67 | --- | 150.0 | H | 359.0 | 8.9 | 74.00 | 20.33 |
| 17678.70 | --- | 47.61 | 150.0 | H | 359.0 | 8.9 | 54.00 | 6.39 |

High Channel: 2462MHz

Full Spectrum



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBµV/m) | Average (dBµV/m) | Height (cm) | Polar (H/V) | | | | |
| 1365.50 | --- | 23.84 | 150.0 | H | 354.0 | -17.1 | 54.00 | 30.16 |
| 1365.50 | 32.95 | --- | 150.0 | H | 354.0 | -17.1 | 74.00 | 41.05 |
| 3238.90 | --- | 32.45 | 150.0 | H | 0.0 | -9.5 | 54.00 | 21.55 |
| 3238.90 | 41.10 | --- | 150.0 | H | 0.0 | -9.5 | 74.00 | 32.90 |
| 4924.00 | 50.58 | --- | 150.0 | V | 139.0 | -5.3 | 74.00 | 23.42 |
| 4924.00 | --- | 44.33 | 150.0 | V | 139.0 | -5.3 | 54.00 | 9.67 |
| 12288.00 | --- | 40.63 | 150.0 | V | 151.0 | 3.3 | 54.00 | 13.37 |
| 12288.00 | 49.54 | --- | 150.0 | V | 151.0 | 3.3 | 74.00 | 24.46 |
| 14623.80 | --- | 42.76 | 150.0 | V | 253.0 | 6.2 | 54.00 | 11.24 |
| 14623.80 | 53.29 | --- | 150.0 | V | 253.0 | 6.2 | 74.00 | 20.71 |
| 17636.20 | 54.21 | --- | 150.0 | H | 149.0 | 8.9 | 74.00 | 19.79 |
| 17636.20 | --- | 48.96 | 150.0 | V | 102.0 | 8.9 | 54.00 | 5.04 |


802.11n-HT20 Mode:

(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
 Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)


Low Channel : 2412MHz



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBµV/m) | Average (dBµV/m) | Height (cm) | Polar (H/V) | | | | |
| 1669.80 | 34.25 | --- | 150.0 | V | 67.0 | -15.7 | 74.00 | 39.75 |
| 1669.80 | --- | 25.25 | 150.0 | H | 262.0 | -15.7 | 54.00 | 28.75 |
| 3371.50 | --- | 31.75 | 150.0 | H | 313.0 | -9.1 | 54.00 | 22.25 |
| 3371.50 | 39.91 | --- | 150.0 | V | 54.0 | -9.1 | 74.00 | 34.09 |
| 4824.00 | 47.24 | --- | 150.0 | V | 241.0 | -5.5 | 74.00 | 26.76 |
| 4824.00 | --- | 41.63 | 150.0 | V | 241.0 | -5.5 | 54.00 | 12.37 |
| 9146.40 | --- | 39.40 | 150.0 | H | 262.0 | 2.0 | 54.00 | 14.60 |
| 9146.40 | 50.50 | --- | 150.0 | H | 262.0 | 2.0 | 74.00 | 23.50 |
| 14707.10 | --- | 44.93 | 150.0 | V | 0.0 | 5.9 | 54.00 | 9.07 |
| 14707.10 | 52.92 | --- | 150.0 | V | 0.0 | 5.9 | 74.00 | 21.08 |
| 17612.40 | 53.34 | --- | 150.0 | V | 123.0 | 8.9 | 74.00 | 20.66 |
| 17614.10 | --- | 47.68 | 150.0 | H | 90.0 | 8.9 | 54.00 | 6.32 |

Middle Channel: 2437MHz


Full Spectrum



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBμV/m) | Average (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 1457.30 | --- | 23.47 | 150.0 | V | 284.0 | -16.6 | 54.00 | 30.53 |
| 1457.30 | 32.05 | --- | 150.0 | V | 284.0 | -16.6 | 74.00 | 41.95 |
| 3531.30 | --- | 31.98 | 150.0 | V | 98.0 | -8.7 | 54.00 | 22.02 |
| 3531.30 | 41.70 | --- | 150.0 | V | 98.0 | -8.7 | 74.00 | 32.30 |
| 4874.00 | --- | 44.85 | 150.0 | V | 187.0 | -5.4 | 54.00 | 9.15 |
| 4874.00 | 50.59 | --- | 150.0 | V | 187.0 | -5.4 | 74.00 | 23.41 |
| 9658.10 | --- | 38.12 | 150.0 | V | 47.0 | 2.1 | 54.00 | 15.88 |
| 9658.10 | 48.73 | --- | 150.0 | V | 47.0 | 2.1 | 74.00 | 25.27 |
| 13780.60 | --- | 42.50 | 150.0 | V | 34.0 | 5.9 | 54.00 | 11.50 |
| 13780.60 | 52.55 | --- | 150.0 | V | 34.0 | 5.9 | 74.00 | 21.45 |
| 17573.30 | 54.86 | --- | 150.0 | V | 324.0 | 8.9 | 74.00 | 19.14 |
| 17573.30 | --- | 48.24 | 150.0 | V | 324.0 | 8.9 | 54.00 | 5.76 |

High Channel : 2462MHz

Full Spectrum



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBμV/m) | Average (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 1340.00 | 33.82 | --- | 150.0 | H | 237.0 | -17.2 | 74.00 | 40.18 |
| 1340.00 | --- | 23.18 | 150.0 | H | 237.0 | -17.2 | 54.00 | 30.82 |
| 4924.00 | --- | 43.06 | 150.0 | V | 189.0 | -5.3 | 54.00 | 10.94 |
| 4924.00 | 49.15 | --- | 150.0 | V | 189.0 | -5.3 | 74.00 | 24.85 |
| 7720.10 | --- | 39.35 | 150.0 | V | 138.0 | 1.4 | 54.00 | 14.65 |
| 7720.10 | 47.36 | --- | 150.0 | V | 138.0 | 1.4 | 74.00 | 26.64 |
| 10506.40 | --- | 37.26 | 150.0 | V | 189.0 | 2.3 | 54.00 | 16.74 |
| 10506.40 | 47.43 | --- | 150.0 | V | 189.0 | 2.3 | 74.00 | 26.57 |
| 14661.20 | --- | 43.61 | 150.0 | H | 0.0 | 6.1 | 54.00 | 10.39 |
| 14661.20 | 53.09 | --- | 150.0 | H | 0.0 | 6.1 | 74.00 | 20.91 |
| 17660.00 | --- | 47.66 | 150.0 | V | 125.0 | 8.9 | 54.00 | 6.34 |
| 17660.00 | 54.26 | --- | 150.0 | V | 125.0 | 8.9 | 74.00 | 19.74 |


802.11n-HT40 Mode:

(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)
 Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)


Low Channel : 2422MHz



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBµV/m) | Average (dBµV/m) | Height (cm) | Polar (H/V) | | | | |
| 1598.40 | --- | 27.88 | 150.0 | V | 194.0 | -16.0 | 54.00 | 26.12 |
| 1598.40 | 38.67 | --- | 150.0 | V | 194.0 | -16.0 | 74.00 | 35.33 |
| 4844.00 | 47.84 | --- | 150.0 | V | 105.0 | -5.5 | 74.00 | 26.16 |
| 4844.00 | --- | 40.11 | 150.0 | V | 105.0 | -5.5 | 54.00 | 13.89 |
| 7968.30 | --- | 37.89 | 150.0 | V | 81.0 | 1.8 | 54.00 | 16.11 |
| 7968.30 | 47.23 | --- | 150.0 | V | 81.0 | 1.8 | 74.00 | 26.77 |
| 10343.20 | --- | 39.92 | 150.0 | V | 39.0 | 2.2 | 54.00 | 14.08 |
| 10343.20 | 48.16 | --- | 150.0 | V | 39.0 | 2.2 | 74.00 | 25.84 |
| 13291.00 | --- | 43.44 | 150.0 | H | 276.0 | 5.5 | 54.00 | 10.56 |
| 13291.00 | 51.87 | --- | 150.0 | H | 276.0 | 5.5 | 74.00 | 22.13 |
| 17867.40 | 52.76 | --- | 150.0 | H | 94.0 | 8.8 | 74.00 | 21.24 |
| 17867.40 | --- | 48.41 | 150.0 | H | 94.0 | 8.8 | 54.00 | 5.59 |

Middle Channel: 2437MHz


Full Spectrum



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBμV/m) | Average (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 1596.70 | --- | 31.44 | 150.0 | V | 164.0 | -16.0 | 54.00 | 22.56 |
| 1596.70 | 37.94 | --- | 150.0 | V | 164.0 | -16.0 | 74.00 | 36.06 |
| 3500.70 | --- | 31.57 | 150.0 | H | 0.0 | -8.8 | 54.00 | 22.43 |
| 3500.70 | 40.27 | --- | 150.0 | H | 0.0 | -8.8 | 74.00 | 33.73 |
| 4862.40 | 47.04 | --- | 150.0 | V | 126.0 | -5.5 | 74.00 | 26.96 |
| 4862.40 | --- | 35.50 | 150.0 | V | 126.0 | -5.5 | 54.00 | 18.50 |
| 10302.40 | --- | 38.54 | 150.0 | H | 315.0 | 2.2 | 54.00 | 15.46 |
| 10302.40 | 47.94 | --- | 150.0 | H | 315.0 | 2.2 | 74.00 | 26.06 |
| 13874.10 | --- | 45.05 | 150.0 | H | 89.0 | 6.0 | 54.00 | 8.95 |
| 13874.10 | 52.50 | --- | 150.0 | H | 89.0 | 6.0 | 74.00 | 21.50 |
| 17838.50 | 54.90 | --- | 150.0 | V | 39.0 | 8.8 | 74.00 | 19.10 |
| 17838.50 | --- | 48.73 | 150.0 | V | 39.0 | 8.8 | 54.00 | 5.27 |

High Channel : 2452MHz

Full Spectrum




| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBμV/m) | Average (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 1544.00 | --- | 25.15 | 150.0 | H | 135.0 | -16.2 | 54.00 | 28.85 |
| 1544.00 | 34.47 | --- | 150.0 | H | 135.0 | -16.2 | 74.00 | 39.53 |
| 4904.00 | --- | 38.80 | 150.0 | V | 210.0 | -5.4 | 54.00 | 15.20 |
| 4904.00 | 46.47 | --- | 150.0 | V | 210.0 | -5.4 | 74.00 | 27.53 |
| 8804.70 | --- | 36.33 | 150.0 | H | 135.0 | 1.7 | 54.00 | 17.67 |
| 8804.70 | 47.05 | --- | 150.0 | H | 135.0 | 1.7 | 74.00 | 26.95 |
| 11679.40 | --- | 38.89 | 150.0 | V | 116.0 | 3.2 | 54.00 | 15.11 |
| 11679.40 | 49.27 | --- | 150.0 | V | 116.0 | 3.2 | 74.00 | 24.73 |
| 16232.00 | --- | 44.72 | 150.0 | V | 0.0 | 5.2 | 54.00 | 9.28 |
| 16232.00 | 52.63 | --- | 150.0 | V | 0.0 | 5.2 | 74.00 | 21.37 |
| 17671.90 | --- | 48.17 | 150.0 | V | 261.0 | 8.9 | 54.00 | 5.83 |
| 17671.90 | 54.25 | --- | 150.0 | V | 261.0 | 8.9 | 74.00 | 19.75 |

18GHz-25GHz:


Pre-scan with 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case low channel of 802.11b mode in Z-axis of orientation was recorded

Horizontal



Date: 14.SEP.2020 22:00:28

Vertical



Date: 14.SEP.2020 21:30:02

Restricted Bands Emissions Test:

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)

Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

802.11b Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded)

| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBµV/m) | Average (dBµV/m) | Height (cm) | Polar (H/V) | | | | |
| Low Channel: 2412MHz | | | | | | | | |
| 2390.00 | 55.86 | --- | 200.0 | V | 0.0 | -2.9 | 74.00 | 18.14 |
| 2390.00 | --- | 47.94 | 200.0 | V | 0.0 | -2.9 | 54.00 | 6.06 |
| High Channel: 2462MHz | | | | | | | | |
| 2483.50 | --- | 46.43 | 200.0 | V | 358.0 | -2.5 | 54.00 | 7.57 |
| 2483.50 | 56.10 | --- | 200.0 | V | 358.0 | -2.5 | 74.00 | 17.90 |

802.11g Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded)

| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBµV/m) | Average (dBµV/m) | Height (cm) | Polar (H/V) | | | | |
| Low Channel: 2412MHz | | | | | | | | |
| 2390.00 | 56.25 | --- | 150.0 | V | 193.0 | -2.9 | 74.00 | 17.75 |
| 2390.00 | --- | 49.67 | 150.0 | V | 193.0 | -2.9 | 54.00 | 4.33 |
| High Channel: 2462MHz | | | | | | | | |
| 2483.50 | 57.92 | --- | 200.0 | V | 347.0 | -2.5 | 74.00 | 16.08 |
| 2483.50 | --- | 49.42 | 200.0 | V | 347.0 | -2.5 | 54.00 | 4.58 |

802.11n-HT20 Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBµV/m) | Average (dBµV/m) | Height (cm) | Polar (H/V) | | | | |
| Low Channel: 2412MHz | | | | | | | | |
| 2390.00 | --- | 50.71 | 150.0 | V | 224.0 | -2.9 | 54.00 | 3.29 |
| 2390.00 | 59.63 | --- | 150.0 | V | 224.0 | -2.9 | 74.00 | 14.37 |
| High Channel: 2462MHz | | | | | | | | |
| 2483.50 | 57.44 | --- | 150.0 | V | 222.0 | -2.5 | 74.00 | 16.56 |
| 2483.50 | --- | 51.11 | 150.0 | V | 222.0 | -2.5 | 54.00 | 2.89 |

802.11n-HT40 Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)


| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBµV/m) | Average (dBµV/m) | Height (cm) | Polar (H/V) | | | | |
| Low Channel: 2422MHz | | | | | | | | |
| 2390.00 | 56.81 | --- | 200.0 | V | 258.0 | -2.9 | 74.00 | 17.19 |
| 2390.00 | --- | 50.65 | 200.0 | V | 258.0 | -2.9 | 54.00 | 3.35 |
| High Channel: 2452MHz | | | | | | | | |
| 2483.50 | --- | 50.24 | 150.0 | V | 242.0 | -2.5 | 54.00 | 3.76 |
| 2483.50 | 57.89 | --- | 150.0 | V | 242.0 | -2.5 | 74.00 | 16.11 |

For BLE Mode:

Spurious Emission Test:

30MHz-1GHz:

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **high** channel of operation in the X axis of orientation was recorded)



| Frequency (MHz) | Corrected Amplitude | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | Quasi-peak (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 37.16 | 23.50 | 100.0 | V | 14.0 | -9.2 | 40.00 | 26.50 |
| 44.41 | 32.39 | 100.0 | V | 45.0 | -14.2 | 40.00 | 7.61 |
| 66.66 | 18.70 | 100.0 | V | 98.0 | -17.9 | 40.00 | 21.30 |
| 79.50 | 17.77 | 100.0 | V | 72.0 | -18.2 | 40.00 | 22.23 |
| 89.80 | 16.51 | 200.0 | V | 30.0 | -17.9 | 43.50 | 26.99 |
| 203.69 | 16.55 | 100.0 | V | 172.0 | -12.8 | 43.50 | 26.95 |


1GHz-18GHz

(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
 Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)


Low Channel: 2402MHz



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBµV/m) | Average (dBµV/m) | Height (cm) | Polar (H/V) | | | | |
| 1493.00 | --- | 25.08 | 150.0 | V | 114.0 | -16.4 | 54.00 | 28.92 |
| 1493.00 | 32.94 | --- | 150.0 | V | 114.0 | -16.4 | 74.00 | 41.06 |
| 3648.60 | --- | 30.86 | 150.0 | H | 0.0 | -8.3 | 54.00 | 23.14 |
| 3648.60 | 39.80 | --- | 150.0 | H | 0.0 | -8.3 | 74.00 | 34.20 |
| 4804.00 | --- | 33.66 | 150.0 | V | 152.0 | -5.6 | 54.00 | 20.34 |
| 4804.00 | 42.93 | --- | 150.0 | H | 182.0 | -5.6 | 74.00 | 31.07 |
| 8670.40 | --- | 38.73 | 150.0 | V | 114.0 | 1.5 | 54.00 | 15.27 |
| 8670.40 | 47.81 | --- | 150.0 | V | 114.0 | 1.5 | 74.00 | 26.19 |
| 14069.60 | --- | 42.94 | 150.0 | H | 90.0 | 6.2 | 54.00 | 11.06 |
| 14069.60 | 51.96 | --- | 150.0 | H | 90.0 | 6.2 | 74.00 | 22.04 |
| 17382.90 | 55.23 | --- | 150.0 | V | 24.0 | 8.5 | 74.00 | 18.77 |
| 17382.90 | --- | 48.41 | 150.0 | V | 24.0 | 8.5 | 54.00 | 5.59 |

Middle Channel: 2440MHz


Full Spectrum



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBμV/m) | Average (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 1579.70 | --- | 25.39 | 150.0 | H | 194.0 | -16.1 | 54.00 | 28.61 |
| 1579.70 | 34.38 | --- | 150.0 | H | 194.0 | -16.1 | 74.00 | 39.62 |
| 4880.00 | 46.90 | --- | 150.0 | V | 174.0 | -5.4 | 74.00 | 27.10 |
| 4880.00 | --- | 43.40 | 150.0 | V | 174.0 | -5.4 | 54.00 | 10.60 |
| 6757.90 | --- | 36.15 | 150.0 | V | 200.0 | -0.6 | 54.00 | 17.85 |
| 6757.90 | 46.42 | --- | 150.0 | V | 200.0 | -0.6 | 74.00 | 27.58 |
| 9722.70 | --- | 39.56 | 150.0 | H | 257.0 | 2.0 | 54.00 | 14.44 |
| 9722.70 | 47.25 | --- | 150.0 | H | 257.0 | 2.0 | 74.00 | 26.75 |
| 13263.80 | --- | 42.62 | 150.0 | H | 345.0 | 5.5 | 54.00 | 11.38 |
| 13263.80 | 52.21 | --- | 150.0 | H | 345.0 | 5.5 | 74.00 | 21.79 |
| 17450.90 | 53.83 | --- | 150.0 | V | 98.0 | 8.7 | 74.00 | 20.17 |
| 17450.90 | --- | 48.45 | 150.0 | V | 98.0 | 8.7 | 54.00 | 5.55 |

High Channel: 2480MHz

Full Spectrum




| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBμV/m) | Average (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 1792.20 | --- | 25.75 | 150.0 | V | 335.0 | -15.3 | 54.00 | 28.25 |
| 1792.20 | 34.34 | --- | 150.0 | V | 335.0 | -15.3 | 74.00 | 39.66 |
| 4960.00 | 45.71 | --- | 150.0 | V | 161.0 | -5.3 | 74.00 | 28.29 |
| 4960.00 | --- | 39.71 | 150.0 | V | 161.0 | -5.3 | 54.00 | 14.29 |
| 7198.20 | --- | 39.41 | 150.0 | V | 148.0 | 0.4 | 54.00 | 14.59 |
| 7198.20 | 47.83 | --- | 150.0 | V | 148.0 | 0.4 | 74.00 | 26.17 |
| 10282.00 | --- | 39.55 | 150.0 | V | 0.0 | 2.1 | 54.00 | 14.45 |
| 10282.00 | 48.31 | --- | 150.0 | H | 356.0 | 2.1 | 74.00 | 25.69 |
| 13172.00 | --- | 42.25 | 150.0 | V | 123.0 | 5.4 | 54.00 | 11.75 |
| 13172.00 | 51.63 | --- | 150.0 | H | 339.0 | 5.4 | 74.00 | 22.37 |
| 17399.90 | 55.34 | --- | 150.0 | H | 314.0 | 8.5 | 74.00 | 18.66 |
| 17399.90 | --- | 48.39 | 150.0 | H | 314.0 | 8.5 | 54.00 | 5.61 |

18GHz-25GHz


(The worst case **high channel of operation in the Z axis of orientation** was recorded)

Horizontal



Date: 14.SEP.2020 22:08:54

Vertical



Date: 14.SEP.2020 21:42:48

Restricted Bands Emissions Test:

(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)


Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)

Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)


| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBµV/m) | Average (dBµV/m) | Height (cm) | Polar (H/V) | | | | |
| Low Channel: 2402MHz | | | | | | | | |
| 2390.00 | --- | 44.04 | 200.0 | V | 7.0 | -2.9 | 54.00 | 9.96 |
| 2390.00 | 49.12 | --- | 200.0 | V | 7.0 | -2.9 | 74.00 | 24.88 |
| High Channel: 2480MHz | | | | | | | | |
| 2483.50 | 52.74 | --- | 200.0 | V | 358.0 | -2.5 | 74.00 | 21.26 |
| 2483.50 | --- | 48.56 | 200.0 | V | 358.0 | -2.5 | 54.00 | 5.44 |

Conducted Spurious Emissions at Antenna Port


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

| | |
|---------------------------|----------|
| Temperature: | 24.6 °C |
| Relative Humidity: | 50 % |
| ATM Pressure: | 101.2kPa |

The testing was performed by CK Huang on 2020-09-16.

Test Result: Compliant.

EUT operation mode: Transmitting

| Channel | Frequency (MHz) | 6 dB Emission Bandwidth (MHz) | Limit (MHz) |
|-------------------|-----------------|-------------------------------|-------------|
| 802.11b Mode | | | |
| Low | 2412 | 10.040 | ≥0.5 |
| Middle | 2437 | 10.040 | ≥0.5 |
| High | 2462 | 9.559 | ≥0.5 |
| 802.11g Mode | | | |
| Low | 2412 | 16.413 | ≥0.5 |
| Middle | 2437 | 16.413 | ≥0.5 |
| High | 2462 | 16.413 | ≥0.5 |
| 802.11n-HT20 Mode | | | |
| Low | 2412 | 17.615 | ≥0.5 |
| Middle | 2437 | 17.615 | ≥0.5 |
| High | 2462 | 17.495 | ≥0.5 |
| 802.11n-HT40 Mode | | | |
| Low | 2422 | 36.433 | ≥0.5 |
| Middle | 2437 | 36.313 | ≥0.5 |
| High | 2452 | 36.433 | ≥0.5 |
| BLE Mode | | | |
| Low | 2402 | 0.703 | ≥0.5 |
| Middle | 2440 | 0.697 | ≥0.5 |
| High | 2480 | 0.697 | ≥0.5 |

802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

For Wi-Fi:

According to ANSI C63.10-2013 sub-clause 11.9.1.3


The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.



For BLE:

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW \geq DTS bandwidth.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 3 \times$ RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data**Environmental Conditions**

| | |
|---------------------------|----------|
| Temperature: | 24.6 °C |
| Relative Humidity: | 51% |
| ATM Pressure: | 101.1kPa |


The testing was performed by CK Huang on 2020-09-16.

Test Result: Compliant.


EUT operation mode: Transmitting

| Channel | Frequency (MHz) | Max Conducted Peak Output Power (dBm) | Limit (dBm) | Result |
|-------------------|-----------------|---------------------------------------|-------------|--------|
| 802.11b Mode | | | | |
| Low | 2412 | 25.15 | 30 | Pass |
| Middle | 2437 | 24.78 | 30 | Pass |
| High | 2462 | 24.50 | 30 | Pass |
| 802.11g Mode | | | | |
| Low | 2412 | 23.61 | 30 | Pass |
| Middle | 2437 | 23.89 | 30 | Pass |
| High | 2462 | 23.63 | 30 | Pass |
| 802.11n-HT20 Mode | | | | |
| Low | 2412 | 23.77 | 30 | Pass |
| Middle | 2437 | 23.95 | 30 | Pass |
| High | 2462 | 23.76 | 30 | Pass |
| 802.11n-HT40 Mode | | | | |
| Low | 2422 | 23.10 | 30 | Pass |
| Middle | 2437 | 23.29 | 30 | Pass |
| High | 2452 | 23.17 | 30 | Pass |
| BLE Mode | | | | |
| Low | 2402 | 5.05 | 30 | Pass |
| Middle | 2440 | 5.31 | 30 | Pass |
| High | 2480 | 5.29 | 30 | Pass |


BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(d) – BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions


| | |
|---------------------------|----------|
| Temperature: | 24.6 °C |
| Relative Humidity: | 50 % |
| ATM Pressure: | 101.1kPa |

The testing was performed by CK Huang on 2020-09-16.


Test Result: Compliant.

EUT operation mode: Transmitting


802.11b Mode Left Side




802.11b Mode Right Side




802.11g Mode Left Side




802.11g Mode Right Side




802.11n-HT20 Mode Left Side




802.11n-HT20 Mode Right Side




802.11n-HT40 Mode Left Side




802.11n-HT40 Mode Right Side



BLE Mode Left Side



BLE Mode Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq [3 \times \text{RBW}]$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

| | |
|---------------------------|----------|
| Temperature: | 24.6 °C |
| Relative Humidity: | 50 % |
| ATM Pressure: | 101.1kPa |


The testing was performed by CK Huang on 2020-09-16.

Test Result: Compliant.


EUT operation mode: Transmitting

| Channel | Frequency (MHz) | PSD (dBm/3kHz) | Limit (dBm/3kHz) |
|-------------------|-----------------|----------------|------------------|
| 802.11b mode | | | |
| Low | 2412 | -7.31 | ≤8 |
| Middle | 2437 | -6.04 | ≤8 |
| High | 2462 | -5.99 | ≤8 |
| 802.11g mode | | | |
| Low | 2412 | -10.86 | ≤8 |
| Middle | 2437 | -11.30 | ≤8 |
| High | 2462 | -9.98 | ≤8 |
| 802.11n-HT20 mode | | | |
| Low | 2412 | -10.89 | ≤8 |
| Middle | 2437 | -10.76 | ≤8 |
| High | 2462 | -10.72 | ≤8 |
| 802.11n-HT40 mode | | | |
| Low | 2422 | -14.14 | ≤8 |
| Middle | 2437 | -15.01 | ≤8 |
| High | 2452 | -14.54 | ≤8 |
| BLE mode | | | |
| Low | 2402 | -10.90 | ≤8 |
| Middle | 2440 | -10.64 | ≤8 |
| High | 2480 | -10.62 | ≤8 |


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



Declarations

- 1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.
- 2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
- 3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
- 4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.
- 5: This report cannot be reproduced except in full, without prior written approval of the Company.
- 6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

******* END OF REPORT *******