


RF Exposure Evaluation Report

Product : Pilot Translating Earpiece
Trade mark :  **WAVERLY LABS**
Model/Type reference : V100RR,V100RB,V100RW
Serial Number : N/A
Report Number : EED32J00237206
FCC ID : 2AN4B-WLABSV1PR
Date of Issue : Nov. 23, 2017
47 CFR Part 1.1307
Test Standards : 47 CFR Part 2.1093
KDB447498D01 v06
Test result : PASS

Prepared for:

Waverly Labs Inc.

19 Morris Ave Brooklyn New York United States 11205

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Tested By:

Tom chen

Tom chen (Test Project)

Compiled by:

Kevin lan

Kevin lan (Project Engineer)

Reviewed by:

Kevin Yang

Kevin yang (Reviewer)

Approved by:

Sheek Luo

Sheek Luo (Lab supervisor)

Report Seal

Date:

Nov. 23, 2017

Check No.: 2392114011

2 Version

Version No.	Date	Description
00	Nov. 23, 2017	Original

3 Contents


	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 SAR EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 Standard Requirement.....	6
5.1.2 Limits.....	6
5.1.3 EUT RF Exposure.....	6
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	7

4 General Information

4.1 Client Information

Applicant:	Waverly Labs Inc.
Address of Applicant:	19 Morris Ave Brooklyn New York United States 11205
Manufacturer:	Waverly Labs Inc.
Address of Manufacturer:	19 Morris Ave Brooklyn New York United States 11205
Factory:	ShengHai Electronics (Shenzhen) Ltd.
Address of Factory:	Block 17-19, Hui Ming Ying Industry, Yan Chuan, Song Gang, Baoan County, Shenzhen, China 518105

4.2 General Description of EUT

Product Name:	Pilot Translating Earpiece
Model No.(EUT):	V100RR,V100RB,V100RW
Test Model No.:	V100RR
Trade Mark:	 WAVERLY LABS
EUT Supports Radios application:	BT4.1 Dual mode, 2402-2480MHz

4.3 Product Specification subjective to this standard

Frequency Range:	2402-2480MHz
Modulation Type:	GFSK; 8DPSK; $\pi/4$ DQPSK
Test Power Grade:	Class 1(manufacturer declare)
Test Software of EUT:	Blue Suite 2.4.8(manufacturer declare)
Antenna Type:	Monopole antenna
Antenna Gain:	0dBi
Power Supply:	Lithium-ion button cell:1x3.7V(Z55)=3.7V
Output Power:	8.0dBm
	The Maximum Conducted Output Power is declared by the client
Sample Received Date:	Oct. 25, 2017
Sample tested Date:	Oct. 25, 2017 Nov. 21, 2017
Remark:	<p>The tested sample(s) and the sample information are provided by the client.</p> <p>Model No.: V100RR,V100RB,V100RW</p> <p>Only the model V100RR was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.</p>

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China 518101

Telephone: +86 (0) 755 3368 3668 Fax: +86 (0) 755 3368 3385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v05
Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

The Maximum Conducted Output Power is 8.0dBm declared by the client;

The best case gain of the antenna is 0dBi.

$EIRP = 8.0\text{dBm} + 0\text{dBi} = 8.0\text{dBm}$

8.0dBm logarithmic terms convert to numeric result is nearly 6.310mW

According to the formula. calculate the EIRP test result:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})}$$

General RF Exposure = $(6.310\text{mW} / 5 \text{ mm}) \times \sqrt{2.480\text{GHz}} = 1.987$ ①

SAR requirement:

$S = 3.0$ ② ;

① < ②.

So the SAR report is not required.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32J00237203 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.