



## MPE Test Report

**Report No.:** XKH-18JA2705VTSPB-2

**FCC ID:** 2AN4DM101

**Product:** Pill Box

**Model:** M101

**Received Date:** Feb.02, 2018

**Test Date:** Feb.02 to Mar.03, 2018

**Issued Date:** Mar.08, 2018

**Applicant:** XiaMen ZAYATA Technology Inc.

**Address:** Room 904-6, 9/F, Venture Building, NO.1302 Jimei Avenue, Jimei District, Xiamen, Fujian, China

**Manufacturer:** XiaMen ZAYATA Technology Inc.

**Address:** Room 904-6, 9/F, Venture Building, NO.1302 Jimei Avenue, Jimei District, Xiamen, Fujian, China

**Issued By:** BUREAU VERITAS ADT (Shanghai) Corporation

**Lab Address:** No. 829, Xinzhan Road, Shanghai, P.R.China (201612)

---

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



## Table of Contents

Release Control Record .....	3
1      Certificate of Conformity .....	4
2      General Information .....	5
2.1    General Description of EUT .....	5
3      Test Standards and Limits.....	6
3.1    Limits For FCC Radiofrequency radiation exposure:.....	6
4      Measurement and Calculation .....	7
4.1    Maximum transmit power .....	7



### Release Control Record

Issue No.	Description	Date Issued
XKH-18JA2705VTSPB-2	Original release	Mar.08, 2018



## 1 Certificate of Conformity

**Product:** Pill Box

**Brand:** --

**Model:** M101

**Applicant:** XiaMen ZAYATA Technology Inc.

**Test Date:** Feb.02 to Mar.03, 2018

**Standards:** FCC Part 2 (Section 2.1093)


KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **BUREAU VERITAS ADT (Shanghai) Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**  \_\_\_\_\_, **Date:** Mar.08, 2018

Bing YE

Testing Engineer

**Approved by :**  \_\_\_\_\_, **Date:** Mar.08, 2018

Joy ZHU

Testing Manager



## 2 General Information

### 2.1 General Description of EUT

Product	Pill Box
Brand	--
Test Model	M101
Model Difference	--
Power Rating	2x1.5V BATTERY
Modulation Type	GFSK
Modulation Technology	Bluetooth Low Energy 4.2
Operating Frequency	2.402 ~ 2.480GHz
Number of Channel	40
Antenna Type	PCB antenna
Antenna Connector	--
Antenna Gain	1 dBi

Note: For more details, please refer to the User's manual of the EUT.



### 3 Test Standards and Limits

#### 3.1 Limits For FCC Radiofrequency radiation exposure:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$ 50 mm are determined by:

$[(\text{max power of channel})/(\text{min test separation distance})]^*[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest Mw and mm
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50mm, and for transmission frequencies between 100 MHz and 6GHz. When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm



## 4 Measurement and Calculation

### 4.1 Maximum transmit power

The Power Data is based on the RF Test Report XKH-18JA2705VTSPB-2

CH	Test Channel	Power[dBm]	Max Tune Up Power [dBm]	Max Tune Up Power [mW]	Result	Limit
Low	2402	-5.00	-3.00	0.50	0.155	3
Mid	2440	-4.80	-2.80	0.52	0.162	3
High	2480	-4.59	-2.59	0.55	0.173	3

One antenna is available for the EUT (BLE antenna).

**Test Result: Pass**

No SAR measurement is required.

--- END ---