FCC ID: 2AN6UYTK-356

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· $[\sqrt{f(GHZ)}]$ ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	0.88	1.22	1±1	2	1.58	<5	0.49127	3.00	YES
	2.441	1.01	1.26	1±1	2	1.58	<5	0.49524	3.00	YES
	2.480	0.31	1.07	1±1	2	1.58	<5	0.49918	3.00	YES
π/4- DQPSK	2.402	2.13	1.63	2±1	3	2.00	<5	0.61847	3.00	YES
	2.441	2.24	1.67	2±1	3	2.00	<5	0.62347	3.00	YES
	2.480	1.76	1.50	2±1	3	2.00	<5	0.62843	3.00	YES
8-DPSK	2.402	2.26	1.68	2±1	3	2.00	<5	0.61847	3.00	YES
	2.441	2.38	1.73	2±1	3	2.00	<5	0.62347	3.00	YES
	2.480	1.93	1.56	2±1	3	2.00	<5	0.62843	3.00	YES

Conclusion:

For the max result: 0.62843W/Kg ≤ 3.0, compliance with FCC's RF Exposure

Jason chen

Signature: Date: 2018-08-15

NAME AND TITLE (Please print or type): Jason Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.