



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: [www.cqa-cert.com](http://www.cqa-cert.com)


Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

# RF Exposure Evaluation Report

**Report No. :** CQASZ20180700029E-03  
**Applicant:** SHENZHEN HUBSAN TECHNOLOGY CO., LTD.  
**Address of Applicant:** 13th Floor, Bldg 1C, Shenzhen Software Industry Base, Xuefu Road, Nanshan District, Shenzhen, China. 518054  
**Manufacturer:** SHENZHEN HUBSAN TECHNOLOGY CO., LTD.  
**Address of Manufacturer:** 13th Floor, Bldg 1C, Shenzhen Software Industry Base, Xuefu Road, Nanshan District, Shenzhen, China. 518054  
**Factory:** Dongguan Tengsheng Industrial Co., Ltd.  
**Address of Factory:** A22# Luyi Street, Tianxin Village, Tangxia Town, Dongguan, China.  
**Equipment Under Test (EUT):**  
**Product:** X4 JET  
**Model No.:** H123D  
**Brand Name:** HUBSAN  
**FCC ID:** 2AN75-123DRX  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Test:** 2018-07-15 to 2018-07-23  
**Date of Issue:** 2018-07-23  
**Test Result :** **PASS\***


**Tested By:**

  
\_\_\_\_\_  
(Aaron Ma)

**Reviewed By:**

  
\_\_\_\_\_  
(Owen Zhou)

**Approved By:**

  
\_\_\_\_\_  
(Jack Ai)



\* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

## 2 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20180700029E-03	Rev.01	Initial report	2018-07-23

### 3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION .....	2
3 CONTENTS .....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT .....	4
4.3 GENERAL DESCRIPTION OF 2.4GHZ WIRELESS .....	4
4.4 GENERAL DESCRIPTION OF 5.8GHZ WIRELESS .....	4
5 SAR EVALUATION .....	5
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	5
5.1.1 <i>Standard Requirement</i> .....	5
5.1.2 <i>Limits</i> .....	5
5.1.3 <i>EUT RF Exposure</i> .....	5

## 4 General Information

### 4.1 Client Information

Applicant:	SHENZHEN HUBSAN TECHNOLOGY CO., LTD.
Address of Applicant:	13th Floor, Bldg 1C, Shenzhen Software Industry Base, Xuefu Road, Nanshan District, Shenzhen, China. 518054
Manufacturer:	SHENZHEN HUBSAN TECHNOLOGY CO., LTD.
Address of Manufacturer:	13th Floor, Bldg 1C, Shenzhen Software Industry Base, Xuefu Road, Nanshan District, Shenzhen, China. 518054

### 4.2 General Description of EUT

Product Name:	X4 JET
Model No.:	H123D
Trade Mark:	HUBSAN
Hardware Version:	V05
Software Version:	H123D_FC_V2_0_7, H62_201806191032
Power Supply:	7.6V LiPo battery

### 4.3 General Description of 2.4GHz wireless

Frequency Range:	2410 MHz ~ 2465MHz
Modulation Type:	GFSK
Number of Channels:	12 (declared by the client)
Antenna Type:	Integral antenna
Antenna Gain:	0.5dBi

### 4.4 General Description of 5.8GHz wireless

Frequency Range:	5735MHz ~ 5840MHz
Modulation Type:	GFSK
Number of Channels:	17 (declared by the client)
Antenna Type:	Integral antenna
Antenna Gain:	0.8dBi

## 5 SAR Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 5.1.3 EUT RF Exposure

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{E} \times \text{d})^2 / 30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m,  $10^{(91.00 - \text{dB}\mu\text{V}/\text{m})/20} / 10^6$ ,

d = measurement distance in meters (m)---3m,

$$\text{So pt} = (\text{E} \times \text{d})^2 / 30 / \text{gt}$$

The worst case (refer to report CQASZ20180700029E-01) is below:

For 2.4GHz wireless:

Field strength = 91.00dB $\mu$ V/m @3m

Ant. gain 0.5dBi; so Ant numeric gain=1.12

$$\text{So pt} = \left[ \left( 10^{(91.00/20)} / 10^6 \times 3 \right)^2 / 30 / 1.12 \right] \times 1000 \text{mW} = 0.337 \text{mW}$$

$$\text{So } (0.337 \text{mW} / 5 \text{mm}) \times \sqrt{2.410 \text{GHz}} = 0.105,$$

0.105 < 3.0 for 1-g SAR

The worst case (refer to report CQASZ20180700029E-02) is below:

For 5.8GHz wireless:

Field strength = 96.38dB $\mu$ V/m @3m

Ant. gain 0.8dBi; so Ant numeric gain=1.2

So  $P_t = \left[ \left( 10^{(96.38/20)} / 10^6 \times 3 \right)^2 / 30 / 1.2 \right] \times 1000 \text{mW} = 1.084 \text{mW}$

So  $(1.084 \text{mW} / 5 \text{mm}) \times \sqrt{5.735 \text{GHz}} = 0.519$ ,

0.519 < 3.0 for 1-g SAR

So the SAR report is not required.