



BUREAU  
VERITAS

Test Report No.: RF171110W005-2



# FCC TEST REPORT (Part 15, Subpart C)



Applicant:	Mundo Reader S.L.
Address:	Calle Sofía 10, Parque Industrial y Tecnológico Európolis 28232 Las Rozas - Madrid SPAIN

Manufacturer or Supplier	Mundo Reader S.L.
Address	Calle Sofía 10, Parque Industrial y Tecnológico Európolis 28232 Las Rozas - Madrid SPAIN
Product	Smartphone
Brand Name	BQ
Model Name	Aquaris U2
FCC ID	2AN87AQUARISU2
Date of tests	Nov. 11, 2017 ~ Nov. 21, 2017

The tests have been carried out according to the requirements of the following standard:

- FCC Part 15, Subpart C, Section 15.247
- ANSI C63.10-2013

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Prepared by Yuqiang Yin Engineer / Mobile Department	Approved by Bill Yao Manager / Mobile Department
	
Date: Nov. 22, 2017	Date: Nov. 22, 2017

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

BV 7Layers Communications Technology  
(Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan  
Avenue, North Area, Hi-Tech Industrial Park, Nanshan  
District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566  
Fax: +86 755 8869 6577  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



# TABLE OF CONTENTS

**RELEASE CONTROL RECORD ..... 4**

**1 SUMMARY OF TEST RESULTS..... 5**

1.1 MEASUREMENT UNCERTAINTY ..... 5

**2 GENERAL INFORMATION ..... 6**

2.1 GENERAL DESCRIPTION OF EUT ..... 6

2.2 DESCRIPTION OF TEST MODES ..... 8

2.2.1 CONFIGURATION OF SYSTEM UNDER TEST ..... 9

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... 9

2.3 DUTY CYCLE OF TEST SIGNAL ..... 12

2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS ..... 13

2.5 DESCRIPTION OF SUPPORT UNITS ..... 13

**3 TEST TYPES AND RESULTS..... 14**

3.1 CONDUCTED EMISSION MEASUREMENT ..... 14

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT ..... 14

3.1.2 TEST INSTRUMENTS..... 14

3.1.3 TEST PROCEDURES ..... 15

3.1.4 DEVIATION FROM TEST STANDARD ..... 15

3.1.5 TEST SETUP..... 16

3.1.6 EUT OPERATING CONDITIONS ..... 16

3.1.7 TEST RESULTS ..... 17

3.2 RADIATED EMISSION MEASUREMENT ..... 19

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT ..... 19

3.2.2 TEST INSTRUMENTS..... 20

3.2.3 TEST PROCEDURES ..... 21

3.2.4 DEVIATION FROM TEST STANDARD ..... 21

3.2.5 TEST SETUP..... 22

3.2.6 EUT OPERATING CONDITIONS ..... 23

3.2.7 TEST RESULTS ..... 24

3.3 6 DB BANDWIDTH MEASUREMENT ..... 43

3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT ..... 43

3.3.2 TEST INSTRUMENTS..... 43

3.3.3 TEST PROCEDURE ..... 43

3.3.4 DEVIATION FROM TEST STANDARD ..... 44

3.3.5 TEST SETUP..... 44



3.3.6	EUT OPERATING CONDITIONS .....	44
3.3.7	TEST RESULTS .....	45
3.4	CONDUCTED OUTPUT POWER.....	50
3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT .....	50
3.4.2	TEST SETUP.....	50
3.4.3	TEST INSTRUMENTS.....	50
3.4.4	TEST PROCEDURES .....	50
3.4.5	DEVIATION FROM TEST STANDARD .....	50
3.4.6	EUT OPERATING CONDITIONS.....	50
3.4.7	TEST RESULTS .....	51
3.4.7.1	MAXIMUM PEAK OUTPUT POWER .....	51
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	53
3.5	POWER SPECTRAL DENSITY MEASUREMENT .....	55
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	55
3.5.2	TEST SETUP.....	55
3.5.3	TEST INSTRUMENTS.....	55
3.5.4	TEST PROCEDURE.....	55
3.5.5	DEVIATION FROM TEST STANDARD .....	55
3.5.6	EUT OPERATING CONDITION .....	55
3.5.7	TEST RESULTS .....	56
3.6	OUT OF BAND EMISSION MEASUREMENT .....	61
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT.....	61
3.6.2	TEST SETUP.....	61
3.6.3	TEST INSTRUMENTS.....	61
3.6.4	TEST PROCEDURE.....	61
3.6.5	DEVIATION FROM TEST STANDARD .....	62
3.6.6	EUT OPERATING CONDITION .....	62
3.6.7	TEST RESULTS .....	62
<b>4</b>	<b>PHOTOGRAPHS OF THE TEST CONFIGURATION .....</b>	<b>73</b>
<b>5</b>	<b>APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....</b>	<b>74</b>



**BUREAU**  
**VERITAS**

Test Report No.: RF171110W005-2

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF171110W005-2	Original release	Nov. 22, 2017



## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -22.59dB at 0.162000MHz.
15.205 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -1.19dB at 4824MHz.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used

### 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.68dB
	30MHz ~ 1GMHz	3.26dB
	1GHz ~ 18GHz	4.48dB
	18GHz ~ 40GHz	4.12dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .



## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Smartphone
<b>BRAND NAME</b>	BQ
<b>MODEL NAME</b>	Aquaris U2
<b>NOMINAL VOLTAGE</b>	5.0Vdc (adapter or host equipment) 3.85Vdc (Li-polymer, battery)
<b>MODULATION TECHNOLOGY</b>	DSSS, OFDM, DTS
<b>MODULATION TYPE</b>	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM BT-LE(GFSK) for DTS
<b>TRANSMISSION RATE</b>	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n: up to 135 Mbps BT_LE: 1 Mbps
<b>OPERATING FREQUENCY</b>	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40) 2402-2480MHz for BT-LE(GFSK)
<b>MAX. OUTPUT POWER</b>	WLAN: 92.470mW (Maximum) BT-LE: 1.435mW (Maximum)
<b>ANTENNA TYPE</b>	LDS Antenna with -4dBi gain
<b>HW VERSION</b>	LLDM956B3-3 VER:B34-2 1728 MDK MB- 18 W
<b>SW VERSION</b>	1.9.0_20171116-1320
<b>I/O PORTS</b>	Refer to user's manual
<b>CABLE SUPPLIED</b>	USB cable: Shielded without core, detachable, 1.0m

**NOTE:**

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	1TX /1RX
802.11g	1TX /1RX
802.11n (20MHz)	1TX /1RX
802.11n (40MHz)	1TX /1RX
BT_LE	1TX /1RX



3. The EUT matched the following USB cable:

<b>USB CABLE</b>	
<b>BRAND:</b>	HFG Communication Technology Co., LTD.
<b>MODEL:</b>	HY-005015
<b>SIGNAL LINE:</b>	1.0 METER

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



## 2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480





### 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

### 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz      **RE≥1G**: Radiated Emission above 1GHz  
**PLC**: Power Line Conducted Emission      **APCM**: Antenna Port Conducted Measurement

**NOTE:** No need to concern of Conducted Emission due to the EUT is powered by battery.

### RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1	CCK	DBPSK	1
BT-LE	0 to 39	19	DTS	GFSK	1



**RADIATED EMISSION TEST (ABOVE 1GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5
BT-LE	0 to 39	0,19, 39	DTS	GFSK	1

**POWER LINE CONDUCTED EMISSION TEST:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1	CCK	DBPSK	1

**BANDEDGE MEASUREMENT:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3, 9	OFDM	BPSK	13.5
BT-LE	0 to 39	0, 39	DTS	GFSK	1

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3,6, 9	OFDM	BPSK	13.5
BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	22deg. C, 54%RH	DC 5V from adaptor	Simon Yang
RE≥1G	22deg. C, 54%RH	DC 5V from adaptor	Simon Yang
PLC	24deg. C, 55%RH	DC 5V from adaptor	Jocan Guo
APCM	25deg. C, 60%RH	3.85Vdc from battery	Wenliang Wu



### 2.3 Duty Cycle of Test Signal

#### WIFI 2.4GHz

**802.11b:** Duty cycle = 8.200/8.375 = 0.979 < 98%, Duty factor = 10 \* log( 1/0.979) = 0.092

**802.11g:** Duty cycle = 1.357/1.576 = 0.861 < 98%, Duty factor = 10 \* log( 1/0.861) = 0.650

**802.11n (HT20):** Duty cycle = 1.270/1.474 = 0.862 < 98%, Duty factor = 10 \* log( 1/0.862) = 0.647

**802.11n (HT40):** Duty cycle = 0.629/0.842 = 0.747 < 98%, Duty factor = 10 \* log( 1/0.747) = 1.267





## 2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C, Section 15.247**

**KDB 558074 D01 DTS Meas Guidance v04**

**ANSI C63.10-2013**

Note:

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

## 2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PC	HP	A6608CN	3CR83825X3	N/A
2	Adapter	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	N/A



### 3 TEST TYPES AND RESULTS

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

##### 3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Jun. 28,17	Jun. 27,18
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Sep. 18,17	Sep. 17,18

- NOTE:**
1. The test was performed in CE shielded room.
  2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



### 3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

### 3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



### 3.1.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
  - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.





### 3.1.7 TEST RESULTS


#### CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Jocan Guo	TEST DATE	2017/11/14

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.162000	---	28.28	55.36	-27.08	L1	ON	9.6
<b>0.162000</b>	<b>42.77</b>	---	<b>65.36</b>	<b>-22.59</b>	<b>L1</b>	<b>ON</b>	<b>9.6</b>
0.188000	---	24.43	54.12	-29.69	L1	ON	9.7
0.188000	39.52	---	64.12	-24.60	L1	ON	9.7
0.488000	---	21.25	46.20	-24.95	L1	ON	9.7
0.488000	32.21	---	56.20	-23.99	L1	ON	9.7
1.692000	---	12.06	46.00	-33.94	L1	ON	9.7
1.692000	23.01	---	56.00	-32.99	L1	ON	9.7
2.248000	---	13.10	46.00	-32.90	L1	ON	9.7
2.248000	23.00	---	56.00	-33.00	L1	ON	9.7
14.300000	---	24.39	50.00	-25.61	L1	ON	9.9
14.300000	32.41	---	60.00	-27.59	L1	ON	9.9

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.

Full Spectrum






<b>Frequency Range</b>	150KHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9 kHz
<b>Input Power</b>	120Vac, 60Hz	<b>Environmental Conditions</b>	24deg. C, 55RH
<b>Tested By</b>	Jocan Guo	<b>TEST DATE</b>	2017/11/14

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	CAverage (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.158000	---	22.50	55.57	-33.07	N	ON	10.1
0.158000	35.48	---	65.57	-30.09	N	ON	10.1
0.396000	---	20.44	47.94	-27.50	N	ON	10.1
0.396000	30.53	---	57.94	-27.41	N	ON	10.1
0.584000	---	20.24	46.00	-25.76	N	ON	10.1
0.584000	32.07	---	56.00	-23.93	N	ON	10.1
4.852000	---	14.90	46.00	-31.10	N	ON	9.8
4.852000	27.98	---	56.00	-28.02	N	ON	9.8
9.900000	---	18.85	50.00	-31.15	N	ON	9.9
9.900000	28.83	---	60.00	-31.17	N	ON	9.9
13.928000	---	25.64	50.00	-24.36	N	ON	9.9
13.928000	33.21	---	60.00	-26.79	N	ON	9.9

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



### 3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May 06,17	May 05,18
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Nov. 26,16	Nov. 25,18
Horn Antenna	ETS-LINDGREN	3117	00168728	Nov. 26,16	Nov. 25,18
Loop antenna	Daze	ZN30900A	0708	Nov. 28,16	Nov. 27,17
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Dec. 16,16	Dec. 15,17
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jul. 24,17	Jul. 23,18
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 10,17	Mar. 09,18
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jul. 24,17	Jul. 23,18

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
  2. The test was performed in 3m Chamber.
  3. The FCC Site Registration No. is 525120.



### 3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

#### **Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle  $\geq$  98%) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


### 3.2.4 DEVIATION FROM TEST STANDARD

No deviation




### 3.2.5 TEST SETUP

#### < Frequency Range below 30MHz >




#### < Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



### 3.2.7 TEST RESULTS

#### BELOW 1GHz WORST-CASE DATA:

**9 KHz – 30 KHz data:** the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

**30 MHz – 1GHz data:**


**802.11b**

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
65.89	28.95	58.3	40	-11.05	6.69	1.24	37.28	100	248	QP
144.46	34.45	60.88	43.5	-9.05	8.54	1.85	36.82	100	123	QP
235.64	26.95	49.37	46	-19.05	11.74	2.37	36.53	100	51	QP
400.54	23.97	40.33	46	-22.03	17.21	3.15	36.72	100	196	QP
595.51	23.6	36.64	46	-22.4	20.21	3.99	37.24	100	312	QP
714.82	24.05	34.02	46	-21.95	23.09	4.34	37.4	100	47	QP

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.








<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
30	30.5	50.18	40	-9.5	17.1	0.78	37.56	100	159	QP
65.89	30.4	59.75	40	-9.6	6.69	1.24	37.28	100	32	QP
145.43	21.18	47.49	43.5	-22.32	8.65	1.85	36.81	100	14	QP
327.79	26.75	46.3	46	-19.25	14.17	2.84	36.56	100	269	QP
598.42	23.17	36.15	46	-22.83	20.27	4	37.25	100	315	QP
702.21	24.33	34.31	46	-21.67	23.1	4.29	37.37	100	78	QP

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.





**ABOVE 1GHZ WORST-CASE DATA:**

**Note:** For higher frequency, the emission is too low to be detected.

**802.11b**

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.9	49.38	54	-10.1	32.29	8.15	45.92	118	135	Average
2390	56.18	61.66	74	-17.82	32.29	8.15	45.92	118	135	Peak
2412	101.63	107.04			32.31	8.19	45.91	118	135	Average
2412	103.95	109.36			32.31	8.19	45.91	118	135	Peak
2483.5	44.8	49.99	54	-9.2	32.38	8.32	45.89	118	135	Average
2483.5	55.67	60.86	74	-18.33	32.38	8.32	45.89	118	135	Peak
4824	52.17	51.37	54	-1.83	34.3	12.63	46.13	135	135	Average
4824	61.45	60.65	74	-12.55	34.3	12.63	46.13	135	135	Peak
<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.9	49.38	54	-10.1	32.29	8.15	45.92	135	95	Average
2390	55.13	60.61	74	-18.87	32.29	8.15	45.92	135	95	Peak
2412	102.88	108.29			32.31	8.19	45.91	135	95	Average
2412	105.17	110.58			32.31	8.19	45.91	135	95	Peak
2483.5	44.73	49.92	54	-9.27	32.38	8.32	45.89	135	95	Average
2483.5	54.64	59.83	74	-19.36	32.38	8.32	45.89	135	95	Peak
<b>4824</b>	<b>52.81</b>	<b>52.01</b>	<b>54</b>	<b>-1.19</b>	<b>34.3</b>	<b>12.63</b>	<b>46.13</b>	<b>100</b>	<b>275</b>	<b>Average</b>
4824	56.76	55.96	74	-17.24	34.3	12.63	46.13	100	275	Peak

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.88	49.36	54	-10.12	32.29	8.15	45.92	116	135	Average
2390	54.17	59.65	74	-19.83	32.29	8.15	45.92	116	135	Peak
2437	101.26	106.59	54			8.24	45.91	116	135	Average
2437	104.46	109.79	74			8.24	45.91	116	135	Peak
2483.5	44.36	49.55	54	-9.64	32.38	8.32	45.89	116	135	Average
2483.5	54.5	59.69	74	-19.5	32.38	8.32	45.89	116	135	Peak
4874	51.81	50.84	54	-2.19	34.3	12.81	46.14	135	132	Average
4874	61.49	60.52	74	-12.51	34.3	12.81	46.14	135	132	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.04	49.52	54	-9.96	32.29	8.15	45.92	135	100	Average
2390	54.54	60.02	74	-19.46	32.29	8.15	45.92	135	100	Peak
2437	103.05	108.38			32.34	8.24	45.91	135	100	Average
2437	106.06	111.39			32.34	8.24	45.91	135	100	Peak
2483.5	44.13	49.32	54	-9.87	32.38	8.32	45.89	135	100	Average
2483.5	55	60.19	74	-19	32.38	8.32	45.89	135	100	Peak
4874	52.02	51.05	54	-1.98	34.3	12.81	46.14	100	275	Average
4874	62.74	61.77	74	-11.26	34.3	12.81	46.14	100	275	Peak

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2437MHz: Fundamental frequency.



<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.3	49.78	54	-9.7	32.29	8.15	45.92	100	135	Average
2390	54.77	60.25	74	-19.23	32.29	8.15	45.92	100	135	Peak
2462	99.91	105.17	54			8.28	45.9	100	135	Average
2462	103.13	108.39	74			8.28	45.9	100	135	Peak
2483.5	44.32	49.51	54	-9.68	32.38	8.32	45.89	100	135	Average
2483.5	55.89	61.08	74	-18.11	32.38	8.32	45.89	100	135	Peak
4924	51.93	50.79	54	-2.07	34.3	13	46.16	135	135	Average
4924	61.46	60.32	74	-12.54	34.3	13	46.16	135	135	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.79	49.27	54	-10.21	32.29	8.15	45.92	100	95	Average
2390	54.29	59.77	74	-19.71	32.29	8.15	45.92	100	95	Peak
2462	101.84	107.1			32.36	8.28	45.9	100	95	Average
2462	104.72	109.98			32.36	8.28	45.9	100	95	Peak
2483.5	44.62	49.81	54	-9.38	32.38	8.32	45.89	100	95	Average
2483.5	55.25	60.44	74	-18.75	32.38	8.32	45.89	100	95	Peak
4924	52.26	51.12	54	-1.74	34.3	13	46.16	100	270	Average
4924	61.16	60.02	74	-12.84	34.3	13	46.16	100	270	Peak

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2462MHz: Fundamental frequency.



802.11g

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	47.85	53.33	54	-6.15	32.29	8.15	45.92	118	135	Average
2390	60.58	66.06	74	-13.42	32.29	8.15	45.92	118	135	Peak
2412	94.3	99.71			32.31	8.19	45.91	118	135	Average
2412	105.67	111.08			32.31	8.19	45.91	118	135	Peak
2483.5	45	50.19	54	-9	32.38	8.32	45.89	118	135	Average
2483.5	56.28	61.47	74	-17.72	32.38	8.32	45.89	118	135	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	48.89	54.37	54	-5.11	32.29	8.15	45.92	140	95	Average
2390	67.31	72.79	74	-6.69	32.29	8.15	45.92	140	95	Peak
2412	96.48	101.67			32.38	8.32	45.89	140	95	Average
2412	106.64	112.05			32.31	8.19	45.91	140	95	Peak
2483.5	45.19	50.38	54	-8.81	32.38	8.32	45.89	140	95	Average
2483.5	56.73	61.92	74	-17.27	32.38	8.32	45.89	140	95	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.98	49.46	54	-10.02	32.29	8.15	45.92	105	135	Average
2390	54.88	60.36	74	-19.12	32.29	8.15	45.92	105	135	Peak
2437	95.78	101.11			32.34	8.24	45.91	105	135	Average
2437	105.49	110.82			32.34	8.24	45.91	105	135	Peak
2483.5	44.33	49.52	54	-9.67	32.38	8.32	45.89	105	135	Average
2483.5	55.97	61.16	74	-18.03	32.38	8.32	45.89	105	135	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.09	49.57	54	-9.91	32.29	8.15	45.92	135	98	Average
2390	55.09	60.57	74	-18.91	32.29	8.15	45.92	135	98	Peak
2437	97.34	102.67			32.34	8.24	45.91	135	98	Average
2437	107.21	112.54			32.34	8.24	45.91	135	98	Peak
2483.5	44.58	49.77	54	-9.42	32.38	8.32	45.89	135	98	Average
2483.5	55.2	60.39	74	-18.8	32.38	8.32	45.89	135	98	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.83	49.31	54	-10.17	32.29	8.15	45.92	118	138	Average
2390	54.5	59.98	74	-19.5	32.29	8.15	45.92	118	138	Peak
2462	96.33	101.59			32.36	8.28	45.9	118	138	Average
2462	105.73	110.99			32.36	8.28	45.9	118	138	Peak
2483.5	49.29	54.48	54	-4.71	32.38	8.32	45.89	118	138	Average
2483.5	65.81	71	74	-8.19	32.38	8.32	45.89	118	138	Peak

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.9	49.38	54	-10.1	32.29	8.15	45.92	100	96	Average
2390	55.47	60.95	74	-18.53	32.29	8.15	45.92	100	96	Peak
2462	97.07	102.33			32.36	8.28	45.9	100	96	Average
2462	107.45	112.71			32.36	8.28	45.9	100	96	Peak
2483.5	51.43	56.62	54	-2.57	32.38	8.32	45.89	100	96	Average
2483.5	68.92	74.11	74	-5.08	32.38	8.32	45.89	100	96	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	48.6	54.08	54	-5.4	32.29	8.15	45.92	116	136	Average
2390	65.81	71.29	74	-8.19	32.29	8.15	45.92	116	136	Peak
2412	94.85	100.26			32.31	8.19	45.91	116	136	Average
2412	104.8	110.21			32.31	8.19	45.91	116	136	Peak
2483.5	44.03	49.22	54	-9.97	32.38	8.32	45.89	116	136	Average
2483.5	54.95	60.14	74	-19.05	32.38	8.32	45.89	116	136	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.86	56.34	54	-3.14	32.29	8.15	45.92	135	95	Average
2390	70.75	76.23	74	-3.25	32.29	8.15	45.92	135	95	Peak
2412	95.87	101.28			32.31	8.19	45.91	135	95	Average
2412	106.34	111.75			32.31	8.19	45.91	135	95	Peak
2483.5	43.98	49.17	54	-10.02	32.38	8.32	45.89	135	95	Average
2483.5	54.71	59.9	74	-19.29	32.38	8.32	45.89	135	95	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.





<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.85	49.33	54	-10.15	32.29	8.15	45.92	115	140	Average
2390	54.37	59.85	74	-19.63	32.29	8.15	45.92	115	140	Peak
2437	95.19	100.52			32.34	8.24	45.91	115	140	Average
2437	104.9	110.23			32.34	8.24	45.91	115	140	Peak
2483.5	44.33	49.52	54	-9.67	32.38	8.32	45.89	115	140	Average
2483.5	55.3	60.49	74	-18.7	32.38	8.32	45.89	115	140	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.91	49.39	54	-10.09	32.29	8.15	45.92	120	95	Average
2390	55.99	61.47	74	-18.01	32.29	8.15	45.92	120	95	Peak
2437	97.04	102.37			32.34	8.24	45.91	120	95	Average
2437	107.3	112.63			32.34	8.24	45.91	120	95	Peak
2483.5	44.42	49.61	54	-9.58	32.38	8.32	45.89	120	95	Average
2483.5	55.64	60.83	74	-18.36	32.38	8.32	45.89	120	95	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.88	49.36	54	-10.12	32.29	8.15	45.92	118	138	Average
2390	55.19	60.67	74	-18.81	32.29	8.15	45.92	118	138	Peak
2462	95.77	101.03			32.36	8.28	45.9	118	138	Average
2462	105.2	110.46			32.36	8.28	45.9	118	138	Peak
2483.5	50.26	55.45	54	-3.74	32.38	8.32	45.89	118	138	Average
2483.5	69.23	74.42	74	-4.77	32.38	8.32	45.89	118	138	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.81	49.29	54	-10.19	32.29	8.15	45.92	120	98	Average
2390	54.75	60.23	74	-19.25	32.29	8.15	45.92	120	98	Peak
2462	95.89	101.15			32.36	8.28	45.9	120	98	Average
2462	106.27	111.53			32.36	8.28	45.9	120	98	Peak
2483.5	51	56.19	54	-3	32.38	8.32	45.89	120	98	Average
2483.5	70.89	76.08	74	-3.11	32.38	8.32	45.89	120	98	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



## 802.11n (40MHz)

<b>CHANNEL</b>	TX Channel 3	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.62	56.1	54	-3.38	32.29	8.15	45.92	118	135	Average
2390	66.87	72.35	74	-7.13	32.29	8.15	45.92	118	135	Peak
2422	90.4	95.78			32.32	8.21	45.91	118	135	Average
2422	102.66	108.04			32.32	8.21	45.91	118	135	Peak
2483.5	44.8	49.99	54	-9.2	32.38	8.32	45.89	118	135	Average
2483.5	55.66	60.85	74	-18.34	32.38	8.32	45.89	118	135	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.72	57.2	54	-2.28	32.29	8.15	45.92	135	95	Average
2390	69.85	75.33	74	-4.15	32.29	8.15	45.92	135	95	Peak
2422	93.01	98.39			32.32	8.21	45.91	135	95	Average
2422	104.39	109.77			32.32	8.21	45.91	135	95	Peak
2483.5	45.02	50.21	54	-8.98	32.38	8.32	45.89	135	95	Average
2483.5	56.22	61.41	74	-17.78	32.38	8.32	45.89	135	95	Peak

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2422MHz: Fundamental frequency.



<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.07	51.55	54	-7.93	32.29	8.15	45.92	120	135	Average
2390	60.89	66.37	74	-13.11	32.29	8.15	45.92	120	135	Peak
2437	92.21	97.54			32.34	8.24	45.91	120	135	Average
2437	102.92	108.25			32.34	8.24	45.91	120	135	Peak
2483.5	48.29	53.48	54	-5.71	32.38	8.32	45.89	120	135	Average
2483.5	62.94	68.13	74	-11.06	32.38	8.32	45.89	120	135	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	47.41	52.89	54	-6.59	32.29	8.15	45.92	135	98	Average
2390	64.01	69.49	74	-9.99	32.29	8.15	45.92	135	98	Peak
2437	93.14	98.47			32.34	8.24	45.91	135	98	Average
2437	104.63	109.96			32.34	8.24	45.91	135	98	Peak
2483.5	49.95	55.14	54	-4.05	32.38	8.32	45.89	135	98	Average
2483.5	63.28	68.47	74	-10.72	32.38	8.32	45.89	135	98	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



<b>CHANNEL</b>	TX Channel 9	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.87	49.35	54	-10.13	32.29	8.15	45.92	100	138	Average
2390	54.66	60.14	74	-19.34	32.29	8.15	45.92	100	138	Peak
2452	89.44	94.73			32.35	8.26	45.9	100	138	Average
2452	100.74	106.03			32.35	8.26	45.9	100	138	Peak
2483.5	51.38	56.57	54	-2.62	32.38	8.32	45.89	100	138	Average
2483.5	66.16	71.35	74	-7.84	32.38	8.32	45.89	100	138	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.77	49.25	54	-10.23	32.29	8.15	45.92	135	95	Average
2390	54.73	60.21	74	-19.27	32.29	8.15	45.92	135	95	Peak
2452	91.6	96.89			32.35	8.26	45.9	135	95	Average
2452	102.83	108.12			32.35	8.26	45.9	135	95	Peak
2483.5	51.84	57.03	54	-2.16	32.38	8.32	45.89	135	95	Average
2483.5	66.79	71.98	74	-7.21	32.38	8.32	45.89	135	95	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2452MHz: Fundamental frequency.



**BELOW 1GHz WORST-CASE DATA:**

**9 KHz – 30 KHz data:** the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

**30 MHz – 1GHz data:**


**BT-LE (GFSK)**

<b>CHANNEL</b>	TX Channel 19	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
66.86	30.84	60.13	40	-9.16	6.74	1.25	37.28	100	258	QP
144.46	35.72	62.15	43.5	-7.78	8.54	1.85	36.82	100	157	QP
235.64	31.49	53.91	46	-14.51	11.74	2.37	36.53	100	58	QP
343.31	25.98	44.85	46	-20.02	14.82	2.91	36.6	100	196	QP
597.45	25.44	38.43	46	-20.56	20.25	4	37.24	100	342	QP
722.58	26.75	36.72	46	-19.25	23.08	4.37	37.42	100	72	QP

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value






<b>CHANNEL</b>	TX Channel 19	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
58.13	35.47	65.22	40	-4.53	6.42	1.16	37.33	100	25	QP
144.46	23.45	49.88	43.5	-20.05	8.54	1.85	36.82	100	123	QP
235.64	27.11	49.53	46	-18.89	11.74	2.37	36.53	100	236	QP
327.79	29	48.55	46	-17	14.17	2.84	36.56	100	302	QP
595.51	27.01	40.05	46	-18.99	20.21	3.99	37.24	100	82	QP
796.3	27.19	37.13	46	-18.81	23	4.67	37.61	100	147	QP

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



**ABOVE 1GHz TEST DATA:****Note:** For higher frequency, the emission is too low to be detected.**BT-LE (GFSK)**

<b>CHANNEL</b>	TX Channel 0	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>										
<b>FREQ. (MHz)</b>	<b>EMISSION LEVEL (dBuV/m)</b>	<b>READ LEVEL (dBuV)</b>	<b>LIMIT (dBuV/m)</b>	<b>MARGIN (dB)</b>	<b>ANTENNA FACTOR (dB /m)</b>	<b>CABLE LOSS (dB)</b>	<b>PREAMP FACTOR (dB)</b>	<b>ANTENNA HEIGHT (cm)</b>	<b>TABLE ANGLE (Degree)</b>	<b>REMARK</b>
2390	43.8	49.28	54	-10.2	32.29	8.15	45.92	105	242	Average
2390	55.44	60.92	74	-18.56	32.29	8.15	45.92	105	242	Peak
2402	91.27	96.72			32.3	8.17	45.92	105	242	Average
2402	96.27	101.72			32.3	8.17	45.92	105	242	Peak
2483.5	43.93	49.12	54	-10.07	32.38	8.32	45.89	105	242	Average
2483.5	54.93	60.12	74	-19.07	32.38	8.32	45.89	105	242	Peak
<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>										
<b>FREQ. (MHz)</b>	<b>EMISSION LEVEL (dBuV/m)</b>	<b>READ LEVEL (dBuV)</b>	<b>LIMIT (dBuV/m)</b>	<b>MARGIN (dB)</b>	<b>ANTENNA FACTOR (dB /m)</b>	<b>CABLE LOSS (dB)</b>	<b>PREAMP FACTOR (dB)</b>	<b>ANTENNA HEIGHT (cm)</b>	<b>TABLE ANGLE (Degree)</b>	<b>REMARK</b>
2390	43.64	49.12	54	-10.36	32.29	8.15	45.92	170	275	Average
2390	54.79	60.27	74	-19.21	32.29	8.15	45.92	170	275	Peak
2402	91.91	97.36			32.3	8.17	45.92	170	275	Average
2402	97.49	102.94			32.3	8.17	45.92	170	275	Peak
2483.5	44.14	49.33	54	-9.86	32.38	8.32	45.89	170	275	Average
2483.5	55.59	60.78	74	-18.41	32.38	8.32	45.89	170	275	Peak

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2402MHz: Fundamental frequency.





<b>CHANNEL</b>	TX Channel 19	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.8	49.28	54	-10.2	32.29	8.15	45.92	105	240	Average
2390	55.01	60.49	74	-18.99	32.29	8.15	45.92	105	240	Peak
2440	92.84	98.17			32.34	8.24	45.91	105	240	Average
2440	97.75	103.08			32.34	8.24	45.91	105	240	Peak
2483.5	43.89	49.08	54	-10.11	32.38	8.32	45.89	105	240	Average
2483.5	55.02	60.21	74	-18.98	32.38	8.32	45.89	105	240	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.78	49.26	54	-10.22	32.29	8.15	45.92	165	280	Average
2390	54.65	60.13	74	-19.35	32.29	8.15	45.92	165	280	Peak
2440	95.36	100.69			32.34	8.24	45.91	165	280	Average
2440	100.26	105.59			32.34	8.24	45.91	165	280	Peak
<b>2483.5</b>	<b>44.38</b>	<b>49.57</b>	<b>54</b>	<b>-9.62</b>	<b>32.38</b>	<b>8.32</b>	<b>45.89</b>	<b>165</b>	<b>280</b>	<b>Average</b>
2483.5	55.72	60.91	74	-18.28	32.38	8.32	45.89	165	280	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2440MHz: Fundamental frequency.



<b>CHANNEL</b>	TX Channel 39	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.47	48.95	54	-10.53	32.29	8.15	45.92	100	235	Average
2390	54.13	59.61	74	-19.87	32.29	8.15	45.92	100	235	Peak
2480	92.22	97.43			32.38	8.31	45.9	100	235	Average
2480	97.11	102.32			32.38	8.31	45.9	100	235	Peak
2483.5	43.83	49.02	54	-10.17	32.38	8.32	45.89	100	235	Average
2483.5	54.2	59.39	74	-19.8	32.38	8.32	45.89	100	235	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.57	49.05	54	-10.43	32.29	8.15	45.92	145	278	Average
2390	55.49	60.97	74	-18.51	32.29	8.15	45.92	145	278	Peak
2480	93.19	98.4			32.38	8.31	45.9	145	278	Average
2480	98.18	103.39			32.38	8.31	45.9	145	278	Peak
2483.5	43.77	48.96	54	-10.23	32.38	8.32	45.89	145	278	Average
2483.5	55.92	61.11	74	-18.08	32.38	8.32	45.89	145	278	Peak

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2480MHz: Fundamental frequency.



### 3.3 6 dB BANDWIDTH MEASUREMENT

#### 3.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 3.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	ANRITSU	ML2495A	1506002	Mar. 01,17	Feb. 28,18
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510523	Mar. 01,17	Feb. 28,18
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510332	Mar. 01,17	Feb. 28,18
Power Sensor	ANRITSU	MA2411B	1339352	Mar. 01,17	Feb. 28,18

**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

#### 3.3.3 TEST PROCEDURE


1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



### 3.3.4 DEVIATION FROM TEST STANDARD

No deviation.

### 3.3.5 TEST SETUP



### 3.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



### 3.3.7 TEST RESULTS

#### 802.11b


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	9.04	0.5	PASS
6	2437	8.56	0.5	PASS
11	2462	8.57	0.5	PASS





802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.36	0.5	PASS
6	2437	16.36	0.5	PASS
11	2462	16.35	0.5	PASS






**BUREAU  
VERITAS**

Test Report No.: RF171110W005-2

### 802.11n (20MHz)


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.58	0.5	PASS
6	2437	17.60	0.5	PASS
11	2462	17.56	0.5	PASS





802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
3	2422	35.18	0.5	PASS
6	2437	35.34	0.5	PASS
9	2452	35.19	0.5	PASS








**BT-LF (GFSK)**

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.67	0.5	PASS
19	2440	0.67	0.5	PASS
39	2480	0.68	0.5	PASS






### 3.4 CONDUCTED OUTPUT POWER

#### 3.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

#### 3.4.2 TEST SETUP



#### 3.4.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

#### 3.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

#### 3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 3.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



### 3.4.7 TEST RESULTS

#### 3.4.7.1 MAXIMUM PEAK OUTPUT POWER

##### 802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	17.77	59.841	1	PASS
6	2437	17.28	53.456	1	PASS
11	2462	17.01	50.234	1	PASS

##### 802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	19.30	85.114	1	PASS
6	2437	19.66	<b>92.470</b>	1	PASS
11	2462	18.91	77.804	1	PASS

##### 802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	19.38	86.696	1	PASS
6	2437	19.39	86.896	1	PASS
11	2462	19.30	85.114	1	PASS

##### 802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
3	2422	19.38	86.696	1	PASS
6	2437	19.14	82.035	1	PASS
9	2452	19.44	87.902	1	PASS



**BT-LE (GFSK)**

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
0	2402	0.95	1.245	1	PASS
19	2440	1.57	<b>1.435</b>	1	PASS
39	2480	-0.83	0.826	1	PASS

**3.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)**

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

**802.11b**

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	15.47	N/A
6	2437	14.36	N/A
11	2462	14.52	N/A

**802.11g**

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	13.34	N/A
6	2437	13.34	N/A
11	2462	12.85	N/A

**802.11n (20MHz)**

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	13.47	N/A
6	2437	13.29	N/A
11	2462	13.22	N/A

**802.11n (40MHz)**

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
3	2422	12.18	N/A
6	2437	13.19	N/A
9	2452	11.81	N/A



**BUREAU**  
**VERITAS**

Test Report No.: RF171110W005-2

**BT-LE (GFSK)**

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	0.84	N/A
19	2440	1.45	N/A
39	2480	-0.91	N/A




### 3.5 POWER SPECTRAL DENSITY MEASUREMENT

#### 3.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

#### 3.5.2 TEST SETUP



#### 3.5.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

#### 3.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW  $\geq 3 \times$  RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

#### 3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 3.5.6 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



### 3.5.7 TEST RESULTS

#### 802.11b

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-6.63	8	PASS
6	2437	-6.36	8	PASS
11	2462	-7.39	8	PASS








802.11g

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-10.49	8	PASS
6	2437	-10.54	8	PASS
11	2462	-11.51	8	PASS






**BUREAU  
VERITAS**

Test Report No.: RF171110W005-2

802.11n (20MHz)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-10.70	8	PASS
6	2437	-11.24	8	PASS
11	2462	-11.75	8	PASS






**BUREAU  
VERITAS**

Test Report No.: RF171110W005-2

### 802.11n (40MHz)


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
3	2422	-15.15	8	PASS
6	2437	-14.24	8	PASS
9	2452	-15.09	8	PASS





**BT-LE (GFSK)**

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	-13.48	8	PASS
19	2440	-12.93	8	PASS
39	2480	-14.92	8	PASS






### 3.6 OUT OF BAND EMISSION MEASUREMENT

#### 3.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

#### 3.6.2 TEST SETUP



#### 3.6.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

#### 3.6.4 TEST PROCEDURE

##### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



## MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

### 3.6.5 DEVIATION FROM TEST STANDARD

No deviation.

### 3.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


### 3.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.




802.11b


CH 1



CH 6




CH 11





**BUREAU  
VERITAS**

Test Report No.: RF171110W005-2



BV 7Layers Communications Technology  
(Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan  
Avenue, North Area, Hi-Tech Industrial Park, Nanshan  
District, Shenzhen, Guangdong, China


Tel: +86 755 8869 6566  
Fax: +86 755 8869 6577  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)






802.11g


CH 1



CH 6




CH 11





BUREAU VERITAS

Test Report No.: RF171110W005-2



BV 7Layers Communications Technology  
(Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan  
Avenue, North Area, Hi-Tech Industrial Park, Nanshan  
District, Shenzhen, Guangdong, China


Tel: +86 755 8869 6566  
Fax: +86 755 8869 6577  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



BUREAU VERITAS

Test Report No.: RF171110W005-2

### 802.11n (20MHz)



BV 7Layers Communications Technology (Shenzhen) Co. Ltd


No.B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566  
Fax: +86 755 8869 6577  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



**BUREAU  
VERITAS**

Test Report No.: RF171110W005-2




BV 7Layers Communications Technology  
(Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan  
Avenue, North Area, Hi-Tech Industrial Park, Nanshan  
District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566  
Fax: +86 755 8869 6577  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)




802.11n (40MHz)





BUREAU  
VERITAS

Test Report No.: RF171110W005-2



BV 7Layers Communications Technology  
(Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan  
Avenue, North Area, Hi-Tech Industrial Park, Nanshan  
District, Shenzhen, Guangdong, China


Tel: +86 755 8869 6566  
Fax: +86 755 8869 6577  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



**BUREAU  
VERITAS**

Test Report No.: RF171110W005-2

### BT-LE (GFSK)



BV 7Layers Communications Technology  
(Shenzhen) Co. Ltd


No.B102, Dazu Chuangxin Mansion, North of Beihuan  
Avenue, North Area, Hi-Tech Industrial Park, Nanshan  
District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566  
Fax: +86 755 8869 6577  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



**BUREAU  
VERITAS**

Test Report No.: RF171110W005-2



BV 7Layers Communications Technology  
(Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan  
Avenue, North Area, Hi-Tech Industrial Park, Nanshan  
District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566  
Fax: +86 755 8869 6577  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)





**BUREAU**  
**VERITAS** Test Report No.: RF171110W005-2

## 4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



**BUREAU**  
**VERITAS** Test Report No.: RF171110W005-2

## **5 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications are made to the EUT by the lab during the test.

**---END---**