

Shenzhen Mossloo Industrial Co.,Ltd

2018/7/26

To: Federal Communications Commission  
7435 Oakland Mills Road  
Columbia, MD

FCC ID: 2AN8F-MSLM04Q

To Whom It May Concern:

This letter is to ascertain that **Shenzhen Mossloo Industrial Co.,Ltd** Product **2 coil wireless charger , MSL-M04Q**, has been the units used for conducting FCC compliance testing, and it meets 680106 D01 RF Exposure Wireless Charging App v03 Clause 5(b) all 6 conditions.

|        |  |
|--------|--|
| 1      | Power transfer frequency is less than 1 MHz  |
| Reply: | Yes, frequency is 110 - 205 KHz  |
| 2      | Output power from each primary coil is less than or equal to 15 watts.   |
| Reply: | Yes, output power of the primary coil is 5W.   |
| 3      | The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils. |
| Reply: | Yes, the transfer system includes only single primary and secondary coils.   |
| 4      | Client device is placed directly in contact with the transmitter.  |
| Reply: | Yes, client device is placed directly in contact with the transmitter.   |
| 5      | Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).  |
| Reply: | Yes, the EUT is a Mobile Wireless Charger  |
| 6      | The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.  |
| Reply: | Yes, the EUT field strength levels are 50% x MPE limit.  |

If you have any question or concerns, pls. contact us.

Sincerely,  
Signature: *Orders Cheng*

Name: Orders Cheng  
Title: N/A  
Tel: 0755-89501773  
Email: orders@usbhb.com