



## FCC TEST REPORT

### FCC ID: 2AN8F-MSLW198Q

Product Name:	Wireless Charging Power Bank
Trademark:	N/A
Model Number:	MSL-W198Q
Prepared For :	Shenzhen Mossloo Industrial Co.,Ltd
Address :	Road One No.4, Science Industrial Park, Shangxue Village, Bantian Street, Longgang District, Shenzhen, China
Prepared By :	Shenzhen BCTC Testing Co., Ltd.
Address :	BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China
Test Date:	Oct. 16, 2018 – Nov. 07, 2018
Date of Report :	Nov. 07, 2018
Report No.:	BCTC-FY181005930E



## TABLE OF CONTENTS

<b>TEST REPORT DECLARATION .....</b>	<b>3</b>
<b>1.GENERAL INFORMATION .....</b>	<b>4</b>
1.1. Report information .....	4
1.2. Measurement Uncertainty .....	4
1.3. Test Facility .....	4
1.4. Test Uncertainty .....	4
<b>2.PRODUCT DESCRIPTION .....</b>	<b>5</b>
2.1. EUT Description .....	5
2.2. Test mode .....	5
2.3. Block Diagram of EUT Configuration .....	5
2.4. Test Conditions .....	5
2.5. Description Of Support Units (Conducted Mode) .....	6
<b>3.TEST RESULTS SUMMARY .....</b>	<b>6</b>
<b>4.TEST EQUIPMENT USED.....</b>	<b>7</b>
4.1. For Conducted Emission Test .....	7
4.2. For Radiated Emission Measurement .....	7
<b>5.CONDUCTED EMISSION TEST.....</b>	<b>8</b>
5.1. Block Diagram of Test Setup .....	8
5.2. Test Standard .....	8
5.3. Conducted Emission Limit .....	8
5.4. EUT Configuration on Test .....	8
5.5. Operating Condition of EUT .....	9
5.6. Test Procedure .....	9
5.7. Test Result .....	9
<b>6.RADIATED EMISSION MEASUREMENT .....</b>	<b>12</b>
6.1. Block Diagram of Test Setup .....	12
6.2. Test Standard and Limit .....	13
6.3. EMI Test Receiver Setup .....	14
6.4. Test Procedure .....	14
6.5. Test Result .....	14
<b>7.BANDWIDTH TEST .....</b>	<b>20</b>
<b>8.EUT TEST PHOTOS.....</b>	<b>22</b>
<b>9.EUT PHOTOS .....</b>	<b>24</b>



## TEST REPORT DECLARATION

Applicant : Shenzhen Mossloo Industrial Co.,Ltd  
Address : Road One No.4, Science Industrial Park, Shangxue Village, Bantian Street,  
Longgang District, Shenzhen, China  
EUT Description : Wireless Charging Power Bank  
Model Number : MSL-W198Q  
Serial Model : N/A

Test Standards:

### FCC Part 15 C

This device described above has been tested by BCTC, and the test results show that the equipment under And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Prepared by(Engineer): Leke Xie

*Leke Xie*

Reviewer(Supervisor): Eric Yang

*Eric Yang*

Approved(Manager): Carson Zhang

*Carson Zhang*





## 1. GENERAL INFORMATION

### 1.1. Report information

- 1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BCTC approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BCTC in any way guarantees the later performance of the product/equipment.
- 1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BCTC therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 1.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BCTC, unless the applicant has authorized BCTC in writing to do so.

### 1.2. Measurement Uncertainty

Available upon request.

### 1.3. Test Facility

Site Description  
Name of Firm : Shenzhen BCTC Testing Co., Ltd.

Site Location : BCTC Building & 1-2F, East of B Building,  
Pengzhou Industrial, Fuyuan 1st Road, Qiaotou  
Community, Fuyong Street, Bao'an District,  
Shenzhen, China

### 1.4. Test Uncertainty

Conducted Emission =  $\pm 2.66$ dB  
Uncertainty  
Radiated Emission Uncertainty =  $\pm 4.15$ dB



## 2. PRODUCT DESCRIPTION

### 2.1.EUT Description

Description : Wireless Charging Power Bank

Applicant : **Shenzhen Mossloo Industrial Co.,Ltd**  
Road One No.4, Science Industrial Park, Shangxue Village, Bantian Street, Longgang District, Shenzhen, China

Manufacturer : **Shenzhen Mossloo Industrial Co.,Ltd**  
Road One No.4, Science Industrial Park, Shangxue Village, Bantian Street, Longgang District, Shenzhen, China

Model Number : MSL-W198Q

Serial Model : N/A

Model Difference : N/A

Ratings : Battery DC 3.7V 6000mAh  
DC 5V from adapter


Power Supply : Micro Input: DC 5V 2A, Lightning Input: DC 5V 1A  
USB Output 1/2: DC 5V 2A(MAX), Wireless Input: 5V 0.8A  
Wireless output: 5V 1A

Work Frequency : 120-220KHz

### 2.2.Test mode

Test Modes	keeping TX+Charging mode
------------	--------------------------

### 2.3.Block Diagram of EUT Configuration



### 2.4.Test Conditions

Temperature: 23~26°C

Relative Humidity: 54~63 %



### 2.5. Description Of Support Units (Conducted Mode)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E1	Wireless Charging Power Bank	N/A	MSL-W198Q	N/A	EUT
E2	Adapter	N/A	BCTC-002	N/A	Auxiliary
E3	Dummy load	N/A	DL01	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C1	NO	NO	1.0M	DC cable unshielded

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

## 3. TEST RESULTS SUMMARY

**Table 1 Test Results Summary**

Test Items	Test Results
Conducted disturbance	Pass
Radiated disturbance	Pass

Remark: “N/A” means “Not applicable.”



## 4. TEST EQUIPMENT USED

### 4.1. For Conducted Emission Test


Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Test Receiver	R&S	ESR3	102075	2018.06.20	2019.06.20
2	LISN	SCHWARZBECK	NSLK8127	8127739	2018.06.19	2019.06.19
3	LISN	R&S	ENV216	101375	2018.06.20	2019.06.20
4	RF cables	Huber+Suhnar	9kHz-30MHz	B1702988-0008	2018.02.12	2019.02.12
5	Software	Frad	EZ-EMC	EMC-CON 3A1	\	\

### 4.2. For Radiated Emission Measurement

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4407B	MY45109572	2018.06.20	2019.06.20
2	Test Receiver (9kHz-7GHz)	R&S	ESR7	101154	2018.06.20	2019.06.20
3	Bilog Antenna (30MHz-3GHz)	SCHWARZBECK	VULB9163	VULB9163-942	2018.06.23	2019.06.23
4	Horn Antenna (1GHz-18GHz)	SCHWARZBECK	BBHA9120D	1541	2018.06.23	2019.06.22
5	Horn Antenna (18GHz-40GHz)	SCHWARZBECK	BBHA9170	822	2018.08.06	2019.08.06
6	Amplifier (9kHz-6GHz)	SCHWARZBECK	BBV9744	9744-0037	2018.06.20	2019.06.20
7	Amplifier (0.5GHz-18GHz)	SCHWARZBECK	BBV9718	9718-309	2018.06.20	2019.06.20
8	Amplifier (18GHz-40GHz)	MITEQ	TTA1840-35-HG	2034381	2018.08.06	2019.08.06
9	Loop Antenna (9kHz-30MHz)	SCHWARZBECK	FMZB1519B	014	2018.06.23	2019.06.23
10	RF cables1 (9kHz-30MHz)	Huber+Suhnar	9kHz-30MHz	B1702988-0008	2018.02.12	2019.02.12
11	RF cables2 (30MHz-1GHz)	Huber+Suhnar	30MHz-1GHz	1486150	2018.03.27	2019.03.27
12	RF cables3 (1GHz-40GHz)	Huber+Suhnar	1GHz-40GHz	1607106	2018.06.19	2019.06.19
13	Power Metter	Keysight	E4419	\	2018.04.15	2019.04.15
14	Power Sensor (AV)	Keysight	E9 300A	\	2018.04.15	2019.04.15
15	Signal Analyzer 20kHz-26.5GHz	KEYSIGHT	N9020A	MY49100060	2018.08.14	2019.08.13
16	Test Receiver 9kHz-40GHz	R&S	FSP40	100550	2018.06.13	2019.06.12
17	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
18	Software	Frad	EZ-EMC	FA-03A2 RE	\	\

## 5. CONDUCTED EMISSION TEST

### 5.1. Block Diagram of Test Setup



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

### 5.2. Test Standard

FCC§15.207

### 5.3. Conducted Emission Limit

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. \*Decreasing linearly with logarithm of frequency.

### 5.4. EUT Configuration on Test

The following equipments are installed on conducted emission test to meet FCC Part 15.207 requirement and operating in a manner, which tends to maximize its emission characteristics in a normal application.





## 5.5. Operating Condition of EUT

- 5.5.1. Setup the EUT and simulators as shown in Section 5.1.
- 5.5.2. Turn on the power of all equipments.
- 5.5.3. Let the EUT work in test modes (EUT Working) and test it.

## 5.6. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESHS30) is used to test the emissions form both sides of AC line. The bandwidth of EMI test receiver is set at 9kHz.

The bandwidth of the test receiver (R&S Test Receiver ESHS30) is set at 10KHz.


We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.

## 5.7. Test Result

**PASS**



EUT:	Wireless Charging Power Bank	Model Name :	MSL-W198Q
Temperature:	26 °C	Relative Humidity:	55%
Pressure:	101kPa	Phase :	L
Test Voltage :	DC 5V form Adapter AC 120V/60Hz	Test Mode:	Normal




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1580	39.62	9.51	49.13	65.57	-16.44	QP	
2		0.1580	24.62	9.51	34.13	55.57	-21.44	AVG	
3	*	0.2020	38.10	9.46	47.56	63.53	-15.97	QP	
4		0.2020	23.28	9.46	32.74	53.53	-20.79	AVG	
5		0.5980	27.00	9.99	36.99	56.00	-19.01	QP	
6		0.5980	11.84	9.99	21.83	46.00	-24.17	AVG	
7		1.6740	28.02	9.58	37.60	56.00	-18.40	QP	
8		1.6740	11.59	9.58	21.17	46.00	-24.83	AVG	
9		3.7620	28.19	9.71	37.90	56.00	-18.10	QP	
10		3.7620	11.27	9.71	20.98	46.00	-25.02	AVG	
11		10.6860	32.24	9.69	41.93	60.00	-18.07	QP	
12		10.6860	13.04	9.69	22.73	50.00	-27.27	AVG	



EUT:	Wireless Charging Power Bank	Model Name:	MSL-W198Q
Temperature:	26 °C	Relative Humidity:	55%
Pressure:	101kPa	Phase :	N
Test Voltage :	DC 5V form Adapter AC 120V/60Hz	Test Mode:	Normal



**Remark:**


1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1620	40.43	9.51	49.94	65.36	-15.42	QP	
2		0.1620	26.45	9.51	35.96	55.36	-19.40	AVG	
3	*	0.2020	39.96	9.46	49.42	63.53	-14.11	QP	
4		0.2020	23.11	9.46	32.57	53.53	-20.96	AVG	
5		0.6020	27.86	9.99	37.85	56.00	-18.15	QP	
6		0.6020	9.31	9.99	19.30	46.00	-26.70	AVG	
7		1.4780	25.20	9.58	34.78	56.00	-21.22	QP	
8		1.4780	9.11	9.58	18.69	46.00	-27.31	AVG	
9		3.4020	26.18	9.69	35.87	56.00	-20.13	QP	
10		3.4020	10.04	9.69	19.73	46.00	-26.27	AVG	
11		10.4020	29.66	9.69	39.35	60.00	-20.65	QP	
12		10.4020	12.61	9.69	22.30	50.00	-27.70	AVG	

## 6. RADIATED EMISSION MEASUREMENT


### 6.1. Block Diagram of Test Setup

#### 6.1.1. Block Diagram of connection between the EUT and the simulators




#### 6.1.2. Anechoic Chamber Test Setup Diagram

##### (A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.

## 6.2. Test Standard and Limit

FCC §15.209; §15.205

Test Standard	FCC Part15 C Section 15.209 and 15.205					
	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)	
Test Limit	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300	
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30	
	1.705MHz-30MHz	30	-	-	30	
	30MHz~88MHz	100	40.0	Quasi-peak	3	
	88MHz~216MHz	150	43.5	Quasi-peak	3	
	216MHz~960MHz	200	46.0	Quasi-peak	3	
	Above 1000MHz		500	54.0	Quasi-peak	3
			-	74.0	Peak	3



### 6.3.EMI Test Receiver Setup

The system was investigated from 9kHz to1GHz.  
During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	Video B/W	Detector
9 kHz – 150 kHz	200 kHz	1 kHz	QP
150 kHz – 30MHz	9kHz	30kHz	QP
30 MHz – 1000 MHz	120 kHz	300 kHz	QP

Note: For the frequency bands 9-90 kHz and 110-490 kHz, the test was based on average detector.

### 6.4.Test Procedure

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna (calibrated by dipole antenna) are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on measurement.

### 6.5.Test Result

**PASS**



**9kHz-30MHz**

EUT:	Wireless Charging Power Bank	Model Name:	MSL-W198Q
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Polarization :	Horizontal
Test Voltage :	DC 5V form Adapter AC 120V/60Hz		
Test Mode :	Normal		

Frequency (kHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
19.3400	39.49	20.15	59.64	141.88	-82.24	PK
19.3400	36.12	20.15	56.27	121.88	-65.61	AV
53.3900	50.67	20.33	71.00	133.06	-62.06	PK
53.3900	46.33	20.33	66.66	113.06	-46.40	AV
121.5500	68.27	20.55	88.82	125.91	-37.09	PK
121.5500	63.61	20.55	84.16	105.91	-21.75	AV
685.4800	31.13	20.64	51.77	70.88	-19.11	QP
968.4500	35.12	21.26	56.38	67.88	-11.50	QP
1229.3100	24.69	22.32	47.01	65.81	-18.80	QP

**Note:**

Pre-scan in the all of mode, the worst case in of was recorded.


Factor = antenna factor + cable loss – pre-amplifier.

Margin = Emission Level- Limit.



### 30MHz-1GHz

EUT:	Wireless Charging Power Bank	Model Name:	MSL-W198Q
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Polarization :	Horizontal
Test Voltage :	DC 3.7V		
Test Mode :	Wireless Output		




Remark:  
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		31.6202	30.78	-12.44	18.34	40.00	-21.66	QP
2		50.7637	33.84	-12.59	21.25	40.00	-18.75	QP
3		166.0680	32.54	-11.34	21.20	43.50	-22.30	QP
4		227.6906	48.44	-11.24	37.20	46.00	-8.80	QP
5	*	242.5253	49.81	-10.37	39.44	46.00	-6.56	QP
6		419.1081	31.44	-5.19	26.25	46.00	-19.75	QP





EUT:	Wireless Charging Power Bank	Model Name:	MSL-W198Q
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Polarization :	Vertical
Test Voltage :	DC 3.7V		
Test Mode :	Wireless Output		




Remark:  
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		31.1798	27.96	-12.47	15.49	40.00	-24.51	QP
2		50.7637	28.46	-12.59	15.87	40.00	-24.13	QP
3	*	71.8320	36.40	-14.05	22.35	40.00	-17.65	QP
4		201.3930	38.17	-12.78	25.39	43.50	-18.11	QP
5		244.2321	33.62	-10.26	23.36	46.00	-22.64	QP
6		701.7610	22.74	1.15	23.89	46.00	-22.11	QP



EUT:	Wireless Charging Power Bank	Model Name:	MSL-W198Q
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Polarization :	Horizontal
Test Voltage :	DC 5V		
Test Mode :	Wireless Input		




Remark:  
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		37.2855	31.37	-15.92	15.45	40.00	-24.55	QP
2	*	53.1313	30.78	-15.18	15.60	40.00	-24.40	QP
3		103.8055	27.75	-16.53	11.22	43.50	-32.28	QP
4		167.2368	31.38	-18.40	12.98	43.50	-30.52	QP
5		276.1235	32.60	-14.34	18.26	46.00	-27.74	QP
6		566.6223	27.75	-7.29	20.46	46.00	-25.54	QP



EUT:	Wireless Charging Power Bank	Model Name:	MSL-W198Q
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Polarization :	Vertical
Test Voltage :	DC 5V		
Test Mode :	Wireless Input		



Remark:  
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		34.8823	32.05	-16.37	15.68	40.00	-24.32	QP
2	*	54.4516	31.61	-15.32	16.29	40.00	-23.71	QP
3		105.2718	28.36	-16.62	11.74	43.50	-31.76	QP
4		161.4742	34.98	-18.77	16.21	43.50	-27.29	QP
5		422.0577	29.03	-10.60	18.43	46.00	-27.57	QP
6		501.1790	28.22	-8.91	19.31	46.00	-26.69	QP



## 7. BANDWIDTH TEST

1. Set RBW = 3 kHz.
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.


### TEST SETUP





EUT:	Wireless Charging Power Bank	Model Name:	MSL-W198Q
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa		

Frequency (KHz)	20dB bandwidth (KHz)	99% bandwidth (KHz)	Result
121	20.00	18.936	Pass





## 8. EUT TEST PHOTOS


**Conducted Measurement Photos**





**Radiated Measurement Photos**

9KHz-30MHz



30MHz-1GHz





## 9. EUT PHOTOS



\*\*\*\*\* END OF REPORT \*\*\*\*\*