

**47 C.F.R. Part 1, Subpart I, Section 1.1310  
47 C.F.R. Part 2, Subpart J, Section 2.1091  
Maximum Permissible Exposure Calculations**

**For Carefree Scott Fetzer Co Inc M/N: BT Motion Sensor**

**BLE Transceiver**

EUT Device Category = General Population/Uncontrolled Exposure

EUT consists of one ISM band radio transmitting operating over a range of:  
**2402 MHz to 2480 MHz**

MPE Summary:

According subpart 1.1307 (b)(1) and 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure						
Frequency Range (MHz)	Electric Strength (V/m)	Field Magnetic Strength (A/m)	Field Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)		
0.3-1.34	614	1.63	*(100)	30		
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30		
30-300	27.5	0.073	0.2	30		
300-1500	/	/	f/1500	30		
1500-100,000	/	/	1.0	30		

f = frequency in MHz; \* = Plane-wave equivalent power density

**Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

PG = EIRP

MPE and Limit are calculated as follows:

f (MHz)	EIRP (dBuV/m)	EIRP (mW)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Δ
2402	95.1	0.9708	0.0002	1000	999.99
2440	94.6	0.8652	0.0002	1000	999.99
2480	93.3	0.6414	0.0001	1000	999.99

**Result:** The device meets FCC MPE limit at 20 cm for General Population/Uncontrolled Exposure as specified in 47 CFR §1.1310 and §2.1091.