

SAR Exemption Exhibit

Certification

Applicant Name:
Eko Devices, Inc.**Date of Issue:**
November 11, 2019**Address:**
2600 10th St. Ste 260
Berkeley, CA 94710, USA**Test Site/Location:**
EMCE Engineering
1726 Ringwood Avenue San Jose, California USA
Report No.: EMCE-R-1911-003**FCC ID:** 2ANB3-E6**IC:** 23063-E6**APPLICANT:** Eko Devices, Inc.**Model:** E6**EUT Type:** Electronic Stethoscope System**Frequency Range:** 2402 MHz – 2480 MHz

The measurements shown in this report were made in accordance with the procedures specified in §2.947.

I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them



Steve In
Test Engineer
Certification Division



Billy Kim
Technical Manager
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the EMCE Engineering, Inc.

Version

TEST REPORT NO.	DATE	DESCRIPTION
EMCE-R-1911-003	November 11, 2019	Initial Release

EXPOSURE EVALUATION OF PORTABLE DEVICE

The RF exposure from portable device (47 CFR §2.1091), as defined by FCC, must be evaluated with respect to FCC-adopted limits for SAR.

When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion.

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR.}$

EVALUATION RESULTS

Modulation Mode	Freq.(MHz)	Max Power (dBm)	Max Power (mW)	Limit (mW)
1Mbps	2402	2.44	1.75	10.087
	2440	3.69	2.34	10.018
	2480	0.87	1.22	9.948

Modulation Mode	Freq.(MHz)	Max Power (dBm)	Max Power (mW)	Limit (mW)
2Mbps	2402	2.23	1.67	10.087
	2440	4.03	2.53	10.018
	2480	4.88	3.08	9.948

$$\begin{aligned}
 & \frac{(\text{max. power of channel, including tuneup tolerance, mW})}{(\text{min. test separation distance, mm})} \times \left[\sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR} \\
 & = \frac{3.08 \text{ mW}}{5 \text{ mm}} \times \left[\sqrt{2.480 \text{ GHz}} \right] = 0.97 \leq 3.0
 \end{aligned}$$

Worst SAR Test Exclusion Thresholds is < 9.948 mW and 3.0 for separation distance 5mm.

Conclusion

The result after calculation is less than or equal to 3, the limit for 1-g SAR, therefore this device is exempt from SAR evaluation.