

SHENZHEN MAI XIN DA TECHNOLOGY
CO.,LTD

TEST REPORT

SCOPE OF WORK
FCC TESTING—WBTK

REPORT NUMBER
190403030SZN-001

ISSUE DATE	[REVISED DATE]
April 22, 2019	[-----]

PAGES
43

DOCUMENT CONTROL NUMBER
FCC ID 249_C
© 2017 INTERTEK



SHENZHEN MAI XIN DA TECHNOLOGY CO.,LTD

Application
For
Certification

FCC ID: 2ANBM-88888**Bluetooth audio kit****Model: WBTK****Brand Name: iWorld****2.4GHz Transceiver****Report No.: 190403030SZN-001**

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-17]

Prepared and Checked by:

Approved by:

Damon Wang
Project Engineer

Kidd Yang
Technical Supervisor
Date: April 22, 2019

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Service Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen, P.R. China
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information
<i>EXHIBIT 9:</i>	Confidentiality Request
<i>EXHIBIT 10:</i>	Test Equipment List

MEASUREMENT/TECHNICAL REPORT

SHENZHEN MAI XIN DA TECHNOLOGY CO.,LTD

Model: WBTKK

FCC ID: 2ANBM-88888

This report concerns (check one:) Original Grant X Class II Change _____Equipment Type: DXX - Part 15 Low Power Communication Device TransmitterDeferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes _____ No X _____If yes, defer until: _____
dateCompany Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes _____ No X _____

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-1-17 Edition] provision.

Report prepared by:

Damon Wang
Intertek Testing Services Shenzhen Ltd. Longhua Branch
101, 201, Building B, No. 308 Wuhe Avenue,
Zhangkengjing Community, GuanHu Subdistrict,
LongHua District, ShenZhen, P.R. China
Tel / Fax: 86-755-8601 6288/86-755-8601 6661

Table of Contents

1.0 General Description	7
1.1 Product Description	7
1.3 Test Methodology	7
1.4 Test Facility.....	7
2.0 System Test Configuration	9
2.1 Justification	9
2.2 EUT Exercising Software	9
2.3 Special Accessories	9
2.4 Equipment Modification.....	9
2.5 Measurement Uncertainty	10
2.6 Support Equipment List and Description	10
3.0 Emission Results	12
3.1 Radiated Test Results	13
3.1.1 Field Strength Calculation	13
3.1.2 Radiated Emission Configuration Photograph	14
3.1.3 Radiated Emissions	14
3.1.4 Transmitter Spurious Emissions	17
3.2 Conducted Emission at Mains Terminal	21
3.2.1 Conducted Emission Configuration Photograph	21
3.2.2 Conducted Emission Data	22
4.0 Equipment Photographs	26
5.0 Product Labelling	28
6.0 Technical Specifications	30
7.0 Instruction Manual	32
8.0 Miscellaneous Information	34
8.1 Bandedge Plot	35
8.2 Discussion of Pulse Desensitization	37
8.3 Emissions Test Procedures.....	38
9.0 Confidentiality Request	41
10.0 Test Equipment List	43

List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
Test Report	Bandedge Plot	bandedge.pdf
Test Report	20dB BW Plot	bw.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

EXHIBIT 1

GENERAL DESCRIPTION

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is a Bluetooth audio kit with BT4.2 (Single Mode) operating in 2402-2480MHz. The EUT is powered by DC 3.7V by rechargeable battery or DC 5V with AC adaptor. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Antenna Gain: -0.58 dBi

Modulation Type: GFSK, $\pi/4$ -DQPSK and 8-DPSK

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shielded room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

1.3 Test Facility

The Semi-anechoic chamber and shielded room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen, P.R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: CN1188).

EXHIBIT 2

SYSTEM TEST CONFIGURATION

2.0 System Test Configuration

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The EUT was powered by DC 5V from adapter with 120V/60Hz input during the test, only the worst data was reported in this report.

For maximizing emissions below 30 MHz, the EUT was rotated through 360°, the centre of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.

The rear of unit was flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

The EUT exercise program (provided by client) used during testing was designed to exercise the various system components in a manner similar to a typical use.

2.3 Special Accessories

No special accessories used.

2.4 Equipment Modification

Any modifications installed previous to testing by SHENZHEN MAI XIN DA TECHNOLOGY CO.,LTD will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd Longhua Branch.

2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

Description	Manufacturer	Model No.
Adaptor	OPPO	AG933GB
USB Cable	N/A	N/A
3.5mm connector plug	iWorld	N/A
Audio speaker	N/A	N/A

EXHIBIT 3

EMISSION RESULTS

3.0 Emission Results

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

3.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

3.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB
- AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$\begin{aligned} RA &= 62.0 \text{ dB}\mu\text{V} \\ AF &= 7.4 \text{ dB} \\ CF &= 1.6 \text{ dB} \\ AG &= 29.0 \text{ dB} \\ PD &= 0 \text{ dB} \\ AV &= -10 \text{ dB} \\ FS &= 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m} \end{aligned}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

3.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

3.1.3 Radiated Emissions

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit. Simultaneous transmission was considered.

Worst Case Radiated Emission
at
383.985 MHz

Judgement: Passed by 5.1 dB

TEST PERSONNEL:

Sign on file

Damon Wang, Project Engineer

Typed/Printed Name

12 April 2019

Date

Applicant: SHENZHEN MAI XIN DA TECHNOLOGY CO.,LTD

Date of Test: 12 April 2019


Model: WBTCK

Worst Case Operating Mode:

Transmit(2402MHz)


ANT Polarity: Horizontal

FCC Part 15



ANT Polarity: Vertical

FCC Part 15



Applicant: SHENZHEN MAI XIN DA TECHNOLOGY CO.,LTD

Date of Test: 12 April 2019

Model: WBTCK

Worst Case Operating Mode:

Transmit(2402MHz)

Table 1

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	191.993	44.7	20.0	10.1	34.8	43.5	-8.7
Horizontal	383.995	49.1	20.0	11.3	40.4	46.0	-5.6
Horizontal	671.988	31.9	20.0	21.7	33.6	46.0	-12.4
Vertical	191.979	45.2	20.0	10.1	35.3	43.5	-8.2
Vertical	383.985	57.8	20.0	3.1	40.9	46.0	-5.1
Vertical	576.014	37.4	20.0	21.7	39.1	46.0	-6.9

- NOTES:
1. Quasi-Peak detector is used except for others stated.
 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. All emissions are below the QP limit.

3.1.4 Transmitter Spurious Emissions (Radiated)

Worst Case Radiated Emission
at
7206.000 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 3.2 dB

TEST PERSONNEL:

Sign on file

Damon Wang, Project Engineer

Typed/Printed Name

12 April 2019

Date

Applicant: SHENZHEN MAI XIN DA TECHNOLOGY CO.,LTD

Date of Test: 12 April 2019

Model: WBTCK

Worst Case Operating Mode:

Transmitting

Table 2

Radiated Emissions

(2402MHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Vertical	2402.000	109.1	36.7	28.1	100.5	114.0	-13.5
Vertical	4804.000	56.8	36.7	35.5	55.6	74.0	-18.4
Vertical	7206.000	66.1	36.1	36.5	66.5	74.0	-7.5
Vertical	9608.000	56.2	36.2	37.0	57.0	74.0	-17.0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Vertical	2402.000	73.9	36.7	28.1	65.3	94.0	-28.7
Vertical	4804.000	43.1	36.7	35.5	41.9	54.0	-12.1
Vertical	7206.000	50.4	36.1	36.5	50.8	54.0	-3.2
Vertical	9608.000	46.7	36.2	37.0	47.5	54.0	-6.5

Notes: 1. RBW=1MHz/VBW=3MHz was used for peak measurements and Average measurements were made with measurement instrumentation employing an average detector function using a minimum resolution bandwidth of 1 MHz.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Damon Wang

Applicant: SHENZHEN MAI XIN DA TECHNOLOGY CO.,LTD

Date of Test: 12 April 2019

Model: WBTCK

Worst Case Operating Mode:

Transmitting

Table 3

Radiated Emissions

(2441MHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Vertical	2441.000	108.9	36.7	28.1	100.3	114.0	-13.7
Vertical	4882.000	57.2	36.7	35.5	56.0	74.0	-18.0
Vertical	7323.000	64.8	36.1	37.2	65.9	74.0	-8.1
Vertical	9764.000	56.4	36.2	37.0	57.2	74.0	-16.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Vertical	2441.000	73.8	36.7	28.1	65.2	94.0	-28.8
Vertical	4882.000	43.3	36.7	35.5	42.1	54.0	-11.9
Vertical	7323.000	49.6	36.1	37.2	50.7	54.0	-3.3
Vertical	9764.000	46.9	36.2	37.0	47.7	54.0	-6.3

Notes: 1. RBW=1MHz/VBW=3MHz was used for peak measurements and Average measurements were made with measurement instrumentation employing an average detector function using a minimum resolution bandwidth of 1 MHz.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Damon Wang

Applicant: SHENZHEN MAI XIN DA TECHNOLOGY CO.,LTD

Date of Test: 12 April 2019

Model: WBTCK

Worst Case Operating Mode:

Transmitting

Table 4

Radiated Emissions

(2480MHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Vertical	2480.000	108.8	36.7	28.1	100.2	114.0	-13.8
Vertical	4960.000	59.1	36.7	35.5	57.9	74.0	-16.1
Vertical	7440.000	62.6	36.1	37.2	63.7	74.0	-10.3
Vertical	9920.000	54.5	36.3	38.9	57.1	74.0	-16.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Vertical	2480.000	73.7	36.7	28.1	65.1	94.0	-28.9
Vertical	4960.000	44.8	36.7	35.5	43.6	54.0	-10.4
Vertical	7440.000	48.1	36.1	37.2	49.2	54.0	-4.8
Vertical	9920.000	45.0	36.3	38.9	47.6	54.0	-6.4

Notes: 1. RBW=1MHz/VBW=3MHz was used for peak measurements and Average measurements were made with measurement instrumentation employing an average detector function using a minimum resolution bandwidth of 1 MHz.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Damon Wang

3.2 Conducted Emission at Mains Terminal

3.2.1 Conducted Emission Configuration Photograph

Worst Case Conducted Configuration
at
0.198 MHz (Transmit Mode)

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

3.2.2 Conducted Emission Data

Judgement: Passed by 28.0 dB margin(Transmit Mode)

TEST PERSONNEL:

Sign on file

Damon Wang, Engineer

Typed/Printed Name

12 April 2019

Date

Company: SHENZHEN MAI XIN DA TECHNOLOGY CO.,LTD


Date of Test: 12 April 2019

Model: WBTCK

Operating Mode: Transmit mode

Phase: Live

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ /V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ /V)
0.198000	32.4	9.000	L1	9.6	31.3	63.7
0.306000	26.3	9.000	L1	9.6	33.8	60.1
0.562000	16.8	9.000	L1	9.6	39.2	56.0
0.970000	14.2	9.000	L1	9.7	41.8	56.0
6.930000	17.5	9.000	L1	9.8	42.5	60.0
24.002000	25.5	9.000	L1	10.5	34.5	60.0

Result Table AV

Frequency (MHz)	Average (dB μ /V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ /V)
0.198000	25.7	9.000	L1	9.6	28.0	53.7
0.306000	20.7	9.000	L1	9.6	29.4	50.1
0.562000	13.3	9.000	L1	9.6	32.7	46.0
0.970000	9.8	9.000	L1	9.7	36.2	46.0
6.930000	12.6	9.000	L1	9.8	37.4	50.0
24.002000	19.1	9.000	L1	10.5	30.9	50.0

Test Engineer: Damon Wang

Company: SHENZHEN MAI XIN DA TECHNOLOGY CO.,LTD


Date of Test: 12 April 2019

Model: WBTCK

Operating Mode: Transmit mode

Phase: Neutral

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ /V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ /V)
0.198000	31.3	9.000	N	9.6	32.4	63.7
0.306000	26.2	9.000	N	9.6	33.9	60.1
0.954000	14.6	9.000	N	9.7	41.4	56.0
3.118000	11.3	9.000	N	9.7	44.7	56.0
6.994000	17.1	9.000	N	9.8	42.9	60.0
23.998000	21.7	9.000	N	10.5	38.3	60.0

Result Table AV

Frequency (MHz)	Average (dB μ /V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ /V)
0.198000	25.1	9.000	N	9.6	28.6	53.7
0.306000	20.7	9.000	N	9.6	29.4	50.1
0.954000	10.1	9.000	N	9.7	35.9	46.0
3.118000	6.5	9.000	N	9.7	39.5	46.0
6.994000	10.5	9.000	N	9.8	39.5	50.0
23.998000	18.6	9.000	N	10.5	31.4	50.0

Test Engineer: Damon Wang

EXHIBIT 4

EQUIPMENT PHOTOGRAPHS

4.0 Equipment Photographs

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

EXHIBIT 5

PRODUCT LABELLING

5.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

EXHIBIT 6

TECHNICAL SPECIFICATIONS

6.0 Technical Specifications

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 7

INSTRUCTION MANUAL

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

EXHIBIT 8

MISCELLANEOUS INFORMATION

8.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandedge, the test procedure and calculation of factor such as pulse desensitization.

8.1 Bandedge Plot

For electronic filing, the plot shows the fundamental emission when modulated is saved with filename: bandedge.pdf. From the plot, the field strength of any emissions outside of the specified frequency band are attenuated to the general radiated emission limits in section 15.209. It fulfils the requirement of 15.249(d).

Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e (Bandedge Plot).

(i) Lower channel 2402MHz:

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot

$$\begin{aligned} &= 100.5 \text{ dB}\mu\text{v/m} - 33.41 \text{ dB} \\ &= 67.09 \text{ dB}\mu\text{v/m} \end{aligned}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the bandedge plot

$$\begin{aligned} &= 65.3 \text{ dB}\mu\text{v/m} - 33.41 \text{ dB} \\ &= 31.89 \text{ dB}\mu\text{v/m} \end{aligned}$$

(ii) Upper channel 2480MHz:

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot

$$\begin{aligned} &= 100.2 \text{ dB}\mu\text{v/m} - 41.13 \text{ dB} \\ &= 59.07 \text{ dB}\mu\text{v/m} \end{aligned}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the bandedge plot

$$\begin{aligned} &= 65.1 \text{ dB}\mu\text{v/m} - 41.13 \text{ dB} \\ &= 23.97 \text{ dB}\mu\text{v/m} \end{aligned}$$

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dBμv/m (Peak Limit) and 54dBμv/m (Average Limit).

8.1 Bandedge Plot (cont'd)

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

Figure 8.1 Bandwidth

8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

8.3 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.10 - 2013.

The transmitting equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter and approximately 0.8 meter up to 1GHz and 1.5 meter above 1GHz in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjust through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average Measurements were made with measurement instrumentation employing an average detector function using a minimum resolution bandwidth of 1 MHz.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Detector function for conducted emissions is in QP & AV mode and IFBW setting is 9 kHz from the frequency band 150 kHz to 30MHz.

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.10 - 2013.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used (RBW 3MHz used for fundamental emission).

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

EXHIBIT 9

CONFIDENTIALITY REQUEST

9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

EXHIBIT 10

TEST EQUIPMENT LIST

10.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	14-Sep-2018	14-Sep-2019
SZ185-01	EMI Receiver	R&S	ESCI	100547	04-Jan-2019	04-Jan-2020
SZ061-08	Horn Antenna	ETS	3115	00092346	14-Sep-2018	14-Sep-2019
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	21-May-2018	21-May-2019
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	05-Jun-2018	05-Jun-2019
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	05-Jun-2018	05-Jun-2019
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	15-Jan-2019	15-Jan-2020
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	15-Dec-2018	15-Dec-2020
SZ062-02	RF Cable	RADIAL	RG 213U	--	10-Jun-2018	10-Jun-2019
SZ062-05	RF Cable	RADIAL	0.04-26.5GHz	--	10-Jun-2018	10-Jun-2019
SZ062-12	RF Cable	RADIAL	0.04-26.5GHz	--	10-Jun-2018	10-Jun-2019
SZ067-04	Notch Filter	Micro-Tronics	BRM50702-02	--	05-Jun-2018	05-Jun-2019
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	26-Oct-2018	26-Oct-2019
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	26-Oct-2018	26-Oct-2019
SZ188-03	Shielding Room	ETS	RFD-100	4100	16-Jan-2017	16-Jan-2020

***** End of Report*****