

Test Report

FCC ID:2ANBQ-IM2

Date of issue: Jul. 08, 2017

Report Number:	MTi170809E045
Sample Description:	MOMAX K-MIC PRO Wireless Karaoke Microphone
Model(s):	IM2
Applicant:	Momax Technology (Shenzhen) Limited
Address:	No.709, Floor 7, Vanke Fuchun Eastern Mansion Shennan Road 7006, Futian District, Shenzhen, China
Date of Test:	Jun. 23, 2017 – Jul. 08, 2017

Shenzhen Microtest Co., Ltd.
<http://www.mtitest.com>

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Tel:(86-755)88850135

Fax: (86-755) 88850136

Web: <http://www.mtitest.com>

E-mail: mti@51mti.com

Address: No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China

TEST RESULT CERTIFICATION	
Applicant's name	Momax Technology (Shenzhen) Limited
Address	No.709, Floor 7, Vanke Fuchun Eastern Mansion Shennan Road 7006, Futian District, Shenzhen, China
Manufacture's Name	iMX Electronic (Shenzhen) Co.,LTD
Address	F/4 East Side Mech. Factory, EVOC Tech. Industrial. Park, No.11 Gaoxin Rd., Gaoxin Area, Guangming New Area, Shenzhen City, Guangdong, PRC.
Product name	MOMAX K-MIC PRO Wireless Karaoke Microphone
Model and/or type reference :	IM2
Serial Model	N/A
Standards	FCC Part15.247
Test procedure	ANSI C63.10-2014

This device described above has been tested by Shenzhen Toby Technology Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Amy Lu

Amy Lu

Jul. 08, 2017

Reviewed by:

Smith Chen

Smith Chen

Jul. 08, 2017

Approved by:

Tom Xue

Tom Xue

Jul. 08, 2017

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 RADIATED EMISSION LIMITS	17
3.2.2 TEST PROCEDURE	17
3.2.3 DEVIATION FROM TEST STANDARD	18
3.2.4 TEST SETUP	19
3.2.5 EUT OPERATING CONDITIONS	20
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	21
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	22
3.2.8 TEST RESULTS (1G-25GHZ)	23
4 . 20 DB OCCUPY BANDWIDTH	26
4.1 APPLIED PROCEDURES / LIMIT	26
4.1.1 TEST PROCEDURE	26
4.1.2 DEVIATION FROM STANDARD	26
4.1.3 TEST SETUP	26
4.1.4 EUT OPERATION CONDITIONS	26
4.1.5 TEST RESULTS	27
5 . CARRIER FREQUENCY SEPARATION TEST	29

Table of Contents

	Page
5.1 APPLIED PROCEDURES / LIMIT	29
5.1.1 TEST PROCEDURE	29
5.1.2 DEVIATION FROM STANDARD	29
5.1.3 TEST SETUP	29
5.1.4 EUT OPERATION CONDITIONS	29
5.1.5 TEST RESULTS	30
6 . NUMBER OF HOPPING CHANNEL	32
6.1 APPLIED PROCEDURES / LIMIT	32
6.1.2 DEVIATION FROM STANDARD	32
6.1.3 TEST SETUP	32
6.1.4 EUT OPERATION CONDITIONS	32
6.1.5 TEST RESULTS	32
7 . DWELL TIME	34
7.1 APPLIED PROCEDURES / LIMIT	34
7.1.2 DEVIATION FROM STANDARD	34
7.1.3 TEST SETUP	34
7.1.4 EUT OPERATION CONDITIONS	34
7.1.5 TEST RESULTS	34
8 . PEAK OUTPUT POWER TEST	38
8.1 APPLIED PROCEDURES / LIMIT	38
8.1.1 TEST PROCEDURE	38
8.1.2 DEVIATION FROM STANDARD	38
8.1.3 TEST SETUP	38
8.1.4 EUT OPERATION CONDITIONS	38
8.1.5 TEST RESULTS	39
9 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	40
9.1 DEVIATION FROM STANDARD	40
9.2 TEST SETUP	40
9.3 EUT OPERATION CONDITIONS	40
9.4 TEST RESULTS	41
10 . ANTENNA REQUIREMENT	45
10.1 STANDARD REQUIREMENT	45
10.2 EUT ANTENNA	45

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.203/15.247(c)	Antenna Requirement	PASSED	
15.207	Conducted Emission	PASSED	
15.247(b)(1)	Conducted Peak Output Power	PASSED	
15.247(a)(1)	20dB Occupied Bandwidth	PASSED	
15.247(a)(1)	Carrier Frequencies Separation	PASSED	
15.247(a)(1)	Hopping Channel Number	PASSED	
15.247(a)(1)	Dwell Time	PASSED	
15.205/15.209	Spurious Emission	PASSED	
15.247(d)	Band Edge	PASSED	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen Toby Technology Co., Ltd.
Add.: 10/F.,A Block, Jiada R&D Bldg.,No.5 Songpingshan, Road, Science&Technology Park,
Shenzhen, 518057
FCC Registration No.:811562

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	MOMAX K-MIC PRO Wireless Karaoke Microphone	
Trade Name	MOMAX	
Model Name	IM2	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a MOMAX K-MIC PRO Wireless Karaoke Microphone	
	Operation Frequency:	2402-2480MHz
	Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
	Bit Rate of Transmitter	1,2,3Mbps
	Number Of Channel	79CH
	Antenna Designation:	Please see Note 3.
	Output Power(Conducted):	4.45 dBm
	Antenna Gain (dBi)	2.5dBi
Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.		
Channel List	Please refer to the Note 2.	
Battery	DC 3.7V 2500mAh	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. Channel List

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466

11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		
Remark: Channel 0, 39 &78 selected for GFSK, $\pi/4$ -DQPSK and 8DPSK.					

3. Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	N/A	Integrated antenna	/	2.5	BT Antenna

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	GFSK CH1/CH40/CH79
Mode 2	TX mode


For Conducted Emission	
Final Test Mode	Description
Mode 4	TX mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	GFSK CH1/CH40/CH79

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported
- (3) GFSK PI/4QPSK 8DPSK all tested, GFSK is worse case and only reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	MOMAX K-MIC PRO Wireless Karaoke Microphone	MOMAX	IM2	N/A	EUT
E-2	Adapter	N/A	SAW12-050-2000UD	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	USB cable	NO	0.8mm	NO

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

For RF conducted test:

Equipment	Manufacturer	Model	Serial No.	Calibration Due
Universal Radio Communication Tester	Rohde&schwarz	CMU200	114587	2017/11/4
Spectrum analyzer	Agilent	E4407B	MY41441082	2017/11/4
Dc Power Supply	GW	GPR-6030D	/	2017/11/4
Temperature & Humidity Chamber	GIANT FORCE	GTH-056P	GF-94454-1	2017/11/14
Broadband TRILOG Antenna	Schwarabeck	VULB9163	9163-872	2017/11/14
Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-1145	2017/11/14
Amplifier	HP	8447D	3113A06150	2017/11/4
Amplifier	Agilent	8449B	3008A02400	2018/7/4
Test Receiver	Schwarabeck	ESPI7	100314	2017/11/4
Spectrum analyzer	Agilent	E4407B	MY41441082	2017/11/4
Signal Generator	R&S	SMT 06	832080/007	2017/11/4
Broadband TRILOG Antenna	Schwarabeck	VULB9163	9163-872	2017/11/14
Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-1145	2017/11/14
Amplifier	HP	8447D	3113A06150	2017/11/4
Amplifier	Agilent	8449B	3008A02400	2018/7/4
Test Receiver	Schwarabeck	ESPI	100314	2017/11/4
Spectrum analyzer	Agilent	E4407B	MY41441082	2017/11/4
LISN	R&S	ENV216	1001131	2017/9/25
Test Cable	United Microwave	57793	1m	2017/12/05
Test Cable	United Microwave	A30A30-5006	10m	2017/12/05

Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP




- Note: 1. Support units were connected to second LISN.**
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.6 TEST RESULTS

EUT :	MOMAX K-MIC PRO Wireless Karaoke Microphone	Model Name. :	IM2
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from adapter AC 120V/60Hz	Test Mode :	Mode 4



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1660	24.03	-0.03	24.00	55.16	-31.16	AVG	
2		0.1700	38.13	-0.03	38.10	64.96	-26.86	QP	
3		0.3059	27.93	-0.03	27.90	50.08	-22.18	AVG	
4		0.3140	38.93	-0.03	38.90	59.86	-20.96	QP	
5	*	0.5540	41.63	-0.03	41.60	56.00	-14.40	QP	
6		0.5580	30.75	-0.03	30.72	46.00	-15.28	AVG	
7		0.9060	38.11	-0.04	38.07	56.00	-17.93	QP	
8		0.9060	26.42	-0.04	26.38	46.00	-19.62	AVG	
9		1.4418	24.17	-0.04	24.13	46.00	-21.87	AVG	
10		1.4700	35.14	-0.04	35.10	56.00	-20.90	QP	
11		6.1859	21.18	-0.05	21.13	50.00	-28.87	AVG	
12		6.2778	38.08	-0.05	38.03	60.00	-21.97	QP	

EUT :	MOMAX K-MIC PRO Wireless Karaoke Microphone	Model Name. :	IM2
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from adapter AC 120V/60Hz	Test Mode :	Mode 4



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2660	44.99	-0.03	44.96	61.24	-16.28	QP	
2		0.2660	29.68	-0.03	29.65	51.24	-21.59	AVG	
3	*	0.5660	44.06	-0.03	44.03	56.00	-11.97	QP	
4		0.5660	28.50	-0.03	28.47	46.00	-17.53	AVG	
5		0.9460	40.88	-0.04	40.84	56.00	-15.16	QP	
6		0.9460	26.06	-0.04	26.02	46.00	-19.98	AVG	
7		6.4020	41.78	-0.05	41.73	60.00	-18.27	QP	
8		6.4020	21.25	-0.05	21.20	50.00	-28.80	AVG	
9		22.1259	46.70	-0.29	46.41	60.00	-13.59	QP	
10		22.1259	22.23	-0.29	21.94	50.00	-28.06	AVG	
11		28.8660	43.73	-0.38	43.35	60.00	-16.65	QP	
12		28.8660	35.48	-0.38	35.10	50.00	-14.90	AVG	

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microrvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz PK detector is for AV

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	MOMAX K-MIC PRO Wireless Karaoke Microphone	Model Name. :	IM2
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V from adapter AC 120V/60Hz
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	/
--	--	--	--	/

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance}/\text{test distance})(\text{dB})$;

Limit line = specific limits(dBuv) + distance extrapolation factor.

3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	MOMAX K-MIC PRO Wireless Karaoke Microphone	Model Name :	IM2
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V from adapter
Test Mode :	TX		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	119.4360	15.57	12.08	27.65	43.5	15.85	QP
V	128.1129	15.82	12.2	28.06	43.5	15.44	QP
V	170.7926	20.41	10.35	30.76	43.5	12.74	QP
V	341.9786	12.74	16.19	28.94	46	17.06	QP
V	468.8761	17.87	19.69	37.52	46	8.48	QP
V	935.5462	9.44	29.42	39.06	46	6.94	QP
H	170.7923	27.42	10.35	37.76	43.5	5.74	QP
H	341.9786	24.87	16.19	41.04	46	4.96	QP
H	468.8761	20.41	19.69	40.1	46	5.9	QP
H	726.8052	14.58	26	40.38	46	5.62	QP
H	813.1114	16.53	26.35	42.86	46	3.14	QP
H	854.0247	12.72	27.51	39.96	46	6.04	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level- Limit

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Factor added by measurement software automatically

3.2.8 TEST RESULTS (1G-25GHZ)

GFSK,
Normal Voltage

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (2402 MHz)							
Vertical	2491.777	60.32	-11.65	48.67	74	25.33	Pk
Horizontal	2498.247	57.22	-12.73	44.49	74	29.51	Pk
Vertical	4804.156	57.32	-3.6	53.72	74	20.28	Pk
Horizontal	4804.156	57.32	-9.23	48.09	74	25.91	Pk
Vertical	1485.838	61.02	-17.1	43.92	74	30.08	Pk
Vertical	1636.784	60.71	-16.06	44.65	74	29.35	Pk
Vertical	2095.928	59.52	-11.88	47.64	74	26.36	Pk
Horizontal	1074.301	61.25	-19.69	41.56	74	32.44	Pk
Horizontal	1483.178	60.24	-17.09	43.15	74	30.85	Pk
Horizontal	1895.832	57.26	-14.25	43.01	74	30.99	Pk
Mid Channel (2441 MHz)							
Vertical	2474.777	57.01	-11.65	45.36	74	28.64	Pk
Horizontal	2474.144	57.7	-9.37	48.33	74	25.67	Pk
Vertical	4882.539	57.08	-6.15	50.93	74	23.07	Pk
Horizontal	4882.539	57.08	-6.83	50.25	74	23.75	Pk
Vertical	1433.535	64.07	-17.12	46.95	74	27.05	Pk
Vertical	1636.784	61.4	-16.06	45.34	74	28.66	Pk
Vertical	2284.166	55.14	-12.83	42.31	74	31.69	Pk
Horizontal	1280.515	60.8	-17.82	42.98	74	31.02	Pk
Horizontal	1636.784	59.63	-16.06	43.57	74	30.43	Pk
Horizontal	1892.438	59.75	-14.28	45.47	74	28.53	Pk
High Channel (2480 MHz)							
Vertical	2453.883	57.7	-12.91	44.79	74	29.21	Pk
Horizontal	2453.839	57.7	-11.59	46.11	74	27.89	Pk
Vertical	4960.256	54.21	-9.22	44.99	74	29.01	Pk
Horizontal	4960.478	54.21	-3.64	50.57	74	23.43	Pk
Vertical	1187.688	58.73	-18.27	40.46	74	33.54	Pk
Vertical	1636.784	57.54	-16.06	41.48	74	32.52	Pk
Vertical	2084.693	55.13	-11.99	43.14	74	30.86	Pk
Horizontal	1534.540	57.79	-16.94	40.85	74	33.15	Pk
Horizontal	1786.985	57.5	-15.04	42.46	74	31.54	Pk
Horizontal	1892.438	57.38	-14.28	43.1	74	30.9	Pk

Note: The PK value is less than the AV value, AV value is not required
 Factor added by measurement software automatically.
 GFSK PI/4QPSK 8DPSK all tested, GFSK is worse case and only reported

BAND EDGE(Radiated)

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type	Comment
GFSK							
2390	56.02	-13.06	42.96	74	31.04	peak	Vertical
2390	56.89	-13.06	43.83	74	30.17	peak	Horizontal
2483.5	57.21	-12.78	44.43	74	29.57	peak	Vertical
2483.5	54.43	-12.78	41.65	74	32.35	peak	Horizontal
$\pi/4$-DQPSK							
2390	56.63	-13.06	43.57	74	30.43	peak	Vertical
2390	57.08	-13.06	44.02	74	29.98	peak	Horizontal
2483.5	57.72	-12.78	44.94	74	29.06	peak	Vertical
2483.5	57.98	-12.78	45.2	74	28.8	peak	Horizontal
8-DPSK							
2390	57.57	-13.06	44.51	74	29.49	peak	Vertical
2390	57.88	-13.06	44.82	74	29.18	peak	Horizontal
2483.5	57.6	-12.78	44.82	74	29.18	peak	Vertical
2483.5	56.03	-12.78	43.25	74	30.75	peak	Horizontal

NOTE: The PK value is less than the AV value, AV value is not required.

BAND EDGE(Radiated)(Hopping Mode)

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type	Comment
GFSK							
2390	57.89	-13.06	44.83	74	29.17	peak	Vertical
2390	58.35	-13.06	45.29	74	28.71	peak	Horizontal
2483.5	57.57	-12.78	44.79	74	29.21	peak	Vertical
2483.5	55.93	-12.78	43.15	74	30.85	peak	Horizontal
$\pi/4$-DQPSK							
2390	58.03	-13.06	44.97	74	29.03	peak	Vertical
2390	58.49	-13.06	45.43	74	28.57	peak	Horizontal
2483.5	57.71	-12.78	44.93	74	29.07	peak	Vertical
2483.5	56.07	-12.78	43.29	74	30.71	peak	Horizontal
8-DPSK							
2390	58.46	-13.06	45.4	74	28.6	peak	Vertical
2390	58.92	-13.06	45.86	74	28.14	peak	Horizontal
2483.5	58.14	-12.78	45.36	74	28.64	peak	Vertical
2483.5	56.5	-12.78	43.72	74	30.28	peak	Horizontal

NOTE: The PK value is less than the AV value, AV value is not required.

4. 20 DB OCCUPY BANDWIDTH

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247a(1)	20dB bandwidth	/	2400-2483.5	PASS


4.1.1 TEST PROCEDURE

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
Bandwidth: RBW=30 kHz, VBW=100 kHz, detector= Peak

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP




4.1.4 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

EUT :	MOMAX K-MIC PRO Wireless Karaoke Microphone	Model Name :	IM2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V from adapter
Test Mode :	GFSK Mode /CH01, CH40, CH79		

Frequency	20dB Bandwidth (MHz)	Limit	Result
2402 MHz	0.875	/	PASS
2441 MHz	0.851	/	PASS
2480 MHz	0.872	/	PASS





5. CARRIER FREQUENCY SEPARATION TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)	Channel Separation	>25KHz or >two-thirds of the 20 dB bandwidth (Which is greater)	2400-2483.5	PASS


5.1.1 TEST PROCEDURE

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
RBW=100 kHz, VBW=300 kHz, detector= Peak, Sweep Time =auto.
- (3) The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Test.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP




5.1.4 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

EUT :	MOMAX K-MIC PRO Wireless Karaoke Microphone	Model Name :	IM2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from adapter
Test Mode :	GFSK Mode		

Mode	Channel	Frequency (MHz)	Test Result (MHz)	Limit (MHz)	Result
GFSK	Middle	2441	1000	0.55	Pass
$\pi/4$ -DQPSK	Middle	2441	1000	0.85	Pass
8DPSK	Middle	2441	1000	0.84	Pass





6. NUMBER OF HOPPING CHANNEL

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)	Number of Hopping Channel	>15 channels	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=100 kHz, VBW=300 kHz, Detector=Peak, Sweep time= Auto.
- (3) The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Test.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

EUT :	MOMAX K-MIC PRO Wireless Karaoke Microphone	Model Name :	IM2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5Vfrom adapter
Test Mode :	GFSK Mode		

///

Mode	Quantity of Hopping Channel	Limit	Judgment
GFSK, π/4-DQPSK, 8DPSK	79	>15	PASSED



7. DWELL TIME

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)	Dwell time	0.4 sec	2400-2483.5	PASS

7.1.1 TEST PROCEDURE

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.
- (9) The EUT was set to the Hopping Mode for Dwell Time Test

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


7.1.5 TEST RESULTS


EUT :	MOMAX K-MIC PRO Wireless Karaoke Microphone	Model Name :	IM2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from adapter
Test Mode :	GFSK Mode		

For GFSK:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Mode	Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Conclusion
GFSK	DH1	2441	0.497	159.04	<0.4	PASS
	DH3	2441	1.767	282.72	<0.4	PASS
	DH5	2441	3.01	321.07	<0.4	PASS
Note: 1 A period time = $0.4 \text{ (s)} \times 79 = 31.6 \text{ (s)}$ 2 DH1 time slot = $\text{Pulse Duration} \times (1600 / (2 \times 79)) \times \text{A period time}$ DH3 time slot = $\text{Pulse Duration} \times (1600 / (4 \times 79)) \times \text{A period time}$ DH5 time slot = $\text{Pulse Duration} \times (1600 / (6 \times 79)) \times \text{A period time}$						





8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400-2483.5	PASS

8.1.1 TEST PROCEDURE

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
 RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤1 MHz)
 RBW=3MHz, VBW=10MHz, Detector=Peak (If 20dB BW > 1 MHz)
- (3) The EUT was set to continuously transmitting in the max power during the test.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.1.5 TEST RESULTS

EUT :	MOMAX K-MIC PRO Wireless Karaoke Microphone	Model Name :	IM2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from adapter
Test Mode :	GFSK Mode /CH01, CH40, CH79		

TX GFSK Mode			
Test Channe	Frequency	Maximum Conducted Output Power(PK)	LIMIT
	(MHz)	(dBm)	dBm
CH01	2402	3.73	30
CH40	2441	4.45	30
CH79	2480	2.64	30

||||

9. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

9.1 DEVIATION FROM STANDARD

No deviation.

9.2 TEST SETUP



9.3 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.4 TEST RESULTS


EUT :	MOMAX K-MIC PRO Wireless Karaoke Microphone	Model Name :	IM2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from adapter

Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
GFSK mode			
Left-band	44.25	20	Pass
Right-band	66.26	20	Pass

GFSK: Band Edge, Left Side




GFSK: Band Edge, Right Side




Hopping Mode

Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
GFSK mode			
Left-band	55.35	20	Pass
Right-band	65.66	20	Pass

GFSK: Band Edge, Left Side



GFSK: Band Edge, Right Side



10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

The EUT antenna is Integrated antenna,2.5dBi. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

End of Report