Momax Technology (Shenzhen) Limited

2022/03/21

To: Federal Communications Commission 7435 Oakland Mills Road Columbia, MD

FCC ID: 2ANBQ-IP108

To Whom It May Concern:

This letter is to ascertain that, Product: **WIRELESS CHARGING BATTERY PACK M/N: IP108, IP109** has been the units used for conducting FCC compliance testing, and it meets 680106 D01 RF Exposure Wireless Charging App v03 Clause 5(b) all 6 conditions.

| 1 | Power transfer frequency is less that 1 MHz |
|--------|--|
| Reply: | Yes, Power transfer frequency is less that 1 MHz ; Ans : EUT operating |
| | frequency range is 0.11~0.205MHz. |
| 2 | Output power from each primary coil is less than or equal to 15 watts. |
| Reply: | Yes, Output power from each primary coil is equal to 15 watts. The max |
| | output power is 15W. |
| 3 | The transfer system includes only single primary and secondary coils. This |
| | includes charging systems that may have multiple primary coils and clients |
| | that are able to detect and allow coupling only between individual pairs of |
| | coils. |
| Reply: | Yes, The EUT has only one primary coil. |
| 4 | Client device is placed directly in contact with the transmitter. |
| Reply: | Yes, The client device needs to be in contact with the transmitter base, and |
| | the contact distance is less than 10mm. |
| 5 | Mobile exposure conditions only (portable exposure conditions are not |
| | covered by this exclusion). |
| Reply: | No, EUT is portable device |
| 6 | The aggregate H-field strengths at 15 cm surrounding the device and 20 cm |
| | above the top surface from all simultaneous transmitting coils are |
| | demonstrated to be less than 50% of the MPE limit. |
| Reply: | No. The measurement is based on KDB inquiry which 0mm distance is set for |
| | all positions testing. |
| | |

If you have any question or concerns, pls. contact us.

Sincerely,

kin Kon

Kin kung R&D Momax Technology (Shenzhen) Limited No.709, Floor 7, Vanke Fuchun Eastern Mansion Shennan Road 7006, Futian District, Shenzhen