



Certificate No.: 3745.01



China

# FCC - TEST REPORT

Report Number : **709502303507-00B** Date of Issue: June 29, 2023

Model : CRG1

Product Type : Wi-Fi and Bluetooth Module

Applicant : Hangzhou Tuya Information Technology Co.,Ltd

Address : Room701,Building3,More Center,No.87 GuDun  
Road,Hangzhou,Zhejiang China

Manufacturer : Hangzhou Tuya Information Technology Co.,Ltd

Address : Room701,Building3,More Center,No.87 GuDun  
Road,Hangzhou,Zhejiang China

Test Result :  **Positive**       **Negative**

Total pages including Appendices : 56

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.*

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.*



# 1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory .....	3
3	Description of the Equipment under Test.....	4
4	Summary of Test Standards .....	6
5	Summary of Test Results.....	7
6	General Remarks.....	8
7	Test Setups .....	9
8	Systems test configuration .....	12
9	Technical Requirement.....	13
9.1	Conducted Emission .....	13
9.2	Conducted peak output power.....	18
9.3	6dB bandwidth .....	19
9.4	Power spectral density .....	23
9.5	Spurious RF conducted emissions.....	27
9.6	Band edge.....	37
9.7	Spurious radiated emissions for transmitter .....	44
10	Test Equipment List.....	53
11	System Measurement Uncertainty .....	54
12	Photographs of Test Set-ups .....	55
13	Photographs of EUT .....	56



## 2 Details about the Test Laboratory

### Details about the Test Laboratory

#### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch  
No.16 Lane, 1951 Du Hui Road,  
Shanghai 201108,  
P.R. China

Test Firm FCC  
Registration  
Number: 820234

Designation  
number: CN1183

IC Company  
Number: 25988

CAB identifier: CN0101

Telephone: +86 21 6141 0123  
Fax: +86 21 6140 8600



### 3 Description of the Equipment under Test

Product: Wi-Fi and Bluetooth Module

Model no.: CRG1

FCC ID: 2ANDL-CRG1

Options and accessories: NA

Rating: 3V-3.6V DC

RF Transmission Frequency: For 802.11b/g/n-HT20: 2412~2462 MHz  
For 802.15.1:2402~2480 MHz

No. of Operated Channel: 2.4GHz WIFI: 11 for 802.11b/802.11g/802.11n(H20)  
2.4GHz BLE: 40

Modulation: For 2.4GHz WIFI:  
Direct Sequence Spread Spectrum (DSSS) for 802.11b  
Orthogonal Frequency Division Multiplexing (OFDM) for 802.11g/n  
For 2.4GHz BLE: GFSK

Channel list:

802.11b/g/n(HT20)			
Ch	Fre(MHz)	Ch	Fre(MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

Bluetooth Low Energy							
Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Antenna Type: onboard PCB antenna

Antenna Gain: 1.27dBi

Description of the EUT: The Equipment Under Test (EUT) is a Wi-Fi and Bluetooth module which support 2.4GHz Wi-Fi and BLE 4.2(only support 1Mbps data rate). We tested it and listed the worst data in this report.

Test sample no.: SHA-731498-1

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.



## 4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 and ANSI C63.10 (2013).

## 5 Summary of Test Results

Technical Requirements						
Test Condition	Pages	Test Site	Test Result			
			Pass	Fail	N/A	
§15.207	Conducted emission AC power port	13-17	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247 (b) (3) & RSS-247 5.4(d)	Conducted peak output power and e.i.r.p.	18	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(a)(1) & RSS-247 5.1(b)	20dB bandwidth	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1) & RSS-247 5.1(b)	Carrier frequency separation	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)(iii) & RSS-247 5.1(d)	Number of hopping frequencies	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)(iii) & RSS-247 5.1(d)	Dwell Time	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(2) & RSS-247 5.2(a) & RSS-GEN 6.7	6dB bandwidth and 99% Occupied Bandwidth	19-22	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(e) & RSS-247 5.2(b)	Power spectral density	23-26	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d) & RSS-247 5.5	Spurious RF conducted emissions	27-36	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d) & RSS-247 5.5	Band edge	37-43	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d) & §15.209 & RSS-247 5.5 & RSS-Gen 6.13	Spurious radiated emissions for transmitter	44-52	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.203 & RSS-Gen 6.8	Antenna requirement	See note 1		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses an onboard PCB antenna, which gain is 1.27dBi. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.



**6 General Remarks**

**Remarks**

This submittal(s) (test report) is intended for FCC ID: 2ANDL-CRG1, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

This report is only for the 2.4GHz Wi-Fi test report, for the 2.4GHz BLE test report please refer to 709502303507-00A.

According to the client’s declaration, the “ILAC – A2LA Accredited” symbol is added to the report.

**SUMMARY:**

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: May 26, 2023

Testing Start Date: May 31, 2023

Testing End Date: June 9, 2023

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Hui TONG  
Review Engineer

Prepared by:

Wenqiang LU  
Project Engineer


Tested by:

Yiquan WANG  
Test Engineer




## 7 Test Setups

### 7.1 AC Power Line Conducted Emission test setups




### 7.2 Radiated test setups


#### 9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:



### 18GHz ~ 25GHz Test Setup:



### 7.3 Conducted RF test setups



## 8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenove	E470	PF-OU5TS7 17/09

Test software: UI\_mptool\_1V16 for Wi-Fi  
Bluetooth RF Test Tool (RTLBTAPP Version:5.2.2.34) for BLE

Test software information:

Test Software Version	Broadcom BlueTool	
Modulation	Setting TX Index	Data rate
802.11b	75	1 Mbps
802.11g	65	6 Mbps
802.11n(HT20)	65	13 Mbps

The system was configured to channel 1(2412MHz), 6(2437MHz), and 11(2462MHz) for 802.11 b/g/n HT20 for the test.

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

## 9 Technical Requirement

### 9.1 Conducted Emission

#### Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

#### Limit

According to §15.207 & RSS-GEN 8.8, conducted emissions limit as below:

Frequency MHz	QP Limit dB $\mu$ V	AV Limit dB $\mu$ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

**Conducted Emission**

# 150k-30MHz Conducted Emission Test


## EUT Information

EUT Name: Wi-Fi and Bluetooth Module  
 Model: CRG1  
 Client: Hangzhou Tuya Information Technology Co.,Ltd  
 Op Cond: Power on, TX\_2462MHz for b mode, AC 120V/60Hz, T20.5, H52.3%, P101.1Pa  
 Operator: Wang Yiquan  
 Standard: FCC Part 15B Class B  
 Comment: Phase L  
 Sample No.: SHA-731498-1

## Scan Setup: Voltage with 2-Line-LISN pre [EMI conducted]

Hardware Setup: Voltage with 2-Line-LISN  
 Receiver: [ESR 3]  
 Level Unit: dBuV

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
9 kHz - 150 kHz	100 Hz	PK+	200 Hz	0.02 s	0 dB
150 kHz - 30 MHz	4.5 kHz	PK+; AVG	9 kHz	0.01 s	0 dB





## Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.181500	---	36.19	54.42	18.23	1000.0	9.000	L1	19.6
0.186000	53.02	---	64.21	11.19	1000.0	9.000	L1	19.6
0.492000	---	21.84	46.13	24.29	1000.0	9.000	L1	19.6
0.492000	36.36	---	56.13	19.77	1000.0	9.000	L1	19.6
2.058000	32.05	---	56.00	23.95	1000.0	9.000	L1	19.6
2.085000	---	19.74	46.00	26.26	1000.0	9.000	L1	19.6
3.570000	38.92	---	56.00	17.08	1000.0	9.000	L1	19.6
3.682500	---	28.70	46.00	17.30	1000.0	9.000	L1	19.6
5.149500	33.62	---	60.00	26.38	1000.0	9.000	L1	19.6
12.196500	---	25.58	50.00	24.42	1000.0	9.000	L1	19.8
15.895500	---	32.14	50.00	17.86	1000.0	9.000	L1	19.9
15.994500	39.42	---	60.00	20.58	1000.0	9.000	L1	19.9

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

# 150k-30MHz Conducted Emission Test


## EUT Information

EUT Name: Wi-Fi and Bluetooth Module  
 Model: CRG1  
 Client: Hangzhou Tuya Information Technology Co.,Ltd  
 Op Cond: Power on, TX\_2462MHz for b mode, AC 120V/60Hz, T20.5, H52.3%, P101.1Pa  
 Operator: Wang Yiquan  
 Standard: FCC Part 15B Class B  
 Comment: Phase N  
 Sample No.: SHA-731498-1

## Scan Setup: Voltage with 2-Line-LISN pre [EMI conducted]

Hardware Setup: Voltage with 2-Line-LISN  
 Receiver: [ESR 3]  
 Level Unit: dBuV

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
9 kHz - 150 kHz	100 Hz	PK+	200 Hz	0.02 s	0 dB
150 kHz - 30 MHz	4.5 kHz	PK+; AVG	9 kHz	0.01 s	0 dB







## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.181500	---	33.17	54.42	21.25	1000.0	9.000	N	19.6
0.181500	51.36	---	64.42	13.06	1000.0	9.000	N	19.6
0.514500	---	21.04	46.00	24.96	1000.0	9.000	N	19.6
0.519000	35.81	---	56.00	20.19	1000.0	9.000	N	19.6
2.112000	---	24.39	46.00	21.61	1000.0	9.000	N	19.6
2.121000	35.56	---	56.00	20.44	1000.0	9.000	N	19.6
2.728500	37.88	---	56.00	18.12	1000.0	9.000	N	19.6
3.070500	---	29.80	46.00	16.20	1000.0	9.000	N	19.6
5.820000	---	24.30	50.00	25.70	1000.0	9.000	N	19.7
6.013500	32.05	---	60.00	27.95	1000.0	9.000	N	19.7
16.030500	---	35.04	50.00	14.96	1000.0	9.000	N	19.9
16.048500	40.99	---	60.00	19.01	1000.0	9.000	N	19.9

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

## 9.2 Conducted peak output power

### Test Method: ANSI C63.10-2013 Clause 11.9.1.2 for Wi-Fi

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

### Limits

According to §15.247 (b) (3), conducted peak output power limit as below:

	Frequency Range	Limit
	MHz	W
<b>Conducted peak output power</b>	2400-2483.5	≤1

Test result as below table

802.11b: Antenna gain=1.27dBi			
Frequency (MHz)	Conducted Peak Output Power (dBm) §15.247 (b) (1)		
	Result	limit	Verdict
2412MHz	17.67	≤30	Pass
2437MHz	17.68	≤30	Pass
2462MHz	17.75	≤30	Pass

802.11g: Antenna gain=1.27dBi			
Frequency (MHz)	Conducted Peak Output Power (dBm) §15.247 (b) (1)		
	Result	limit	Verdict
2412MHz	17.69	≤30	Pass
2437MHz	17.55	≤30	Pass
2462MHz	17.26	≤30	Pass

802.11n(HT20): Antenna gain=1.27dBi			
Frequency (MHz)	Conducted Peak Output Power (dBm) §15.247 (b) (1)		
	Result	limit	Verdict
2412MHz	17.32	≤30	Pass
2437MHz	17.22	≤30	Pass
2462MHz	17.02	≤30	Pass

### 9.3 6dB bandwidth

#### Test Method

1. Use the following spectrum analyzer settings:  
RBW=100K, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq$  6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

#### Limit

Limit [kHz]


$\geq$ 500

#### Test result

Test Mode	Frequency MHz	6dB bandwidth (MHz)		Result
		result	limit	verdict
802.11b	2412	9.09	$\geq$ 0.5	Pass
	2437	9.079	$\geq$ 0.5	Pass
	2462	9.082	$\geq$ 0.5	Pass
802.11g	2412	16.546	$\geq$ 0.5	Pass
	2437	16.53	$\geq$ 0.5	Pass
	2462	16.543	$\geq$ 0.5	Pass
802.11n(HT20)	2412	17.795	$\geq$ 0.5	Pass
	2437	17.795	$\geq$ 0.5	Pass
	2462	17.778	$\geq$ 0.5	Pass



6 dB Bandwidth









## 9.4 Power spectral density

### Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency.  
RBW=3kHz, VBW≥3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed.

### Limit

Limit [dBm]

≤8

Test result  
802.11 b

Frequency MHz	Power spectral density dBm/3kHz	Result
Low channel 2412MHz	-12.93	Pass
Middle channel 2437MHz	-12.54	Pass
High channel 2462MHz	-12.02	Pass


802.11 g

Frequency MHz	Power spectral density dBm	Result
Low channel 2412MHz	-11.43	Pass
Middle channel 2437MHz	-11.54	Pass
High channel 2462MHz	-11.46	Pass


802.11 n (HT20)


Frequency MHz	Power spectral density dBm	Result
Low channel 2412MHz	-12.34	Pass
Middle channel 2437MHz	-12.31	Pass
High channel 2462MHz	-12.46	Pass

**Power spectral density**











## 9.5 Spurious RF conducted emissions

### Test Method

1. Establish a reference level by using the following procedure:
  - a. Set RBW=100 kHz. VBW $\geq$ 3RBW. Detector =peak, Sweep time = auto couple, Trace mode = max hold.
  - b. Allow trace to fully stabilize, use the peak marker function to determine the maximum PSD level.
2. Use the maximum PSD level to establish the reference level.
  - a. Set the center frequency and span to encompass frequency range to be measured.
  - b. Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements, report the three highest emissions relative to the limit.
3. Repeat above procedures until other frequencies measured were completed.

### Limit


Frequency Range MHz	Limit (dBc)
30-25000	-20

**Spurious RF conducted emissions**

802.11 B


Out-of-Band Emissions

Channel 1 (2412MHz)




## Out-of-Band Emissions Channel 6 (2437MHz)


### Reference point




### Spurious Emission (30MHz – 1GHz)



### Spurious Emission (1GHz – 5GHz)




### Spurious Emission (5GHz – 26.5GHz)




## Out-of-Band Emissions Channel 11 (2462MHz)


### Reference point




### Spurious Emission (30MHz – 1GHz)



### Spurious Emission (1GHz – 5GHz)




### Spurious Emission (5GHz – 26.5GHz)




802.11 G

Out-of-Band Emissions  
Channel 1 (2412MHz)


Reference point




Spurious Emission (30MHz – 1GHz)



Spurious Emission (1GHz –5GHz)




Spurious Emission (5GHz –26.5GHz)




## Out-of-Band Emissions Channel 6 (2437MHz)


### Reference point




### Spurious Emission (30MHz – 1GHz)



### Spurious Emission (1GHz –5GHz)




### Spurious Emission (5GHz –26.5GHz)






## Out-of-Band Emissions Channel 11 (2462MHz)


### Reference point




### Spurious Emission (30MHz – 1GHz)



### Spurious Emission (1GHz –5GHz)



### Spurious Emission (5GHz –26.5GHz)




802.11 N HT20


Out-of-Band Emissions

Channel 1 (2412MHz)


Reference point




Spurious Emission (30MHz – 1GHz)



Spurious Emission (1GHz –5GHz)




Spurious Emission (5GHz –26.5GHz)




## Out-of-Band Emissions Channel 6 (2437MHz)


### Reference point




### Spurious Emission (30MHz – 1GHz)



### Spurious Emission (1GHz –5GHz)




### Spurious Emission (5GHz –26.5GHz)




## Out-of-Band Emissions Channel 11 (2462MHz)


### Reference point




### Spurious Emission (30MHz – 1GHz)



### Spurious Emission (1GHz – 5GHz)



### Spurious Emission (5GHz – 26.5GHz)



## 9.6 Band edge

### Test Method


- 1 Use the following spectrum analyzer settings:  
Span = wide enough to capture the peak level of the in-band emission and all spurious  
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section.

### Limit

According to §15.247(d) and RSS-247 5.5, in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a) and RSS-Gen 8.10, must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)) and RSS-Gen.




Test result







China







China









China







China





China



## 9.7 Spurious radiated emissions for transmitter

### Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:

#### For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious  
 RBW = 100 kHz to 120 kHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

#### For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious  
 RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

#### Procedures for average unwanted emissions measurements above 1000 MHz

- a) RBW = 1MHz.
- b) VBW ≥ [3 × RBW].
- c) Detector = RMS (power averaging), if  $[\text{span} / (\# \text{ of points in sweep})] \leq \text{RBW} / 2$ . Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
- e) Sweep time = auto.
- f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of  $1 / D$ , where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
- g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:



- 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is  $[10 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.
- 2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is  $[20 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.
- 3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

**Limit**

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205 and RSS-GEN 8.10 must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Measured Distance Meters
0.009~0.490	2400/F (kHz)	300
0.490~1.705	24000/F (kHz)	30
1.705~30	30	30

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

### Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit. The only worse case test result is listed in the report.

Transmitting spurious emission test result as below:

Test mode: 802.11B					
Channel 1 (2412MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2385.88	46.75	74.00	27.25	Peak	Horizontal
4823.86	47.93	74.00	26.07	Peak	Horizontal
2384.19	45.99	74.00	28.01	Peak	Vertical
4823.86	46.96	74.00	27.04	Peak	Vertical

Test mode: 802.11B					
Channel 6 (2437MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4873.73	47.34	74.00	26.66	Peak	Horizontal
4873.73	46.55	74.00	27.45	Peak	Vertical

Test mode: 802.11B					
Channel 11 (2462MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2483.52	47.65	74.00	26.35	Peak	Horizontal
4924.16	46.78	74.00	27.22	Peak	Horizontal
2483.68	45.75	74.00	28.25	Peak	Vertical
4923.60	44.45	74.00	29.55	Peak	Vertical



Test mode: 802.11G					
Channel 1 (2412MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2388.80	54.44	74.00	19.56	Peak	Horizontal
2388.80	43.20	54.00	10.80	AV	Horizontal
4819.90	44.69	74.00	29.31	Peak	Horizontal
2389.76	52.38	74.00	21.62	Peak	Vertical
4818.20	43.08	74.00	30.92	Peak	Vertical

Test mode: 802.11G					
Channel 6 (2437MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4867.50	43.45	74.00	30.55	Peak	Horizontal
4874.30	43.29	74.00	30.71	Peak	Vertical

Test mode: 802.11G					
Channel 11 (2462MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2483.60	63.02	74.00	10.98	Peak	Horizontal
2483.60	49.10	54.00	4.90	AV	Horizontal
4923.60	43.82	74.00	30.18	Peak	Horizontal
2483.60	59.23	74.00	14.77	Peak	Vertical
2484.40	46.80	54.00	7.20	AV	Vertical
4831.23	42.86	74.00	31.14	Peak	Vertical



Test mode: 802.11N(HT20)					
Channel 1 (2412MHz)					
Frequency	Measure	Limit	Margin	Detector	Polarization
(MHz)	Level (dBuV/M)	(dBuV/M)	(dB)		
2384.90	50.79	74.00	23.21	Peak	Horizontal
4825.57	43.67	74.00	30.33	Peak	Horizontal
2386.12	47.45	74.00	26.55	Peak	Vertical
4831.23	43.22	74.00	30.78	Peak	Vertical

Test mode: 802.11N(HT20)					
Channel 6 (2437MHz)					
Frequency	Measure	Limit	Margin	Detector	Polarization
(MHz)	Level (dBuV/M)	(dBuV/M)	(dB)		
4877.7	44.41	74.00	29.59	Peak	Horizontal
4857.87	42.39	74.00	31.61	Peak	Vertical

Test mode: 802.11N(HT20)					
Channel 11 (2462MHz)					
Frequency	Measure	Limit	Margin	Detector	Polarization
(MHz)	Level (dBuV/M)	(dBuV/M)	(dB)		
2483.60	62.13	74.00	11.87	Peak	Horizontal
2483.60	45.90	54.00	8.10	AV	Horizontal
4910.00	43.02	74.00	30.98	Peak	Horizontal
2483.60	59.02	74.00	14.98	Peak	Vertical
2483.55	43.6	54.00	10.40	AV	Vertical
4896.97	42.87	74.00	31.13	Peak	Vertical

Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading



The worst case of Radiated Emission below 1GHz:

# 30-1000MHz Radiated Emission

## EUT Information


EUT Name: Wi-Fi and Bluetooth Module  
 Model: CRG1  
 Client: Hangzhou Tuya Information Technology Co., Ltd  
 Op Cond: Power on, TX\_802.11b\_2462MHz, DC 3.3V, T20.5, H52.3%, P101.1Pa  
 Operator: Wang Yiquan  
 Test Spec: FCC Part 15B Class B  
 Comment: Horizontal  
 Sample No: SHA-731498-1

## Sweep Setup: RE\_VULB9168\_pre\_Cont\_30-1000 [EMI radiated]

Hardware Setup: RE\_VULB9168  
 Receiver: [ESR 3]  
 Level Unit: dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
30 MHz - 1 GHz	48.5 kHz	PK+	120 kHz	0.005 s	20 dB

RE\_VULB9168\_pre\_Cont\_30-1000





## Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
37.760000	19.0	1000.0	120.000	194.0	H	135.0	19.7	21.0	40.0
119.960000	24.5	1000.0	120.000	313.4	H	94.0	18.1	19.0	43.5
168.000000	30.2	1000.0	120.000	155.1	H	178.0	20.4	13.3	43.5
216.000000	31.9	1000.0	120.000	365.7	H	221.0	17.5	14.1	46.0
263.960000	30.2	1000.0	120.000	148.5	H	258.0	20.1	15.8	46.0
382.440000	34.0	1000.0	120.000	124.3	H	289.0	23.8	12.0	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.



# 30-1000MHz Radiated Emission

## EUT Information


EUT Name: Wi-Fi and Bluetooth Module  
 Model: CRG1  
 Client: Hangzhou Tuya Information Technology Co., Ltd  
 Op Cond: Power on, TX\_802.11b\_2462MHz, DC 3.3V, T20.5, H52.3%, P101.1Pa  
 Operator: Wang Yiquan  
 Test Spec: FCC Part 15B Class B  
 Comment: Vertical  
 Sample No: SHA-731498-1

## Sweep Setup: RE\_VULB9168\_pre\_Cont\_30-1000 [EMI radiated]

Hardware Setup: RE\_VULB9168  
 Receiver: [ESR 3]  
 Level Unit: dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
30 MHz - 1 GHz	48.5 kHz	PK+	120 kHz	0.005 s	20 dB

RE\_VULB9168\_pre\_Cont\_30-1000



## Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
58.680000	19.5	1000.0	120.000	150.5	V	195.0	20.3	20.5	40.0
119.960000	23.3	1000.0	120.000	192.3	V	239.0	18.1	20.2	43.5
168.040000	27.6	1000.0	120.000	211.4	V	280.0	20.4	15.9	43.5
215.960000	24.1	1000.0	120.000	312.3	V	99.0	17.5	19.4	43.5
382.560000	33.9	1000.0	120.000	111.9	V	340.0	23.8	12.1	46.0
737.680000	31.7	1000.0	120.000	207.3	V	152.0	31.7	14.3	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.



## 10 Test Equipment List

List of Test Instruments  
Test Site1

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
C	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2022-8-1	2023-7-31
	Wideband power sensor	Rohde & Schwarz	NRP-Z81	104782	2022-3-18	2023-3-17
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2022-8-1	2023-7-31
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2022-8-1	2023-7-31
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2019-9-23	2024-9-22
	Horn Antenna	Rohde & Schwarz	HF907	102393	2021-3-15	2024-3-14
	Pre-amplifier	Rohde & Schwarz	SCU-18D	19006451	2022-8-1	2023-7-31
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2022-6-13	2023-6-12
	DOUBLE-RIDGED WAVEGUIDE HORN WITH PRE-AMPLIFIER (18 GHZ - 40 GHZ)	ETS-Lindgren	3116C-PA	002222727	2020-9-23	2023-9-22
	3m Semi-anechoic chamber	TDK	9X6X6	----	2021-5-8	2024-5-7
CE	EMI Test Receiver	Rohde & Schwarz	ESR3	101907	2022-8-1	2023-7-31
	LISN	Rohde & Schwarz	ENV216	101924	2022-8-1	2023-7-31

Measurement Software Information			
Test Item	Software	Manufacturer	Version
C	MTS 8310	MWRFTest	2.0.0.0
RE	EMC 32	Rohde & Schwarz	V10.50.40
CE	EMC 32	Rohde & Schwarz	V9.15.03

**C - Conducted RF tests**

- Conducted peak output power
- 6dB bandwidth and 99% Occupied Bandwidth
- Power spectral density\*
- Spurious RF conducted emissions
- Band edge



## 11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, 3.16dB
Radiated Disturbance	9kHz to 30MHz, 3.52dB 30MHz to 1GHz, 5.03dB (Horizontal) 5.12dB (Vertical) 1GHz to 18GHz, 5.49dB 18GHz to 40GHz, 5.63dB
RF Conducted Measurement	Power related: 1.16dB Frequency related: $6.00 \times 10^{-8}$

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2021, clause 4.4.3 and 4.5.1.



## 12 Photographs of Test Set-ups

Refer to the < Test Setup photos >.



## 13 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

-----End of Test Report-----