



## FCC/IC - TEST REPORT

Report Number : **708882003234-00** Date of Issue: April 7, 2020

Model : WB8P

Product Type : Wi-Fi and Bluetooth Module

Applicant : Hangzhou Tuya Information Technology Co.,Ltd

Address : Room701,Building3,More Center,No.87 GuDun Road, Hangzhou, Zhejiang China

Production Facility : Hangzhou xicheng electronic technology co. LTD

Address : Building 5 and 6, 123 chutian road, xixing street, binjiang district, hangzhou city, zhejiang province, China

Test Result :  **Positive**       **Negative**

Total pages including Appendices : 60



*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Services according to the principles outlined in ISO 17025.*

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.*



# 1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory .....	3
3	Description of the Equipment under Test .....	4
4	Summary of Test Standards.....	5
5	Summary of Test Results .....	6
6	General Remarks.....	7
7	Test Setups.....	8
8	Systems test configuration .....	11
9	Technical Requirement .....	12
9.1	Conducted Emission .....	12
9.2	Conducted peak output power .....	15
9.3	6dB bandwidth and 99% Occupied Bandwidth .....	16
9.4	Power spectral density .....	26
9.5	Spurious RF conducted emissions .....	31
9.6	Band edge .....	44
9.7	Spurious radiated emissions for transmitter .....	49
10	Test Equipment List.....	57
11	System Measurement Uncertainty.....	58
12	Photographs of Test Set-ups .....	59
13	Photographs of EUT .....	60



## 2 Details about the Test Laboratory

### Details about the Test Laboratory

#### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch  
No.16 Lane, 1951 Du Hui Road,  
Shanghai 201108,  
P.R. China

FCC Registration No.: 820234

IC Registration No.: 25988

Telephone: +86 21 6141 0123  
Fax: +86 21 6140 8600



### 3 Description of the Equipment under Test

#### Description of the Equipment Under Test

Product:	Wi-Fi and Bluetooth Module
Model no.:	WB8P
FCC ID:	2ANDL-WB8P
IC:	23243-WB8P
Options and accessories:	NA
Rating:	DC 3.0-3.6V
RF Transmission Frequency:	For 802.11b/g/n-HT20: 2412~2462 MHz For 802.11n-HT40: 2422~2452 MHz For 802.15.1:2402~2480 MHz
No. of Operated Channel:	2.4GHz WIFI: 11 for 802.11b/802.11g/802.11(H20) 7 for 802.11n(H40) 2.4GHz BLE: 40
Modulation:	For 2.4GHz WIFI: Direct Sequence Spread Spectrum (DSSS) for 802.11b Orthogonal Frequency Division Multiplexing (OFDM) for 802.11g/n For 2.4GHz BLE: GFSK
Antenna Type:	PCB antenna
Antenna Gain:	2.0dBi
Description of the EUT:	The Equipment Under Test (EUT) is a low-power embedded Wi-Fi and Bluetooth module(4.0). We tested it and listed the worst data in this report.

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment, antenna gain or any information supplied.



## 4 Summary of Test Standards

<b>Test Standards</b>	
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5 Amendment 1 March 2019	General Requirements for Compliance of Radio Apparatus
RSS-247 Issue 2 February 2017	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE-LAN) Devices

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 and ANSI C63.10 (2013).



## 5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C						
Test Condition		Page s	Test Site	Test Result		
				Pass	Fail	N/A
§15.207 & RSS-GEN 8.8	Conducted emission AC power port	12-14	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247 (b) (1) & RSS-247 5.4(d)	Conducted peak output power	15	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(a)(1) & RSS-247 5.1(b)	20dB bandwidth	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1) & RSS-247 5.1(b)	Carrier frequency separation	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)(iii) & RSS-247 5.1(d)	Number of hopping frequencies	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)(iii) & RSS-247 5.1(d)	Dwell Time	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(2) & RSS-247 5.2(a) & RSS-GEN 6.7	6dB bandwidth and 99% Occupied Bandwidth	16-25	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(e) & RSS-247 5.2(b)	Power spectral density	26-30	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d) & RSS-247 5.5	Spurious RF conducted emissions	31-43	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d) & RSS-247 5.5	Band edge	44-48	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d) & §15.209 & RSS-247 5.5 & RSS-Gen 6.13	Spurious radiated emissions for transmitter	49-56	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.203 & RSS-Gen 6.8	Antenna requirement	See note 1		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses a patch antenna, which gain is 2.0dBi. In accordance to §15.203 and RSS-Gen 6.8, It is considered sufficiently to comply with the provisions of this section.



## 6 General Remarks

### Remarks

This submittal(s) (test report) is intended for FCC ID: 2ANDL-WB8P, IC: 23243-WB8P complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules and RSS-247, RSS-GEN.

This report is only for the 2.4GHz WiFi test report, for the 2.4GHz BLE test report please refer to 708882003236-00.

### SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed

- **Not** Performed

The Equipment under Test

- **Fulfills** the general approval requirements.

- **Does not** fulfill the general approval requirements.

Sample Received Date: March 22, 2020

Testing Start Date: March 23, 2020

Testing End Date: April 7, 2020

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:

Hui TONG  
Review Engineer




Jiayi XU  
Project Engineer

Wenqiang LU  
Test Engineer


## 7 Test Setups

### 7.1 AC Power Line Conducted Emission test setups




### 7.2 Radiated test setups

#### 9kHz ~ 30MHz Test Setup:







30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:



### 18GHz ~ 25GHz Test Setup:



### 7.3 Conducted RF test setups





## 8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
PC	Lenovo	X240	---

Test software: WIFI Test Toolv1.4.1

The system was configured to channel 1(2412MHz), 6(2437MHz), and 11(2462MHz) for 802.11 b/g/n HT20 test and channel 3(2422MHz), 6(2437MHz), 9(2452MHz) for 802.11n HT40.

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

## 9 Technical Requirement

### 9.1 Conducted Emission

#### Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

#### Limit


According to §15.207 & RSS-GEN 8.8, conducted emissions limit as below:

Frequency MHz	QP Limit dB $\mu$ V	AV Limit dB $\mu$ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

## Conducted Emission

Product Type : Wi-Fi and Bluetooth Module  
 M/N : WB8P  
 Operating Condition : Mode 1: Tx\_2422MHz for 802.11n HT40  
 Test Specification : L-line  
 Comment : AC 120V/60Hz (powered by notebook)



## Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.190500	---	33.11	54.01	20.90	1000.0	9.000	L1	19.4
0.190500	49.22	---	64.01	14.79	1000.0	9.000	L1	19.4
0.402000	33.54	---	57.81	24.27	1000.0	9.000	L1	19.4
0.546000	---	20.80	46.00	25.20	1000.0	9.000	L1	19.4
1.036500	27.16	---	56.00	28.84	1000.0	9.000	L1	19.5
2.013000	---	19.38	46.00	26.62	1000.0	9.000	L1	19.5
3.444000	36.21	---	56.00	19.79	1000.0	9.000	L1	19.5
3.444000	---	27.32	46.00	18.68	1000.0	9.000	L1	19.5
11.598000	34.69	---	60.00	25.31	1000.0	9.000	L1	19.7
12.345000	---	28.65	50.00	21.35	1000.0	9.000	L1	19.7
13.002000	---	29.46	50.00	20.54	1000.0	9.000	L1	19.7
13.533000	35.92	---	60.00	24.08	1000.0	9.000	L1	19.7

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator



Product Type : Wi-Fi and Bluetooth Module  
 M/N : WB8P  
 Operating Condition : Mode 1: Tx\_2422MHz for 802.11n HT40  
 Test Specification : N-line  
 Comment : AC 120V/60Hz (powered by notebook)



### Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.190500	---	31.56	54.01	22.45	1000.0	9.000	N	19.6
0.190500	47.43	---	64.01	16.58	1000.0	9.000	N	19.6
0.541500	33.57	---	56.00	22.43	1000.0	9.000	N	19.5
0.663000	---	21.65	46.00	24.35	1000.0	9.000	N	19.5
2.080500	34.23	---	56.00	21.77	1000.0	9.000	N	19.6
2.121000	---	24.46	46.00	21.54	1000.0	9.000	N	19.6
2.886000	---	28.29	46.00	17.71	1000.0	9.000	N	19.6
3.115500	36.45	---	56.00	19.55	1000.0	9.000	N	19.6
12.142500	29.35	---	60.00	30.65	1000.0	9.000	N	19.7
12.399000	---	24.02	50.00	25.98	1000.0	9.000	N	19.7
17.817000	35.84	---	60.00	24.16	1000.0	9.000	N	19.8
18.024000	---	29.53	50.00	20.47	1000.0	9.000	N	19.8

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)  
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

## 9.2 Conducted peak output power

### Test Method

1. Use the following spectrum analyzer settings:  
RBW > the 6 dB bandwidth of the emission being measured, VBW $\geq$ 3RBW, Span $\geq$ 3RBW  
Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Use a power meter to measure the conducted peak output power.

### Limits

According to §15.247 (b) (1) & RSS-247 5.4(d), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	$\leq 1$	$\leq 30$

Test result as below table

#### 802.11B

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2412MHz	17.82	Pass
Middle channel 2437MHz	18.16	Pass
High channel 2462MHz	18.34	Pass

#### 802.11G

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2412MHz	22.04	Pass
Middle channel 2437MHz	22.02	Pass
High channel 2462MHz	21.63	Pass

#### 802.11N HT20

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2412MHz	21.73	Pass
Middle channel 2437MHz	21.62	Pass
High channel 2462MHz	21.18	Pass

#### 802.11N HT40

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2422MHz	22.09	Pass
Middle channel 2437MHz	21.96	Pass
High channel 2452MHz	21.95	Pass



### 9.3 6dB bandwidth and 99% Occupied Bandwidth

#### Test Method

1. Use the following spectrum analyzer settings:  
RBW=100K, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

#### Test Method for 99 % Bandwidth

1. Use the following spectrum analyzer settings:  
RBW=1% to 5% of the actual occupied, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

#### Limit

Limit [kHz]

≥500

#### Test result

##### 802.11B

Frequency MHz	6dB bandwidth MHz	99% occupied bandwidth MHz	Result
Low channel 2412MHz	9.075	14.585	Pass
Middle channel 2437MHz	9.080	14.585	Pass
High channel 2462MHz	9.073	14.585	Pass

##### 802.11G

Frequency MHz	6dB bandwidth MHz	99% occupied bandwidth MHz	Result
Low channel 2412MHz	11.316	16.224	Pass
Middle channel 2437MHz	13.788	16.464	Pass
High channel 2462MHz	12.564	16.663	Pass





China

802.11N HT20

Frequency MHz	6dB bandwidth MHz	99% occupied bandwidth MHz	Result
Low channel 2412MHz	11.315	16.903	Pass
Middle channel 2437MHz	12.564	17.183	Pass
High channel 2462MHz	12.573	17.343	Pass

802.11N HT40


Frequency MHz	6dB bandwidth MHz	99% occupied bandwidth MHz	Result
Low channel 2422MHz	27.564	35.804	Pass
Middle channel 2437MHz	30.033	35.884	Pass
High channel 2452MHz	28.801	36.044	Pass

6 dB Bandwidth


802.11B

China


2412



2437




2462






### 802.11G

2412




Date: 7 APR 2020 15:01:29

2437



Date: 7 APR 2020 15:04:51

2462




Date: 7 APR 2020 15:08:35




802.11N HT20

2412




Date: 7 APR 2020 15:12:29

2437



Date: 7 APR 2020 15:15:48

2462




Date: 7 APR 2020 15:18:58




802.11N HT40

2422




Date: 7 APR 2020 15:22:29

2437



Date: 7 APR 2020 15:31:36

2452




Date: 7 APR 2020 15:33:53



99% Bandwidth


802.11B

2412




Date: 7 APR 2020 14:45:09

2437



Date: 7 APR 2020 14:54:39

2462



Date: 7 APR 2020 14:58:17




802.11G

2412




Date: 7 APR 2020 15:01:40

2437



Date: 7 APR 2020 15:01:40

2462




Date: 7 APR 2020 15:08:45



### 802.11N HT20

2412




Date: 7.APR.2020 15:12:40

2437



Date: 7.APR.2020 15:15:58

2462



Date: 7.APR.2020 15:19:09







## 9.4 Power spectral density

### Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency.  
RBW=3kHz,VBW≥3RBW,Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed.

### Limit

Limit [dBm]

≤8

Test result  
802.11 B

Frequency MHz	Power spectral density dBm	Result
Low channel 2412MHz	-8.23	Pass
Middle channel 2437MHz	-7.89	Pass
High channel 2462MHz	-7.65	Pass

802.11 G

Frequency MHz	Power spectral density dBm	Result
Low channel 2412MHz	-8.19	Pass
Middle channel 2437MHz	-7.22	Pass
High channel 2462MHz	-7.04	Pass

802.11 N HT20

Frequency MHz	Power spectral density dBm	Result
Low channel 2412MHz	-9.56	Pass
Middle channel 2437MHz	-8.46	Pass
High channel 2462MHz	-8.16	Pass

802.11 N HT40


Frequency MHz	Power spectral density dBm	Result
Low channel 2422MHz	-12.63	Pass
Middle channel 2437MHz	-11.98	Pass
High channel 2452MHz	-11.14	Pass




Power spectral density

802.11B


2412



2437




2462






### 802.11G

2412




Date: 7 APR 2020 15:01:52

2437



Date: 7 APR 2020 15:05:14

2462




Date: 7 APR 2020 15:08:57




### 802.11N HT20

2412




Date: 7 APR 2020 15:12:52

2437



Date: 7 APR 2020 15:16:10

2462




Date: 7 APR 2020 15:19:21




### 802.11N HT40

2422




Date: 7 APR 2020 15:22:51

2437



Date: 7 APR 2020 15:31:58

2452



Date: 7 APR 2020 15:34:15



China

## 9.5 Spurious RF conducted emissions

### Test Method

1. Establish a reference level by using the following procedure:
  - a. Set RBW=100 kHz. VBW $\geq$ 3RBW. Detector =peak, Sweep time = auto couple, Trace mode = max hold.
  - b. Allow trace to fully stabilize, use the peak marker function to determine the maximum PSD level.
2. Use the maximum PSD level to establish the reference level.
  - a. Set the center frequency and span to encompass frequency range to be measured.
  - b. Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements, report the three highest emissions relative to the limit.
3. Repeat above procedures until other frequencies measured were completed.

### Limit


Frequency Range MHz	Limit (dBc)
30-25000	-20



**Spurious RF conducted emissions**

802.11 B

**Out-of-Band Emissions  
Channel 1 (2412MHz)**









Out-of-Band Emissions  
Channel 6 (2437MHz)

Reference point




Date: 7.APR.2020 14:54:56

Spurious Emission (30MHz – 1GHz)




Date: 7.APR.2020 14:55:05

Spurious Emission (1GHz –5GHz)



Date: 7.APR.2020 14:55:20

Spurious Emission (5GHz –26.5GHz)




Date: 7.APR.2020 14:55:56




Out-of-Band Emissions  
Channel 11 (2462MHz)

Reference point




Date: 7.APR.2020 14:59:36

Spurious Emission (30MHz – 1GHz)




Date: 7.APR.2020 14:59:44

Spurious Emission (1GHz –5GHz)



Date: 7.APR.2020 15:00:00

Spurious Emission (5GHz –26.5GHz)



Date: 7.APR.2020 15:00:35




802.11 G

Out-of-Band Emissions


Channel 1 (2412MHz)

Reference point

Spurious Emission (30MHz – 1GHz)




Date: 7.APR.2020 15:02:59




Date: 7.APR.2020 15:03:07

Spurious Emission (1GHz –5GHz)

Spurious Emission (5GHz –26.5GHz)



Date: 7.APR.2020 16:30:13




Date: 7.APR.2020 15:03:58




### Out-of-Band Emissions Channel 6 (2437MHz)

#### Reference point




Date: 7.APR.2020 15:05:19

#### Spurious Emission (30MHz – 1GHz)




Date: 7.APR.2020 15:05:27

#### Spurious Emission (1GHz –5GHz)



Date: 7.APR.2020 15:05:43

#### Spurious Emission (5GHz –26.5GHz)




Date: 7.APR.2020 15:06:19




### Out-of-Band Emissions Channel 11 (2462MHz)

#### Reference point




Date: 7.APR.2020 15:10:04

#### Spurious Emission (30MHz – 1GHz)




Date: 7.APR.2020 15:10:12

#### Spurious Emission (1GHz – 5GHz)



Date: 7.APR.2020 16:29:10

#### Spurious Emission (5GHz – 26.5GHz)




Date: 7.APR.2020 15:11:04




802.11 N HT20  
Out-of-Band Emissions  
Channel 1 (2412MHz)

Reference point




Date: 7 APR 2020 15:13:58

Spurious Emission (30MHz – 1GHz)




Date: 7 APR 2020 15:14:07

Spurious Emission (1GHz –5GHz)



Date: 7 APR 2020 16:27:56

Spurious Emission (5GHz –26.5GHz)




Date: 7 APR 2020 15:14:58




Out-of-Band Emissions  
Channel 6 (2437MHz)

Reference point




Date: 7 APR 2020 15:16:16

Spurious Emission (30MHz – 1GHz)




Date: 7 APR 2020 15:16:24

Spurious Emission (1GHz – 5GHz)



Date: 7 APR 2020 15:16:40

Spurious Emission (5GHz – 26.5GHz)




Date: 7 APR 2020 15:17:16




Out-of-Band Emissions  
Channel 11 (2462MHz)

Reference point




Date: 7.APR.2020 15:20:27

Spurious Emission (30MHz – 1GHz)




Date: 7.APR.2020 15:20:36

Spurious Emission (1GHz –5GHz)



Date: 7.APR.2020 16:27:06

Spurious Emission (5GHz –26.5GHz)



Date: 7.APR.2020 15:21:27







802.11 N HT40

Out-of-Band Emissions  
Channel 3 (2422MHz)

Reference point

Spurious Emission (30MHz – 1GHz)





Date: 7.APR.2020 15:23:58

Date: 7.APR.2020 15:24:07

Spurious Emission (1GHz –5GHz)

Spurious Emission (5GHz –26.5GHz)



Date: 7.APR.2020 16:26:14



Date: 7.APR.2020 15:24:58



Out-of-Band Emissions  
Channel 6 (2437MHz)

Reference point

Spurious Emission (30MHz – 1GHz)





Date: 7.APR.2020 15:32:04

Date: 7.APR.2020 15:32:12

Spurious Emission (1GHz – 5GHz)

Spurious Emission (5GHz – 26.5GHz)




Date: 7.APR.2020 16:24:15

Date: 7.APR.2020 15:33:03




Out-of-Band Emissions  
Channel 9 (2452MHz)

Reference point




Date: 7 APR 2020 15:35:22

Spurious Emission (30MHz – 1GHz)




Date: 7 APR 2020 15:35:30

Spurious Emission (1GHz –5GHz)



Date: 7 APR 2020 16:25:03

Spurious Emission (5GHz –26.5GHz)



Date: 7 APR 2020 15:36:21



## 9.6 Band edge

### Test Method

- 1 Use the following spectrum analyzer settings:  
Span = wide enough to capture the peak level of the in-band emission and all spurious  
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section.

### Limit


According to §15.247(d) and RSS-247 5.5, in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a) and RSS-Gen 8.10, must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)) and RSS-Gen.



Test result


802.11 B

Low\_2412



Date: 7.APR.2020 14:45:31

High\_2462




Date: 7.APR.2020 14:58:38




### 802.11 G

#### Low\_2412




### High\_2462






### 802.11 N HT20

#### Low\_2412




#### High\_2462






### 802.11 N HT40

Low\_2422



Date: 7.APR.2020 15:23:01

### High\_2452



Date: 7.APR.2020 15:34:25



## 9.7 Spurious radiated emissions for transmitter

### Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:

#### For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious  
 RBW = 100 kHz to 120 kHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

#### For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious  
 RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

#### Procedures for average unwanted emissions measurements above 1000 MHz

- a) RBW = 1MHz.
- b)  $VBW \geq [3 \times RBW]$ .
- c) Detector = RMS (power averaging), if  $[\text{span} / (\# \text{ of points in sweep})] \leq RBW / 2$ .  
 Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
- e) Sweep time = auto.
- f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of  $1 / D$ , where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
- g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the



emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

- 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is  $[10 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.
- 2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is  $[20 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.
- 3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

**Limit**

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205 and RSS-GEN 8.10 must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Measured Distance Meters
0.009~0.490	2400/F (kHz)	300
0.490~1.705	24000/F (kHz)	30
1.705~30	30	30

Frequency MHz	Field Strength uV/m	Field Strength dBuV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

### Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case (which is subject to the maximum EIRP, B mode) test result is listed in the report.

#### Transmitting spurious emission test result as below:

Test mode: 802.11B					
Channel 1 (2412MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2390.0	43.3	74.0	30.7	Peak	Horizontal
4823.5	44.4	74.0	29.6	Peak	Horizontal
2390.0	44.1	74.0	29.9	Peak	Vertical
4823.8	43.6	74.0	30.4	Peak	Vertical

Test mode: 802.11B					
Channel 6 (2437MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4873.3	41.8	74.0	32.2	Peak	Horizontal
4873.0	40.1	74.0	33.9	Peak	Vertical

Test mode: 802.11B					
Channel 11 (2462MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2483.5	45.4	74.0	28.6	Peak	Horizontal
4924.6	45.6	74.0	28.4	Peak	Horizontal
2488.5	49.8	74.0	24.2	Peak	Vertical
2483.5	44.5	74.0	29.5	Peak	Vertical

#### Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading



China

Test mode: 802.11G					
Channel 1 (2412MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2390.0	56.2	74.0	17.8	Peak	Horizontal
2390.0	46.4	54.0	7.6	Average	Horizontal
4826.0	42.7	74.0	31.3	Peak	Horizontal
2390.0	55.2	74.0	18.8	Peak	Vertical
2390.0	43.3	54.0	10.7	Average	Vertical
4820.0	42.2	74.0	31.8	Peak	Vertical

Test mode: 802.11G					
Channel 6 (2437MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4873.9	44.7	74.0	29.3	Peak	Horizontal
4873.9	41.2	74.0	32.8	Peak	Vertical

Test mode: 802.11G					
Channel 11 (2462MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2483.5	46.2	74.0	27.8	Peak	Horizontal
4921.3	43.3	74.0	30.7	Peak	Horizontal
2483.5	45.3	74.0	28.7	Peak	Vertical
4917.8	42.3	74.0	31.7	Peak	Vertical

Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading



China

Test mode: 802.11N HT20					
Channel 1 (2412MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2390.0	53.3	74.0	20.7	Peak	Horizontal
2390.0	43.7	54.0	10.3	Average	Horizontal
4824.0	44.8	74.0	29.2	Peak	Horizontal
2389.5	50.5	74.0	23.5	Peak	Vertical
4824.0	41.5	74.0	32.5	Peak	Vertical

Test mode: 802.11N HT20					
Channel 6 (2437MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4873.0	42.8	74.0	31.2	Peak	Horizontal
4879.0	41.2	74.0	32.8	Peak	Vertical

Test mode: 802.11N HT20					
Channel 11 (2462MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2485.1	47.3	74.0	26.7	Peak	Horizontal
4920.2	42.9	74.0	31.1	Peak	Horizontal
2483.5	42.3	74.0	31.7	Peak	Vertical
4919.2	41.3	74.0	32.7	Peak	Vertical

Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading



Test mode: 802.11N HT40					
Channel 1 (2412MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2390.0	63.3	74.0	10.7	Peak	Horizontal
2390.0	52.3	54.0	1.7	Average	Horizontal
4844.0	40.8	74.0	33.2	Peak	Horizontal
2389.5	60.5	74.0	13.5	Peak	Vertical
2389.5	48.5	54.0	5.5	Average	Vertical
4844.0	41.5	74.0	32.5	Peak	Vertical

Test mode: 802.11N HT40					
Channel 6 (2437MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4681.0	42.8	74.0	31.2	Peak	Horizontal
4879.0	41.2	74.0	32.8	Peak	Vertical

Test mode: 802.11N HT40					
Channel 11 (2462MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2484.1	60.3	74.0	13.7	Peak	Horizontal
2484.1	47.3	54.0	6.7	Average	Horizontal
4904.2	42.9	74.0	31.1	Peak	Horizontal
2483.5	55.3	74.0	18.7	Peak	Vertical
2483.5	43.3	54.0	10.7	Average	Vertical
4909.2	41.3	74.0	32.7	Peak	Vertical

Remark:


- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading



The worst case of Radiated Emission below 1GHz:

Site: 3-meter chamber	Time: 2020/03/31 - 15:43
Limit: FCC_Part15.209 and RSS-GEN 8.8_RE(3m)	Engineer: Jiaxi XU
Probe: VULB9168	Polarity: Horizontal
EUT: Wi-Fi and Bluetooth Module, Model no:WB8P	Power: 120VAC, 60Hz (powered by notebook)
Note: Transmit by 802.11n HT40 at channel 2422MHz.	
Note: There is the worst case within frequency range 30MHz~1GHz.	

RE\_VULB9168\_pre\_Cont\_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
335.320000	39.1	1000.0	120.000	100.1	V	359.0	16.0	6.9	46.0
384.080000	39.2	1000.0	120.000	100.1	V	359.0	16.0	6.9	46.0
385.840000	41.1	1000.0	120.000	100.1	V	359.0	17.1	4.9	46.0
386.640000	40.6	1000.0	120.000	100.1	V	359.0	17.0	5.4	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)


Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.



Site: 3-meter chamber	Time: 2020/03/31 - 15:08
Limit: FCC_Part15.209 and RSS-GEN 8.8_RE(3m)	Engineer: Jiaxi XU
Probe: VULB9168	Polarity: Vertical
EUT: Wi-Fi and Bluetooth Module, Model no: WB8P	Power: 120VAC, 60Hz (powered by notebook)
Note: Transmit by 802.11n HT40 at channel 2422MHz.	
Note: There is the worst case within frequency range 30MHz~1GHz.	

RE\_VULB9168\_pre\_Cont\_30-1000



Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.





## 10 Test Equipment List

List of Test Instruments  
Test Site1

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
C	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2019-8-5	2020-8-4
	Wideband power sensor	Rohde & Schwarz	NRP-Z81	104782	2019-12-23	2020-12-22
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2019-8-5	2020-8-4
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2019-8-5	2020-8-4
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2019-3-16	2022-3-15
	Horn Antenna	Rohde & Schwarz	HF907	102393	2018-6-11	2021-4-1
	Pre-amplifier	Rohde & Schwarz	SCU-18D	19006451	2019-8-5	2020-8-4
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2019-6-28	2020-6-27
	DOUBLE-RIDGED WAVEGUIDE HORN WITH PRE-AMPLIFIER (18 GHZ - 40 GHZ)	ETS-Lindgren	3116C-PA	002222727	2018-1-29	2021-1-28
	3m Semi-anechoic chamber	TDK	9X6X6	----	2018-5-11	2021-5-10
CE	EMI Test Receiver	Rohde & Schwarz	ESR3	101907	2019-8-5	2020-8-4
	LISN	Rohde & Schwarz	ENV216	101924	2019-8-5	2020-8-4
Measurement Software Information						
Test Item	Software	Manufacturer	Version			
C	Power Viewer	Rohde & Schwarz	V 11.0			
RE	EMC 32	Rohde & Schwarz	V9.15.00			
CE	EMC 32	Rohde & Schwarz	V9.15.03			

**C - Conducted RF tests**

- Conducted peak output power
- 6dB bandwidth and 99% Occupied Bandwidth
- Power spectral density\*
- Spurious RF conducted emissions
- Band edge

## 11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, $\pm 3.16$ dB
Radiated Disturbance	30MHz to 1GHz, $\pm 5.03$ dB (Horizontal) $\pm 5.12$ dB (Vertical) 1GHz to 18GHz, $\pm 5.49$ dB 18GHz to 40GHz, $\pm 5.63$ dB
Carrier power conducted measurement	50MHz~18GHz, $\pm 1.238$ dB
Spurious Emission Conducted Measurement	9kHz ~40GHz, $\pm 1.224$ dB



## 12 Photographs of Test Set-ups

Refer to the < Test Setup photos >.



## 13 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

---

THE END