

## FCC - TEST REPORT

Report Number : **708881974839-00** Date of Issue: October 21, 2019

Model : WRD2L

Product Type : WIFI Module

FCC ID : 2ANDL-WRD2L

Applicant : Hangzhou Tuya Information Technology Co.,Ltd

Address of Applicant : Room701,Building3,More Center,No.87 GuDun  
Road, Hangzhou, Zhejiang China

Manufacturer : Hangzhou Tuya Information Technology Co.,Ltd

Address of Manufacturer : Room701,Building3,More Center,No.87 GuDun  
Road, Hangzhou, Zhejiang China

Factory : Newtronics Hangzhou Co.,Ltd

Address of Factory : No.15,Jiu zhou Road,Jiang Gan Science&Technology  
Economic Park Hangzhou

Test Result :  **Positive**       **Negative**

Total pages including Appendices : 46

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.*

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.*



## 1 Table of Contents

1	Table of Contents .....	2
2	Details about the Test Laboratory .....	3
3	Description of the Equipment under Test .....	4
4	Summary of Test Standards .....	5
5	Summary of Test Results.....	6
6	General Remarks.....	7
7	Test Setups .....	8
8	Systems test configuration.....	11
9	Technical Requirement .....	12
9.1	Conducted Emission .....	12
9.2	Conducted peak output power.....	15
9.3	6dB bandwidth Occupied Bandwidth .....	16
9.4	Power spectral density .....	20
9.5	Spurious RF conducted emissions.....	24
9.6	Spurious radiated emissions for transmitter .....	34
10	Test Equipment List.....	43
11	System Measurement Uncertainty .....	44
12	Photographs of Test Set-ups .....	45
13	Photographs of EUT .....	46



## 2 Details about the Test Laboratory

### Details about the Test Laboratory

#### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai  
Branch  
No.16 Lane, 1951 Du Hui Road,  
Shanghai 201108,  
P.R. China

FCC Registration No.: 820234  
Telephone: +86 21 6141 0123  
Fax: +86 21 6140 8600



### 3 Description of the Equipment under Test

#### Description of the Equipment Under Test

Product: WIFI Module

Model no.: WRD2L

FCC ID: 2ANDL-WRD2L

Trade Mark: NA

Options and accessories: NA

Input Rated Voltage: DC 3.0-3.6V

RF Transmission Frequency: 802.11b/g/n-HT20: 2412~2462 MHz

No. of Operated Channel: 11 for 802.11b/802.11g/802.11(H20)

Channel list:

Operation Frequency each of channel For 802.11b/g/n(H20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Radio technology: IEEE 802.11b/802.11g/802.11(H20)

Modulation: Direct Sequence Spread Spectrum (DSSS) for 802.11b  
Orthogonal Frequency Division Multiplexing(OFDM) for 802.11g/n

Data speed (IEEE 802.11b): 1Mbps, 2Mbps, 5.5Mbps, 11Mbps

Data speed (IEEE 802.11g): 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps,54Mbps

Data speed (IEEE 802.11n): Up to 72Mbps

Antenna Type: PCB antenna

Antenna Gain: 2.0dBi

Description of the EUT: The Equipment Under Test (EUT) is a WIFI Module supports 2.4GHz WIFI functions.



## 4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB558074 D01 DTS Measurement Guidance v05r02 and ANSI C63.10 (2013).

## 5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C						
Test Condition		Pages	Test Site	Test Result		
				Pass	Fail	N/A
§15.207	Conducted emission AC power port	12-14	---	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247 (b) (1)	Conducted peak output power	15	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(a)(1)	20dB bandwidth	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)	Carrier frequency separation	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)(iii)	Number of hopping frequencies	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)(iii)	Dwell Time	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(e)	Power spectral density	20-23	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(a)(2)	6dB bandwidth and 99% Occupied Bandwidth	16-19	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d)	Spurious RF conducted emissions	24-33	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d)	Spurious radiated emissions and Band edge for transmitter	34-42	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.203	Antenna requirement	See note 1		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses a permanently integral antenna, which gain is 2.0dBi. According to §15.203, it is considered sufficiently to comply with the provisions of this section.

15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.



## 6 General Remarks

### Remarks

This submittal(s) (test report) is intended for FCC ID: 2ANDL-WRD2L, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

### SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: September 21, 2019

Testing Start Date: September 21, 2019

Testing End Date: September 30, 2019

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:


Hui TONG  
EMC Section Manager

Jiaxi XU  
EMC Project Engineer

Wenqiang LU  
EMC Test Engineer


## 7 Test Setups

### 7.1 AC Power Line Conducted Emission test setups




### 7.2 Radiated test setups

#### 9kHz ~ 30MHz Test Setup:







30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:



### 18GHz ~ 25GHz Test Setup:



### 7.3 Conducted RF test setups



## 8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)
Notebook	Lenove	X240

Test channel & mode:

The EUT configured using a proprietary communication interface provided by the client. The interface allows channel control required to support the evaluation.

Test software	SecureCRT
---------------	-----------

802.11b/802.11g/802.11n-HT20

Test mode	Channel	Frequency (MHz)
Tx	1	2412
Tx	6	2437
Tx	11	2462

The pre-test has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

Tested Channel	Modulation Type	Data Rate
Low, Middle, High	802.11b: DSSS	1Mbps
Low, Middle, High	802.11g: OFDM	6Mbps
Low, Middle, High	802.11n (HT20): OFDM	MCS0 (6.5Mbps)

### Device Capabilities

This device contains the following capabilities:

802.11b/g/n-HT20 Wi-Fi Device.

Duty Cycle: 100%

**Note:** 2.4GHz WLAN (DTS) operation is possible in 20MHz channel bandwidths.

## 9 Technical Requirement

### 9.1 Conducted Emission

#### Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line


#### Limit

Frequency MHz	QP Limit dB $\mu$ V	AV Limit dB $\mu$ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

## Conducted Emission


Product Type : WIFI Module  
 M/N : WRD2L  
 Operating Condition : Mode 1: Tx\_802.11g 2462MHz, powered by notebook  
 Test Specification : FCC\_Part15.207  
 Comment : L-line, AC 120V/60Hz



## Final Result

Frequency (MHz)	Quasi Peak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.163500	62.68	---	65.28	2.60	1000.0	9.000	L1	19.4
0.168000	---	46.77	55.06	8.29	1000.0	9.000	L1	19.4
0.222000	53.54	---	62.74	9.20	1000.0	9.000	L1	19.4
0.226500	---	34.89	52.58	17.69	1000.0	9.000	L1	19.4
0.276000	46.49	---	60.94	14.45	1000.0	9.000	L1	19.4

Product Type : WIFI Module  
 M/N : WRD2L  
 Mode 1: Tx\_802.11g 2462MHz, powered by notebook  
 Test Specification : FCC\_Part15.207  
 Comment : N-line, AC 120V/60Hz



### Final Result

Frequency (MHz)	Quasi Peak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.177000	---	46.34	54.63	8.29	1000.0	9.000	N	19.4
0.177000	56.80	---	64.63	7.83	1000.0	9.000	N	19.4
0.240000	---	32.44	52.10	19.66	1000.0	9.000	N	19.4
0.240000	49.03	---	62.10	13.07	1000.0	9.000	N	19.4
0.523500	50.70	---	56.00	5.30	1000.0	9.000	N	19.4
0.532500	---	37.77	46.00	8.23	1000.0	9.000	N	19.4
0.586500	46.29	---	56.00	9.71	1000.0	9.000	N	19.4

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)  
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

## 9.2 Conducted peak output power

### Test Method

1. Use the following spectrum analyzer settings:  
RBW > the 6 dB bandwidth of the emission being measured, VBW $\geq$ 3RBW, Span $\geq$ 3RBW  
Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Use a power meter to measure the conducted peak output power.

### Limits

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	$\leq 1$	$\leq 30$

Test result as below table

Mode	Antenna Gain (dBi)	Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)
b	N/A	CH01	2412	19.23	30.00
		CH06	2437	18.83	30.00
		CH11	2462	19.52	30.00
g		CH01	2412	23.27	30.00
		CH06	2437	23.13	30.00
		CH11	2462	<b>23.41</b>	30.00
n-HT20		CH01	2412	22.62	30.00
		CH06	2437	22.41	30.00
		CH11	2462	22.82	30.00

### 9.3 6dB bandwidth Occupied Bandwidth

#### Test Method

1. Use the following spectrum analyzer settings:  
RBW=100K, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq$  6 dB.
3. Allow the trace to stabilize, record the 6 dB Bandwidth value.

#### Limit

Limit [kHz]

≥500

#### Test result


Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	6db Bandwidth (MHz)	Limit (MHz)	Result
802.11b	1Mbps	01	2412	10.032	≥ 0.5	Pass
802.11b	1Mbps	06	2437	10.020	≥ 0.5	Pass
802.11b	1Mbps	11	2462	10.026	≥ 0.5	Pass
802.11g	6Mbps	01	2412	16.086	≥ 0.5	Pass
802.11g	6Mbps	06	2437	16.308	≥ 0.5	Pass
802.11g	6Mbps	11	2462	16.314	≥ 0.5	Pass
802.11n-HT20	6.5Mbps	01	2412	17.298	≥ 0.5	Pass
802.11n-HT20	6.5Mbps	06	2437	17.184	≥ 0.5	Pass
802.11n-HT20	6.5Mbps	11	2462	17.286	≥ 0.5	Pass






802.11b 6dB Bandwidth

Channel 01 (2412MHz) Reference level




Date: 26 SEP 2019 10:36:56

Channel 01 (2412MHz)




Date: 26 SEP 2019 10:38:01

Channel 06 (2437MHz) Reference level




Date: 26 SEP 2019 10:45:04

Channel 06 (2437MHz)



Date: 26 SEP 2019 10:47:11

Channel 11 (2462MHz) Reference level



Date: 26 SEP 2019 10:53:18

Channel 11 (2462MHz)




Date: 26 SEP 2019 10:54:24




802.11g 6dB Bandwidth

Channel 01 (2412MHz) Reference level




Date: 26 SEP 2019 13:47:04

Channel 01 (2412MHz)




Date: 26 SEP 2019 13:48:11

Channel 06 (2437MHz) Reference level




Date: 26 SEP 2019 13:57:16

Channel 06 (2437MHz)




Date: 26 SEP 2019 13:58:15

Channel 11 (2462MHz) Reference level



Date: 26 SEP 2019 14:02:13

Channel 11 (2462MHz)




Date: 26 SEP 2019 14:03:14




802.11n 6dB Bandwidth

Channel 01 (2412MHz) Reference level




Date: 26 SEP.2019 14:15:45

Channel 01 (2412MHz)




Date: 26 SEP.2019 14:16:44

Channel 06 (2437MHz) Reference level




Date: 26 SEP.2019 14:21:09

Channel 06 (2437MHz)




Date: 26 SEP.2019 14:21:54

Channel 11 (2462MHz) Reference level



Date: 26 SEP.2019 14:25:56

Channel 11 (2462MHz)



Date: 26 SEP.2019 14:27:10

## 9.4 Power spectral density

### Test Method

This procedure shall be used if average conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency. RBW=3kHz, VBW $\geq$ 3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed.

### Limit

Limit [dBm]

≤8


### Test result

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	PSD (dBm / 10kHz)	Limit (dBm/3kHz)	Result
802.11b	1Mbps	01	2412	-5.16	≤8	Pass
802.11b	1Mbps	06	2437	-5.44	≤8	Pass
802.11b	1Mbps	11	2462	-5.87	≤8	Pass
802.11g	6Mbps	01	2412	-11.41	≤8	Pass
802.11g	6Mbps	06	2437	-11.87	≤8	Pass
802.11g	6Mbps	11	2462	-10.62	≤8	Pass
802.11n-HT20	6.5Mbps	01	2412	-12.34	≤8	Pass
802.11n-HT20	6.5Mbps	06	2437	-12.56	≤8	Pass
802.11n-HT20	6.5Mbps	11	2462	-11.63	≤8	Pass




### 802.11b PSD

#### Channel 01 (2412MHz)




Date: 26 SEP 2019 10:39:20

#### Channel 06 (2437MHz)



Date: 26 SEP 2019 10:48:22

#### Channel 11 (2462MHz)




Date: 26 SEP 2019 14:11:41




802.11g PSD

Channel 01 (2412MHz)




Date: 26.SEP.2019 13:49:04

Channel 06 (2437MHz)



Date: 26.SEP.2019 13:59:02

Channel 11 (2462MHz)




Date: 26.SEP.2019 14:04:02




802.11n HT20 PSD


Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



## 9.5 Spurious RF conducted emissions

### Test Method

1. Establish a reference level by using the following procedure:
  - a. Set RBW=100 kHz. VBW $\geq$ 3RBW. Detector =peak, Sweep time = auto couple, Trace mode = max hold.
  - b. Allow trace to fully stabilize, use the peak marker function to determine the maximum PSD level.
2. Use the maximum PSD level to establish the reference level.
  - a. Set the center frequency and span to encompass frequency range to be measured.
  - b. Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements, report the three highest emissions relative to the limit.
3. Repeat above procedures until other frequencies measured were completed.

### Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20

### Test result

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	Limit	Result
802.11b	1Mbps	01	2412	20dBc	Pass
802.11b	1Mbps	06	2437	20dBc	Pass
802.11b	1Mbps	11	2462	20dBc	Pass
802.11g	6Mbps	01	2412	20dBc	Pass
802.11g	6Mbps	06	2437	20dBc	Pass
802.11g	6Mbps	11	2462	20dBc	Pass
802.11n-HT20	6.5Mbps	01	2412	20dBc	Pass
802.11n-HT20	6.5Mbps	06	2437	20dBc	Pass
802.11n-HT20	6.5Mbps	11	2462	20dBc	Pass




**Spurious RF conducted emissions**


**802.11b Out-of-Band Emissions**

**Channel 01 (2412MHz)**


**Reference point**




**Spurious Emission (30MHz – 1GHz)**




**Spurious Emission (1GHz –5GHz)**



**Spurious Emission (5GHz –25GHz)**




**Low band edge**






802.11b Out-of-Band Emission  
Channel 06 (2437MHz)


Reference point




Spurious Emission (30MHz – 1GHz)



Spurious Emission (1GHz –5GHz)




Spurious Emission (5GHz –25GHz)




### 802.11b Out-of-Band Emissions Channel 01 (2462MHz)


#### Reference point




#### Spurious Emission (30MHz – 1GHz)




#### Spurious Emission (1GHz –5GHz)



#### Spurious Emission (5GHz –25GHz)




#### High band edge






### 802.11g Out-of-Band Emissions Channel 01 (2412MHz)


#### Reference point




#### Spurious Emission (30MHz – 1GHz)




#### Spurious Emission (1GHz –5GHz)



#### Spurious Emission (5GHz –25GHz)




#### Low band edge






### 802.11g Out-of-Band Emissions Channel 06 (2437MHz)






### 802.11g Out-of-Band Emissions Channel 11 (2462MHz)


#### Reference point




#### Spurious Emission (30MHz – 1GHz)




#### Spurious Emission (1GHz –5GHz)



#### Spurious Emission (5GHz –25GHz)




#### High band edge






### 802.11n-HT20 Out-of-Band Emissions Channel 01 (2412MHz)


#### Reference point




#### Spurious Emission (30MHz – 1GHz)




#### Spurious Emission (1GHz –5GHz)



#### Spurious Emission (5GHz –25GHz)



#### Low band edge







### 802.11n-HT20 Out-of-Band Emissions Channel 06 (2437MHz)

#### Reference point

#### Spurious Emission (30MHz – 1GHz)




Date: 26 SEP.2019 14:21:09




Date: 26 SEP.2019 14:23:08

#### Spurious Emission (1GHz – 5GHz)

#### Spurious Emission (5GHz – 25GHz)



Date: 26 SEP.2019 14:23:51



Date: 26 SEP.2019 14:24:31







## 802.11n-HT20 Out-of-Band Emissions Channel 11 (2462MHz)



### Reference point

### Spurious Emission (30MHz – 1GHz)




### Spurious Emission (1GHz –5GHz)

### Spurious Emission (5GHz –25GHz)



### High band edge



## 9.6 Spurious radiated emissions for transmitter

### Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:

#### For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious  
 RBW = 100 kHz to 120 kHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

#### For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious  
 RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

#### Procedures for average unwanted emissions measurements above 1000 MHz

- a) RBW = 1MHz.
- b)  $VBW \geq [3 \times RBW]$ .
- c) Detector = RMS (power averaging), if  $[\text{span} / (\# \text{ of points in sweep})] \leq RBW / 2$ . Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
- e) Sweep time = auto.
- f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of  $1 / D$ , where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
- g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
  - 1) If power averaging (rms) mode was used in the preceding step e), then the correction



factor is  $[10 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.

2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is  $[20 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.

3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.



**Limit**

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205, must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Measured Distance Meters
0.009~0.490	2400/F (kHz)	300
0.490~1.705	24000/F (kHz)	30
1.705~30	30	30

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

## Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case (which is subject to the maximum EIRP, B mode) test result is listed in the report.

### Transmitting spurious emission test result as below:

**Remark 1:** There are the ambient noise within frequency range 9kHz ~ 30MHz and 18GHz ~ 25GHz, the permissible value is not show in the report.

**Remark 2:** Average measurement was not performed if peak level lower than average limit.

**Remark 3:** Other frequency was 20dB below limit line with 1-18GHz, there is not show in the report.

## Test Result

Test mode: 802.11b					
Channel 01 (2412MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2390.0	52.60	74.0	-21.40	Peak	Horizontal
4824.0	57.80	74.0	-16.20	Peak	Horizontal
4824.0	51.80	54.0	-2.20	Average	Horizontal
2390.0	50.37	74.0	-23.63	Peak	Vertical
4823.9	48.09	74.0	-25.91	Peak	Vertical

Test mode: 802.11b					
Channel 06 (2437 MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4873.8	51.33	74.0	-22.67	Peak	Horizontal
7310.7	40.20	74.0	-33.80	Peak	Horizontal
4874.3	46.87	74.0	-27.13	Peak	Vertical
7310.7	39.25	74.0	-34.75	Peak	Vertical

Test mode: 802.11b					
Channel 11 (2462MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2483.5	56.20	74.0	-17.80	Peak	Horizontal
2483.5	40.12	54.0	-13.88	Average	Horizontal
4923.1	54.43	74.0	-19.57	Peak	Horizontal
4923.1	53.30	54.0	-0.70	Average	Horizontal
2483.7	51.46	74.0	-22.54	Peak	Vertical
4923.8	50.334	74.0	-23.67	Peak	Vertical

## Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading

Test mode: 802.11g					
Channel 01 (2412MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2390.0	50.60	74.0	-23.40	Peak	Horizontal
4823.3	46.93	74.0	-27.07	Peak	Horizontal
2389.6	51.37	74.0	-22.63	Peak	Vertical
4823.2	44.37	74.0	-29.63	Peak	Vertical

Test mode: 802.11g					
Channel 06 (2437 MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4869.2	45.22	74.0	-28.78	Peak	Horizontal
7311.1	40.34	74.0	-33.66	Peak	Horizontal
4878.1	42.60	74.0	-31.40	Peak	Vertical
7312.5	39.40	74.0	-34.60	Peak	Vertical

Test mode: 802.11g					
Channel 11 (2462MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2483.5	62.44	74.0	-11.56	Peak	Horizontal
2483.5	45.60	54.0	-8.40	Average	Horizontal
4924.2	46.67	74.0	-27.33	Peak	Horizontal
2483.6	56.40	74.0	-17.60	Peak	Vertical
2483.6	41.40	54.0	-12.60	Average	Vertical
4923.1	45.58	74.0	-28.42	Peak	Vertical

Remark:

- (4) Emission level= Original Receiver Reading + Correct Factor
- (5) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (6) Margin = limit – Corrected Reading

Test mode: 802.11n-HT20					
Channel 01 (2412MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2389.6	50.10	74.0	-23.90	Peak	Horizontal
4825.3	42.20	74.0	-31.80	Peak	Horizontal
2390.0	48.02	74.0	-25.98	Peak	Vertical
4825.0	40.16	74.0	-33.84	Peak	Vertical

Test mode: 802.11n-HT20					
Channel 06 (2437 MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4873.9	40.12	74.0	-33.88	Peak	Horizontal
7312.8	40.11	74.0	-33.89	Peak	Horizontal
4872.5	40.08	74.0	-33.92	Peak	Vertical
7312.8	40.04	74.0	-33.96	Peak	Vertical

Test mode: 802.11n-HT20					
Channel 11 (2462MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2484.0	50.44	74.0	-23.56	Peak	Horizontal
4920.4	40.35	74.0	-33.65	Peak	Horizontal
2485.2	48.48	74.0	-25.52	Peak	Vertical
4923.6	40.24	74.0	-33.76	Peak	Vertical

## Remark:


- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading



The worst case of Radiated Emission below 1GHz:

Site: 3-meter chamber	Time: 2019/09/29 - 13:45
Limit: FCC_Part15.109_RE(3m)_ClassB	Engineer: Jiaxi XU
Probe: VULB9168	Polarity: Horizontal
EUT: WIFI Module, Model no: WRD2L	Power: 120VAC, 60Hz (powered by notebook)
Note: Transmit by 802.11g at channel 2437MHz.	
Note: There is the worst case within frequency range 30MHz~1GHz.	

RE\_VULB9168\_pre\_Cant\_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
239.200000	33.5	1000.0	120.000	100.0	H	150.0	13.4	12.5	46.0
287.720000	34.9	1000.0	120.000	100.0	H	1.0	14.7	11.1	46.0
335.720000	32.5	1000.0	120.000	100.0	H	359.0	16.0	13.5	46.0
383.680000	34.7	1000.0	120.000	100.0	H	61.0	17.0	11.3	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)


Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.



Site: 3-meter chamber	Time: 2019/09/30 - 13:35
Limit: FCC_Part15.109_RE(3m)_ClassB	Engineer: Jiaxi XU
Probe: VULB9168	Polarity: Vertical
EUT: WIFI Module, Model no: WRD2L	Power: 120VAC, 60Hz (powered by notebook)
Note: Transmit by 802.11g at channel 2437MHz.	
Note: There is the worst case within frequency range 30MHz~1GHz.	

PE\_VULB9168\_pre\_Cont\_30-1000





## 10 Test Equipment List

List of Test Instruments  
Test Site1

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
C	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2020-8-4
	Wideband power sensor	Rohde & Schwarz	NRP-Z81	104782	2019-12-27
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2020-8-4
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2020-8-4
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2022-3-15
	Horn Antenna	Rohde & Schwarz	HF907	102393	2021-4-1
	Pre-amplifier	Rohde & Schwarz	SCU-18D	19006451	2020-8-4
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2020-6-27
	DOUBLE-RIDGED WAVEGUIDE HORN WITH PRE-AMPLIFIER (18 GHZ - 40 GHZ)	ETS-Lindgren	3116C-PA	E326	2021-1-28
	3m Semi-anechoic chamber	TDK	9X6X6	----	2021-5-10
CE	EMI Test Receiver	Rohde & Schwarz	ESR3	101907	2020-8-4
	LISN	Rohde & Schwarz	ENV216	101924	2020-8-4
Measurement Software Information					
Test Item	Software	Manufacturer	Version		
RE	EMC 32	Rohde & Schwarz	V9.15.00		
CE	EMC 32	Rohde & Schwarz	V9.15.03		

### C - Conducted RF tests

- Conducted peak output power
- 6dB Occupied Bandwidth
- Power spectral density\*
- Spurious RF conducted emissions
- Conducted Band edge



## 11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

### Test Site1

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, 3.16dB
Radiated Disturbance	30MHz to 1GHz, $\pm 5.03$ dB (Horizontal) $\pm 5.12$ dB (Vertical) 1GHz to 18GHz, $\pm 5.15$ dB (Horizontal) $\pm 5.12$ dB (Vertical) 18GHz to 25GHz, $\pm 4.76$ dB



## 12 Photographs of Test Set-ups

Refer to the < Test Setup photos >.



## 13 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

---

THE END