

**CFR 47 FCC PART 15 SUBPART C  
ISED RSS-247 Issue 3**

**TEST REPORT**

*For*

**DJI Focus Pro Hand Unit**

**MODEL NUMBER: DF03-004**

**REPORT NUMBER: 4790983922.2-1-RF-1**

**ISSUE DATE: January 10, 2024**

**FCC ID: 2ANDR-DF03423**

**IC: 23060-DF03423**

*Prepared for*

**SZ DJI Osmo Technology Co.,Ltd.  
4F, Jingkou Community Comprehensive Service Building, No. 83 Bishui Road  
North, Guangming Street, Guangming District, Shenzhen, China**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

## Revision History

Rev.	Issue Date	Revisions	Revised By
V0	January 10, 2024	Initial Issue	

## Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c) RSS-GEN Clause 6.8	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207 RSS-GEN Clause 8.8	N/A
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.1.3	FCC Part 15.247 (b)(3) RSS-247 Clause 5.4 (d)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d) RSS-247 Clause 5.5	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.12 & Clause 11.13	FCC Part 15.247 (d) FCC Part 15.205/15.209 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

**Note:**

1. N/A: In this whole report not applicable.

\*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

\*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C ISED RSS-247 Issue 3> when <Simple Acceptance> decision rule is applied.

## CONTENTS

<b>1. ATTESTATION OF TEST RESULTS</b> .....	<b>6</b>
<b>2. TEST METHODOLOGY</b> .....	<b>7</b>
<b>3. FACILITIES AND ACCREDITATION</b> .....	<b>7</b>
<b>4. CALIBRATION AND UNCERTAINTY</b> .....	<b>8</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i> .....	8
4.2. <i>MEASUREMENT UNCERTAINTY</i> .....	8
<b>5. EQUIPMENT UNDER TEST</b> .....	<b>9</b>
5.1. <i>DESCRIPTION OF EUT</i> .....	9
5.2. <i>CHANNEL LIST</i> .....	9
5.3. <i>MAXIMUM POWER</i> .....	9
5.4. <i>TEST CHANNEL CONFIGURATION</i> .....	9
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i> .....	10
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i> .....	10
5.7. <i>SUPPORT UNITS FOR SYSTEM TEST</i> .....	11
<b>6. MEASURING EQUIPMENT AND SOFTWARE USED</b> .....	<b>12</b>
<b>7. ANTENNA PORT TEST RESULTS</b> .....	<b>15</b>
7.1. <i>CONDUCTED OUTPUT POWER</i> .....	15
7.2. <i>6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH</i> .....	16
7.3. <i>POWER SPECTRAL DENSITY</i> .....	18
7.4. <i>CONDUCTED BAND EDGE AND SPURIOUS EMISSION</i> .....	20
7.5. <i>DUTY CYCLE</i> .....	22
<b>8. RADIATED TEST RESULTS</b> .....	<b>23</b>
8.1. <i>RESTRICTED BANDEDGE</i> .....	31
8.2. <i>SPURIOUS EMISSIONS(1 GHZ~3 GHZ)</i> .....	49
8.3. <i>SPURIOUS EMISSIONS(3 GHZ~18 GHZ)</i> .....	59
8.4. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ)</i> .....	79
8.5. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ)</i> .....	82
8.6. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ)</i> .....	84
<b>9. ANTENNA REQUIREMENT</b> .....	<b>86</b>
<b>10. TEST DATA</b> .....	<b>87</b>
10.1. <i>APPENDIX A: DTS BANDWIDTH</i> .....	87
10.1.1.    Test Result .....	87
10.1.2.    Test Graphs .....	88
10.2. <i>APPENDIX B: OCCUPIED CHANNEL BANDWIDTH</i> .....	91

---

10.2.1.	Test Result .....	91
10.2.2.	Test Graphs .....	92
10.3.	<i>APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER</i> .....	95
10.3.1.	Test Result .....	95
10.4.	<i>APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY</i> .....	96
10.4.1.	Test Result .....	96
10.4.2.	Test Graphs .....	97
10.5.	<i>APPENDIX E: BAND EDGE MEASUREMENTS</i> .....	100
10.5.1.	Test Result .....	100
10.5.2.	Test Graphs .....	101
10.6.	<i>APPENDIX F: CONDUCTED SPURIOUS EMISSION</i> .....	104
10.6.1.	Test Result .....	104
10.6.2.	Test Graphs .....	105
10.7.	<i>APPENDIX G: DUTY CYCLE</i> .....	114
10.7.1.	Test Result .....	114
10.7.2.	Test Graphs .....	115

# 1. ATTESTATION OF TEST RESULTS

## Applicant Information

Company Name: SZ DJI Osmo Technology Co.,Ltd.  
Address: 4F, Jinkou Community Comprehensive Service Building, No. 83 Bishui Road North, Guangming Street, Guangming District, Shenzhen, China

## Manufacturer Information

Company Name: SZ DJI Osmo Technology Co.,Ltd.  
Address: 4F, Jinkou Community Comprehensive Service Building, No. 83 Bishui Road North, Guangming Street, Guangming District, Shenzhen, China

## EUT Information

EUT Name: DJI Focus Pro Hand Unit  
Model: DF03-004  
Brand: DJI  
Sample Received Date: November 16, 2023  
Sample Status: Normal  
Sample ID: 6425698-2  
Date of Tested: January 10, 2024 to January 10, 2024

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C ISED RSS-247 Issue 3	Pass

Prepared By:

*Fanny Huang*

Fanny Huang  
Engineer Project Associate

Checked By:

*Denny Huang*

Denny Huang  
Senior Project Engineer

Approved By:

*Stephen Guo*

Stephen Guo  
Operations Manager

## 2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C ISED RSS-247 Issue 3, KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, ANSI C63.10-2013 and ISED RSS-GEN Issue 5.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20192, C-20153, T-20155 and R-20202)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20192 and R-20202 Shielding Room B, the VCCI registration No. is C-20153 and T-20155</p>
---------------------------	--

**Note 1:**

All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China.

**Note 2:**

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

**Note 3:**

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	DJI Focus Pro Hand Unit
Model	DF03-004

Frequency Range:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK
Data Rates:	1Mbps/2Mbps
Normal Test Voltage:	7.2 Vdc

### 5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2468	/	/

### 5.3. MAXIMUM POWER

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)
LE 1M	2402 ~ 2480	0-39[40]	3.31
LE 2M	2402 ~ 2480	0-39[40]	3.20

### 5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
LE 1M	CH 0(Low Channel), CH 1 CH 19(MID Channel), CH38 CH 39(High Channel)	2402 MHz, 2404 MHz, 2440 MHz, 2478 MHz, 2480 MHz
LE 2M	CH 0(Low Channel), CH 1 CH 19(MID Channel), CH38 CH 39(High Channel)	2402 MHz, 2404 MHz, 2440 MHz, 2478 MHz, 2480 MHz

### 5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band						
Test Software Version		DTM				
Modulation Type	Transmit Antenna Number	Test Software setting value				
		CH 0	CH 1	CH 19	CH 38	CH 39
GFSK(1Mbps)	1	-8	1	1	1	-8
GFSK(2Mbps)	1	-8	1	1	1	-8

### 5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	FPC	1.66

Test Mode	Transmit and Receive Mode	Description
LE 1M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
LE 2M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

Note: BLE&SRD can transmit simultaneously. (declared by client)

## 5.7. SUPPORT UNITS FOR SYSTEM TEST

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	Lenovo	E42-80	R303U5AG
2	UART	/	/	/
3	Battery Pack	/	/	7.2V 2400mAh
4	DC Source	Twintex	TP-3010	Max out: 30V/10A

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.0	/


### ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

### TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

### SETUP DIAGRAM FOR TESTS



## 6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Mar.31,2023	Mar.30,2024
Vector Signal Generator	R&S	SMBV100A	261637	Oct.12, 2023	Oct.11, 2024
Signal Generator	R&S	SMB100A	178553	Oct.12, 2023	Oct.11, 2024
Signal Analyzer	R&S	FSV40	101118	Oct.12, 2023	Oct.11, 2024
Software					
Description	Manufacturer	Name		Version	
For R&S TS 8997 Test System	Rohde & Schwarz	EMC 32		10.60.10	
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Oct.12, 2023	Oct.11, 2024
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.25, 2023	Sep.24, 2024
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.12, 2023	Oct.11, 2024
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Oct.12, 2023	Oct.11, 2024
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Oct.12, 2023	Oct.11, 2024
DC power supply	Keysight	E3642A	MY55159130	Oct.12, 2023	Oct.11, 2024
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Oct.12, 2023	Oct.11, 2024
Attenuator	Aglient	8495B	2814a12853	Oct.12, 2023	Oct.11, 2024
RF Control Unit	Tonscend	JS0806-2	23B80620666	April 18, 2023	April 17, 2024
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		V3.2.22	

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.12, 2023	Oct.11, 2024
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.12, 2023	Oct.11, 2024
EMI Measurement Receiver	R&S	ESR26	101377	Oct.12, 2023	Oct.11, 2024
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.12, 2023	Oct.11, 2024
Horn Antenna	Schwarzbeck	BBHA9170	697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.12, 2023	Oct.11, 2024
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.12, 2023	Oct.11, 2024
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13, 2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.12, 2023	Oct.11, 2024
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Oct.12, 2023	Oct.11, 2024
Highpass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	Oct.12, 2023	Oct.11, 2024
Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	Oct.12, 2023	Oct.11, 2024
Band Reject Filter	Wainwright	WRCJV20-5120-5150-5350-5380-60SS	2	Oct.12, 2023	Oct.11, 2024
Band Reject Filter	Wainwright	WRCJV20-5440-5470-5725-5755-60SS	1	Oct.12, 2023	Oct.11, 2024
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Oct.12, 2023	Oct.11, 2024
Band Reject Filter	Wainwright	WRCD5-1879-1879.85-1880.15-1881-40SS	1	Oct.12, 2023	Oct.11, 2024

Notch Filter	Wainwright	WHJ10-882-980-7000-40SS	1	Oct.12, 2023	Oct.11, 2024
Highpass Filter	Xingbo	XBLBQ-GTA68	211115-2-1	Oct.12, 2023	Oct.11, 2024
Notch Filter (5905-6445 MHz)	Xingbo	XBLBQ-DZA175	210922-2-1	Oct.12, 2023	Oct.11, 2024
Notch Filter (6425-6525 MHz)	Xingbo	XBLBQ-DZA176	210922-2-2	Oct.12, 2023	Oct.11, 2024
Notch Filter (6825-7125 MHz)	Xingbo	XBLBQ-DZA177	210922-2-3	Oct.12, 2023	Oct.11, 2024
Notch Filter (6525-6875 MHz)	Xingbo	XBLBQ-DZA178	210922-2-4	Oct.12, 2023	Oct.11, 2024
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Oct.21, 2023	Oct.20, 2024
Barometer	Yiyi	Baro	N/A	Oct.19, 2023	Oct.18, 2024
Attenuator	Agilent	8495B	2814a12853	Oct.12, 2023	Oct.11, 2024

## 7. ANTENNA PORT TEST RESULTS

### 7.1. CONDUCTED OUTPUT POWER

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	Peak Conduct Output Power	1 watt or 30 dBm	2400-2483.5

#### TEST PROCEDURE

Peak Power:

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.


Average Power:

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding  $[10 \log (1 / D)]$ , where D is the duty cycle.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	25.4°C	Relative Humidity	45.5%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2 V

#### TEST DATE / ENGINEER

Test Date	December 2, 2023	Test By	Johnson Liu
-----------	------------------	---------	-------------

#### TEST RESULTS

Please refer to section "Test Data" - Appendix C

## 7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: ≥3 × RBW For 99 % Occupied Bandwidth: ≥3 × RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### TEST SETUP





**TEST ENVIRONMENT**

Temperature	25.4°C	Relative Humidity	45.5%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2 V

**TEST DATE / ENGINEER**

Test Date	December 2, 2023	Test By	Johnson Liu
-----------	------------------	---------	-------------

**TEST RESULTS**

Please refer to section "Test Data" - Appendix A&B

### 7.3. POWER SPECTRAL DENSITY

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

#### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.5.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	power averaging (rms)
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x OBW bandwidth
Trace	Employ trace averaging(rms)mode over a minimum of 100 traces
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	25.4°C	Relative Humidity	45.5%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2 V

#### TEST DATE / ENGINEER

Test Date	December 2, 2023	Test By	Johnson Liu
-----------	------------------	---------	-------------

**TEST RESULTS**

Please refer to section "Test Data" - Appendix D

## 7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

**TEST SETUP****TEST ENVIRONMENT**

Temperature	25.4°C	Relative Humidity	45.5%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2 V

**TEST DATE / ENGINEER**

Test Date	December 2, 2023	Test By	Johnson Liu
-----------	------------------	---------	-------------

**TEST RESULTS**

Please refer to section "Test Data" - Appendix E&F

## 7.5. DUTY CYCLE


### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	25.4°C	Relative Humidity	45.5%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2 V

### TEST DATE / ENGINEER

Test Date	December 2, 2023	Test By	Johnson Liu
-----------	------------------	---------	-------------

### TEST RESULTS

Please refer to section "Test Data" - Appendix G

## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (µA/m)	Measurement distance (m)
9 - 490 kHz <sup>Note 1</sup>	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands <sup>Note 1</sup>		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

**Note 1:** Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

**TEST PROCEDURE**

Below 30 MHz



### The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of  $377\Omega$ . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to  $Y-51.5 = Z$  dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5.  $\text{dBuA/m} = \text{dBuV/m} - 20\text{Log}_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/T_{on}$ , where:  $T_{on}$  is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


### TEST SETUP



Below 1 GHz and above 30 MHz



Above 1 GHz



**TEST ENVIRONMENT**

Temperature	24.8°C	Relative Humidity	57%
Atmosphere Pressure	101kPa	Test Voltage	


**TEST DATE / ENGINEER**

Test Date	January 10, 2024	Test By	Rex Huang
-----------	------------------	---------	-----------

**TEST RESULTS**


### 8.1. RESTRICTED BANDEDGE

Test Mode:	BLE 1M PK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.19	32.16	61.35	74.00	-12.65	peak


Test Mode:	BLE 1M AV	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	1.43	32.16	33.59	54.00	-20.41	AVG




Test Mode:	BLE 1M PK	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	25.67	32.16	57.83	74.00	-16.17	peak

Test Mode:	BLE 1M AV	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	1.32	32.16	33.48	54.00	-20.52	AVG

Test Mode:	BLE 1M PK	Frequency(MHz):	2404
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	32.61	32.16	64.77	74.00	-9.23	peak

Test Mode:	BLE 1M AV	Frequency(MHz):	2404
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	2.17	32.16	34.33	54.00	-19.67	AVG

Test Mode:	BLE 1M PK	Frequency(MHz):	2478
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	40.26	32.44	72.70	74.00	-1.30	peak
2	2483.550	40.36	32.44	72.80	74.00	-1.20	peak

Test Mode:	BLE 1M AV	Frequency(MHz):	2478
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	7.58	32.44	40.02	54.00	-13.98	AVG
2	2483.550	7.48	32.44	39.92	54.00	-14.08	AVG

Test Mode:	BLE 1M PK	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	37.72	32.44	70.16	74.00	-3.84	peak
2	2483.600	39.71	32.44	72.15	74.00	-1.85	peak


Test Mode:	BLE 1M AV	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	9.32	32.44	41.76	54.00	-12.24	AVG
2	2483.600	9.18	32.44	41.62	54.00	-12.38	AVG




Test Mode:	BLE 2M PK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.800	29.71	32.16	61.87	74.00	-12.13	peak
2	2390.000	29.75	32.16	61.91	74.00	-12.09	peak

Test Mode:	BLE 2M AV	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.800	1.90	32.16	34.06	54.00	-19.94	AVG
2	2390.000	2.13	32.16	34.29	54.00	-19.71	AVG

Test Mode:	BLE 2M PK	Frequency(MHz):	2404
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	33.13	32.16	65.29	74.00	-8.71	peak

Test Mode:	BLE 2M AV	Frequency(MHz):	2404
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	2.70	32.16	34.86	54.00	-19.14	AVG

Test Mode:	BLE 2M PK	Frequency(MHz):	2478
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	40.12	32.44	72.56	74.00	-1.44	peak
2	2483.600	40.54	32.44	72.98	74.00	-1.02	peak

Test Mode:	BLE 2M AV	Frequency(MHz):	2478
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	8.60	32.44	41.04	54.00	-12.96	AVG
2	2483.600	8.05	32.44	40.49	54.00	-13.51	AVG

Test Mode:	BLE 2M PK	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	39.17	32.44	71.61	74.00	-2.39	peak
2	2483.550	39.91	32.44	72.35	74.00	-1.65	peak

Test Mode:	BLE 2M AV	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	12.75	32.44	45.19	54.00	-8.81	AVG
2	2483.550	12.39	32.44	44.83	54.00	-9.17	AVG




## 8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1058.000	48.65	-14.76	33.89	74.00	-40.11	peak
2	1600.000	46.12	-12.38	33.74	74.00	-40.26	peak
3	2350.000	52.88	-9.26	43.62	74.00	-30.38	peak
4	2402.000	50.37	-8.99	41.38	/	/	fundamental
5	2590.000	45.41	-8.22	37.19	74.00	-36.81	peak
6	2832.000	44.27	-7.49	36.78	74.00	-37.22	peak

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1058.000	47.16	-14.76	32.40	74.00	-41.60	peak
2	1600.000	46.60	-12.38	34.22	74.00	-39.78	peak
3	1774.000	46.49	-11.80	34.69	74.00	-39.31	peak
4	2336.000	48.84	-9.33	39.51	74.00	-34.49	peak
5	2402.000	46.10	-8.99	37.11	/	/	fundamental
6	2676.000	45.33	-7.96	37.37	74.00	-36.63	peak

Test Mode:	BLE 1M	Frequency(MHz):	2404
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1474.000	45.92	-12.83	33.09	74.00	-40.91	peak
2	1774.000	44.60	-11.80	32.80	74.00	-41.20	peak
3	2066.000	44.94	-10.72	34.22	74.00	-39.78	peak
4	2404.000	49.50	-8.99	40.51	/	/	fundamental
5	2638.000	43.56	-8.07	35.49	74.00	-38.51	peak
6	2820.000	42.63	-7.52	35.11	74.00	-38.89	peak

Test Mode:	BLE 1M	Frequency(MHz):	2404
Polarity:	Vertical	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1298.000	47.37	-13.65	33.72	74.00	-40.28	peak
2	1362.000	46.58	-13.35	33.23	74.00	-40.77	peak
3	1726.000	44.64	-11.97	32.67	74.00	-41.33	peak
4	1952.000	44.42	-11.22	33.20	74.00	-40.80	peak
5	2404.000	48.78	-8.99	39.79	/	/	fundamental
6	2856.000	43.23	-7.41	35.82	74.00	-38.18	peak

Test Mode:	BLE 1M	Frequency(MHz):	2440
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1600.000	46.36	-12.38	33.98	74.00	-40.02	peak
2	2080.000	45.68	-10.64	35.04	74.00	-38.96	peak
3	2300.000	45.84	-9.52	36.32	74.00	-37.68	peak
4	2440.000	47.51	-8.80	38.71	/	/	fundamental
5	2586.000	44.52	-8.24	36.28	74.00	-37.72	peak
6	2918.000	44.26	-7.23	37.03	74.00	-36.97	peak

Test Mode:	BLE 1M	Frequency(MHz):	2440
Polarity:	Vertical	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1410.000	46.65	-13.13	33.52	74.00	-40.48	peak
2	1760.000	46.55	-11.86	34.69	74.00	-39.31	peak
3	2024.000	45.66	-10.94	34.72	74.00	-39.28	peak
4	2348.000	46.61	-9.28	37.33	74.00	-36.67	peak
5	2440.000	46.22	-8.80	37.42	/	/	fundamental
6	2780.000	44.77	-7.64	37.13	74.00	-36.87	peak

Test Mode:	BLE 1M	Frequency(MHz):	2478
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1326.000	47.14	-13.52	33.62	74.00	-40.38	peak
2	1464.000	46.64	-12.87	33.77	74.00	-40.23	peak
3	2092.000	45.54	-10.59	34.95	74.00	-39.05	peak
4	2478.000	46.32	-8.61	37.71	/	/	fundamental
5	2672.000	43.20	-7.97	35.23	74.00	-38.77	peak
6	2954.000	43.30	-7.11	36.19	74.00	-37.81	peak


Test Mode:	BLE 1M	Frequency(MHz):	2478
Polarity:	Vertical	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1146.000	47.78	-14.35	33.43	74.00	-40.57	peak
2	1424.000	47.12	-13.06	34.06	74.00	-39.94	peak
3	2004.000	44.89	-11.04	33.85	74.00	-40.15	peak
4	2226.000	44.30	-9.89	34.41	74.00	-39.59	peak
5	2478.000	42.99	-8.61	34.38	/	/	fundamental
6	2774.000	43.64	-7.67	35.97	74.00	-38.03	peak




Test Mode:	BLE 1M	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1058.000	47.63	-14.76	32.87	74.00	-41.13	peak
2	1236.000	46.89	-13.94	32.95	74.00	-41.05	peak
3	1590.000	46.25	-12.41	33.84	74.00	-40.16	peak
4	1954.000	46.66	-11.21	35.45	74.00	-38.55	peak
5	2494.000	45.00	-8.52	36.48	74.00	-37.52	peak
6	2578.000	44.81	-8.26	36.55	74.00	-37.45	peak


Test Mode:	BLE 1M	Frequency(MHz):	2480
Polarity:	Vertical	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1472.000	46.97	-12.84	34.13	74.00	-39.87	peak
2	1722.000	45.88	-11.98	33.90	74.00	-40.10	peak
3	2020.000	45.05	-10.96	34.09	74.00	-39.91	peak
4	2470.000	44.86	-8.80	36.06	74.00	-37.94	peak
5	2588.000	44.21	-8.22	35.99	74.00	-38.01	peak
6	2956.000	44.33	-7.11	37.22	74.00	-36.78	peak


### 8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	44.64	-0.31	44.33	74.00	-29.67	peak
2	9180.000	37.52	10.56	48.08	74.00	-25.92	peak
3	10605.000	35.81	13.37	49.18	74.00	-24.82	peak
4	11385.000	33.32	16.17	49.49	74.00	-24.51	peak
5	13920.000	28.49	21.79	50.28	74.00	-23.72	peak
6	17925.000	25.30	25.25	50.55	74.00	-23.45	peak

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	48.45	-0.31	48.14	74.00	-25.86	peak
2	5385.000	43.89	0.76	44.65	74.00	-29.35	peak
3	9060.000	37.98	10.51	48.49	74.00	-25.51	peak
4	10785.000	35.03	14.01	49.04	74.00	-24.96	peak
5	13440.000	28.40	20.64	49.04	74.00	-24.96	peak
6	17985.000	23.13	25.60	48.73	74.00	-25.27	peak

Test Mode:	BLE 1M	Frequency(MHz):	2404
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	43.62	-0.31	43.31	74.00	-30.69	peak
2	7215.000	41.21	6.54	47.75	74.00	-26.25	peak
3	9255.000	37.79	10.59	48.38	74.00	-25.62	peak
4	12690.000	32.37	18.02	50.39	74.00	-23.61	peak
5	13695.000	28.78	21.31	50.09	74.00	-23.91	peak
6	17985.000	25.50	25.60	51.10	74.00	-22.90	peak

Test Mode:	BLE 1M	Frequency(MHz):	2404
Polarity:	Vertical	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	49.88	-0.31	49.57	74.00	-24.43	peak
2	7215.000	39.15	6.54	45.69	74.00	-28.31	peak
3	10575.000	36.40	13.25	49.65	74.00	-24.35	peak
4	12030.000	31.82	17.94	49.76	74.00	-24.24	peak
5	13680.000	28.32	21.29	49.61	74.00	-24.39	peak
6	17985.000	24.43	25.60	50.03	74.00	-23.97	peak

Test Mode:	BLE 1M	Frequency(MHz):	2440
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	46.78	-0.03	46.75	74.00	-27.25	peak
2	9300.000	37.89	10.61	48.50	74.00	-25.50	peak
3	11625.000	33.41	16.94	50.35	74.00	-23.65	peak
4	12705.000	32.80	18.06	50.86	74.00	-23.14	peak
5	13515.000	29.82	20.93	50.75	74.00	-23.25	peak
6	17955.000	24.38	25.42	49.80	74.00	-24.20	peak


Test Mode:	BLE 1M	Frequency(MHz):	2440
Polarity:	Vertical	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	47.21	-0.03	47.18	74.00	-26.82	peak
2	7320.000	38.95	6.46	45.41	74.00	-28.59	peak
3	9195.000	37.44	10.56	48.00	74.00	-26.00	peak
4	11430.000	33.40	16.34	49.74	74.00	-24.26	peak
5	13800.000	28.90	21.54	50.44	74.00	-23.56	peak
6	17970.000	25.28	25.51	50.79	74.00	-23.21	peak




Test Mode:	BLE 1M	Frequency(MHz):	2478
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	43.57	0.26	43.83	74.00	-30.17	peak
2	7425.000	40.69	6.39	47.08	74.00	-26.92	peak
3	10485.000	36.35	12.97	49.32	74.00	-24.68	peak
4	13050.000	31.19	18.93	50.12	74.00	-23.88	peak
5	13920.000	28.30	21.79	50.09	74.00	-23.91	peak
6	17925.000	25.57	25.25	50.82	74.00	-23.18	peak

Test Mode:	BLE 1M	Frequency(MHz):	2478
Polarity:	Vertical	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	41.15	0.26	41.41	74.00	-32.59	peak
2	7425.000	40.68	6.39	47.07	74.00	-26.93	peak
3	11520.000	33.70	16.65	50.35	74.00	-23.65	peak
4	12645.000	32.79	17.92	50.71	74.00	-23.29	peak
5	13920.000	28.84	21.79	50.63	74.00	-23.37	peak
6	17985.000	24.90	25.60	50.50	74.00	-23.50	peak

Test Mode:	BLE 1M	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	44.50	0.26	44.76	74.00	-29.24	peak
2	7740.000	39.36	6.32	45.68	74.00	-28.32	peak
3	9300.000	37.29	10.61	47.90	74.00	-26.10	peak
4	10755.000	35.18	13.90	49.08	74.00	-24.92	peak
5	13920.000	28.02	21.79	49.81	74.00	-24.19	peak
6	17940.000	23.80	25.34	49.14	74.00	-24.86	peak

Test Mode:	BLE 1M	Frequency(MHz):	2480
Polarity:	Vertical	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	42.98	0.26	43.24	74.00	-30.76	peak
2	7185.000	38.48	6.55	45.03	74.00	-28.97	peak
3	9135.000	36.92	10.55	47.47	74.00	-26.53	peak
4	10875.000	33.97	14.32	48.29	74.00	-25.71	peak
5	13215.000	29.04	19.65	48.69	74.00	-25.31	peak
6	17955.000	23.11	25.42	48.53	74.00	-25.47	peak

Test Mode:	BLE 2M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	49.36	-0.31	49.05	74.00	-24.95	peak
2	8040.000	38.89	6.34	45.23	74.00	-28.77	peak
3	9240.000	37.57	10.58	48.15	74.00	-25.85	peak
4	11055.000	35.27	14.96	50.23	74.00	-23.77	peak
5	13890.000	28.26	21.72	49.98	74.00	-24.02	peak
6	17985.000	24.62	25.60	50.22	74.00	-23.78	peak

Test Mode:	BLE 2M	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	45.71	-0.31	45.40	74.00	-28.60	peak
2	6630.000	38.72	4.86	43.58	74.00	-30.42	peak
3	9210.000	37.55	10.57	48.12	74.00	-25.88	peak
4	11835.000	32.22	17.51	49.73	74.00	-24.27	peak
5	13860.000	28.06	21.67	49.73	74.00	-24.27	peak
6	17940.000	23.44	25.34	48.78	74.00	-25.22	peak

Test Mode:	BLE 2M	Frequency(MHz):	2404
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	47.44	-0.31	47.13	74.00	-26.87	peak
2	7215.000	40.80	6.54	47.34	74.00	-26.66	peak
3	9135.000	37.66	10.55	48.21	74.00	-25.79	peak
4	11655.000	33.77	17.01	50.78	74.00	-23.22	peak
5	13620.000	29.48	21.15	50.63	74.00	-23.37	peak
6	18000.000	24.87	25.69	50.56	74.00	-23.44	peak


Test Mode:	BLE 2M	Frequency(MHz):	2404
Polarity:	Vertical	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	49.61	-0.31	49.30	74.00	-24.70	peak
2	9135.000	36.47	10.55	47.02	74.00	-26.98	peak
3	11280.000	33.99	15.80	49.79	74.00	-24.21	peak
4	11850.000	32.75	17.56	50.31	74.00	-23.69	peak
5	12600.000	32.65	17.82	50.47	74.00	-23.53	peak
6	17985.000	24.31	25.60	49.91	74.00	-24.09	peak




Test Mode:	BLE 2M	Frequency(MHz):	2440
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	46.94	-0.03	46.91	74.00	-27.09	peak
2	9060.000	37.61	10.51	48.12	74.00	-25.88	peak
3	11055.000	34.28	14.96	49.24	74.00	-24.76	peak
4	11730.000	33.02	17.22	50.24	74.00	-23.76	peak
5	13530.000	29.13	20.96	50.09	74.00	-23.91	peak
6	17985.000	24.65	25.60	50.25	74.00	-23.75	peak

Test Mode:	BLE 2M	Frequency(MHz):	2440
Polarity:	Vertical	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	46.51	-0.03	46.48	74.00	-27.52	peak
2	7320.000	38.55	6.46	45.01	74.00	-28.99	peak
3	9195.000	38.09	10.56	48.65	74.00	-25.35	peak
4	12000.000	32.25	17.96	50.21	74.00	-23.79	peak
5	13920.000	28.78	21.79	50.57	74.00	-23.43	peak
6	17775.000	25.97	24.36	50.33	74.00	-23.67	peak

Test Mode:	BLE 2M	Frequency(MHz):	2478
Polarity:	Horizontal	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4935.000	41.21	0.20	41.41	74.00	-32.59	peak
2	7425.000	41.86	6.39	48.25	74.00	-25.75	peak
3	9135.000	37.76	10.55	48.31	74.00	-25.69	peak
4	11715.000	33.02	17.19	50.21	74.00	-23.79	peak
5	13680.000	29.55	21.29	50.84	74.00	-23.16	peak
6	17970.000	24.90	25.51	50.41	74.00	-23.59	peak

Test Mode:	BLE 2M	Frequency(MHz):	2478
Polarity:	Vertical	Test Voltage:	DC 7.2 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	41.12	-0.03	41.09	74.00	-32.91	peak
2	7170.000	43.24	6.56	49.80	74.00	-24.20	peak
3	8910.000	37.70	9.82	47.52	74.00	-26.48	peak
4	11085.000	34.76	15.08	49.84	74.00	-24.16	peak
5	13875.000	28.89	21.70	50.59	74.00	-23.41	peak
6	17985.000	25.09	25.60	50.69	74.00	-23.31	peak

Test Mode:	BLE 2M	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	42.33	0.26	42.59	74.00	-31.41	peak
2	7875.000	38.59	6.31	44.90	74.00	-29.10	peak
3	9060.000	37.61	10.51	48.12	74.00	-25.88	peak
4	11760.000	32.63	17.31	49.94	74.00	-24.06	peak
5	12690.000	32.14	18.02	50.16	74.00	-23.84	peak
6	17985.000	23.79	25.60	49.39	74.00	-24.61	peak


Test Mode:	BLE 2M	Frequency(MHz):	2480
Polarity:	Vertical	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	41.69	0.26	41.95	74.00	-32.05	peak
2	7740.000	38.26	6.32	44.58	74.00	-29.42	peak
3	9375.000	38.25	10.64	48.89	74.00	-25.11	peak
4	11400.000	33.31	16.23	49.54	74.00	-24.46	peak
5	12675.000	32.03	17.99	50.02	74.00	-23.98	peak
6	17985.000	23.81	25.60	49.41	74.00	-24.59	peak


### 8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.01	77.22	-101.4	-24.18	47.6	-75.68	-3.9	-71.78	peak
2	0.0114	76.38	-101.4	-25.02	46.46	-76.52	-5.04	-71.48	peak
3	0.0171	72.38	-101.36	-28.98	42.94	-80.48	-8.56	-71.92	peak
4	0.0233	68.08	-101.36	-33.28	40.25	-84.78	-11.25	-73.53	peak
5	0.0376	63.75	-101.42	-37.67	36.1	-89.17	-15.4	-73.77	peak
6	0.0918	59.91	-101.73	-41.82	28.35	-93.32	-23.15	-70.17	peak


Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1595	78.36	-101.65	-23.29	23.55	-74.79	-27.95	-46.84	peak
2	0.1794	75.27	-101.68	-26.41	22.53	-77.91	-28.97	-48.94	peak
3	0.219	69.27	-101.75	-32.48	20.79	-83.98	-30.71	-53.27	peak
4	0.2442	67.03	-101.79	-34.76	19.85	-86.26	-31.65	-54.61	peak
5	0.3234	62.48	-101.88	-39.4	17.41	-90.9	-34.09	-56.81	peak
6	0.38	59.52	-101.94	-42.42	16.01	-93.92	-35.49	-58.43	peak




Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.5106	65.3	-62.07	3.23	33.44	-48.27	-18.06	-30.21	peak
2	0.6671	64.75	-62.1	2.65	31.12	-48.85	-20.38	-28.47	peak
3	0.8296	62.94	-62.17	0.77	29.23	-50.73	-22.27	-28.46	peak
4	2.0539	57.7	-61.81	-4.11	29.54	-55.61	-21.96	-33.65	peak
5	6.2445	54.63	-61.32	-6.69	29.54	-58.19	-21.96	-36.23	peak
6	11.8513	53.06	-60.88	-7.82	29.54	-59.32	-21.96	-37.36	peak


### 8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18576.000	49.22	-5.30	43.92	74.00	-30.08	peak
2	19392.000	49.62	-5.57	44.05	74.00	-29.95	peak
3	20216.000	50.02	-5.60	44.42	74.00	-29.58	peak
4	22160.000	48.08	-4.31	43.77	74.00	-30.23	peak
5	23744.000	48.15	-3.20	44.95	74.00	-29.05	peak
6	25072.000	46.67	-1.97	44.70	74.00	-29.30	peak


Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18640.000	49.11	-5.35	43.76	74.00	-30.24	peak
2	20240.000	49.82	-5.61	44.21	74.00	-29.79	peak
3	21544.000	48.26	-4.63	43.63	74.00	-30.37	peak
4	23360.000	46.60	-3.26	43.34	74.00	-30.66	peak
5	24568.000	46.10	-2.33	43.77	74.00	-30.23	peak
6	25728.000	44.61	-0.72	43.89	74.00	-30.11	peak


### 8.6. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	101.7800	54.86	-20.67	34.19	43.50	-9.31	QP
2	215.2700	56.01	-16.60	39.41	43.50	-4.09	QP
3	239.5200	53.66	-17.83	35.83	46.00	-10.17	QP
4	299.6600	50.20	-14.83	35.37	46.00	-10.63	QP
5	372.4100	44.55	-12.50	32.05	46.00	-13.95	QP
6	796.3000	41.37	-6.31	35.06	46.00	-10.94	QP

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 7.2 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	47.4600	50.27	-19.87	30.40	40.00	-9.60	QP
2	108.5700	50.54	-20.06	30.48	43.50	-13.02	QP
3	216.2400	47.04	-16.64	30.40	46.00	-15.60	QP
4	320.0300	43.04	-13.88	29.16	46.00	-16.84	QP
5	504.3300	45.67	-10.32	35.35	46.00	-10.65	QP
6	540.2199	42.61	-10.33	32.28	46.00	-13.72	QP

## 9. ANTENNA REQUIREMENT

### REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### DESCRIPTION

Pass


## 10. TEST DATA

### 10.1. APPENDIX A: DTS BANDWIDTH





#### 10.1.1. Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.62	2401.67	2402.29	≥0.5	PASS
		2404	0.70	2403.65	2404.35	≥0.5	PASS
		2440	0.72	2439.63	2440.35	≥0.5	PASS
		2478	0.68	2477.66	2478.34	≥0.5	PASS
		2480	0.62	2479.67	2480.29	≥0.5	PASS
BLE_2M	Ant1	2402	1.04	2401.47	2402.50	≥0.5	PASS
		2404	1.04	2403.47	2404.51	≥0.5	PASS
		2440	1.03	2439.47	2440.50	≥0.5	PASS
		2478	1.05	2477.46	2478.51	≥0.5	PASS
		2480	1.05	2479.46	2480.51	≥0.5	PASS


### 10.1.2. Test Graphs








## BLE\_2M\_Ant1\_2404




Date: 22 DEC 2023 09:27:20

## BLE\_2M\_Ant1\_2440



Date: 22 DEC 2023 09:29:27

## BLE\_2M\_Ant1\_2478



Date: 2 DEC 2023 10:44:19


## BLE\_2M\_Ant1\_2480


## 10.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH

### 10.2.1. Test Result


Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
BLE_1M	Ant1	2402	1.187	2401.4046	2402.5914	PASS
		2404	1.103	2403.4446	2404.5475	PASS
		2440	1.155	2439.4246	2440.5794	PASS
		2478	1.115	2477.4406	2478.5554	PASS
		2480	1.187	2479.4086	2480.5954	PASS
BLE_2M	Ant1	2402	2.086	2400.9491	2403.0350	PASS
		2404	2.126	2402.9371	2405.0629	PASS
		2440	2.154	2438.9171	2441.0709	PASS
		2478	2.118	2476.9451	2479.0629	PASS
		2480	2.062	2478.9650	2481.0270	PASS

### 10.2.2. Test Graphs







BLE\_1M\_Ant1\_2478




BLE\_1M\_Ant1\_2480



BLE\_2M\_Ant1\_2402





### 10.3. APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER

#### 10.3.1. Test Result

Test Mode	Antenna	Frequency[MHz]	Peak Result[dBm]	AVG Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-4.11	-6.95	≤30	PASS
		2404	3.31	1.61	≤30	PASS
		2440	3.03	1.63	≤30	PASS
		2478	3.24	1.62	≤30	PASS
		2480	-4.02	-6.59	≤30	PASS
BLE_2M	Ant1	2402	-4.10	-6.97	≤30	PASS
		2404	3.16	1.6	≤30	PASS
		2440	3.03	1.62	≤30	PASS
		2478	3.20	1.61	≤30	PASS
		2480	-3.99	-6.67	≤30	PASS


## 10.4. APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY


### 10.4.1. Test Result

Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-19.74	≤8.00	PASS
		2404	-11.00	≤8.00	PASS
		2440	-10.17	≤8.00	PASS
		2478	-10.10	≤8.00	PASS
		2480	-19.63	≤8.00	PASS
BLE_2M	Ant1	2402	-19.12	≤8.00	PASS
		2404	-12.29	≤8.00	PASS
		2440	-9.79	≤8.00	PASS
		2478	-10.99	≤8.00	PASS
		2480	-19.06	≤8.00	PASS




### 10.4.2. Test Graphs







BLE\_1M\_Ant1\_2478




BLE\_1M\_Ant1\_2480



BLE\_2M\_Ant1\_2402









## 10.5. APPENDIX E: BAND EDGE MEASUREMENTS


### 10.5.1. Test Result

Test Mode	Antenna	ChName	Frequency [MHz]	RefLevel [dBm]	Result [dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-7.14	-36.87	≤-27.14	PASS
			2404	2.19	-36.59	≤-17.81	PASS
		High	2478	2.11	-35.11	≤-17.89	PASS
			2480	-7.13	-35.49	≤-27.13	PASS
BLE_2M	Ant1	Low	2402	-7.20	-36.28	≤-27.2	PASS
			2404	2.13	-36.43	≤-17.87	PASS
		High	2478	2.13	-35.16	≤-17.87	PASS
			2480	-7.13	-35.5	≤-27.13	PASS

### 10.5.2. Test Graphs








## 10.6. APPENDIX F: CONDUCTED SPURIOUS EMISSION


### 10.6.1. Test Result

Test Mode	Antenna	Frequency [MHz]	FreqRange [MHz]	Result [dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	-7.17	---	PASS
			30~1000	-45.34	≤-27.17	PASS
			1000~26500	-39.77	≤-27.17	PASS
		2404	Reference	2.13	---	PASS
			30~1000	-45.49	≤-17.87	PASS
			1000~26500	-40.78	≤-17.87	PASS
		2440	Reference	1.87	---	PASS
			30~1000	-44.69	≤-18.13	PASS
			1000~26500	-39.98	≤-18.13	PASS
		2478	Reference	2.05	---	PASS
			30~1000	-44.96	≤-17.95	PASS
			1000~26500	-40.1	≤-17.95	PASS
		2480	Reference	-7.14	---	PASS
			30~1000	-45.39	≤-27.14	PASS
			1000~26500	-40.05	≤-27.14	PASS
BLE_2M	Ant1	2402	Reference	-7.21	---	PASS
			30~1000	-45.11	≤-27.21	PASS
			1000~26500	-40.25	≤-27.21	PASS
		2404	Reference	2.11	---	PASS
			30~1000	-44.96	≤-17.89	PASS
			1000~26500	-40.28	≤-17.89	PASS
		2440	Reference	1.84	---	PASS
			30~1000	-45.66	≤-18.16	PASS
			1000~26500	-40.24	≤-18.16	PASS
		2478	Reference	2.02	---	PASS
			30~1000	-45	≤-17.98	PASS
			1000~26500	-39.83	≤-17.98	PASS
		2480	Reference	-7.22	---	PASS
			30~1000	-45.59	≤-27.22	PASS
			1000~26500	-40.02	≤-27.22	PASS




### 10.6.2. Test Graphs







BLE\_1M\_Ant1\_2404\_0~Reference





BLE\_1M\_Ant1\_2404\_30~1000




BLE\_1M\_Ant1\_2404\_1000~26500









BLE\_1M\_Ant1\_2478\_30~1000





BLE\_1M\_Ant1\_2478\_1000~26500




BLE\_1M\_Ant1\_2480\_0~Reference









BLE\_2M\_Ant1\_2402\_1000~26500





BLE\_2M\_Ant1\_2404\_0~Reference




BLE\_2M\_Ant1\_2404\_30~1000









BLE\_2M\_Ant1\_2478\_0~Reference




BLE\_2M\_Ant1\_2478\_30~1000



BLE\_2M\_Ant1\_2478\_1000~26500







## 10.7. APPENDIX G: DUTY CYCLE

### 10.7.1. Test Result

Test Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
BLE_1M	0.42	0.62	0.6774	67.74	1.69	2.38	3
BLE_2M	1.10	1.85	0.5946	59.46	2.26	0.91	1

Note:


Duty Cycle Correction Factor= $10\log(1/x)$ .

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

### 10.7.2. Test Graphs



**END OF REPORT**