

**Test Plot 1#: FSK 2.4G\_Body Back\_Low Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**

Communication System: FSK\_2.4G; Frequency: 2408 MHz; Duty Cycle: 1:17.55

Medium parameters used:  $f = 2408 \text{ MHz}$ ;  $\sigma = 1.907 \text{ S/m}$ ;  $\epsilon_r = 54.397$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (71x161x1):** Interpolated grid:  $dx=1.200 \text{ mm}$ ,  $dy=1.200 \text{ mm}$

Maximum value of SAR (interpolated) = 0.679 W/kg


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 4.415 V/m; Power Drift = -0.20 dB

Peak SAR (extrapolated) = 0.833 W/kg

**SAR(1 g) = 0.369 W/kg; SAR(10 g) = 0.166 W/kg**

Maximum value of SAR (measured) = 0.647 W/kg



0 dB = 0.647 W/kg = -1.89 dBW/kg

**Test Plot 2#: FSK 2.4G\_Body Back\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**

Communication System: FSK\_2.4G; Frequency: 2442.5 MHz; Duty Cycle: 1:17.55

Medium parameters used:  $f = 2442.5$  MHz;  $\sigma = 1.937$  S/m;  $\epsilon_r = 54.023$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (71x161x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.13 W/kg


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.312 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 1.57 W/kg

**SAR(1 g) = 0.668 W/kg; SAR(10 g) = 0.284 W/kg**

Maximum value of SAR (measured) = 1.22 W/kg



0 dB = 1.22 W/kg = 0.86 dBW/kg

**Test Plot 3#: FSK 2.4G\_Body Back\_High Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**

Communication System: FSK\_2.4G; Frequency: 2475.5 MHz; Duty Cycle: 1:17.55

Medium parameters used:  $f = 2475.5$  MHz;  $\sigma = 1.951$  S/m;  $\epsilon_r = 53.646$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (71x161x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.635 W/kg


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.359 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.767 W/kg

**SAR(1 g) = 0.335 W/kg; SAR(10 g) = 0.147 W/kg**

Maximum value of SAR (measured) = 0.600 W/kg



0 dB = 0.600 W/kg = -2.22 dBW/kg

**Test Plot 4#: FSK 2.4G\_Body Back Antenna Fold\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**


Communication System: FSK\_2.4G; Frequency: 2442.5 MHz; Duty Cycle: 1:17.55  
 Medium parameters used:  $f = 2442.5 \text{ MHz}$ ;  $\sigma = 1.937 \text{ S/m}$ ;  $\epsilon_r = 54.023$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (71x101x1):** Interpolated grid:  $dx=1.200 \text{ mm}$ ,  $dy=1.200 \text{ mm}$   
 Maximum value of SAR (interpolated) = 0.0471 W/kg

**Zoom Scan (5x6x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 4.255 V/m; Power Drift = -0.15 dB  
 Peak SAR (extrapolated) = 0.0630 W/kg  
**SAR(1 g) = 0.034 W/kg; SAR(10 g) = 0.022 W/kg**  
 Maximum value of SAR (measured) = 0.0520 W/kg



0 dB = 0.0520 W/kg = -12.84 dBW/kg

**Test Plot 5#: FSK 2.4G\_Body Left\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**


Communication System: FSK\_2.4G; Frequency: 2442.5 MHz; Duty Cycle: 1:17.55  
 Medium parameters used:  $f = 2442.5 \text{ MHz}$ ;  $\sigma = 1.937 \text{ S/m}$ ;  $\epsilon_r = 54.023$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (141x61x1):** Interpolated grid:  $dx=1.200 \text{ mm}$ ,  $dy=1.200 \text{ mm}$   
 Maximum value of SAR (interpolated) = 0.0892 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 3.257 V/m; Power Drift = -0.15 dB  
 Peak SAR (extrapolated) = 0.108 W/kg  
**SAR(1 g) = 0.055 W/kg; SAR(10 g) = 0.036 W/kg**  
 Maximum value of SAR (measured) = 0.0839 W/kg



0 dB = 0.0839 W/kg = -10.76 dBW/kg

**Test Plot 6#: FSK 2.4G\_Body Left Antenna Fold\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**


Communication System: FSK\_2.4G; Frequency: 2442.5 MHz; Duty Cycle: 1:17.55  
 Medium parameters used:  $f = 2442.5 \text{ MHz}$ ;  $\sigma = 1.937 \text{ S/m}$ ;  $\epsilon_r = 54.023$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid:  $dx=1.200 \text{ mm}$ ,  $dy=1.200 \text{ mm}$   
 Maximum value of SAR (interpolated) = 0.0887 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 3.099 V/m; Power Drift = -0.13 dB  
 Peak SAR (extrapolated) = 0.106 W/kg  
**SAR(1 g) = 0.061 W/kg; SAR(10 g) = 0.040 W/kg**  
 Maximum value of SAR (measured) = 0.0872 W/kg



0 dB = 0.0872 W/kg = -10.59 dBW/kg

**Test Plot 7#: FSK 2.4G\_Body Right\_Middle Channel****DUT: Force Pro; Type: P1F1; Serial: 18032500220**

Communication System: FSK\_2.4G; Frequency: 2442.5 MHz; Duty Cycle: 1:17.55

Medium parameters used:  $f = 2442.5$  MHz;  $\sigma = 1.937$  S/m;  $\epsilon_r = 54.023$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (141x61x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.0941 W/kg


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.020 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.112 W/kg

**SAR(1 g) = 0.054 W/kg; SAR(10 g) = 0.034 W/kg**

Maximum value of SAR (measured) = 0.0860 W/kg



0 dB = 0.0860 W/kg = -10.66 dBW/kg

**Test Plot 8#: FSK 2.4G\_Body Right Antenna Fold\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**


Communication System: FSK\_2.4G; Frequency: 2442.5 MHz; Duty Cycle: 1:17.55  
 Medium parameters used:  $f = 2442.5 \text{ MHz}$ ;  $\sigma = 1.937 \text{ S/m}$ ;  $\epsilon_r = 54.023$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid:  $dx=1.200 \text{ mm}$ ,  $dy=1.200 \text{ mm}$   
 Maximum value of SAR (interpolated) = 0.0692 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 3.107 V/m; Power Drift = -0.06 dB  
 Peak SAR (extrapolated) = 0.0780 W/kg  
**SAR(1 g) = 0.048 W/kg; SAR(10 g) = 0.032 W/kg**  
 Maximum value of SAR (measured) = 0.0655 W/kg



0 dB = 0.0655 W/kg = -11.84 dBW/kg



**Test Plot 9#: FSK 2.4G\_Body Front\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**


Communication System: FSK\_2.4G; Frequency: 2442.5 MHz; Duty Cycle: 1:17.55  
 Medium parameters used:  $f = 2442.5$  MHz;  $\sigma = 1.937$  S/m;  $\epsilon_r = 54.023$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (71x161x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
 Maximum value of SAR (interpolated) = 0.0767 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Reference Value = 3.260 V/m; Power Drift = -0.15 dB  
 Peak SAR (extrapolated) = 0.0870 W/kg  
**SAR(1 g) = 0.051 W/kg; SAR(10 g) = 0.033 W/kg**  
 Maximum value of SAR (measured) = 0.0706 W/kg



0 dB = 0.0706 W/kg = -11.51 dBW/kg

**Test Plot 10#: FSK 5.8G\_Body Back\_Low Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**


Communication System: FSK\_5.8G; Frequency: 5729 MHz; Duty Cycle: 1:10.9  
 Medium parameters used:  $f = 5729 \text{ MHz}$ ;  $\sigma = 5.992 \text{ S/m}$ ;  $\epsilon_r = 49.549$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(4.35, 4.35, 4.35); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (71x191x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$   
 Maximum value of SAR (interpolated) = 0.902 W/kg

**Zoom Scan (7x7x6)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=2\text{mm}$   
 Reference Value = 4.479 V/m; Power Drift = -0.19 dB  
 Peak SAR (extrapolated) = 1.95 W/kg  
**SAR(1 g) = 0.344 W/kg; SAR(10 g) = 0.105 W/kg**  
 Maximum value of SAR (measured) = 1.01 W/kg



0 dB = 1.01 W/kg = 0.04 dBW/kg

**Test Plot 11#: FSK 5.8G\_Body Back\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**


Communication System: FSK\_5.8G; Frequency: 5775 MHz; Duty Cycle: 1:10.9  
 Medium parameters used:  $f = 5775 \text{ MHz}$ ;  $\sigma = 6.024 \text{ S/m}$ ;  $\epsilon_r = 49.432$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(4.35, 4.35, 4.35); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (71x191x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$   
 Maximum value of SAR (interpolated) = 0.739 W/kg

**Zoom Scan (7x7x6)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=2\text{mm}$   
 Reference Value = 3.457 V/m; Power Drift = -0.14 dB  
 Peak SAR (extrapolated) = 1.72 W/kg  
**SAR(1 g) = 0.324 W/kg; SAR(10 g) = 0.112 W/kg**  
 Maximum value of SAR (measured) = 0.872 W/kg



0 dB = 0.872 W/kg = -0.59 dBW/kg

**Test Plot 12#: FSK 5.8G\_Body Back\_High Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**

Communication System: FSK\_5.8G; Frequency: 5843 MHz; Duty Cycle: 1:10.9

Medium parameters used:  $f = 5843 \text{ MHz}$ ;  $\sigma = 6.234 \text{ S/m}$ ;  $\epsilon_r = 49.336$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(4.35, 4.35, 4.35); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (71x191x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$

Maximum value of SAR (interpolated) = 0.521 W/kg


**Zoom Scan (7x7x6)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=2\text{mm}$

Reference Value = 5.414 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.49 W/kg

**SAR(1 g) = 0.245 W/kg; SAR(10 g) = 0.086 W/kg**

Maximum value of SAR (measured) = 0.636 W/kg



0 dB = 0.636 W/kg = -1.97 dBW/kg

**Test Plot 13#: FSK 5.8G\_Body Back Antenna Fold\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**

Communication System: FSK\_5.8G; Frequency: 5775 MHz; Duty Cycle: 1:10.9

Medium parameters used:  $f = 5775 \text{ MHz}$ ;  $\sigma = 6.024 \text{ S/m}$ ;  $\epsilon_r = 49.432$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(4.35, 4.35, 4.35); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (71x111x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$

Maximum value of SAR (interpolated) = 0.0610 W/kg


**Zoom Scan (7x7x6)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=2\text{mm}$

Reference Value = 2.368 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.0960 W/kg

**SAR(1 g) = 0.035 W/kg; SAR(10 g) = 0.032 W/kg**

Maximum value of SAR (measured) = 0.0472 W/kg



$0 \text{ dB} = 0.0472 \text{ W/kg} = -13.26 \text{ dBW/kg}$

**Test Plot 14#: FSK 5.8G\_Body Left\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**


Communication System: FSK\_5.8G; Frequency: 5775 MHz; Duty Cycle: 1:10.9  
 Medium parameters used:  $f = 5775 \text{ MHz}$ ;  $\sigma = 6.024 \text{ S/m}$ ;  $\epsilon_r = 49.432$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(4.35, 4.35, 4.35); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (171x61x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$   
 Maximum value of SAR (interpolated) = 0.128 W/kg

**Zoom Scan (8x8x6)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=2\text{mm}$   
 Reference Value = 2.920 V/m; Power Drift = 0.09 dB  
 Peak SAR (extrapolated) = 0.292 W/kg  
**SAR(1 g) = 0.074 W/kg; SAR(10 g) = 0.048 W/kg**  
 Maximum value of SAR (measured) = 0.131 W/kg



0 dB = 0.131 W/kg = -8.83 dBW/kg

**Test Plot 15#: FSK 5.8G\_Body Left Antenna Fold\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**


Communication System: FSK\_5.8G; Frequency: 5775 MHz; Duty Cycle: 1:10.9  
 Medium parameters used:  $f = 5775 \text{ MHz}$ ;  $\sigma = 6.024 \text{ S/m}$ ;  $\epsilon_r = 49.432$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(4.35, 4.35, 4.35); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x131x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$   
 Maximum value of SAR (interpolated) = 0.147 W/kg

**Zoom Scan (7x7x6)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=2\text{mm}$   
 Reference Value = 2.019 V/m; Power Drift = 0.16 dB  
 Peak SAR (extrapolated) = 0.250 W/kg  
**SAR(1 g) = 0.076 W/kg; SAR(10 g) = 0.050 W/kg**  
 Maximum value of SAR (measured) = 0.138 W/kg



0 dB = 0.138 W/kg = -8.60 dBW/kg

**Test Plot 16#: FSK 5.8G\_Body Right\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**


Communication System: FSK\_5.8G; Frequency: 5775 MHz; Duty Cycle: 1:10.9  
 Medium parameters used:  $f = 5775 \text{ MHz}$ ;  $\sigma = 6.024 \text{ S/m}$ ;  $\epsilon_r = 49.432$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(4.35, 4.35, 4.35); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (171x61x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$   
 Maximum value of SAR (interpolated) = 0.126 W/kg

**Zoom Scan (7x7x6)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=2\text{mm}$   
 Reference Value = 2.748 V/m; Power Drift = -0.19 dB  
 Peak SAR (extrapolated) = 0.280 W/kg  
**SAR(1 g) = 0.070 W/kg; SAR(10 g) = 0.045 W/kg**  
 Maximum value of SAR (measured) = 0.123 W/kg



0 dB = 0.123 W/kg = -9.10 dBW/kg



**Test Plot 17#: FSK 5.8G\_Body Right Antenna Fold\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**


Communication System: FSK\_5.8G; Frequency: 5775 MHz; Duty Cycle: 1:10.9  
 Medium parameters used:  $f = 5775 \text{ MHz}$ ;  $\sigma = 6.024 \text{ S/m}$ ;  $\epsilon_r = 49.432$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(4.35, 4.35, 4.35); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x131x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$   
 Maximum value of SAR (interpolated) = 0.159 W/kg

**Zoom Scan (7x7x6)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=2\text{mm}$   
 Reference Value = 2.334 V/m; Power Drift = -0.19 dB  
 Peak SAR (extrapolated) = 0.283 W/kg  
**SAR(1 g) = 0.081 W/kg; SAR(10 g) = 0.051 W/kg**  
 Maximum value of SAR (measured) = 0.149 W/kg



0 dB = 0.149 W/kg = -8.27 dBW/kg

**Test Plot 18#: FSK 5.8G\_Body Front\_Middle Channel**

**DUT: Force Pro; Type: P1F1; Serial: 18032500220**

Communication System: FSK\_5.8G; Frequency: 5775 MHz; Duty Cycle: 1:10.9

Medium parameters used:  $f = 5775 \text{ MHz}$ ;  $\sigma = 6.024 \text{ S/m}$ ;  $\epsilon_r = 49.432$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(4.35, 4.35, 4.35); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (71x191x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$

Maximum value of SAR (interpolated) = 0.172 W/kg


**Zoom Scan (7x7x6)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=2\text{mm}$

Reference Value = 3.763 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.315 W/kg

**SAR(1 g) = 0.087 W/kg; SAR(10 g) = 0.052 W/kg**

Maximum value of SAR (measured) = 0.166 W/kg



0 dB = 0.166 W/kg = -7.80 dBW/kg