

# TEST REPORT

**Product Name** : Body Composition Scale  
**Brand Mark** : NA  
**Model No.** : CS20M  
**Report Number** : BLA-EMC-202103-A9101  
**Date of Sample Receipt** : 2021/3/24  
**Date of Test** : 2021/3/24 to 2021/4/23  
**Date of Issue** : 2021/4/23  
**FCC ID** : 2ANDX-CS20X1  
**Test Standard** : 47 CFR Part 15, Subpart C 15.247  
**Test Result** : Pass

Prepared for:

**Shenzhen Yolanda Technology Co., Ltd**  
**Room 201, Jinfulai Building, No.49-1, Dabao Road, Dalang Area, Xinan Street, Baoan, Shenzhen**

Prepared by:

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**  
**Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China**  
**TEL: +86-755-23059481**

Compiled by:

Sven

Review by:

Sweet. Liang

Approved by:

Jamen Li

Date:

2021/4/23



## REPORT REVISE RECORD

Version No.	Date	Description
00	2021/4/23	Original

BlueAsia

## TABLE OF CONTENTS

<b>1</b>	<b>TEST SUMMARY .....</b>	<b>5</b>
<b>2</b>	<b>GENERAL INFORMATION .....</b>	<b>6</b>
<b>3</b>	<b>GENERAL DESCRIPTION OF E.U.T. ....</b>	<b>6</b>
<b>4</b>	<b>TEST ENVIRONMENT .....</b>	<b>7</b>
<b>5</b>	<b>TEST MODE .....</b>	<b>7</b>
<b>6</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>7</b>
<b>7</b>	<b>DESCRIPTION OF SUPPORT UNIT.....</b>	<b>8</b>
<b>8</b>	<b>LABORATORY LOCATION.....</b>	<b>8</b>
<b>9</b>	<b>TEST INSTRUMENTS LIST .....</b>	<b>9</b>
<b>1</b>	<b>CONDUCTED BAND EDGES MEASUREMENT.....</b>	<b>12</b>
1.1	LIMITS .....	12
1.2	BLOCK DIAGRAM OF TEST SETUP .....	12
1.3	TEST DATA .....	13
<b>2</b>	<b>RADIATED SPURIOUS EMISSIONS.....</b>	<b>14</b>
2.1	LIMITS .....	14
2.2	BLOCK DIAGRAM OF TEST SETUP .....	15
2.3	PROCEDURE .....	15
2.4	TEST DATA .....	17
<b>3</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>25</b>
3.1	CONCLUSION .....	25
<b>4</b>	<b>RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....</b>	<b>26</b>
4.1	LIMITS .....	26
4.2	BLOCK DIAGRAM OF TEST SETUP .....	27
4.3	PROCEDURE .....	27
4.4	TEST DATA .....	29
<b>5</b>	<b>CONDUCTED SPURIOUS EMISSIONS .....</b>	<b>33</b>
5.1	LIMITS .....	33
5.2	BLOCK DIAGRAM OF TEST SETUP .....	33
5.3	TEST DATA .....	34

<b>6</b>	<b>POWER SPECTRUM DENSITY.....</b>	<b>35</b>
6.1	LIMITS .....	35
6.2	BLOCK DIAGRAM OF TEST SETUP .....	35
6.3	TEST DATA .....	35
<b>7</b>	<b>CONDUCTED PEAK OUTPUT POWER .....</b>	<b>36</b>
7.1	LIMITS .....	36
7.2	BLOCK DIAGRAM OF TEST SETUP .....	36
7.3	TEST DATA .....	37
<b>8</b>	<b>MINIMUM 6DB BANDWIDTH .....</b>	<b>38</b>
8.1	LIMITS .....	38
8.2	BLOCK DIAGRAM OF TEST SETUP .....	38
8.3	TEST DATA .....	38
<b>10</b>	<b>APPENDIX.....</b>	<b>39</b>
	<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>	<b>51</b>
	<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>52</b>

## 1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass

## 2 GENERAL INFORMATION

<b>Applicant</b>	Shenzhen Yolanda Technology Co., Ltd
<b>Address</b>	Room 201,Jinfulai Building, No.49-1, Dabao Road,Dalang Area,Xinan Street,Baoan, Shenzhen
<b>Manufacturer</b>	Shenzhen Yolanda Technology Co., Ltd
<b>Address</b>	Room 201,Jinfulai Building, No.49-1, Dabao Road,Dalang Area,Xinan Street,Baoan, Shenzhen
<b>Product Name</b>	Body Composition Scale
<b>Test Model No.</b>	CS20M
<b>Exension Model</b>	CS20A,CS20C1,CS20C2,CS20C3,CS10,CS10C,CS20B,CS20C,CS20D,CS20E,CS20F,CS20G, CS20H, CS20I, CS20J, CS20K, CS20X1,CS20X2, CS20X3, CS20L, CS20M,CS20N,CS20P,CS20M1,CS20M2,CS20M3,CS20W,CS20W1,CS20Q,CS20Q1US20E,CS20C1,FF20G,MF-BS02,ES-CS20M,ES-CS20C,HSF-1,SC101-Black,SC101-White,FF30G,BS412,BS414,BS416,BS418,BS600,BS602,BS650,BS652,US30HRC,US20M,US20E,US10C,sensit,sensit-mini,UNOTEC XCALE II,FitScale W5 BT, ABYON20N, GOLDEN WHEAT, ENERGY OATS, AS-01A, BCA-130, UNOTEC XCALE II, LC10, ES-CS20M, ES-CS20M-W, ES-26M-W, ES-26M-B, ES-28ML, ES-30M, ES-24M, ES-26BB-B, ES-26P3, ES-32MD, ES-BR001, ES-BR003, FT-24D, FT-24D-W, FT-26BB-B, FT-26H-B, FT-28WBL, MAES-28P1, ES-26P1, ES-26P2, ES-WBE28,ES-WBE28W, ES-26R-W,ES-26R-B, ES-26R-MG,FT-26R-W,FT-26R-B,FT-30D,NK-BTBASCULA, WS1, B11, B12, B14, B15, JL-001, 31400, 31401, 31402, 31403, 31406, 1901.1902, HGSS-20, NX4501, GB10W, MYIA20C, A017-SC 01, A017-SCPRO01, S-5, IGBWS-864, 9BBF001, CS20H, H5010, Savvy, Savvy plus, Slinky, Slinky Lite, ESF24, ESF17, ESF28, ESF38, ESF14, ESF18, Sophie, WMP-BTS1U, SECONDNATURE

## 3 GENERAL DESCRIPTION OF E.U.T.

<b>Hardware Version</b>	COM201110
<b>Software Version</b>	0101
<b>Operation Frequency:</b>	2402MHz-2480MHz
<b>Modulation Type:</b>	GFSK
<b>Channel Spacing:</b>	2MHz
<b>Number of Channels:</b>	40
<b>Antenna Type:</b>	PCB Antenna
<b>Antenna Gain:</b>	0.5dBi(Provided by customer)

#### 4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	+25°C	3.0Vdc

#### 5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
TX	Keep the EUT in transmitting mode
TX Low channel	Keep the EUT in continuously transmitting mode in low channel
TX middle channel	Keep the EUT in continuously transmitting mode in middle channel
TX high channel	Keep the EUT in continuously transmitting mode in high channel
Remark: Only the data of the worst mode would be recorded in this report.	

#### 6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

Parameter	Expanded Uncertainty (Confidence of 95%)
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %
Radiated Emission (30MHz ~ 1000MHz)	±4.35 dB
Radiated Emission (1GHz ~ 18GHz)	±4.44 dB

## 7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	HASEE	K610D	--	--

**Note:**

--" means no any support device during testing.

## 8 LABORATORY LOCATION

All tests were performed at:  
BlueAsia of Technical Services(Shenzhen) Co., Ltd.  
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China  
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673  
No tests were sub-contracted.



## 9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Band Edges Measurement					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Conducted Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of Power Spectrum Density**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of Conducted Peak Output Power**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of Minimum 6dB Bandwidth**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11


## 1 CONDUCTED BAND EDGES MEASUREMENT

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Sven
<b>Temperature</b>	25°C
<b>Humidity</b>	52%

### 1.1 LIMITS

<b>Limit:</b>	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

### 1.2 BLOCK DIAGRAM OF TEST SETUP



### 1.3 TEST DATA

**Pass: Please Refer To Appendix: For Details**

BlueAsia

## 2 RADIATED SPURIOUS EMISSIONS


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.4,6.5,6.6
<b>Test Mode (Pre-Scan)</b>	TX;TX Low channel;TX middle channel;TX high channel
<b>Test Mode (Final Test)</b>	TX;TX Low channel;TX middle channel;TX high channel
<b>Tester</b>	Sven
<b>Temperature</b>	25℃
<b>Humidity</b>	52%

### 2.1 LIMITS

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 2.2 BLOCK DIAGRAM OF TEST SETUP



## 2.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter ,and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



## 2.4 TEST DATA

[TestMode: TX Low channel]; [Polarity: Horizontal]




\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX Low channel]; [Polarity: Vertical]

### Radiated Emission Measurement



Site Limit: FCC Part15 (PK) Polarization: **Vertical** Temperature:  
EUT: Body Composition Scale Power: Humidity: %  
M/N: CS20M Distance: 3m  
Mode: TX-L  
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		4804.000	40.97	3.71	44.68	74.00	-29.32	peak		
2		7206.000	40.52	5.96	46.48	74.00	-27.52	peak		
3	*	9608.000	38.99	9.29	48.28	74.00	-25.72	peak		


\*:Maximum data x:Over limit !:over margin

〈Reference Only

**Test Result: Pass**

[TestMode: TX middle channel]; [Polarity: Horizontal]

### Radiated Emission Measurement



Site Limit: FCC Part15 (PK) Polarization: **Horizontal** Temperature:  
EUT: Body Composition Scale Power: Humidity: %  
M/N: CS20M Distance: 3m  
Mode: TX-M  
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		4882.000	42.02	3.36	45.38	74.00	-28.62	peak		
2		7323.000	39.72	6.43	46.15	74.00	-27.85	peak		
3	*	9764.000	38.71	9.63	48.34	74.00	-25.66	peak		


\*:Maximum data x:Over limit !:over margin

〈Reference Only

**Test Result: Pass**

[TestMode: TX middle channel]; [Polarity: Vertical]

### Radiated Emission Measurement



Site Limit: FCC Part15 (PK) Polarization: **Vertical** Temperature:   
EUT: Body Composition Scale Power: Humidity: %   
M/N: CS20M Distance: 3m   
Mode: TX-M   
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		4884.000	41.81	3.34	45.15	74.00	-28.85	peak		
2		7323.000	40.01	6.43	46.44	74.00	-27.56	peak		
3	*	9764.000	38.54	9.63	48.17	74.00	-25.83	peak		


\*:Maximum data x:Over limit !:over margin

〈Reference Only

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Horizontal]

### Radiated Emission Measurement



Site Limit: FCC Part15 (PK) Polarization: **Horizontal** Temperature:  
EUT: Body Composition Scale Power: Humidity: %  
M/N: CS20M Distance: 3m  
Mode: TX-H  
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		4960.000	40.77	3.75	44.52	74.00	-29.48	peak		
2		7440.000	40.04	6.86	46.90	74.00	-27.10	peak		
3	*	9920.000	37.83	10.16	47.99	74.00	-26.01	peak		


\*:Maximum data x:Over limit !:over margin

〈Reference Only

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Vertical]

### Radiated Emission Measurement



Site Limit: FCC Part15 (PK) Polarization: **Vertical** Temperature:  
EUT: Body Composition Scale Power: Humidity: %  
M/N: CS20M Distance: 3m  
Mode: TX-H  
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		4960.000	40.89	3.75	44.64	74.00	-29.36	peak		
2		7440.000	41.25	6.86	48.11	74.00	-25.89	peak		
3	*	9920.000	38.06	10.16	48.22	74.00	-25.78	peak		

\*:Maximum data x:Over limit !:over margin

〈Reference Only

**Test Result: Pass**

[TestMode: TX]; [Polarity: Horizontal]


**Radiated Emission Measurement**

File :RE  
72.0 dBuV/m

Data :#18

Date: 2021/4/20 星期

Time: 下午 4:25:22



Site

Limit: FCC Part15 Class B

EUT: Body Composition Scale

M/N: CS20M

Mode: TX

Note:

Polarization: **Horizontal**

Power:

Distance: 3m

Temperature:

Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		54.6429	6.16	23.63	29.79	40.00	-10.21	QP		
2		83.2298	3.68	19.52	23.20	40.00	-16.80	QP		
3		148.4410	1.46	23.32	24.78	43.50	-18.72	QP		
4		316.5890	-0.81	24.49	23.68	46.00	-22.32	QP		
5		574.6258	0.03	30.76	30.79	46.00	-15.21	QP		
6	*	839.1818	1.29	34.83	36.12	46.00	-9.88	QP		

\*:Maximum data x:Over limit !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX]; [Polarity: Vertical]

### Radiated Emission Measurement


File :RE

Data :#17

Date: 2021/4/20 星期

Time: 下午 4:24:24

72.0 dBuV/m



Site

Limit: FCC Part15 Class B

EUT: Body Composition Scale

M/N: CS20M

Mode: TX

Note:

Polarization: **Vertical**

Temperature:

Power:

Humidity: %

Distance: 3m

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		48.8429	6.63	23.81	30.44	40.00	-9.56	QP		
2		84.7019	11.02	19.44	30.46	40.00	-9.54	QP		
3		116.1321	2.89	22.16	25.05	43.50	-18.45	QP		
4		148.4410	3.53	23.32	26.85	43.50	-16.65	QP		
5		432.5457	2.05	27.92	29.97	46.00	-16.03	QP		
6	*	649.6597	4.59	32.11	36.70	46.00	-9.30	QP		

\*:Maximum data x:Over limit !:over margin

&lt;Reference Only

**Test Result: Pass**



### 3 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


#### 3.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.5dBi.



#### 4 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.10.5
<b>Test Mode (Pre-Scan)</b>	TX Low channel;TX high channel
<b>Test Mode (Final Test)</b>	TX Low channel;TX high channel
<b>Tester</b>	Sven
<b>Temperature</b>	25°C
<b>Humidity</b>	52%

##### 4.1 LIMITS

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 4.2 BLOCK DIAGRAM OF TEST SETUP



## 4.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1:  $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

#### 4.4 TEST DATA

[TestMode: TX Low channel]; [Polarity: Horizontal]

##### Radiated Emission Measurement



Site Polarization: **Horizontal** Temperature:  
Limit: FCC Part15 (PK) Power: Humidity: %  
EUT: Body Composition Scale Distance: 3m  
M/N: CS20M  
Mode: TX-L  
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2310.000	44.70	-4.61	40.09	74.00	-33.91	peak		Comment
2	*	2390.000	46.45	-4.27	42.18	74.00	-31.82	peak		


\*:Maximum data x:Over limit !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX Low channel]; [Polarity: Vertical]

### Radiated Emission Measurement



Site Limit: FCC Part15 (PK) Polarization: **Vertical** Temperature:   
EUT: Body Composition Scale Power: Humidity: %   
M/N: CS20M Distance: 3m   
Mode: TX-L   
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		2310.000	45.25	-4.61	40.64	74.00	-33.36	peak		
2	*	2390.000	46.55	-4.27	42.28	74.00	-31.72	peak		


\*:Maximum data x:Over limit !:over margin

〈Reference Only

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Horizontal]

### Radiated Emission Measurement



Site Limit: FCC Part15 (PK) Polarization: **Horizontal** Temperature:   
EUT: Body Composition Scale Power: Humidity: %   
M/N: CS20M Distance: 3m   
Mode: BLE-TX-M   
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	*	2483.500	52.84	-3.84	49.00	74.00	-25.00	peak		
2		2500.000	44.63	-3.78	40.85	74.00	-33.15	peak		
3		2500.000	44.63	-3.78	40.85	74.00	-33.15	peak		


\*:Maximum data x:Over limit !:over margin

〈Reference Only

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Vertical]

### Radiated Emission Measurement



Site Limit: FCC Part15 (PK) Polarization: **Vertical** Temperature:  
EUT: Body Composition Scale Power: Humidity: %  
M/N: CS20M Distance: 3m  
Mode: BLE-TX-M  
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	*	2483.500	47.73	-3.84	43.89	74.00	-30.11	peak		
2		2500.000	43.15	-3.78	39.37	74.00	-34.63	peak		

\*:Maximum data x:Over limit !:over margin

〈Reference Only

**Test Result: Pass**




## 5 CONDUCTED SPURIOUS EMISSIONS

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Sven
<b>Temperature</b>	25°C
<b>Humidity</b>	52%

### 5.1 LIMITS

<b>Limit:</b>	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

### 5.2 BLOCK DIAGRAM OF TEST SETUP



### 5.3 TEST DATA

**Pass: Please Refer To Appendix: For Details**

BlueAsia


## 6 POWER SPECTRUM DENSITY

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.10.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

### 6.1 LIMITS

<b>Limit:</b>	$\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission
---------------	--

### 6.2 BLOCK DIAGRAM OF TEST SETUP



### 6.3 TEST DATA

<b>Pass: Please Refer To Appendix: For Details</b>
--


## 7 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

### 7.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq \text{hopping channels} < 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

### 7.2 BLOCK DIAGRAM OF TEST SETUP



### 7.3 TEST DATA

**Pass: Please Refer To Appendix: For Details**

BlueAsia


## 8 MINIMUM 6DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

### 8.1 LIMITS

<b>Limit:</b>	$\geq 500$ kHz
---------------	----------------

### 8.2 BLOCK DIAGRAM OF TEST SETUP



### 8.3 TEST DATA


**Pass: Please Refer To Appendix: For Details**

## 10 APPENDIX


### Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	0.947	0.947	30	Pass
NVNT	BLE 1M	2442	Ant1	0.568	0.568	30	Pass
NVNT	BLE 1M	2480	Ant1	0.018	0.018	30	Pass


Power NVNT BLE 1M 2402MHz Ant1



Power NVNT BLE 1M 2442MHz Ant1



Power NVNT BLE 1M 2480MHz Ant1







### -6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.673	0.5	Pass
NVNT	BLE 1M	2442	Ant1	0.676	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.689	0.5	Pass


### -6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



### -6dB Bandwidth NVNT BLE 1M 2442MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1




### Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1M	2402	Ant1	1.023762124
NVNT	BLE 1M	2442	Ant1	1.019181332
NVNT	BLE 1M	2480	Ant1	1.022867069


### OBW NVNT BLE 1M 2402MHz Ant1



### OBW NVNT BLE 1M 2442MHz Ant1




OBW NVNT BLE 1M 2480MHz Ant1




### Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	0.835	8	Pass
NVNT	BLE 1M	2442	Ant1	0.4	8	Pass
NVNT	BLE 1M	2480	Ant1	-0.708	8	Pass


PSD NVNT BLE 1M 2402MHz Ant1



PSD NVNT BLE 1M 2442MHz Ant1




PSD NVNT BLE 1M 2480MHz Ant1




### Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-56.1	-30	Pass
NVNT	BLE 1M	2480	Ant1	-54.56	-30	Pass

### Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



### Band Edge NVNT BLE 1M 2480MHz Ant1 Emission







### Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	11.32	-30	Fail
NVNT	BLE 1M	2442	Ant1	-46.13	-30	Pass
NVNT	BLE 1M	2480	Ant1	-45.76	-30	Pass


#### Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



#### Tx. Spurious NVNT BLE 1M 2442MHz Ant1 Emission




### Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission




## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### Radiated Spurious Emissions




## APPENDIX B: PHOTOGRAPHS OF EUT









----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.