



Maximum Permissible Exposure (MPE)

EUT INFORMATION

FCC ID	2ANH6-SportDV
EUT	STM Sport DV
Frequency band (Operating)	2.412 GHz ~ 2.462 GHz
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power	18.09 dBm (64.473 mW)
Antenna gain (Max)	4.97 dBi

TEST RESULT

The modular use shall be at least 20cm distance away from human body.

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \cdot P \cdot G}}{d}$$

$$\text{Power Density} = Pd \text{ (mW/cm}^2\text{)} = E^2 / 3770$$

Combine these two formulas can be changed to

$$Pd = (30 \cdot P \cdot G) / (3770 \cdot d^2)$$

Note:

1. "E" means Electric field (V/m).
2. "P" means Peak RF output power (W).
3. "G" means EUT Antenna numeric gain (numeric).
4. "d" means the minimum mobile separation distance is 0.2m between radiator and human body.



Modulation Type	Channel	Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
802.11b	01	2412	17.23	0.033010	<1
	06	2437	17.74	0.037124	<1
	11	2462	18.09	0.040239	<1
802.11g	01	2412	16.31	0.026709	<1
	06	2437	16.76	0.029624	<1
	11	2462	17.20	0.032783	<1
802.11n HT20	01	2412	16.65	0.028883	<1
	06	2437	17.01	0.031380	<1
	11	2462	17.36	0.034013	<1
802.11n HT40	03	2422	15.83	0.023914	<1
	06	2437	16.19	0.025981	<1
	09	2452	16.44	0.027520	<1

Tested By:

Reviewed by:

Nov. 02, 2017

Nov. 02, 2017

Date

Bell Wei/ Engineer

Date

Mike Lee / Manager
Designation Number: TW1083