

■Report No.: DDT-R18051702-1E3

■Issued Date: Jun. 29, 2018

# RF EXPOSURE REPORT

## **FOR**

Applicant		MODERN ELECTRONICS FACTORY LIMITED
Address	•	FLAT/RM C, BLK 4, 10/F., KWUN TONG INDUSTRIAL CENTRE, 436-446 KWUN TONG ROAD, KWUN TONG, HONG KONG
Equipment under Test		PORTABLE BOOMBOX WITH BLUETOOTH, CD PLAYER AND FM RADIO
Model No.		MET1401, SB2145, SB2145B, SB2145S, SB2145XXXXX (where XXXXX denote any printable characters in the ASCII Standard Character Table to represent variances in cosmetics or buyers), MD1401
Trade Mark	•	MET, Studebaker, Modern
FCC ID	••	2ANH76961401
Manufacturer		MODERN ELECTRONICS FACTORY LIMITED
Address	• •	FLAT/RM C, BLK 4, 10/F., KWUN TONG INDUSTRIAL CENTRE, 436-446 KWUN TONG ROAD, KWUN TONG, HONG KONG

# Issued By: Dongguan Dongdian Testing Service Co., Ltd.

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

**Tel:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, http://www.dgddt.com



## **TABLE OF CONTENTS**

	Test report declares	.3
1.	General information	. 5
1.1.	Description of Equipment	
	Assess laboratory	
	RF Exposure evaluation for FCC	

## **TEST REPORT DECLARE**

Applicant	:	: MODERN ELECTRONICS FACTORY LIMITED	
Address	:	FLAT/RM C, BLK 4, 10/F., KWUN TONG INDUSTRIAL CENTRE, 436-446 KWUN TONG ROAD, KWUN TONG, HONG KONG	
Equipment under Test : PORTABLE BOOMBOX WITH BLUETOOTH, CD PLAYER A		PORTABLE BOOMBOX WITH BLUETOOTH, CD PLAYER AND FM RADIO	
Model No.	:	MET1401, SB2145, SB2145B, SB2145S, SB2145XXXXX (where XXXXX denote any printable characters in the ASCII Standard Character Table to represent variances in cosmetics or buyers), MD1401	
Trade mark	:	: MET, Studebaker, Modern	
Manufacturer	:	: MODERN ELECTRONICS FACTORY LIMITED	
Address	:	. FLAT/RM C, BLK 4, 10/F., KWUN TONG INDUSTRIAL CENTRE, 436-446 KWUN TONG ROAD, KWUN TONG, HONG KONG	

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

#### We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

#### After evaluation, our opinion is that the equipment In Accordance with above standard.

	<b>.</b>	<u> </u>	
Report No:	DDT-R18051702-1E3		
Date of Receipt:	Jun. 12, 2018	Date of Test:	Jun. 12, 2018 ~ Jun. 29, 2018

Prepared By:	Approved By:		
Sam Li/Engineer	Damon Hu/FMC Manager		

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

# **Revision history**

Rev.	Revisions	Issue Date	Revised By
	Initial issue	Jun. 29, 2018	

### 1. General information

### 1.1. Description of Equipment

EUT* Name	:	PORTABLE BOOMBOX WITH BLUETOOTH, CD PLAYER AND FM RADIO	
Model Number	:	MET1401, SB2145, SB2145B, SB2145S, SB2145XXXXX (where XXXXX denote any printable characters in the ASCII Standard Character Table to represent variances in cosmetics or buyers), MD1401	
Difference of model number		All models are identical, only the color and brand are different; therefore, the test performed on the model MET1401.	
EUT function description	:	Please reference user manual of this device	
Power supply	:	DC 12V/1.5A from external AC adapter	
Radio Specification	:	: Bluetooth V4.2	
Operation frequency	:	: 2402MHz -2480MHz	
Modulation	:	GFSK, π/4-DQPSK, 8DPSK	
Data rate	:	1Mbps, 2Mbps, 3Mbps	
Antenna Type	:	: Integral PCB antenna, maximum PK gain: -0.68dBi	
Sample Type	:	: Series production	

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,

Guangdong Province, China, 523808

Tel: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com

## 2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,

mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Worse case is as below: [2402MHz, -12.02dBm (0.06mW) output power]

 $(0.06/5) \cdot [\sqrt{2.402(GHz)}] = 0.0186 < 3.0 \text{ for } 1-g \text{ SAR}$ 

Then SAR evaluation is not required

#### **END OF REPORT**