

## FCC CERTIFICATION TEST REPORT

### FOR

<b>Applicant</b>	:	MODERN ELECTRONICS FACTORY LIMITED
<b>Address</b>	:	FLAT/RM C, BLK 4, 10/F., KWUN TONG INDUSTRIAL CENTRE, 436-446 KWUN TONG ROAD, KWUN TONG, HONG KONG
<b>Equipment under Test</b>	:	PORTABLE BOOMBOX WITH BLUETOOTH, CD PLAYER, USB AND AM/FM RADIO
<b>Model No.</b>	:	MET1401USB, SB2149, SB2149B, SB2149S, SB2149XXXXX(where XXXXX denote any printable characters in the ASCII Standard Character Table to represent variances in cosmetics or buyers), MD1401USB
<b>Trade Mark</b>	:	MET, Studebaker, Modern
<b>FCC ID</b>	:	2ANH76961401USB
<b>Manufacturer</b>	:	MODERN ELECTRONICS FACTORY LIMITED
<b>Address</b>	:	FLAT/RM C, BLK 4, 10/F., KWUN TONG INDUSTRIAL CENTRE, 436-446 KWUN TONG ROAD, KWUN TONG, HONG KONG

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan  
City, Guangdong Province, China, 523808

**Tel:** +86-0769-89201699, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

# REPORT

## TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results .....	6
2.	General test information .....	7
2.1.	Description of EUT.....	7
2.2.	Accessories of EUT .....	8
2.3.	Assistant equipment used for test.....	8
2.4.	Block diagram of EUT configuration for test .....	8
2.5.	Deviations of test standard .....	9
2.6.	Test environment conditions .....	9
2.7.	Test laboratory.....	9
2.8.	Measurement uncertainty .....	9
3.	Equipment used during test .....	10
4.	Maximum Peak Output Power .....	12
4.1.	Block diagram of test setup .....	12
4.2.	Limits .....	12
4.3.	Test Procedure .....	12
4.4.	Test Result .....	12
4.5.	Original test data.....	13
5.	20dB Bandwidth.....	15
5.1.	Block diagram of test setup .....	15
5.2.	Limits .....	15
5.3.	Test Procedure .....	15
5.4.	Test Result .....	15
5.5.	Original test data.....	16
6.	Carrier Frequency Separation.....	18
6.1.	Block diagram of test setup .....	18
6.2.	Limits .....	18
6.3.	Test Procedure .....	18
6.4.	Test Result .....	18
6.5.	Original test data.....	18
7.	Number Of Hopping Channel.....	19
7.1.	Block diagram of test setup .....	19
7.2.	Limits .....	19
7.3.	Test Procedure .....	19
7.4.	Test Result .....	19
7.5.	Original test data.....	20

8.	Dwell Time .....	21
8.1.	Block diagram of test setup .....	21
8.2.	Limits .....	21
8.3.	Test Procedure .....	21
8.4.	Test Result .....	21
8.5.	Original test data.....	22
9.	Band Edge Compliance (conducted method) .....	26
9.1.	Block diagram of test setup .....	26
9.2.	Limit .....	26
9.3.	Test result.....	26
9.4.	Original test data.....	26
10.	Radiated emission .....	30
10.1.	Block diagram of test setup .....	30
10.2.	Limit .....	31
10.3.	Test Procedure .....	32
10.4.	Test result.....	34
11.	RF Conducted Spurious Emissions .....	38
11.1.	Block diagram of test setup .....	38
11.2.	Limits .....	38
11.3.	Test Procedure .....	38
11.4.	Test Result .....	39
11.5.	Original test data.....	39
12.	Band Edge Compliance (radiated method).....	46
12.1.	Block diagram of test setup .....	46
12.2.	Limit .....	46
12.3.	Test Procedure .....	46
12.4.	Test result.....	46
13.	Power Line Conducted Emission .....	55
13.1.	Block diagram of test setup .....	55
13.2.	Power Line Conducted Emission Limits.....	55
13.3.	Test Procedure .....	55
13.4.	Test Result .....	56
14.	Antenna Requirements .....	59
14.1.	Limit .....	59
14.2.	Result .....	59
15.	Test setup photograph.....	60
16.	Photos of the EUT .....	62

## TEST REPORT DECLARE

<b>Applicant</b>	: MODERN ELECTRONICS FACTORY LIMITED
<b>Address</b>	: FLAT/RM C, BLK 4, 10/F., KWUN TONG INDUSTRIAL CENTRE, 436-446 KWUN TONG ROAD, KWUN TONG, HONG KONG
<b>Equipment under Test</b>	: PORTABLE BOOMBOX WITH BLUETOOTH, CD PLAYER, USB AND AM/FM RADIO
<b>Model No.</b>	: MET1401USB, SB2149, SB2149B, SB2149S, SB2149XXXXX(where XXXXX denote any printable characters in the ASCII Standard Character Table to represent variances in cosmetics or buyers), MD1401USB
<b>Trade mark</b>	: MET, Studebaker, Modern
<b>Manufacturer</b>	: MODERN ELECTRONICS FACTORY LIMITED
<b>Address</b>	: FLAT/RM C, BLK 4, 10/F., KWUN TONG INDUSTRIAL CENTRE, 436-446 KWUN TONG ROAD, KWUN TONG, HONG KONG

**Test Standard Used:**

FCC Rules and Regulations Part 15 Subpart C: August 18, 2015

**Test procedure used:**

ANSI C63.10:2013

**We Declare:**

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.


**After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&IC standards.**

<b>Report No.:</b>	DDT-R18051701-1E2		
<b>Date of Receipt:</b>	Jun. 19, 2018	<b>Date of Test:</b>	Jun. 19, 2018 ~ Jul. 02, 2018

**Prepared By:**

*Ella Gong*

**Ella Gong/Engineer**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

### Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jul. 02, 2018	

## 1. Summary of test results

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10:2013	PASS
20dB Bandwidth	FCC Part 15: 15.215 ANSI C63.10:2013	PASS
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10:2013	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10:2013	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10:2013	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10:2013	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10:2013	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10:2013	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

## 2. General test information

### 2.1. Description of EUT

EUT* Name	: PORTABLE BOOMBOX WITH BLUETOOTH, CD PLAYER, USB AND AM/FM RADIO
Model Number	: MET1401USB, SB2149, SB2149B, SB2149S, SB2149XXXXX(where XXXXX denote any printable characters in the ASCII Standard Character Table to represent variances in cosmetics or buyers), MD1401USB
Difference of model number	: All models are identical, only the color and brand are different; therefore, the test performed on the model MET1401USB.
EUT function description	: Please reference user manual of this device
Power supply	: Input: DC 12V/1.5A from external AC adapter or DC 7.4V built-in battery
Radio Specification	: Bluetooth V4.2
Operation frequency	: 2402MHz -2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK
Data rate	: 1Mbps, 2Mbps
Antenna Type	: Integral PCB antenna, maximum PK gain: -0.68dBi
Sample Type	: Series production

Note: EUT is the ab. of equipment under test.

Channel information					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	28	2429MHz	55	2456MHz
2	2403MHz	29	2430MHz	56	2457MHz
3	2404MHz	30	2431MHz	57	2458MHz
4	2405MHz	31	2432MHz	58	2459MHz
5	2406MHz	32	2433MHz	59	2460MHz
6	2407MHz	33	2434MHz	60	2461MHz
7	2408MHz	34	2435MHz	61	2462MHz
8	2409MHz	35	2436MHz	62	2463MHz
9	2410MHz	36	2437MHz	63	2464MHz
10	2411MHz	37	2438MHz	64	2465MHz
11	2412MHz	38	2439MHz	65	2466MHz
12	2413MHz	39	2440MHz	66	2467MHz
13	2414MHz	40	2441MHz	67	2468MHz
14	2415MHz	41	2442MHz	68	2469MHz
15	2416MHz	42	2443MHz	69	2470MHz
16	2417MHz	43	2444MHz	70	2471MHz
17	2418MHz	44	2445MHz	71	2472MHz
18	2419MHz	45	2446MHz	72	2473MHz
19	2420MHz	46	2447MHz	73	2474MHz
20	2421MHz	47	2448MHz	74	2475MHz
21	2422MHz	48	2449MHz	75	2476MHz
22	2423MHz	49	2450MHz	76	2477MHz
23	2424MHz	50	2451MHz	77	2478MHz
24	2425MHz	51	2452MHz	78	2479MHz
25	2426MHz	52	2453MHz	79	2480MHz

26	2427MHz	53	2454MHz	
27	2428MHz	54	2455MHz	


## 2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
SWITCHING ADAPTEOR	Hung Kay Industrial Co., Ltd.	HKP24-1201500dU	N/A	INPUT: 100-240V/50-60Hz, 0.68A OUTPUT: DC 12.0V/1.5A Length: 1.5m
CAR charger	N/A	N/A	N/A	INPUT: DC12V OUTPUT: DC 12.0V/1.5A Length: 3m

## 2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
Notebook	DELL	Latitude D610	FCC DOC	00045-534-136-300
AC Adapter	Group Intellect Power Technology Limited	F5V-2.3C-1U	/	Input: AC 100-240V -50/60Hz, 0.5A; Output: DC 5V, 2.3A

## 2.4. Block diagram of EUT configuration for test



Test software: FCC Assist.EXE

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as blow table.



Tested mode, channel, information		
Mode	Channel	Frequency (MHz)
GFSK hopping on Tx mode	CH0 to CH78	2402 to 2480
$\pi/4$ -DQPSK hopping on Tx mode	CH0 to CH78	2402 to 2480
GFSK hopping off Tx mode	CH0	2402
	CH39	2441
	CH78	2480
$\pi/4$ -DQPSK hopping off Tx mode	CH0	2402
	CH39	2441
	CH78	2480

## 2.5. Deviations of test standard

No Deviation.

## 2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

## 2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-89201699, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com)

CNAS Accreditation No. L6451; A2LA Accreditation No. 3870.01

Designation Number: CN1182; Test Firm Registration Number: 540522

Industry Canada site registration number: 10288A-1

## 2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power(Conducted)(Spectrum analyzer)	0.86dB (10 MHz $\leq$ f < 3.6GHz);
	1.38dB (3.6GHz $\leq$ f < 8GHz)
Peak Output Power(Conducted)(Power Sensor)	0.74dB
Power Spectral Density	0.74dB (10 MHz $\leq$ f < 3.6GHz);
	1.38dB (3.6GHz $\leq$ f < 8GHz)
Frequencies Stability	$6.7 \times 10^{-8}$ (Antenna couple method)
	$5.5 \times 10^{-8}$ (Conducted method)
Conducted spurious emissions	0.86dB (10 MHz $\leq$ f < 3.6GHz);
	1.40dB (3.6GHz $\leq$ f < 8GHz)
	1.66dB (8GHz $\leq$ f < 22GHz)

Uncertainty for radio frequency (RBW<20kHz)	3×10 <sup>-8</sup>
Temperature	0.4°C
Humidity	2%
Uncertainty for Radiation Emission test (30MHz-1GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz-40GHz)	4.10dB (1-6GHz)
	4.40dB (6GHz-18GHz)
	3.54dB (18GHz-26GHz)
	4.30dB (26GHz-40GHz)
Uncertainty for Power line conduction emission test	3.32dB (150kHz-30MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	


### 3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
<b>RF Connected Test (Tonscend RF Measurement System)</b>					
Spectrum analyzer	R&S	FSU26	200071	Oct. 23, 2017	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jun. 16, 2018	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Oct. 23, 2017	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jun. 16, 2018	1 Year
Power Sensor	Agilent	U2021XA	MY55150010	Oct. 21, 2017	1 Year
Power Sensor	Agilent	U2021XA	MY55150011	Oct. 23, 2017	1 Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Aug. 18, 2017	1 Year
Attenuator	Mini-Circuits	BW-S10W2	101109	Aug. 18, 2017	1 Year
RF Cable	Micable	C10-01-01-1	100309	Oct. 21, 2017	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Oct. 21, 2017	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.7	N/A	N/A
<b>Radiated Emission Test Chamber 1#</b>					
EMI Test Receiver	R&S	ESU8	100316	Oct. 21, 2017	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jun. 16, 2018	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Nov. 09, 2017	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Oct. 17, 2017	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Oct. 17, 2017	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Nov. 09, 2017	1 Year
Pre-amplifier	A.H.	PAM-0118	360	Oct. 21, 2017	1 Year
Pre-amplifier	TERA-MW	TRLA-0040 G35	101303	Oct. 21, 2017	1 Year
RF Cable	HUBSER	CP-X2+ CP-X1	W11.03+ W12.02	Oct. 21, 2017	1 Year
RF Cable	N/A	SMAJ-SMA	17070133+17	Nov. 08, 2017	1 Year

		J-1M+ 11M	070131		
MI Cable	HUBSER	C10-01-01-1 M	1091629	Oct. 21, 2017	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
<b>Power Line Conducted Emissions Test</b>					
EMI Test Receiver	R&S	ESU8	100316	Oct. 21, 2017	1 Year
LISN 1	R&S	ENV216	101109	Oct. 21, 2017	1 Year
LISN 2	R&S	ESH2-Z5	100309	Oct. 21, 2017	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Oct. 21, 2017	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Oct. 21, 2017	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

## 4. Maximum Peak Output Power

### 4.1. Block diagram of test setup



### 4.2. Limits

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

### 4.3. Test Procedure


- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Measure the maximum output power of EUT by spectrum analyzer with PK detector and RBW=3MHz (above 20dB bandwidth of measured signal), VBW=10MHz

Note: The attenuator loss was inputted into spectrum analyzer as amplitude offset.


### 4.4. Test Result

Mode	Freq (MHz)	Result (dBm)	Limit (dBm)	Conclusion
GFSK	2402	-7.87	21	PASS
	2441	-7.93	21	PASS
	2480	-8.70	21	PASS
$\pi/4$ -DQPSK	2402	-6.94	21	PASS
	2441	-6.94	21	PASS
	2480	-7.78	21	PASS

### 4.5. Original test data




### 2DH5\_ANT1\_2402




Date: 23.JUN.2018 14:40:22

### 2DH5\_ANT1\_2441



Date: 23.JUN.2018 14:41:35

### 2DH5\_ANT1\_2480



Date: 23.JUN.2018 14:42:33

## 5. 20dB Bandwidth

### 5.1. Block diagram of test setup

Same as section 4.1

### 5.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


### 5.3. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 kHz RBW and 100 kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

### 5.4. Test Result


Mode	Freq. (MHz)	20dB bandwidth Result (MHz)	Conclusion
GFSK	2402	0.952	PASS
	2441	0.950	PASS
	2480	0.954	PASS
$\pi/4$ -DQPSK	2402	1.286	PASS
	2441	1.286	PASS
	2480	1.288	PASS

### 5.5. Original test data






### 2DH5\_ANT1\_2402




Date: 23.JUN.2018 14:40:09

### 2DH5\_ANT1\_2441



Date: 23.JUN.2018 14:41:21

### 2DH5\_ANT1\_2480



Date: 23.JUN.2018 14:42:20

## 6. Carrier Frequency Separation

### 6.1. Block diagram of test setup

Same as section 4.1

### 6.2. Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.


### 6.3. Test Procedure


- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The carrier frequency was measured by spectrum analyzer with 100 kHz RBW and 300 kHz VBW.

### 6.4. Test Result

Mode	Channel separation (MHz)	20dB bandwidth (MHz) (worse case)	Limit (MHz) 2/3 of 20dB bandwidth	Conclusion
GFSK	1.058	0.954	≥0.636	PASS
π/4-DQPSK	1.000	1.288	≥0.859	PASS

### 6.5. Original test data





## 7. Number Of Hopping Channel

### 7.1. Block diagram of test setup

Same as section 4.1

### 7.2. Limits

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


### 7.3. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The number of hopping channel was measured by spectrum analyzer with 100 kHz RBW and 300 kHz VBW.

### 7.4. Test Result

Mode	Number of hopping channel	Limit	Conclusion
GFSK	79	>15	PASS
$\pi/4$ -DQPSK	79	>15	PASS

### 7.5. Original test data



## 8. Dwell Time

### 8.1. Block diagram of test setup

Same as section 4.1

### 8.2. Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 8.3. Test Procedure


- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The test period:  $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$
- (3) Measure the hopping number and on time of each pulse with spectrum analyzer in zero span set, and calculate dwell time with formula  $\text{Dwell time} = \text{total hops} * \text{pulse's on time}$ .


### 8.4. Test Result

Mode	Dwell time (s)	Pulse's on time (ms)	Total hops	Limit	Conclusion
DH1	0.01	0.36	27	<400ms	PASS
DH3	0.152	1.62	94	<400ms	PASS
DH5	0.316	2.87	110	<400ms	PASS
2-DH1	0.116	0.37	314	<400ms	PASS
2-DH3	0.275	1.63	169	<400ms	PASS
2-DH5	0.301	2.89	104	<400ms	PASS



Note:  $\text{Dwell time} = \text{total hops} * \text{pulse's on time}$ .

### 8.5. Original test data






### DH5 ANT1 HOP




### 2DH1\_ANT1\_HOP




Date: 14.JUN.2018 10:04:16

### 2DH3\_ANT1\_HOP




Date: 14.JUN.2018 10:04:49

### 2DH3\_ANT1\_HOP





Date: 14.JUN.2018 10:07:22





2DH5\_ANT1\_HOP



## 9. Band Edge Compliance (conducted method)

### 9.1. Block diagram of test setup

Same as section 4.1


### 9.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.


### 9.3. Test result

Mode	Freq (MHz)	Conclusion
GFSK	Hopping off 2402	PASS
	Hopping off 2480	PASS
	Hopping on	PASS
$\pi/4$ -DQPSK	Hopping off 2402	PASS
	Hopping off 2480	PASS
	Hopping on	PASS

### 9.4. Original test data




### DH5\_ANT1\_High




Date: 23.JUN.2018 14:39:18

### DH5\_ANT1\_Low




Date: 23.JUN.2018 14:46:11

### DH5\_ANT1\_High




Date: 23.JUN.2018 14:46:01

### 2DH5\_ANT1\_Low




Date: 23.JUN.2018 14:40:32

### 2DH5\_ANT1\_High




Date: 23.JUN.2018 14:42:43

### 2DH5\_ANT1\_Low




Date: 23.JUN.2018 14:56:47




### 10. Radiated emission

#### 10.1. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9kHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

## 10.2. Limit

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.1775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.2075	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

## (2) FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Note: (1)The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30\text{m}/3\text{m})$$

## (3) Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

**10.3. Test Procedure**

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a semi-anechoic chamber for above 1G.

(2) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9kHz-30MHz	Active Loop antenna	3m
30MHz-1GHz	Trilog Broadband Antenna	3m
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3m
18GHz-40GHz	Horn Antenna(18GHz-40GHz)	1m

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the



loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9kHz to 25GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9kHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below final test was performed with frequency range from 9kHz to 18GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.

(5) The emissions from 9kHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz, for emissions from 9kHz-90kHz,110kHz-490kHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9kHz to 1GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9kHz-150kHz	200Hz
150kHz-30MHz	9kHz
30MHz-1GHz	120kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RMS detector RBW 1MHz VBW 3MHz for Average measure(according ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure).

(8) X axis, Y axis, Z axis are tested, and worse setup X axis is reported.

## 10.4. Test result

### **PASS. (See below detailed test result)**

All the emissions except fundamental emission from 9 kHz to 25GHz were comply with 15.209 limits.

Note1: According exploratory test no any obvious emission were detected from 9kHz to 30MHz and 18GHz to 25GHz.


Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in  $\pi/4$ -DQPSK, Tx 2402MHz mode.

Note3: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

## Radiated Emission test (below 1GHz) TR-4-E-009 Radiated Emission Test Result

<b>Test Site</b>	: DDT 3m Chamber 1#	D:\2018 RE1# Report Data\Q18051701-1E MET1401USB\FCC	BELOW1G.EM6
<b>Test Date</b>	: 2018-06-24	<b>Tested By</b>	: TALENT
<b>EUT</b>	: PORTABLE BOOMBOX WITH BLUETOOTH, CD PLAYER, USB AND AM/FM RADIO	<b>Model Number</b>	: MET1401USB
<b>Power Supply</b>	: DC 12V from AC Adapter	<b>Test Mode</b>	: Tx mode
<b>Condition</b>	: Temp:24.5'C,Humi:55.5%, Press:100.1kPa	<b>Antenna/Distance</b>	: 2017 VULB 9163 1#/3m/VERTICAL
<b>Memo</b>	: BT		

Data: 1




Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	47.49	2.69	13.52	3.96	20.17	40.00	-19.83	QP	VERTICAL
2	96.78	2.70	10.85	4.39	17.94	43.50	-25.56	QP	VERTICAL
3	196.51	1.86	11.20	5.00	18.06	43.50	-25.44	QP	VERTICAL
4	269.43	3.36	12.82	5.39	21.57	46.00	-24.43	QP	VERTICAL
5	465.60	2.76	16.77	5.52	25.05	46.00	-20.95	QP	VERTICAL
6	638.37	3.48	19.52	6.81	29.81	46.00	-16.19	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2018 RE1# Report Data\Q18051701-1E MET1401USB\FCC BELOW1G.EM6  
**Test Date** : 2018-06-24 **Tested By** : TALENT  
**EUT** : PORTABLE BOOMBOX WITH  
 : BLUETOOTH,CD PLAYER, USB AND **Model Number** : MET1401USB  
 : AM/FM RADIO  
**Power Supply** : DC 12V from AC Adapter **Test Mode** : Tx mode  
**Condition** : Temp:24.5°C,Humi:55.5%,  
 : Press:100.1kPa **Antenna/Distance** : 2017 VULB 9163 1#/3m/HORIZONTAL  
**Memo** : BT

Data: 2



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	49.71	1.73	13.77	3.99	19.49	40.00	-20.51	QP	HORIZONTAL
2	98.83	2.94	11.27	4.40	18.61	43.50	-24.89	QP	HORIZONTAL
3	197.20	2.60	11.26	5.01	18.87	43.50	-24.63	QP	HORIZONTAL
4	290.02	3.56	13.15	5.48	22.19	46.00	-23.81	QP	HORIZONTAL
5	397.63	3.24	15.16	5.94	24.34	46.00	-21.66	QP	HORIZONTAL
6	618.54	3.88	19.46	6.74	30.08	46.00	-15.92	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

**Radiated Emission test (above 1GHz)**

Freq. (MHz)	Read level (dB $\mu$ V)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/ m)	Margin (dB)	Detector type	Polarization
<b><math>\pi/4</math>-DQPSK Tx mode 2402MHz</b>									
4808.00	54.88	34.69	43.92	7.39	53.04	74.00	-20.96	Peak	HORIZONTAL
5726.00	46.97	35.59	43.36	8.04	47.24	74.00	-26.76	Peak	HORIZONTAL
7273.00	46.37	36.91	43.58	8.58	48.28	74.00	-25.72	Peak	HORIZONTAL
9160.00	46.84	37.56	44.15	10.45	50.70	74.00	-23.30	Peak	HORIZONTAL
11098.00	46.66	38.76	44.24	11.05	52.23	74.00	-21.77	Peak	HORIZONTAL
12509.00	44.74	38.81	44.23	11.16	50.48	74.00	-23.52	Peak	HORIZONTAL
4808.00	51.43	34.69	43.92	7.39	49.59	54.00	-4.41	Average	VERTICAL
4808.00	56.15	34.69	43.92	7.39	54.31	74.00	-19.69	Peak	VERTICAL
5981.00	49.30	35.69	43.21	8.20	49.98	74.00	-24.02	Peak	VERTICAL
6695.00	46.13	36.13	43.41	8.29	47.14	74.00	-26.86	Peak	VERTICAL
8429.00	45.37	37.29	43.93	9.72	48.45	74.00	-25.55	Peak	VERTICAL
9976.00	46.69	38.18	44.39	10.88	51.36	74.00	-22.64	Peak	VERTICAL
13427.00	45.49	39.73	44.46	11.78	52.54	74.00	-21.46	Peak	VERTICAL
<b><math>\pi/4</math>-DQPSK Tx mode 2441MHz</b>									
4876.00	54.63	34.80	43.87	7.46	53.02	74.00	-20.98	Peak	HORIZONTAL
5913.00	47.08	35.67	43.25	8.16	47.66	74.00	-26.34	Peak	HORIZONTAL
7171.00	46.35	36.87	43.55	8.48	48.15	74.00	-25.85	Peak	HORIZONTAL
8259.00	46.24	37.25	43.88	9.53	49.14	74.00	-24.86	Peak	HORIZONTAL
9007.00	46.73	37.50	44.10	10.37	50.50	74.00	-23.50	Peak	HORIZONTAL
13614.00	45.28	39.85	44.50	11.97	52.60	74.00	-21.40	Peak	HORIZONTAL
4876.00	52.12	34.80	43.87	7.46	50.51	54.00	-3.49	Average	VERTICAL
4876.00	55.94	34.80	43.87	7.46	54.33	74.00	-19.67	Peak	VERTICAL
5590.00	47.98	35.54	43.45	7.95	48.02	74.00	-25.98	Peak	VERTICAL
6984.00	46.36	36.76	43.50	8.33	47.95	74.00	-26.05	Peak	VERTICAL
7902.00	46.51	37.16	43.77	9.14	49.04	74.00	-24.96	Peak	VERTICAL
8803.00	46.84	37.42	44.04	10.15	50.37	74.00	-23.63	Peak	VERTICAL
11897.00	45.99	38.84	44.12	10.98	51.69	74.00	-22.31	Peak	VERTICAL
<b><math>\pi/4</math>-DQPSK Tx mode 2480MHz</b>									
4961.00	53.89	34.94	43.82	7.54	52.55	74.00	-21.45	Peak	HORIZONTAL
6287.00	46.77	35.70	43.29	8.24	47.42	74.00	-26.58	Peak	HORIZONTAL
7239.00	45.77	36.90	43.57	8.55	47.65	74.00	-26.35	Peak	HORIZONTAL
8548.00	46.62	37.32	43.96	9.85	49.83	74.00	-24.17	Peak	HORIZONTAL
9517.00	46.74	37.72	44.26	10.64	50.84	74.00	-23.16	Peak	HORIZONTAL
12101.00	44.33	38.88	44.13	11.01	50.09	74.00	-23.91	Peak	HORIZONTAL
4961.00	52.78	34.94	43.82	7.54	51.44	74.00	-22.56	Peak	VERTICAL
5947.00	46.67	35.68	43.23	8.18	47.30	74.00	-26.70	Peak	VERTICAL
6933.00	44.47	36.65	43.48	8.32	45.96	74.00	-28.04	Peak	VERTICAL
8582.00	46.06	37.33	43.97	9.89	49.31	74.00	-24.69	Peak	VERTICAL
11829.00	44.54	38.80	44.13	10.99	50.20	74.00	-23.80	Peak	VERTICAL
12985.00	45.28	39.28	44.35	11.34	51.55	74.00	-22.45	Peak	VERTICAL
<b>Result: Pass</b>									

Note: 1.30MHz~25GHz: (Scan with GFSK,  $\pi/4$ -DQPSK, the worst case is  $\pi/4$ -DQPSK Mode)

2. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

3: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

## 11. RF Conducted Spurious Emissions

### 11.1. Block diagram of test setup

Same as section 4.1

### 11.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

### 11.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100kHz
VBW:	300kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:


RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


### 11.4. Test Result

Mode	Freq. (MHz)	Conclusion
GFSK	Hopping off 2402	PASS
	Hopping off 2441	PASS
	Hopping off 2480	PASS
$\pi/4$ -DQPSK	Hopping off 2402	PASS
	Hopping off 2441	PASS
	Hopping off 2480	PASS

### 11.5. Original test data




### DH5\_ANT1\_2402\_1000~26500




Date: 23.JUN.2018 14:36:02

### DH5\_ANT1\_2441\_Ref



Date: 23.JUN.2018 14:38:18


### DH5\_ANT1\_2441\_30~1000



Date: 23.JUN.2018 14:38:27




### DH5\_ANT1\_2441\_1000~26500




Date: 23.JUN.2018 14:38:38

### DH5\_ANT1\_2480\_Ref




Date: 23.JUN.2018 14:39:26

### DH5\_ANT1\_2480\_30~1000




Date: 23.JUN.2018 14:39:34

### DH5\_ANT1\_2480\_1000~26500




Date: 23.JUN.2018 14:39:46

### 2DH5\_ANT1\_2402\_Ref




Date: 23.JUN.2018 14:40:40

### 2DH5\_ANT1\_2402\_30~1000




Date: 23.JUN.2018 14:40:49

### 2DH5\_ANT1\_2402\_1000~26500




Date: 23.JUN.2018 14:41:00

### 2DH5\_ANT1\_2441\_Ref




Date: 23.JUN.2018 14:41:42

### 2DH5\_ANT1\_2441\_30~1000




Date: 23.JUN.2018 14:41:51

### 2DH5\_ANT1\_2441\_1000~26500




Date: 23.JUN.2018 14:42:02

### 2DH5\_ANT1\_2480 Ref




Date: 23.JUN.2018 14:42:51

### 2DH5\_ANT1\_2480\_30~1000




Date: 23.JUN.2018 14:43:00



## 12. Band Edge Compliance (radiated method)

### 12.1. Block diagram of test setup



### 12.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

### 12.3. Test Procedure

Same with clause 10.3 except change investigated frequency range from 2310MHz to 2415MHz and 2475MHz to 2500MHz.

Remark: All restriction band have been tested, and only the worse case is shown in report.

### 12.4. Test result

PASS. (See below detailed test result)


Remark: hopping on and hopping off mode all have been test, hopping off mode is worst and reported only.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#  
**Test Date** : 2018-06-26  
**EUT** : PORTABLE BOOMBOX WITH BLUETOOTH,CD PLAYER, USB AND AM/FM RADIO  
**Power Supply** : DC 12V from AC Adapter  
**Condition** : Temp:24.5°C,Humi:55.5%, Press:100.1kPa  
**Memo** : GFSK 2480

D:\2018 RE1# Report Data\Q18051701-1E MET1401USB\FCC ABOVE1G.EM6  
**Tested By** : Talent  
**Model Number** : MET1401USB  
**Test Mode** : Tx mode  
**Antenna/Distance** : 2017 HF907/3m/VERTICAL

Data: 8




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	52.20	27.34	44.32	5.21	40.43	74.00	-33.57	Peak	VERTICAL
2	2489.32	55.07	27.36	44.32	5.22	43.33	74.00	-30.67	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

<b>Test Site</b>	: DDT 3m Chamber 1#	<b>Tested By</b>	: Talent
<b>Test Date</b>	: 2018-06-26	<b>Model Number</b>	: MET1401USB
<b>EUT</b>	: PORTABLE BOOMBOX WITH BLUETOOTH,CD PLAYER, USB AND AM/FM RADIO	<b>Test Mode</b>	: Tx mode
<b>Power Supply</b>	: DC 12V from AC Adapter	<b>Antenna/Distance</b>	: 2017 HF907/3m/HORIZONTAL
<b>Condition</b>	: Temp:24.5°C,Humi:55.5%, Press:100.1kPa		
<b>Memo</b>	: GFSK 2480		

Data: 9



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m )	Limit Line (dBμV/ m)	Over Limit (dB)	Detector	Polarization
1	2483.50	52.55	27.34	44.32	5.21	40.78	74.00	-33.22	Peak	HORIZONTAL
2	2486.29	54.20	27.35	44.32	5.21	42.44	74.00	-31.56	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.




# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#  
**Test Date** : 2018-06-26  
**EUT** : PORTABLE BOOMBOX WITH BLUETOOTH,CD PLAYER, USB AND AM/FM RADIO  
**Power Supply** : DC 12V from AC Adapter  
**Condition** : Temp:24.5°C,Humi:55.5%, Press:100.1kPa  
**Memo** : GFSK 2402

**D:\2018 RE1# Report Data\Q18051701-1E MET1401USB\FCC ABOVE1G.EM6**  
**Tested By** : Talent  
**Model Number** : MET1401USB  
**Test Mode** : Tx mode  
**Antenna/Distance** : 2017 HF907/3m/HORIZONTAL

Data: 10



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2364.70	55.27	26.91	44.32	5.08	42.94	74.00	-31.06	Peak	HORIZONTAL
2	2390.00	51.28	27.00	44.32	5.11	39.07	74.00	-34.93	Peak	HORIZONTAL


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#  
**Test Date** : 2018-06-26  
**EUT** : PORTABLE BOOMBOX WITH BLUETOOTH,CD PLAYER, USB AND AM/FM RADIO  
**Power Supply** : DC 12V from AC Adapter  
**Condition** : Temp:24.5°C,Humi:55.5%, Press:100.1kPa  
**Memo** : GFSK 2402

D:\2018 RE1# Report Data\Q18051701-1E  
 MET1401USB\FCC ABOVE1G.EM6  
**Tested By** : Talent  
**Model Number** : MET1401USB  
**Test Mode** : Tx mode  
**Antenna/Distance** : 2017 HF907/3m/VERTICAL

Data: 11



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2364.90	57.23	26.91	44.32	5.08	44.90	74.00	-29.10	Peak	VERTICAL
2	2390.00	52.00	27.00	44.32	5.11	39.79	74.00	-34.21	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.


# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#  
**Test Date** : 2018-06-26  
**EUT** : PORTABLE BOOMBOX WITH BLUETOOTH,CD PLAYER, USB AND AM/FM RADIO  
**Power Supply** : DC 12V from AC Adapter  
**Condition** : Temp:24.5°C,Humi:55.5%, Press:100.1kPa  
**Memo** :  $\pi/4$ -DQPSK 2402

**Tested By** : Talent  
**Model Number** : MET1401USB  
**Test Mode** : Tx mode  
**Antenna/Distance** : 2017 HF907/3m/VERTICAL

D:\2018 RE1# Report Data\Q18051701-1E MET1401USB\FCC ABOVE1G.EM6

Data: 12




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2371.00	58.20	26.94	44.32	5.09	45.91	74.00	-28.09	Peak	VERTICAL
2	2390.00	53.10	27.00	44.32	5.11	40.89	74.00	-33.11	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

<b>Test Site</b>	: DDT 3m Chamber 1#	D:\2018 RE1# Report Data\Q18051701-1E MET1401USB\FCC ABOVE1G.EM6
<b>Test Date</b>	: 2018-06-26	<b>Tested By</b> : Talent
<b>EUT</b>	: PORTABLE BOOMBOX WITH BLUETOOTH,CD PLAYER, USB AND AM/FM RADIO	<b>Model Number</b> : MET1401USB
<b>Power Supply</b>	: DC 12V from AC Adapter	<b>Test Mode</b> : Tx mode
<b>Condition</b>	: Temp:24.5°C,Humi:55.5%, Press:100.1kPa	<b>Antenna/Distance</b> : 2017 HF907/3m/HORIZONTAL
<b>Memo</b>	: $\pi/4$ -DQPSK 2402	

Data: 13



Item (Mark)	Freq. (MHz)	Read Level (dB $\mu$ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dB $\mu$ V/m )	Limit Line (dB $\mu$ V/ m)	Over Limit (dB)	Detector	Polarization
1	2382.00	56.46	26.98	44.32	5.10	44.22	74.00	-29.78	Peak	HORIZONTAL
2	2390.00	51.87	27.00	44.32	5.11	39.66	74.00	-34.34	Peak	HORIZONTAL


- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#  
**Test Date** : 2018-06-26  
**EUT** : PORTABLE BOOMBOX WITH BLUETOOTH,CD PLAYER, USB AND AM/FM RADIO  
**Power Supply** : DC 12V from AC Adapter  
**Condition** : Temp:24.5°C,Humi:55.5%, Press:100.1kPa  
**Memo** :  $\pi/4$ -DQPSK 2480

D:\2018 RE1# Report Data\Q18051701-1E MET1401USB\FCC ABOVE1G.EM6  
**Tested By** : Talent  
**Model Number** : MET1401USB  
**Test Mode** : Tx mode  
**Antenna/Distance** : 2017 HF907/3m/HORIZONTAL

Data: 14



Item (Mark)	Freq. (MHz)	Read Level (dB $\mu$ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dB $\mu$ V/m)	Limit Line (dB $\mu$ V/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	50.99	27.34	44.32	5.21	39.22	74.00	-34.78	Peak	HORIZONTAL
2	2487.94	52.68	27.36	44.32	5.22	40.94	74.00	-33.06	Peak	HORIZONTAL


- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#  
**Test Date** : 2018-06-26  
**EUT** : PORTABLE BOOMBOX WITH BLUETOOTH,CD PLAYER, USB AND AM/FM RADIO  
**Power Supply** : DC 12V from AC Adapter  
**Condition** : Temp:24.5°C,Humi:55.5%, Press:100.1kPa  
**Memo** :  $\pi/4$ -DQPSK 2480

D:\2018 RE1# Report Data\Q18051701-1E MET1401USB\FCC ABOVE1G.EM6  
**Tested By** : Talent  
**Model Number** : MET1401USB  
**Test Mode** : Tx mode  
**Antenna/Distance** : 2017 HF907/3m/VERTICAL

Data: 15




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	51.52	27.34	44.32	5.21	39.75	74.00	-34.25	Peak	VERTICAL
2	2488.57	53.69	27.36	44.32	5.22	41.95	74.00	-32.05	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## 13. Power Line Conducted Emission

### 13.1. Block diagram of test setup



### 13.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB( $\mu$ V)	Average Level dB( $\mu$ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: \* Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

### 13.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

#### **13.4. Test Result**

**PASS. (See below detailed test result)**

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: "----" means Peak detection; "----" means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/60Hz, recorded worst case.



# TR-4-E-010 Conducted Emission Test Result

**Test Site** : DDT 1# Shield Room

D:\2018 CE report

**Test Date** : 2018-06-19

**Tested By** : Shaul

**EUT** : PORTABLE BOOMBOX WITH BLUETOOTH, CD PLAYER, USB AND AM/FM RADIO

**Model Number** : MET1401USB


**Power** : DC 12V from AC Adapter

**Test Mode** : Tx mode

**Condition** : Temp:24.5°C, Humi:55.5%, Press:100.1kPa

**LISN** : 2017 ENV216/LINE

**Memo** :



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.15	23.54	9.52	0.04	9.86	42.96	65.78	-22.82	QP	LINE
2	0.15	6.29	9.52	0.04	9.86	25.71	55.78	-30.07	Average	LINE
3	0.18	16.66	9.52	0.04	9.86	36.08	64.55	-28.47	QP	LINE
4	0.18	2.30	9.52	0.04	9.86	21.72	54.55	-32.83	Average	LINE
5	0.21	12.21	9.51	0.04	9.86	31.62	63.18	-31.56	QP	LINE
6	0.21	1.21	9.51	0.04	9.86	20.62	53.18	-32.56	Average	LINE
7	1.17	18.04	9.57	0.14	9.86	37.61	56.00	-18.39	QP	LINE
8	1.17	17.27	9.57	0.14	9.86	36.84	46.00	-9.16	Average	LINE
9	2.35	6.89	9.61	0.12	9.87	26.49	56.00	-29.51	QP	LINE
10	2.35	3.46	9.61	0.12	9.87	23.06	46.00	-22.94	Average	LINE
11	10.29	0.66	9.82	0.12	9.89	20.49	60.00	-39.51	QP	LINE
12	10.29	-4.28	9.82	0.12	9.89	15.55	50.00	-34.45	Average	LINE

- Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.  
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).  
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

# TR-4-E-010 Conducted Emission Test Result

**Test Site** : DDT 1# Shield Room

D:\2018 CE report

**Test Date** : 2018-06-19

**Tested By** : Shaul

**EUT** : PORTABLE BOOMBOX WITH BLUETOOTH,CD PLAYER, USB AND AM/FM RADIO

**Model Number** : MET1401USB


**Power** : DC 12V from AC Adapter

**Test Mode** : Tx mode

**Condition** : Temp:24.5°C,Humi:55.5%, Press:100.1kPa

**LISN** : 2017 ENV216/NEUTRAL

**Memo** :



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.15	23.64	9.49	0.04	9.86	43.03	65.87	-22.84	QP	NEUTRAL
2	0.15	7.04	9.49	0.04	9.86	26.43	55.87	-29.44	Average	NEUTRAL
3	0.20	13.62	9.45	0.04	9.86	32.97	63.62	-30.65	QP	NEUTRAL
4	0.20	1.53	9.45	0.04	9.86	20.88	53.62	-32.74	Average	NEUTRAL
5	0.89	0.00	9.30	0.12	9.86	19.28	56.00	-36.72	QP	NEUTRAL
6	0.89	-3.27	9.30	0.12	9.86	16.01	46.00	-29.99	Average	NEUTRAL
7	1.17	7.50	9.29	0.14	9.86	26.79	56.00	-29.21	QP	NEUTRAL
8	1.17	1.16	9.29	0.14	9.86	20.45	46.00	-25.55	Average	NEUTRAL
9	2.02	1.56	9.29	0.12	9.87	20.84	56.00	-35.16	QP	NEUTRAL
10	2.02	-3.20	9.29	0.12	9.87	16.08	46.00	-29.92	Average	NEUTRAL
11	3.53	0.95	9.27	0.11	9.87	20.20	56.00	-35.80	QP	NEUTRAL
12	3.53	-4.02	9.27	0.11	9.87	15.23	46.00	-30.77	Average	NEUTRAL

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

## **14. Antenna Requirements**


### **14.1. Limit**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **14.2. Result**

The antennas used for this product are integrated antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only -0.68dBi.

15. Test setup photograph









16. Photos of the EUT



































































































**END OF REPORT**