

GD-R34



TheGarageStop.com

### Programming with an existing working remote:

1. Locate the included programming connector pin. Connect the currently working transmitter to the new transmitter.
2. Press and hold the first button you wish to program. The LED will illuminate.
3. Continue pressing the button from step 2. Now press and hold the same button on the new transmitter.
4. The LED will blink then turn solid when programming is complete.
5. Repeat steps 2-4 for each button you wish to program.



### Programming without an existing working remote:

Please visit [www.thegaragestop.com](http://www.thegaragestop.com) (select installation videos) for detailed instructions. Instructions will vary based on the opener you have.

#### **⚠ WARNING**

In order to prevent possible **SERIOUS INJURY** or **DEATH** from a moving gate or garage door:

- keep remote controls out of the reach of children.
- Only use the remote control when the gate/garage door can be seen clearly, is properly adjusted, and there are no obstructions to door travel.
- Keep the gate/garage door in sight until it is completely closed. Do not allow anyone to cross paths with the gate/garage door while moving or operating the remote control.



Live Chat Available

**FCC Statement:**

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

**Note:** This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

—Reorient or relocate the receiving antenna.

—Increase the separation between the equipment and receiver.

—Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

—Consult the dealer or an experienced radio/TV technician for help.