

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2ANIFDS01H

EUT Specification

| | |
|-----------------------------------|--|
| EUT | Smart Dimmer Switch |
| Frequency band (Operating) | <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____ |
| Exposure classification | <input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²) |
| Antenna diversity | <input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Antenna gain (Max) | 4dBi |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |

Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm ²) | Average Time |
|--|------------------------------|------------------------------|------------------------------------|--------------|
| (A) Limits for Occupational/Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/Uncontrol Exposures | | | | |
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100000 | -- | -- | 1 | 30 |

Friis transmission formula: $P_d = \frac{P_{out} \cdot G}{4 \cdot \pi \cdot R^2}$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

| Modulation | Maximum Peak Output Power (dBm) | | |
|--------------|---------------------------------|----------------|--------------|
| | Low Channel | Middle Channel | High Channel |
| 802.11b | 8.68 | 7.43 | 6.34 |
| 802.11g | 8.46 | 7.26 | 6.67 |
| 802.11n-HT20 | 8.37 | 7.21 | 6.31 |

| Operating Mode | Test Channel | Tune up tolerance (dBm) | Max tune up conducted power (dBm) | Output Peak power (mW) | Ant. Gain (dBi) | Ant. Gain (numeric) | Power density at 20cm (mW/cm ²) | Power density Limits (mW/cm ²) |
|----------------|--------------|-------------------------|-----------------------------------|------------------------|-----------------|---------------------|---|--|
| 802.11b | 1 | 8.68 ± 1 | 9.68 | 9.29 | 4 | 2.51 | 0.00464 | 1 |
| | 6 | 7.43 ± 1 | 8.43 | 6.97 | 4 | 2.51 | 0.00348 | 1 |
| | 11 | 6.34 ± 1 | 7.34 | 5.42 | 4 | 2.51 | 0.00271 | 1 |
| 802.11g | 1 | 8.46 ± 1 | 9.46 | 8.83 | 4 | 2.51 | 0.00441 | 1 |
| | 6 | 7.26 ± 1 | 8.26 | 6.70 | 4 | 2.51 | 0.00335 | 1 |
| | 11 | 6.67 ± 1 | 7.67 | 5.85 | 4 | 2.51 | 0.00292 | 1 |
| 802.11n-H T20 | 1 | 8.37 ± 1 | 9.37 | 8.65 | 4 | 2.51 | 0.00432 | 1 |
| | 6 | 7.21 ± 1 | 8.21 | 6.62 | 4 | 2.51 | 0.00331 | 1 |
| | 11 | 6.31 ± 1 | 7.31 | 5.38 | 4 | 2.51 | 0.00269 | 1 |

Signature



Date: 2019-10-26