



**MPE/RF EXPOSURE TEST REPORT**

**FCC CFR 47 Part 1.1310**

**Report No.: KUMO06-U6\_FCC\_MPE Rev A**

**Company:** Kumu Networks Inc

**Model:** Relay 2.0

## MPE/RF EXPOSURE TEST REPORT

**Company:** Kumu Networks Inc.

**Model:** Relay 2.0

**Standard:** FCC CFR 47 Part 1.1310

**Test Report Serial No.:** KUMO06-U6 FCC MPE Rev A

This report supersedes: NONE

Applicant: Kumu Networks Inc  
390 Hamlin Court  
Sunnyvale, California 94089  
USA

Issue Date: 14<sup>th</sup> September 2020

### **This Test Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**  
575 Boulder Court  
Pleasanton California 94566  
USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



**MiCOM Labs is an ISO 17025 Accredited Testing Laboratory**

## 1. MAXIMUM PERMISSIBLE EXPOSURE

### Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4*\pi*d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10 \wedge (\text{G (dBi)}/10)$$

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm <sup>2</sup> ) @ 20cm	Power Density Limit (mW/cm <sup>2</sup> )	Min Calculated safe distance for Limit (cm)
1850.0 – 1910.0	0.00	1.00	24.12	258.23	0.05137	1.00	4.53
700.0 - 800.0	0.00	1.00	23.81	240.44	0.0480	1.00	4.37

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

### Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310.



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)