

# Maximum Permissible Exposure Evaluation

## **FCC ID: 2ANJ7-CV01**

### 1. Client Information

<b>Applicant</b>	:	Dongguan MaiJia Intelligent Technology Co., Ltd.
<b>Address</b>	:	Room 202,2F,Building A,No.2 Of ManYuan,Hengtang ,Tangxia ,Dongguan,China
<b>Manufacturer</b>	:	Dongguan MaiJia Intelligent Technology Co., Ltd.
<b>Address</b>	:	Room 202,2F,Building A,No.2 Of ManYuan,Hengtang ,Tangxia ,Dongguan,China

## 2. General Description of EUT

<b>EUT Name</b>	:	Smart Plug Mini 2 in 1	
<b>Models No.</b>	:	MJ-CV01,MJ-CV02,MJ-CV03,MJ-CV04,MJ-CV05,MJ-CV06	
<b>Model Difference</b>	:	All these models are identical in the same PCB layout and electrical circuit, The only difference is appearance.	
<b>Product Description</b>	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz
	:	Max Output Power:	WIFI: 16.92dBm
	:	Antenna Gain:	2.5dBi PCB Antenna
<b>Power Supply</b>	:	AC 100-240V 60Hz	
<b>Hardware Version</b>	:	V0.0.1	
<b>Software Version</b>	:	1.0.6	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	

## MPE Calculations for WIFI

### 1. Antenna Gain:

PCB Antenna: 2.5dBi.

### 2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

**S:** power density

**P:** power input to the antenna

**G:** power gain of the antenna in the direction of interest relative to an isotropic radiator.

**R:** distance to the center of radiation of the antenna

### 4. Test Result:

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm <sup>2</sup> ) [S]
802.11b	16.92	16±1	17	2.5	20	0.01773
802.11g	15.51	15±1	16	2.5	20	0.014085
802.11n (HT20)	15.49	15±1	16	2.5	20	0.014085

**5. Conclusion:**

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

**Limits for General Population/ Uncontrolled Exposure**

Frequency Range (MHz)	Power density (mW/ cm <sup>2</sup> )
300-1,500	F/1500
1,500-100,000	1.0

For 802.11b/g/n:2412~2462 MHz

MPE limit S: 1mW/ cm<sup>2</sup>

The MPE is calculated as  $0.01773\text{mW} / \text{cm}^2 < \text{limit } 1\text{mW} / \text{cm}^2$ . So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

**Note**

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----