

## Declaration of the Modular Approval

<b>Applicant:</b>	Aurolite Electrical Panyu Guangzhou Limited
<b>FCC ID:</b>	2ANJCALSKY580SH
<b>Model:</b>	ALSKY580SH

**The single module transmitter has been evaluated then tested meeting the requirements under Part 15C Section 2.12 as below:**

<b>Modular approval requirement</b>	<b>EUT Condition</b>	<b>Comply</b>
(a) The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	Please refer exhibition External Photo	Yes
(b) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	This modular has buffered data inputs, it is integrated in chip "STM8S003F3P6"	Yes
(c) The modular transmitter must have its own power supply regulation.	The part number of this regulator is "SBK201209T-102Y-N"	Yes
(d) The modular transmitter must comply with the antenna and transmission system requirements of Sections 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of Section 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.	The EUT meets the FCC antenna requirements. The spurious emission and photo of antennas are shown in the test setup photos.	Yes

<p>(e) The modular transmitter must be tested in a stand-alone configuration, <i>i.e.</i>, the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see Section 15.31(i)) must not be inside another device during testing.</p>	<p>The EUT was tested in a standalone configuration. Please see section Photographs of Test Configuration.</p>	<p>Yes</p>
<p>(f) (f)The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number.</p>	<p>Please see exhibition Label Sample for the FCC ID of this module. And also in the exhibition Users Manual, there are instructions give to the OEM on how to label the end product.</p>	<p>Yes</p>
<p>(g) The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization requirements, which are based on the intended use/configurations.</p>	<p>The EUT is compliant with all applicable FCC rules. Detail instructions for maintaining compliance are given in the User Manual.</p>	<p>Yes</p>

(h) The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	The EUT is compliant with all applicable FCC 15.249 and it comply with the KDB447898	Yes
--	--	-----

Luo Wangxian

Name: Luo Wangxian

Position: Manager

Aurolite Electrical Panyu Guangzhou Limited