



PANTONE 2398 C



PANTONE 446 C

40mm

40mm

neos
SMART LEAK
SENSOR KIT
QUICK START

1

Ensure your SmartCam is setup online and has the updated firmware.

2

Solid blue light
Plug the Smart Bridge and wait until you get a solid blue light.

3

Connect the device in the app by following the in-app instruction.

WHERE TO PLACE DEVICES

Please note, this is just an example of where the Smart Leak can be placed.

NEED HELP?

✉ smartcam@neos.co.uk

📺 youtube.com/c/NeosSmartHome

❓ FAQ and Support Centre

Follow us @NeosSmartHome

📱 📺 📷

CE COMPLIANCE STATEMENT

RoHS Directive 2011/65/EU
The Neos Smart Leak Sensor complies with the relevant provisions of the RoHS Directive for the European Union. In common with all Electrical and Electronic Equipment (EEE) the Neos Smart Leak Sensor should not be disposed of as household waste.

<p>Radio Equipment Directive 2014/53/EU Hereby, Neos Ventures Limited declares that the radio equipment type Neos Smart Leak Sensor is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at www.neos.co.uk/compliance.</p> <p>Designed in UK Made in China 47 Bermondsey Street, London, SE1 3XT, United Kingdom www.neos.co.uk Manufactured by: Tianjin Hualai Technology Co., Ltd. Address: 9/F, Huaqiao Chuangye building, No.10, Jinping Road, Ya'an Road, Nankai District, Tianjin (Science and Technology Park) China.</p>	<p>Instructions for safe use To avoid malfunction or damage to your Neos Smart Leak Sensor please observe the following:</p> <ul style="list-style-type: none"> + Designed for indoor use only. + Ensure battery compartment is closed and sealed properly, so not to expose the batteries or internal workings of the Neos Smart Leak Sensor to water or moisture at any time. + The Neos Smart Leak Sensor is designed for reliable operation between the temperatures of -10°C to 50°C. 	<p>Battery When the batteries are depleted in your Neos Smart Leak Sensor we recommend replacing with the following:</p> <p>2 new AAA battery for the Neos Smart Leak Sensor.</p>	<p>Caution: Keep small cells and batteries away from children. Swallowing may lead to burn, perforation of soft tissue and death. Severe burns can occur within 2h of ingestion.</p> <p>If swallowed, consult a doctor at once. Battery can explode or leak if heated, disassembled, shorted, recharged, exposed to fire or high temperature or instead inserted incorrectly.</p> <p>Keep in original packaging until ready to use, and please retain original product literature for future reference.</p> <p>Do not carry batteries loose in your pockets or bag.</p>	<p>Maintenance If you decide to clean the device, remove the battery from the Neos Smart Leak Sensor. This also applied when the equipment is not in use. Please make sure you keep the equipment away from water and other liquids at all times.</p>	<p>To avoid environmental and health problems due to hazardous substances in electrical and electronic goods, the following symbol indicates that this product and/or battery should not be disposed of with household waste. When you decide to dispose of this product and / or its battery, do so in accordance with local environmental laws. Your local authority will be able to advise you on the location of the nearest recycling centre that is authorised to accept this type of waste. Please recycle responsibly.</p>	
--	--	--	--	--	--	--

切刀
压线
齿刀
开槽
半穿
粘合

Scale 1:1 Unit:mm

型号:N-LSP-EU1

规格:
N-LSP-EU1-
KSZP01 V1.0

物料编码:
040600600062

UPC:

产品名 ▶ NEOS水浸套装 (欧)
快速指南

印刷颜色 ▶ CY+PANTONE 2398C+PANTONE 446C

物料材质 ▶ 105g无光铜

样品

设计于 ▶ 于树媛

成品尺寸 ▶ 40*40mm

特种工艺 ▶

样品数量 ▶