











Lowest Channel













TEST A.6: SPURIOUS EMISSIONS AT ANTENNA TERMINALS AT BLOCK EDGES						
	Product standard:	FCC Part 24 / IC RSS-133				
LIMITS: Test standard: FCC § 24.238 and FCC §2.1051 / RSS 133- Clause 6						
LIMITS According to specification, the power of emissions shall be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. P in watts. At Po transmitting power of 2 watts (33 dBm), the specified minimum attenuation becomes 43+10log (Po). and the level in dBm relative to Po becomes: Po (dBm) – [43 + 10 log (Po in watts)] = -13 dBm						
TEST SE	ETUP					
THE EUT RF output connector was connected to a spectrum analyzer and to the Universal Radio Communication Tester R&S CMW500 (selecting maximum transmission power of the EUT and different modes of modulation) using a 50 ohm attenuator and a power splitter. The reading of the spectrum analyzer is corrected with the attenuation loss of connection between output terminal of EUT and input of the spectrum analyzer. For LTE mode the configuration of modulation which is the worst case for conducted power was used. As indicated in FCC part 24, in the 1 MHz bands immediately outside and adjacent to the licensee's frequency block or band, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.						
Po	wer pply	Signalling				



TESTED SAMPLES:			S/01				
TESTED CONDITIONS MODES:			TC#01				
TEST RESULTS:			PASS				
LTE QPSK MODULATION	RB=1.	RB=1.	RB=1.	RB=1.	RB=1.	RB=1.	
	Offset=0.	Offset =0.					
	BW=1.4 MHz	BW = 3 MHz	BW = 5 MHz	BW = 10 MHz	BW = 15 MHz	BW = 20 MHz	
Maximum measured level at lowest Block Edge at antenna port (dBm)	-16.88	-17.34	-18.04	-15.86	-15.93	-19.7	
[1	
LTE QPSK MODULATION:	RB= All.						
):	Offset=0.	Offset =0.					
	BW=1.4 MHz	BW = 3 MHz	BW = 5 MHz	BW = 10 MHz	BW = 15 MHz	BW = 20 MHz	
Maximum measured level at lowest Block Edge at antenna port (dBm)	-22.15	-20.24	-15.48	-16.26	-20.39	-21.09	
LTE QPSK MODULATION:	RB= 1.						
	Offset=Max.	Offset=Max.	Offset=Max.	Offset=Max.	Offset=Max.	Offset=Max.	
	BW=1.4 MHz	BW = 3 MHz	BW = 5 MHz	BW = 10 MHz	BW = 15 MHz	BW = 20 MHz	
Maximum measured level at highest Block Edge at antenna port (dBm)	-18.43	-17.77	-15.31	-15.41	-17.39	-20.45	
			•				
LTE QPSK MODULATION:	RB= All.						
	Offset=0.	Offset =0.					
	BW=1.4 MHz	BW = 3 MHz	BW = 5 MHz	BW = 10 MHz	BW = 15 MHz	BW = 20 MHz	
Maximum measured level at highest Block Edge at antenna port (dBm)	-16.01	-24.39	-14.82	-18.23	-21.76	-26.61	

















Lowest Channel



Highest Channel

















LTE QPSK MODULATION. RB = 50. Offset = 0. BW = 10 MHz

Lowest Channel

Ref Level 39.50 dBm Offset 11.00 dB 👄 RBW 100 kHz 45 dB 👄 SWT Att 1 s 🖷 VBW 300 kHz Mode Auto Sweep Input 1 AC PS 01Rm View -16.26 dBm 1.84981830 GHz M1[1] 30 dBm-20 dBm-10 dBm-0 dBm--10 dBm-D1 -13.000 dBm-41 -20 dBm--30 dBm -40 dBm 50 dBm CF 1.85 GHz Span 2.0 MHz 600 pts

Highest Channel

)1Rm View								
					M	1[1]	-	18.23 dB
30 dBm							1.915	08830 GF
20 d8m								
20 UBIN								
10 dBm-								
0 dBm								
U UBIII								
-10 dBm	1 12 000	dam						
20 d8m	71 -13.000	ubin			M1			
-20 UBIII							 	
-30 dBm			-					
-40 dBm								
io dolli								
-50 dBm								
CF 1.915 G	Hz			600) pts		Spa	n 2.0 MHz











LTE QPSK MODULATION. RB = 1. Offset = 0. BW = 20 MHz

Lowest Channel



Highest Channel









TEST A.7: RADIATED EMISSIONS Product standard: FCC Part 24 / IC RSS-133 LIMITS: Test standard: FCC §2.1053 and §24.238 /RSS-133 Clause 6.6 LIMITS According to specification, the power of emissions shall be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. P in watts. At Po transmitting power of 2 watts (33 dBm), the specified minimum attenuation becomes 43+10log (Po). and the level in dBm relative to Po becomes: Po (dBm) - [43 + 10 log (Po in watts)] = -13 dBm **TEST SETUP** The measurement was performed with the EUT inside an anechoic chamber. The spectrum was scanned from 30 MHz to at least the 10th harmonic of the highest frequency generated within the equipment. The EUT was placed on a non-conductive stand at a 3-meter distance from the measuring antenna for measurements below 1 GHz and at 1-meter distance for measurements above 1 GHz. Detected emissions were maximized at each frequency by rotating the EUT and adjusting the measuring antenna height and polarization. The maximum reading was recorded. Radiated measurements < 1GHz ALC Chamber Antenna Tower Bi-log Antenna 3m EUT Reference point RF EMI Test cable Sec. Prod Receiver Tumtable 0.8m Pre-amplifie Control room Reference ground plane Radiated measurements > 1GHz 1m Boresight Antenna tower Horn Intenna EUT Spectrum analyzei Turntable 0.8r 1m Pre-amp Control room ALC chamber Report No: 2416ERM.003 Page 110 of 119 03-19-2019



TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#01
TEST RESULTS:	PASS
RESULTS	

A preliminary scan determined the QPSK 1.4 MHz bandwidth as the worst case. The configuration of Resource Blocks which is the worst case for conducted power was used.

The following plots show the results for this configuration.

No spurious signal was found at less than 20dB respect to the limit in all the frequency ranges.

LTE QPSK MODULATION. RB = 1. Offset = 0. BW = 1.4 MHz

TEST RESULTS (Cont):

Low Channel

FREQUENCY RANGE: 30-1000 MHz

Frequency (MHz)	PK+_CLRWR (dBm)	PK+_MAXH (dBm)	Comment
60.425667	-67.52	-57.68	
806.291000	-46.48	-40.70	





























High Channel

FREQUENCY RANGE: 1-18 GHz

Frequency (MHz)	PK+_CLRWR (dBm)	PK+_MAXH (dBm)	Comment
1249.500000	-43.19	-41.13	
1914.000000	1.58	22.81	Fundamental
1994.500000	-23.40	-20.13	
3829.500000	-54.92	-48.60	
5742.500000	-52.50	-44.57	
9571.500000	-60.23	-53.59	
13053.500000	-56.92	-49.88	





