



Test report

REP0030760-1R1TRFWL

Date of issue: May 26, 2023

Applicant:

Echodyne Corporation

Product:

Ku Band Radar

Model:

EchoShield 700025-200

Variant(s):

N/A


FCC ID:

2ANLB-MESA00054

Specifications:

- ◆ FCC CFR 47 Part 87
Aviation Services
- ◆ FCC CFR 47 Part 2
Frequency Allocations and Radio Treaty Matters, General Rules and Regulations

Lab and test locations

Company name	Nemko USA Inc.
Address	2210 Faraday Ave, Suite 150
City	Carlsbad
State	California
Postal code	92008
Country	USA
Telephone	+1 760 444 3500
Website	www.nemko.com
FCC Site Number	Test Firm Registration Number: 392943; Designation Number: US5058
ISED Test Site	2040B-3
Tested by	Martha Espinoza, Wireless Test Engineer
Reviewed by	James Cunningham, Wireless Supervisor
Review date	May 26, 2023
Reviewer signature	

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contain in this report are within Nemko USA's ISO/IEC 17025 accreditation.

Copyright notification

Nemko USA Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko USA Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko USA Inc.

Table of Contents

Table of Contents	3
Section 1 Report summary	4
1.1 Test specifications	4
1.2 Test methods	4
1.3 Exclusions	4
1.4 Statement of compliance	4
1.5 Test report revision history	4
Section 2 Summary of test results	5
2.1 FCC Part 2 and Part 87 test results	5
Section 3 Equipment under test (EUT) details	6
3.1 Disclaimer	6
3.2 Sample information	6
3.3 Testing period	6
3.4 Applicant	6
3.5 Manufacturer	6
3.6 EUT information	6
3.7 EUT exercise and monitoring details	7
3.8 EUT setup details	7
Section 4 Engineering considerations	8
4.1 Modifications incorporated in the EUT	8
4.2 Technical judgement	8
4.3 Deviations from laboratory test procedures	8
Section 5 Test conditions	9
5.1 Atmospheric conditions	9
5.2 Power supply range	9
Section 6 Measurement uncertainty	10
6.1 Uncertainty of measurement	10
Section 7 Test equipment	11
7.1 Test equipment list	11
Section 8 Testing data	12
8.1 Bandwidth of emission (99%)	12
8.2 Bandwidth of emission (26 dB)	16
8.3 Power and emissions	20
8.4 Emission limitations	24
8.5 Transmitter spurious emissions	32
8.6 Frequency stability	53

Section 1 Report summary

1.1 Test specifications

FCC CFR 47 Part 2	Frequency Allocations and Radio Treaty Matters General Rules and Regulations
FCC CFR 47 Part 87	Aviation Services

1.2 Test methods

ANSI C63.26-2015	American National Standard of Procedures for Compliance Testing of Transmitters Used in Licensed Radio Services
------------------	---

1.3 Exclusions

None.

1.4 Statement of compliance

Testing was performed against all relevant requirements of the test standard(s).

Results obtained indicate that the product under test complies in full with the tested requirements.

The test results relate only to the item(s) tested.

See "Section 2 Summary of test results" for full details.

1.5 Test report revision history

Table 1.5-1: Test report revision history

Revision #	Issue Date	Details of changes made to test report
REP0030760-1TRFEMC	May 8, 2023	Original report issued
REP0030760-1R1TRFEMC	May 26, 2023	Test method typo: C63.10 was replaced by C63.26 (pages 20, 24,32). Calculation added at page 20.

Section 2 Summary of test results

2.1 FCC Part 2 and Part 87 test results

Part	Test description	Verdict
§2.1049 and Part 87.135 (a)	Bandwidth of emission	Pass
§2.1046 (a) and §87.131	Power and emissions	Pass
§87.139 (a)	Emission limitations	Pass
§2.1055 and §87.133 (a)	Frequency stability	Pass
§2.1051 and §87.139 (a)	Spurious emissions at antenna port	Not applicable ¹
§2.1053 and §87.139 (a)	Emission limitations	Pass

¹Note: Conducted port not available, except for frequency stability test where a special arrangement was configured.

Section 3 Equipment under test (EUT) details

3.1 Disclaimer

This section contains information provided by the applicant and has been utilized to support the test plan. Inaccurate information provided by the applicant can affect the validity of the results within this test report. Nemko accepts no responsibility for the information contained within this section and the impact it may have on the test plan and resulting measurements.

3.2 Sample information

Receipt date	24-Mar-23
Nemko sample ID number	REP0030760

3.3 Testing period

Test start date	27-Mar-23
Test end date	06-Apr-23

3.4 Applicant

Company name	Echodyne Corporation
Address	12112 115th Ave NE
City	Kirkland
State	WA
Postal/Zip code	98034
Country	United States of America

3.5 Manufacturer

Company name	Echodyne Corporation
Address	12112 115th Ave NE
City	Kirkland
State	WA
Postal/Zip code	98034
Country	United States of America

3.6 EUT information

Product name	Ku Band Radar
Model	EchoShield 700025-200
Variant(s)	N/A
Serial number	N/A
Part number	N/A
Power requirements	28 VDC
Description/theory of operation	Ground-based location and navigation radar
Software details	N/A
Operating band	Ku Band: 15.4 GHz – 15.7 GHz
Operational frequencies	15.45 GHz – 15.55 GHz – 15.65 GHz (25 MHz BW); 15.50 GHz – 15.55 GHz – 15.60 GHz (50 MHz BW); 15.55 GHz (100 MHz BW); 15.55 GHz (200 MHz BW).
Antenna type	AESA (Active Electronically Scanned Array)
Antenna gain (declared)	27 dBi

3.7 EUT exercise and monitoring details

EUT description of the methods used to exercise the EUT and all relevant ports:

- EUT was configured with a channel frequency and bandwidth fixed via ethernet port using a computer (via client’s software).

EUT setup/configuration rationale:

- The EUT setup in a configuration that was expected to produce the highest amplitude emissions.

3.8 EUT setup details

Table 3.8-1: EUT sub assemblies

Description	Brand name	Model/Part number	Serial number	Rev.
N/A	N/A	N/A	N/A	N/A

Table 3.8-2: EUT interface ports

Description	Qty.
1G Base-T Ethernet.	1

Table 3.8-3: Support equipment

Description	Brand name	Model/Part number	Serial number	Rev.
Control PC	ThinkPad	N/A	N/A	N/A
Universal AC/DC Power supply	Echodyne	N/A	N/A	--
Junction Box (1 Channel)	Echodyne	N/A	N/A	--

Table 3.8-4: Inter-connection cables

Cable description	From	To	Length (m)
Primary radar cable	EUT	Junction Box (1 CH)	2
CAT5e 1G Ethernet cable	Junction Box (1 CH)	Control PC	5
DC Power cable	Junction Box (1 CH)	Universal AC/DC Power supply	2
NEMA 5-15P Cable	AC Outlet	Universal AC/DC Power supply	1




Figure 3.8-1: Test setup diagram

Section 4 Engineering considerations

4.1 Modifications incorporated in the EUT

None.

4.2 Technical judgement

None.

4.3 Deviations from laboratory test procedures

None.

Section 5 Test conditions

5.1 Atmospheric conditions

Temperature	15–30 °C
Relative humidity	20–75 %
Air pressure	86–106 kPa

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

5.2 Power supply range

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages $\pm 5\%$, for which the equipment was designed.

Section 6 Measurement uncertainty

6.1 Uncertainty of measurement

Nemko USA Inc. has calculated measurement uncertainty and is documented in EMC/MUC/001 "Uncertainty in EMC measurements." Measurement uncertainty was calculated using the methods described in CISPR 16-4-2 Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainties, statistics, and limit modelling – Measurement instrumentation uncertainty. The expression of Uncertainty in EMC testing. Measurement uncertainty calculations assume a coverage factor of K=2 with 95% certainty.

Table 6.1-1: Measurement uncertainty calculations

Measurement		U_{cispr} dB	U_{lab} dB
Conducted disturbance at AC mains and other port power using a V-AMN	9 kHz to 150 kHz	3.8	2.9
	150 kHz to 30 MHz	3.4	2.3
Conducted disturbance at telecommunication port using AAN	150 kHz to 30 MHz	5.0	4.3
Conducted disturbance at telecommunication port using CVP	150 kHz to 30 MHz	3.9	2.9
Conducted disturbance at telecommunication port using CP	150 kHz to 30 MHz	2.9	1.4
Conducted disturbance at telecommunication port using CP and CVP	150 kHz to 30 MHz	4.0	3.1
Radiated disturbance (electric field strength in a SAC)	30 MHz to 1 GHz	6.3	5.5
Radiated disturbance (electric field strength in a FAR)	1 GHz to 6 GHz	5.2	4.7
Radiated disturbance (electric field strength in a FAR)	6 GHz to 18 GHz	5.5	5.0

- Notes: Compliance assessment:
- If U_{lab} is less than or equal to U_{cispr} then:
- compliance is deemed to occur is no measured disturbance level exceeds the disturbance limit;
 - non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit
- If U_{lab} is greater than U_{cispr} then:
- compliance is deemed to occur is no measured disturbance level, increased by $(U_{\text{lab}} - U_{\text{cispr}})$, exceeds the disturbance limit;
 - non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} - U_{\text{cispr}})$, exceeds the disturbance limit

V-AMN: V type artificial mains network
 AAN: Asymmetric artificial network
 CP: Current probe
 CVP: Capacitive voltage probe
 SAC: Semi-anechoic chamber
 FAR: Fully anechoic room

Section 7 Test equipment

7.1 Test equipment list

Table 7.1-1: Test equipment list

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
Signal & Spectrum Analyzer 2Hz / 43.5 GHz	Rohde & Schwarz	FSW43	E1302	1 year	Oct-20-2023
Antenna Horn	EMCO	3115	1033	2 years	Nov-02-2024
EMC Test Receiver	Rohde & Schwarz	ESU 40	E1121	1 year	May-31-2023
Antenna, Bilog	Schaffner-Chase	CBL6111C	1480	1 year	Feb-21-2024
Antenna, Horn	ETS-Lingren	3117-PA	E1139	2 years	April-19-2023
Standard Gain Horn Antenna	Eravant	SAZ-2410-42-S1	EW107	1 year	Nov-22-2023
Standard Gain Horn Antenna	Eravant	SAZ-2410-2-S1	EW108	1 year	Nov-22-2023
Low Noise Amplifier	Sage Millimeter	SBL-1834034030-KFKF-SI	E1228	NCR	NCR
Antenna, Horn	Sage Millimeter	SAR-2309-19-S2	E1144	NCR	NCR
Mixer	Rohde & Schwarz	FS-Z60	E1138	VOU	VOU
Antenna, Horn	Sage Millimeter	SAR-2408-15-S2	E1152	NCR	NCR
Mixer	Rohde & Schwarz	FS-Z75	E1149	VOU	VOU
Antenna, Horn	Sage Millimeter	SAR-2507-10-S2	E1146	NCR	NCR
Mixer	Rohde & Schwarz	FS-Z110	E1154	VOU	VOU
Environmental chamber	Cincinnati Sub-Zero	ZPH-32-2-2-H/ACa	S1179	1 year	Aug-29-2023
Low pass filter	RF-Lambda	RLPF13G14	PBC	VOU	VOU
High pass filter	Anatech Electronics	AE18000SSH6616	PBC	VOU	VOU
High pass filter	Anatech Electronics	AE18000SSH6615	PBC	VOU	VOU

Notes: N/A – not applicable
 NCR – no calibration required
 VOU – verify on use
 PBC – provided by client

Table 7.1-2: Test software details

Manufacturer of Software	Details
Rohde & Schwarz	EMC 32 V10.60.15

Notes: None

Section 8 Testing data

8.1 Bandwidth of emission (99%)

8.1.1 References and limits

- FCC 47 CFR Part 87: §87.135
- Test method: ANSI C63.26-2014 (5.4.4)

(a) Occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to 0.5 percent of the total mean power of a given emission.

(b) The authorized bandwidth is the maximum occupied bandwidth authorized to be used by a station.

(c) The necessary bandwidth for a given class of emission is the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

8.1.2 Test summary

Verdict	Pass		
Test date	March 29, 2023; March 30, 2023; March 31, 2023; April 3, 2023	Temperature	19°C; 20°C; 18°C; 20°C
Test engineer	Martha Espinoza, Wireless Test Engineer	Air pressure	1003mbar; 1005mbar; 1006mbar; 1001mbar
Test location	<input type="checkbox"/> Wireless bench <input checked="" type="checkbox"/> Other: 3M Chamber	Relative humidity	58%; 59%; 56%; 57%

8.1.3 Notes

Testing was performed with the transmitter operating on a fixed channel at full power.

Two modes related to the width of the radar pulse were tested and the summary of the time duration of each pulse is described in the following table:

Frequency	Bandwidth declared	Type of pulse	Time duration
15.45 GHz	25 MHz	Longest pulse	30 µs
15.55 GHz	25 MHz	Longest pulse	30 µs
15.65 GHz	25 MHz	Longest pulse	30 µs
15.50 GHz	50 MHz	Longest pulse	30 µs
15.55 GHz	50 MHz	Longest pulse	30 µs
15.60 GHz	50 MHz	Longest pulse	30 µs
15.55 GHz	100 MHz	Longest pulse	30 µs
15.55 GHz	200 MHz	Longest pulse	28.494 µs
15.45 GHz	25 MHz ¹	Shortest pulse	2 µs
15.55 GHz	25 MHz ¹	Shortest pulse	1 µs
15.65 GHz	25 MHz ¹	Shortest pulse	2 µs
15.50 GHz	50 MHz ¹	Shortest pulse	5 µs
15.55 GHz	50 MHz ¹	Shortest pulse	500 ns
15.60 GHz	50 MHz ¹	Shortest pulse	5 µs
15.55 GHz	100 MHz ¹	Shortest pulse	5 µs
15.55 GHz	200 MHz ¹	Shortest pulse	10 µs

Note 1: These bandwidths are declared only as reference, the real number is shown in table 8.1-2 of this section.

Table 8.1-1: Pulse description table.

Testing was done at 3 meters with the antenna and turntable fixed. A maximization of the signal was done to define the position of the max power:

Antenna height: 150 cm Turntable: 4.5 Degrees

8.1.4 Setup details

EUT power input during test	28 V DC
EUT setup configuration	<input type="checkbox"/> Table-top <input type="checkbox"/> Floor standing <input checked="" type="checkbox"/> Other: Tripod mounted (1.5 m)

Receiver settings:

Resolution bandwidth	Approximately 1-5 % of the emission bandwidth
Video bandwidth	Approximately 3 x resolution bandwidth
Detector mode	Peak
Trace mode	Max Hold
Measurement time	Long enough for trace to stabilize

8.1.5 Test data

Frequency	Bandwidth	Type of pulse	Time duration
15.45 GHz	24.602 MHz	Longest pulse	30 µs
15.55 GHz	24.721 MHz	Longest pulse	30 µs
15.65 GHz	24.712 MHz	Longest pulse	30 µs
15.50 GHz	48.404 MHz	Longest pulse	30 µs
15.55 GHz	48.461 MHz	Longest pulse	30 µs
15.60 GHz	48.520 MHz	Longest pulse	30 µs
15.55 GHz	97.008 MHz	Longest pulse	30 µs
15.55 GHz	193.090 MHz	Longest pulse	28.494 µs
15.45 GHz	27.858 MHz	Shortest pulse	2 µs
15.55 GHz	30.350 MHz	Shortest pulse	1 µs
15.65 GHz	27.635 MHz	Shortest pulse	2 µs
15.50 GHz	49.537 MHz	Shortest pulse	5 µs
15.55 GHz	59.623 MHz	Shortest pulse	500 ns
15.60 GHz	49.464 MHz	Shortest pulse	5 µs
15.55 GHz	97.975 MHz	Shortest pulse	5 µs
15.55 GHz	192.496 MHz	Shortest pulse	10 µs

Table 8.1-2: 99% OBW results.




Figure 8.1-1: 99% OBW Low channel: 15.45 GHz, longest pulse (25 MHz BW)






Figure 8.1-2: 99% OBW Middle channel: 15.55 GHz, longest pulse (25 MHz BW)



Section 8
Test name
Specification(s)

Testing data
 Bandwidth of emission (99%)
 FCC Part 87



Figure 8.1-3: 99% OBW High channel: 15.65 GHz, longest pulse (25 MHz BW)




Figure 8.1-5: 99% OBW Middle channel: 15.55 GHz, longest pulse (50 MHz BW)




Figure 8.1-7: 99% OBW Middle channel: 15.55 GHz, longest pulse (100 MHz BW)




Figure 8.1-9: 99% OBW Low channel: 15.45 GHz, shortest pulse (25 MHz BW)




Figure 8.1-4: 99% OBW Low channel: 15.50 GHz, longest pulse (50 MHz BW)




Figure 8.1-6: 99% OBW High channel: 15.60 GHz, longest pulse (50 MHz BW)




Figure 8.1-8: 99% OBW Middle channel: 15.55 GHz, longest pulse (200 MHz BW)




Figure 8.1-10: 99% OBW Middle channel: 15.55 GHz, shortest pulse (25 MHz BW)




Figure 8.1-11: 99% OBW High channel: 15.65 GHz, shortest pulse (25 MHz BW)




Figure 8.1-12: 99% OBW Low channel: 15.50 GHz, shortest pulse (50 MHz BW)



Figure 8.1-13: 99% OBW Middle channel: 15.55 GHz, shortest pulse (50 MHz BW)




Figure 8.1-15: 99% OBW Middle channel: 15.55 GHz, shortest pulse (100 MHz BW)

Figure 8.1-14: 99% OBW High channel: 15.60 GHz, shortest pulse (50 MHz BW)




Figure 8.1-16: 99% OBW Middle channel: 15.55 GHz, shortest pulse (200 MHz BW)

8.2 Bandwidth of emission (26 dB)

8.2.1 References and limits

- Test method: ANSI C63.26-2014 (5.4.3)

8.2.2 Test summary

Verdict	Pass		
Test date	March 29, 2023; March 30, 2023; March 31, 2023; April 3, 2023	Temperature	19°C; 20°C; 18°C; 20°C
Test engineer	Martha Espinoza, Wireless Test Engineer	Air pressure	1003mbar; 1005mbar; 1006mbar; 1001mbar
Test location	<input type="checkbox"/> Wireless bench <input checked="" type="checkbox"/> Other: 3M Chamber	Relative humidity	58%; 59%; 56%; 57%

8.2.3 Notes

Testing was performed with the transmitter operating on a fixed channel at full power following the cases shown on table 8.1-1 from section 8.1.3 of this document. This measurement is not a requirement, but it is used for the mask calculation shown on section 8.4 of this document.

Testing was done at 3 meters with the antenna and turntable fixed. A maximization of the signal was done to define the position of the max power:

Antenna height: 150 cm

Turntable: 4.5 Degrees

8.2.4 Setup details

EUT power input during test	28 V DC
EUT setup configuration	<input type="checkbox"/> Table-top <input type="checkbox"/> Floor standing <input checked="" type="checkbox"/> Other: Tripod mounted (1.5 m)

Receiver settings:

Resolution bandwidth	Approximately 1-5 % of the emission bandwidth
Video bandwidth	Approximately 3 x resolution bandwidth
Detector mode	Peak
Trace mode	Max Hold
Measurement time	Long enough for trace to stabilize

8.2.5 Test data

Frequency	Bandwidth	Type of pulse	Time duration
15.45 GHz	27.45 MHz	Longest pulse	30 μ s
15.55 GHz	27.63 MHz¹	Longest pulse	30 μ s
15.65 GHz	27.62 MHz	Longest pulse	30 μ s
15.50 GHz	52.40 MHz	Longest pulse	30 μ s
15.55 GHz	52.49 MHz	Longest pulse	30 μ s
15.60 GHz	52.65 MHz¹	Longest pulse	30 μ s
15.55 GHz	103.61 MHz²	Longest pulse	30 μ s
15.55 GHz	204.24 MHz²	Longest pulse	28.494 μ s
15.45 GHz	40.29 MHz³	Shortest pulse	2 μ s
15.55 GHz	44.09 MHz²	Shortest pulse	1 μ s
15.65 GHz	39.54 MHz	Shortest pulse	2 μ s
15.50 GHz	62.27 MHz	Shortest pulse	5 μ s
15.55 GHz	90.43 MHz²	Shortest pulse	500 ns
15.60 GHz	62.71 MHz³	Shortest pulse	5 μ s
15.55 GHz	116.34 MHz²	Shortest pulse	5 μ s
15.55 GHz	206.72 MHz²	Shortest pulse	10 μ s

Note 1: 26 dB bandwidth selected from the three channels under investigation to be used as common mask for the three cases.

Note 2: Single case.

Note 3: 26 dB bandwidth selected from the two channels with the same pulse width under investigation to be used as common mask for the two cases.

Table 8.2-1: 26 dB OBW results.




Figure 8.2-1: 26 dB OBW Low channel: 15.45 GHz, longest pulse (25 MHz BW)




Figure 8.2-2: 26 dB OBW Middle channel: 15.55 GHz, longest pulse (25 MHz BW)




Figure 8.2-3: 26 dB OBW High channel: 15.65 GHz, longest pulse (25 MHz BW)




Figure 8.2-4: 26 dB OBW Low channel: 15.50 GHz, longest pulse (50 MHz BW)

Section 8
Test name
Specification(s)

Testing data
 Bandwidth of emission (26 dB)
 FCC Part 87




Figure 8.2-5: 26 dB OBW Middle channel: 15.55 GHz, longest pulse (50 MHz BW)




Figure 8.2-6: 26 dB OBW High channel: 15.60 GHz, longest pulse (50 MHz BW)




Figure 8.2-7: 26 dB OBW Middle channel: 15.55 GHz, longest pulse (100 MHz BW)




Figure 8.2-8: 26 dB OBW Middle channel: 15.55 GHz, longest pulse (200 MHz BW)




Figure 8.2-9: 26 dB OBW Low channel: 15.45 GHz, shortest pulse (25 MHz BW)




Figure 8.2-10: 26 dB OBW Middle channel: 15.55 GHz, shortest pulse (25 MHz BW)




Figure 8.2-11: 26 dB OBW High channel: 15.65 GHz, shortest pulse (25 MHz BW)




Figure 8.2-12: 26 dB OBW Low channel: 15.50 GHz, shortest pulse (50 MHz BW)

Section 8
Test name
Specification(s)

Testing data
 Bandwidth of emission (26 dB)
 FCC Part 87




Figure 8.2-13: 26 dB OBW Middle channel: 15.55 GHz, shortest pulse (50 MHz BW)




Figure 8.2-14: 26 dB OBW High channel: 15.60 GHz, shortest pulse (50 MHz BW)




Figure 8.2-15: 26 dB OBW Middle channel: 15.55 GHz, shortest pulse (100 MHz BW)




Figure 8.2-16: 26 dB OBW Middle channel: 15.55 GHz, shortest pulse (200 MHz BW)

8.3 Power and emissions

8.3.1 References and limits

- FCC 47 CFR Part 87: §87.131
- Test method: ANSI C63.26-2014 (5.2.4.4.2)

The following table lists authorized emissions and maximum power. Power must be determined by direct measurement.

Class of station	Frequency band/frequency	Authorized emission(s) ⁷	Maximum power ¹
(Radionavigation)	Various ⁷	Various ⁷	Various. ⁷

⁷ Frequency, emission, and maximum power will be determined by appropriate standards during the certification process.

8.3.2 Test summary

Verdict	Pass		
Test date	March 29, 2023; March 30, 2023; March 31, 2023; April 3, 2023	Temperature	19°C; 20°C; 18°C; 20°C
Test engineer	Martha Espinoza, Wireless Test Engineer	Air pressure	1003mbar; 1005mbar; 1006mbar; 1001mbar
Test location	<input type="checkbox"/> Wireless bench <input checked="" type="checkbox"/> Other: 3M Chamber	Relative humidity	58%; 59%; 56%; 57%

8.3.3 Notes

Testing was performed with the transmitter operating on a fixed channel at full power following the cases shown on table 8.1-1 from section 8.1.3 of this document. All correction factors corresponding cables losses, receiving antenna gain, and air path losses were compensated to get the real EIRP value of the product. Both polarizations were evaluated, horizontal and vertical (linear polarization per client declaration) and only the worst case (max power) was taken for the testing purposes: horizontal polarization. The duty cycle correction factor was added according to each frequency channel tested. Table 8.3-1 shows the constant duty cycle corresponding to each case.

The equation to calculate the total correction factor corresponding to each frequency tested is given by the following expression as well as the table with the corresponding duty cycle to each case:

$$E.I.R.P = P_r - G_r - 20 \log_{10} \left(\frac{\lambda}{4\pi d} \right)$$

Adding cable losses and duty cycle correction factors (absolute values):

$$E.I.R.P = P_r - G_r - 20 \log_{10} \left(\frac{\lambda}{4\pi d} \right) + L_{cable} + 10 \log_{10} \left(\frac{1}{Duty\ cycle} \right)$$

Where:

P_r = Power received in the spectrum analyzer

λ = Wavelength of the signal

L_{cable} = Losses corresponding to interconnexion cables

d = Measuring distance (3 meters)

G_r = Receiving antenna gain

DC = Duty cycle declared

Example:

$$E.I.R.P = P_r - 15.555 - 20 \log_{10} \left(\frac{299792458}{15450000000} \right) + 19.434 + 10 \log_{10} \left(\frac{1}{0.15} \right)$$

$$E.I.R.P = P_r - 15.555 - (-65.768) + 19.434 + 8.239 = P_r + 77.886 \text{ (offset)}$$

8.3.3 Notes, continued

Frequency	Type of pulse	Time duration	Constant duty cycle
15.45 GHz	Longest pulse	30 µs	15%
15.55 GHz	Longest pulse	30 µs	15%
15.65 GHz	Longest pulse	30 µs	15%
15.50 GHz	Longest pulse	30 µs	15%
15.55 GHz	Longest pulse	30 µs	15%
15.60 GHz	Longest pulse	30 µs	15%
15.55 GHz	Longest pulse	30 µs	15%
15.55 GHz	Longest pulse	28.494 µs	15%
15.45 GHz	Shortest pulse	2 µs	10%
15.55 GHz	Shortest pulse	1 µs	10%
15.65 GHz	Shortest pulse	2 µs	10%
15.50 GHz	Shortest pulse	5 µs	10%
15.55 GHz	Shortest pulse	500 ns	10%
15.60 GHz	Shortest pulse	5 µs	10%
15.55 GHz	Shortest pulse	5 µs	10%
15.55 GHz	Shortest pulse	10 µs	10%

Table 8.3-1: Duty cycle table.

Testing was done at 3 meters with the antenna and turntable fixed. A maximization of the signal was done to define the position of the max power:
 Antenna height: 150 cm Turntable: 4.5 Degrees

8.3.4 Setup details

EUT power input during test	28 VDC
EUT setup configuration	<input type="checkbox"/> Table-top <input type="checkbox"/> Floor standing <input checked="" type="checkbox"/> Other: Tripod mounted (1.5 m)

Receiver settings:

Resolution bandwidth	Approximately 1-5 % of the emission bandwidth
Video bandwidth	Approximately 3 x resolution bandwidth
Detector mode	RMS
Trace mode	Average (at least 100 traces)
Measurement points	≥ (2xspan)/RBW
Span	2 times or 3 times the 99% OBW

8.3.5 Test data

Frequency	Power (EIRP)	Type of pulse	Time duration
15.45 GHz	74.31 dBm	Longest pulse	30 µs
15.55 GHz	74.74 dBm	Longest pulse	30 µs
15.65 GHz	73.79 dBm	Longest pulse	30 µs
15.50 GHz	75.09 dBm	Longest pulse	30 µs
15.55 GHz	75.55 dBm¹	Longest pulse	30 µs
15.60 GHz	75.34 dBm	Longest pulse	30 µs
15.55 GHz	74.67 dBm	Longest pulse	30 µs
15.55 GHz	75.17 dBm	Longest pulse	28.494 µs
15.45 GHz	73.82 dBm	Shortest pulse	2 µs
15.55 GHz	73.73 dBm	Shortest pulse	1 µs
15.65 GHz	72.61 dBm	Shortest pulse	2 µs
15.50 GHz	70.08 dBm	Shortest pulse	5 µs
15.55 GHz	71.93 dBm	Shortest pulse	500 ns
15.60 GHz	70.25 dBm	Shortest pulse	5 µs
15.55 GHz	73.50 dBm	Shortest pulse	5 µs
15.55 GHz	73.49 dBm	Shortest pulse	10 µs

Note 1: Max power measured (worst case)

Table 8.3-2: Power results (EIRP)




Figure 8.3-1: EIRP Power, Low channel: 15.45 GHz, longest pulse (25 MHz BW)




Figure 8.3-2: EIRP Power, Middle channel: 15.55 GHz, longest pulse (25 MHz BW)




Figure 8.3-3: EIRP Power, High channel: 15.65 GHz, longest pulse (25 MHz BW)




Figure 8.3-4: EIRP Power, Low channel: 15.50 GHz, longest pulse (50 MHz BW)




Figure 8.3-5: EIRP Power, Middle channel: 15.55 GHz, longest pulse (50 MHz BW)




Figure 8.3-6: EIRP Power, High channel: 15.60 GHz, longest pulse (50 MHz BW)




Figure 8.3-7: EIRP Power, Middle channel: 15.55 GHz, longest pulse (100 MHz BW)




Figure 8.3-8: EIRP Power, Middle channel: 15.55 GHz, longest pulse (200 MHz BW)

Section 8
Test name
Specification(s)

Testing data
 Power and emissions
 FCC Part 87




Figure 8.3-9EIRP Power, Low channel: 15.45 GHz, shortest pulse (25 MHz BW)




Figure 8.3-10: EIRP Power, Middle channel: 15.55 GHz, shortest pulse (25 MHz BW)




Figure 8.3-11: EIRP Power, High channel: 15.65 GHz, shortest pulse (25 MHz BW)




Figure 8.3-12: EIRP Power, Low channel: 15.50 GHz, shortest pulse (50 MHz BW)




Figure 8.3-13: EIRP Power, Middle channel: 15.55 GHz, shortest pulse (50 MHz BW)




Figure 8.3-14: EIRP Power, High channel: 15.60 GHz, shortest pulse (50 MHz BW)




Figure 8.3-15: EIRP Power, Middle channel: 15.55 GHz, shortest pulse (100 MHz BW)




Figure 8.3-16: EIRP Power, Middle channel: 15.55 GHz, shortest pulse (200 MHz BW)

8.4 Emission limitations

8.4.1 References and limits

- FCC 47 CFR Part 87: §87.139
- Test method: ANSI C63.26-2014 (5.5)

(a) Except for ELTs and when using single sideband (R3E, H3E, J3E), or frequency modulation (F9) or digital modulation (F9Y) for telemetry or telecommand in the 1435–1525 MHz, 2345–2395 MHz, or 5091–5150 MHz band or digital modulation (G7D) for differential GPS, the mean power of any emissions must be attenuated below the mean power of the transmitter (pY) as follows:

- (1) When the frequency is removed from the assigned frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth the attenuation must be at least 25 dB;
- (2) When the frequency is removed from the assigned frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth the attenuation must be at least 35 dB.
- (3) When the frequency is removed from the assigned frequency by more than 250 percent of the authorized bandwidth the attenuation for aircraft station transmitters must be at least 40 dB; and the attenuation for aeronautical station transmitters must be at least 43 + 10 log₁₀ pY dB.

8.4.2 Test summary

Verdict	Pass		
Test date	March 29, 2023; March 30, 2023; March 31, 2023; April 3, 2023	Temperature	19°C; 20°C; 18°C; 20°C
Test engineer	Martha Espinoza, Wireless Test Engineer	Air pressure	1003mbar; 1005mbar; 1006mbar; 1001mbar
Test location	<input type="checkbox"/> Wireless bench <input checked="" type="checkbox"/> Other: 3M Chamber	Relative humidity	58%; 59%; 56%; 57%

8.4.3 Notes

Testing was performed with the transmitter operating on a fixed channel at full power following the cases shown on table 8.1-1 from section 8.1.3 of this document. The width of the mask was defined according to the 26 dB bandwidth widest results (one measured bandwidth selected for each declared bandwidth and each pulse width) shown in table 8.2-1 from section 8.2.5 of this document.

The emission mask was separated into two sections of this document: section 8.4, range from 14 GHz to 18 GHz (including the frequency of operation within ±250% from occupied bandwidth) and section 8.5 which considered the emissions before 14 GHz and after 18 GHz.

The range between the ±250% is a relative limit, therefore, no correction factors were added. For the frequency range beyond ±250% the limit is an absolute value (-13 dBm), which means the corrections factors corresponding to air path losses and interconnection cables were added as an offset in the spectrum analyzer.

In this section, for the middle channel, 15.55 GHz, 25 MHz declared BW, shortest pulse (1 μs) and the middle channel, 15.55 GHz, 50 MHz declared BW, shortest pulse (500 ns), a frequency offset equivalent to RBW/2 in the edges of these channels was applied (frequency in band), according to the basic guidelines described on C63.26 (5.7.2). In the other cases, the mask was applied without frequency offset.

8.4.4 Setup details

EUT power input during test	28 V DC
EUT setup configuration	<input type="checkbox"/> Table-top <input type="checkbox"/> Floor standing <input checked="" type="checkbox"/> Other: Tripod mounted (1.5 m)

Receiver settings:

Resolution bandwidth	Approximately 1-5 % of the emission bandwidth
Video bandwidth	Approximately 3 x resolution bandwidth
Detector mode	RMS
Trace mode	Average (at least 100 traces)
Span	Enough to see the spectrum under investigation

8.4.5 Test data




Figure 8.4-1: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), Low channel: 15.45 GHz, longest pulse. (25 MHz BW)




Figure 8.4-3: Emission mask, beyond $\pm 250\%$ of BW (high frequency range), Low channel: 15.45 GHz, longest pulse. (25 MHz BW)




Figure 8.4-2: Emission mask, Low channel: 15.45 GHz, longest pulse. (25 MHz BW)




Figure 8.4-4: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), Middle channel: 15.55 GHz, longest pulse. (25 MHz BW)




Figure 8.4-5: Emission mask, Middle channel: 15.55 GHz, longest pulse. (25 MHz BW)




Figure 8.4-6: Emission mask, beyond $\pm 250\%$ of BW (high frequency range), Middle channel: 15.55 GHz, longest pulse. (25 MHz BW)




Figure 8.4-7: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), High channel: 15.65 GHz, longest pulse. (25 MHz BW)




Figure 8.4-9: Emission mask, beyond $\pm 250\%$ of BW (high frequency range), High channel: 15.65 GHz, longest pulse. (25 MHz BW)




Figure 8.4-11: Emission mask, Low channel: 15.50 GHz, longest pulse. (50 MHz BW)




Figure 8.4-13: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), Middle channel: 15.55 GHz, longest pulse. (50 MHz BW)




Figure 8.4-8: Emission mask, High channel: 15.65 GHz, longest pulse. (25 MHz BW)




Figure 8.4-10: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), Low channel: 15.50 GHz, longest pulse. (50 MHz BW)




Figure 8.4-12: Emission mask, beyond $\pm 250\%$ of BW (high frequency range), Low channel: 15.50 GHz, longest pulse. (50 MHz BW)




Figure 8.4-14: Emission mask, Middle channel: 15.55 GHz, longest pulse. (50 MHz BW)

Section 8
Test name
Specification(s)

Testing data
 Emission limitations
 FCC Part 87




Figure 8.4-15: Emission mask, beyond $\pm 250\%$ of BW (high frequency range), Middle channel: 15.55 GHz, longest pulse. (50 MHz BW)




Figure 8.4-16: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), High channel: 15.60 GHz, longest pulse. (50 MHz BW)




Figure 8.4-17: Emission mask, High channel: 15.60 GHz, longest pulse. (50 MHz BW)




Figure 8.4-18: Emission mask, beyond $\pm 250\%$ of BW (high frequency range), High channel: 15.60 GHz, longest pulse. (50 MHz BW)




Figure 8.4-19: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), Middle channel: 15.55 GHz, longest pulse. (100 MHz BW)




Figure 8.4-20: Emission mask, Middle channel: 15.55 GHz, longest pulse. (100 MHz BW)




Figure 8.4-21: Emission mask, beyond $\pm 250\%$ of BW (high frequency range), Middle channel: 15.55 GHz, longest pulse. (100 MHz BW)




Figure 8.4-22: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), Middle channel: 15.55 GHz, longest pulse. (200 MHz BW)




Figure 8.4-23: Emission mask, Middle channel: 15.55 GHz, longest pulse. (200 MHz BW)




Figure 8.4-24: Emission mask, beyond ±250% of BW (high frequency range), Middle channel: 15.55 GHz, longest pulse. (200 MHz BW)




Figure 8.4-25: Emission mask, beyond ±250% of BW (low frequency range), Low channel: 15.45 GHz, shortest pulse. (25 MHz BW)




Figure 8.4-26: Emission mask, Low channel: 15.45 GHz, shortest pulse. (25 MHz BW)




Figure 8.4-27: Emission mask, beyond ±250% of BW (high frequency range), Low channel: 15.45 GHz, shortest pulse. (25 MHz BW)




Figure 8.4-28: Emission mask, beyond ±250% of BW (low frequency range), Middle channel: 15.55 GHz, shortest pulse. (25 MHz BW)




Figure 8.4-29: Emission mask, Middle channel: 15.55 GHz, shortest pulse. (25 MHz BW). RBW/2 Added at the edges.




Figure 8.4-30: Emission mask, beyond ±250% of BW (high frequency range), Middle channel: 15.55 GHz, shortest pulse. (25 MHz BW)

Section 8
Test name
Specification(s)

Testing data
 Emission limitations
 FCC Part 87




Figure 8.4-31: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), High channel: 15.65 GHz, shortest pulse. (25 MHz BW)




Figure 8.4-33: Emission mask, beyond $\pm 250\%$ of BW (high frequency range), High channel: 15.65 GHz, shortest pulse. (25 MHz BW)




Figure 8.4-35: Emission mask, Low channel: 15.50 GHz, shortest pulse. (50 MHz BW)




Figure 8.4-37: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), Middle channel: 15.55 GHz, shortest pulse. (50 MHz BW)




Figure 8.4-32: Emission mask, High channel: 15.65 GHz, shortest pulse. (25 MHz BW)




Figure 8.4-34: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), Low channel: 15.50 GHz, shortest pulse. (50 MHz BW)




Figure 8.4-36: Emission mask, beyond $\pm 250\%$ of BW (high frequency range), Low channel: 15.50 GHz, shortest pulse. (50 MHz BW)




Figure 8.4-38: Emission mask, Middle channel: 15.55 GHz, shortest pulse. (50 MHz BW)

Section 8
Test name
Specification(s)

Testing data
 Emission limitations
 FCC Part 87




Figure 8.4-39: Emission mask, beyond $\pm 250\%$ of BW (high frequency range), Middle channel: 15.55 GHz, shortest pulse. (50 MHz BW)




Figure 8.4-41: Emission mask, High channel: 15.60 GHz, shortest pulse. (50 MHz BW)




Figure 8.4-43: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), Middle channel: 15.55 GHz, shortest pulse. (100 MHz BW)




Figure 8.4-45: Emission mask, beyond $\pm 250\%$ of BW (high frequency range), Middle channel: 15.55 GHz, shortest pulse. (100 MHz BW)




Figure 8.4-40: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), High channel: 15.60 GHz, shortest pulse. (50 MHz BW)




Figure 8.4-42: Emission mask, beyond $\pm 250\%$ of BW (high frequency range), High channel: 15.60 GHz, shortest pulse. (50 MHz BW)




Figure 8.4-44: Emission mask, Middle channel: 15.55 GHz, shortest pulse. (100 MHz BW)




Figure 8.4-46: Emission mask, beyond $\pm 250\%$ of BW (low frequency range), Middle channel: 15.55 GHz, shortest pulse. (200 MHz BW)




Figure 8.4-47: Emission mask, Middle channel: 15.55 GHz, shortest pulse. (200 MHz BW)




Figure 8.4-48: Emission mask, beyond ±250% of BW (high frequency range), Middle channel: 15.55 GHz, shortest pulse. (200 MHz BW)