

FCC ID: 2ANLJ-SMMMN17C01
Report No.: T190417W02-RP

Page: 1 / 31
Rev.: 02

FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Reserva Edge

Model No.: RESERVA-EDGE-10T-W

Trade Name: Reserva

Issued to

**ONELAN Ltd.
Bryants Farm, Kiln Road
Dunsden, Reading, RG4 9PB
United Kingdom**

Issued by

**Compliance Certification Services Inc.
Wugu Laboratory
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)
Issued Date: October 31, 2019**

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部分複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	May 20, 2019	Initial Issue	ALL	May Lin
01	August 15, 2019	See the following Note Rev. (01)	P.1, P.4-5	May Lin
02	October 31, 2019	See the following Note Rev. (02)	P.5	May Lin

Rev (01):

1. Revised the model number.

Rev (02):

1. Revised the EUT description.

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	4
2. EUT DESCRIPTION.....	5
3. TEST METHODOLOGY.....	6
3.1 EUT CONFIGURATION	6
3.2 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	6
3.3 DESCRIPTION OF TEST MODES.....	8
4. INSTRUMENT CALIBRATION.....	9
4.1 MEASURING INSTRUMENT CALIBRATION.....	9
4.2 MEASUREMENT EQUIPMENT USED.....	10
4.3 MEASUREMENT UNCERTAINTY	11
5. FACILITIES AND ACCREDITATIONS.....	12
5.1 FACILITIES.....	12
5.2 EQUIPMENT	12
6. SETUP OF EQUIPMENT UNDER TEST.....	13
6.1 SETUP CONFIGURATION OF EUT	13
6.2 SUPPORT EQUIPMENT	13
7. FCC PART 15.225 REQUIREMENTS & RSS-210 REQUIREMENTS.....	14
7.1 OCCUPIED BANDWIDTH (99%) AND 20 DB BANDWIDTH.....	14
7.2 RADIATED EMISSIONS	16
7.3 FREQUENCY STABILITY	27
7.4 POWERLINE CONDUCTED EMISSIONS	29
APPENDIX I PHOTOGRAPHS OF TEST SETUP.....	A-1
APPENDIX 1 - PHOTOGRAPHS OF EUT	

1. TEST RESULT CERTIFICATION

Applicant: ONELAN Ltd.
Bryants Farm, Kiln Road
Dunsden, Reading, RG4 9PB
United Kingdom

Manufacturer: ONELAN Ltd.
Bryants Farm, Kiln Road
Dunsden, Reading, RG4 9PB
United Kingdom

Equipment Under Test: Reserva Edge

Trade Name: Reserva

Model No.: RESERVA-EDGE-10T-W

Date of Test: April 23 ~ 24, 2019

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.225.


The test results of this report relate only to the tested sample identified in this report.

Approved by:



Kevin Tsai
Deputy Manager
Compliance Certification Services Inc.

Tested by:



Dally Hong
Engineer
Compliance Certification Services Inc.

2. EUT DESCRIPTION

Product	Reserva Edge
Model No.	RESERVA-EDGE-10T-W
Model Discrepancy	N/A
Trade	Reserva
Received Date	April 17, 2019
Power Supply	VDC from Power Adapter Model no: SYS1541-2412 I/P: 100-240Vac, 1.0A, 50-60Hz O/P: 12Vdc, 2.0A, 24W MAX
Frequency Range	13.56MHz
Modulation Technique	ASK
Number of Channels	1 Channel

Remark:

1. *The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.*

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10: 2013 and FCC CFR 47 Part 15.207, 15.209, 15.225.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.3 DESCRIPTION OF TEST MODES

The EUT had been tested under engineering test mode condition and the EUT staying in continuous transmitting mode.

3.3.1 The worst mode of measurement

AC Power Line Conducted Emission	
Test Condition	AC Power line conducted emission for line and neutral
Power supply Mode	Mode 1: EUT power by Adapter (DC 12V)
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4

Radiated Emission Measurement	
Test Condition	Band edge, Emission for Unwanted and Fundamental
Power supply Mode	Mode 1: EUT power by Adapter (DC 12V)
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4
Position	<input type="checkbox"/> Placed in fixed position. <input type="checkbox"/> Placed in fixed position at X-Plane (E2-Plane) <input checked="" type="checkbox"/> Placed in fixed position at Y-Plane (E1-Plane) <input type="checkbox"/> Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Adapter (DC 12V)
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis, X, Y, Z and two polarity, Horizontal and Vertical for radiated measurement. The worst case (Y-Plane and Vertical) were recorded in this report
3. AC power line conducted emission and for below 1G radiation emission were performed the EUT transmit at the highest output power channel as worse case.

4. INSTRUMENT CALIBRATION

4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

Report No.: T190417W02-RP

Page: 10 / 31
Rev.: 02

4.2 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Conducted Emissions Test Site					
Name of Equipment	Manufacturer	Model	S/N	Calibration Date	Calibration Due
Signal Analyzer	R&S	FSV 40	101073	09/27/2018	09/26/2019
Thermostatic/ Hrgrosatic Chamber	TAICHY	MHG-150LF	930619	10/08/2018	10/07/2019

Wugu 966 Chamber A					
Name of Equipment	Manufacturer	Model	S/N	Calibration Date	Calibration Due
Bilog Antenna	Sunol Sciences	JB3	A030105	07/13/2018	07/12/2019
Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/26/2019	02/25/2020
Digital Thermo- Hygro Meter	WISEWIND	1206	D07	01/30/2019	01/29/2020
Loop Ant	COM-POWER	AL-130	121051	03/22/2019	03/21/2020
Pre-Amplifier	EMEC	EM330	060609	02/26/2019	02/25/2020
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	05/31/2018	05/30/2019
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

AC Conducted Emissions Test Site					
Name of Equipment	Manufacturer	Model	S/N	Calibration Date	Calibration Due
CABLE	EMCI	CFD300-NL	CERF	06/29/2018	06/28/2019
EMI Test Receiver	R&S	ESCI	100064	07/24/2018	07/23/2019
LISN	SCHWARZBECK	NSLK 8127	8127-541	01/31/2019	01/30/2020
LISN	SCHAFFNER	NNB 41	03/10013	02/13/2019	02/12/2020
Software	EZ-EMC(CCS-3A1-CE)				

Remark:

1. Each piece of equipment is scheduled for calibration once a year.
2. N.C.R. = No Calibration Request.

4.3 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

- No.199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.
Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029
- No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)
Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10: 2013 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bucolical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix I for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT


No.	Device Type	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
	N/A						

Remark:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

7. FCC PART 15.225 REQUIREMENTS

7.1 OCCUPIED BANDWIDTH (99%) AND 20 dB BANDWIDTH TEST CONFIGURATION




TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=1kHz, VBW = 3kHz, Span = 10kHz, Sweep = auto.
4. Record the max. reading.

TEST RESULTS

No non-compliance noted

Test Condition	Frequency(MHz)	Occupied Bandwidth 99% (kHz)	20 dB Bandwidth (kHz)
NFC	13.56	2.0984	2.46

Test Plot

Date: 23 APR 2019 10:56:14

7.2 RADIATED EMISSIONS

LIMIT



According to §15.225

- (a) The field strength of any emissions within the band 13.553 – 13.567 MHz shall not exceed 15,848 microvolts / meter at 30 meters.
- (b) Within the bands 13.410 – 13.553 MHz and 13.567 – 13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts / meter at 30 meters.
- (c) Within the bands 13.110 – 13.410 MHz and 13.710 – 14.010 MHz the field strength of any emissions shall not exceed 106 microvolts / meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110 – 14.010 MHz and shall not exceed the general radiated emission limits in §15.209.

According to §15.225, except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μ V/m at meter)	Measurement Distance (meter)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

*** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.*

Test Configuration**9kHz ~ 30MHz****30MHz ~ 1GHz**

TEST PROCEDURE

For 9kHz ~ 30MHz

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, The center of the loop shall be 1 m above the ground then to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Set the spectrum analyzer in the following setting as:
9KHz-490KHz : RBW=200Hz / VBW=1kHz / Sweep=AUTO
490KHz-30MHz : RBW=10kHz / VBW=30kHz / Sweep=AUTO
6. Repeat above procedures until the measurements for all frequencies are complete.

For 30MHz ~ 1GHz

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
RBW=100kHz / VBW=300kHz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.


Remark :

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Report No.: T190417W02-RP

Page: 19 / 31
Rev.: 02

Operation Mode: TX mode **Test Date:** April 23, 2019
Temperature: 23°C **Tested by:** Dally Hong
Humidity: 53 % RH **Polarity:** Ver.




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	13.56	49.04	15.91	64.95	124.00	-59.05	peak

Remark:

1. Radiated emissions measured were made with an instrument using peak/quasi-peak/average detector mode.
2. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).

Operation Mode: TX mode **Test Date:** April 23, 2019
Temperature: 23°C **Tested by:** Dally Hong
Humidity: 53 % RH **Polarity:** Hor.




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	13.56	48.06	15.91	63.97	124.00	-60.03	peak

Remark:

1. Radiated emissions measured were made with an instrument using peak/quasi-peak/average detector mode.
2. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).

Operation Mode: TX mode **Test Date:** April 23, 2019
Temperature: 24°C **Tested by:** Dally Hong
Humidity: 53 % RH **Polarity:** Ver.




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	13.35	31.65	15.92	47.57	80.54	-32.97	peak
2	13.55	43.00	15.91	58.91	90.47	-31.56	peak
3	13.57	43.53	15.91	59.44	90.47	-31.03	peak
4	13.77	29.32	15.90	45.22	80.50	-35.28	peak

Remark:

1. Radiated emissions measured were made with an instrument using peak/quasi-peak/average detector mode.
2. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).

Operation Mode: TX mode **Test Date:** April 23, 2019
Temperature: 24°C **Tested by:** Dally Hong
Humidity: 53 % RH **Polarity:** Hor.



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	13.35	30.97	15.92	46.89	80.54	-33.65	peak
2	13.55	43.04	15.91	58.95	90.47	-31.52	peak
3	13.57	42.97	15.91	58.88	90.47	-31.59	peak
4	13.77	29.71	15.90	45.61	80.50	-34.89	peak


Remark:

1. Radiated emissions measured were made with an instrument using peak/quasi-peak/average detector mode.
2. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).

Report No.: T190417W02-RP

Page: 23 / 31
Rev.: 02**9kHz ~ 30MHz**

Operation Mode:	TX mode	Test Date:	April 23, 2019
Temperature:	24°C	Tested by:	Dally Hong
Humidity:	53 % RH	Polarity:	Ver.




Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Mode (PK/QP/AVG)
1.96	30.53	14.92	45.45	69.54	-24.09	peak
4.12	24.13	15.24	39.37	69.54	-30.17	peak
6.07	26.97	15.58	42.55	69.54	-26.99	peak
19.11	12.49	15.62	28.11	69.54	-41.43	peak
22.71	11.73	14.98	26.71	69.54	-42.83	peak
27.12	12.54	14.16	26.70	69.54	-42.84	peak

Report No.: T190417W02-RP

Page: 24 / 31
Rev.: 02**490kHz ~ 30MHz**

Operation Mode:	TX mode	Test Date:	April 23, 2019
Temperature:	24°C	Tested by:	Dally Hong
Humidity:	53 % RH	Polarity:	Hor.





Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Mode (PK/QP/AVG)
1.87	25.49	14.90	40.39	69.54	-29.15	peak
6.16	27.50	15.60	43.10	69.54	-26.44	peak
11.20	12.77	16.07	28.84	69.54	-40.70	peak
16.11	14.02	15.76	29.78	69.54	-39.76	peak
20.79	14.06	15.40	29.46	69.54	-40.08	peak
27.12	13.38	14.16	27.54	69.54	-42.00	peak

Report No.: T190417W02-RP

Page: 25 / 31
Rev.: 02**30MHz ~ 1GHz**

Operation Mode: TX mode **Test Date:** April 23, 2019
Temperature: 24°C **Tested by:** Dally Hong
Humidity: 53 % RH

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit 3m (dBuV/m)	Margin (dB)	Detector Mode (PK/QP/AVG)
39.70	43.10	-9.31	33.79	40.00	-6.21	peak
105.66	42.98	-11.02	31.96	43.50	-11.54	peak
277.35	33.83	-8.41	25.42	46.00	-20.58	peak
386.96	40.05	-6.17	33.88	46.00	-12.12	peak
555.74	34.39	-2.39	32.00	46.00	-14.00	peak
832.19	26.80	3.45	30.25	46.00	-15.75	peak
54.25	47.31	-15.95	31.36	40.00	-8.64	peak
122.15	36.57	-8.78	27.79	43.50	-15.71	peak
230.79	34.77	-10.80	23.97	46.00	-22.03	peak
416.06	28.45	-4.89	23.56	46.00	-22.44	peak
647.89	31.02	-0.06	30.96	46.00	-15.04	peak
833.16	28.00	3.51	31.51	46.00	-14.49	peak

Vertical**Horizontal**


7.3 FREQUENCY STABILITY

LIMIT

According to §15.225(e), the frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Configuration

Temperature and Voltage Measurement (under normal and extreme test conditions)



TEST PROCEDURE

1. Turn the EUT off, and place it inside the environmental temperature chamber.
2. Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.
3. Set the spectrum analyzer as RBW=1kHz, VBW = RBW, Span = 200kHz, Sweep = auto.
4. Turn the EUT on and record the operating frequency at startup and two, five, and ten minutes after the EUT is energized.
5. Switch off the EUT and Lower the chamber temperature by not more than 10 °C and allow the temperature inside the chamber to stabilize.
6. Mark the peak frequency and measure the frequency tolerance using frequency counter function.
7. Repeat step 4 through step 6 down to the lowest specified temperature.

TEST RESULTS

No non-compliance noted.

TEST DATA

Condition			Frequency Error (ppm)									
Temperature	Modulation Mode	Test Freq.	0 min	2 min	5 min	10 min	0 min	2 min	5 min	10 min	Limit (ppm)	Result
Normal												
T _{20°C} V _{max}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00	100	Pass
T _{20°C} V _{min}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00	100	Pass
Extreme												
T _{55°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00	100	Pass
T _{50°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{40°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{30°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{20°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{10°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{0°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{-10°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{0°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass

7.4 POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

TEST RESULTS


The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Operation Mode: NFC mode **Test Date:** April 24, 2019
Temperature: 24°C **Tested by:** Dally Hong
Humidity: 50% RH

Freq. (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Corr. factor (dB/m)	QP Result (dBuV/m)	AV Result (dBuV/m)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
0.1620	54.66	37.88	0.16	54.82	38.04	65.36	55.36	-10.54	-17.32	L1
0.1940	48.51	35.38	0.15	48.66	35.53	63.86	53.86	-15.20	-18.33	L1
0.2340	40.97	28.54	0.15	41.12	28.69	62.31	52.31	-21.19	-23.62	L1
0.4020	28.02	16.60	0.16	28.18	16.76	57.81	47.81	-29.63	-31.05	L1
6.5180	22.61	16.72	0.35	22.96	17.07	60.00	50.00	-37.04	-32.93	L1
15.4100	23.15	17.45	0.59	23.74	18.04	60.00	50.00	-36.26	-31.96	L1
0.1660	56.70	41.25	0.10	56.80	41.35	65.16	55.16	-8.36	-13.81	L2
0.1940	50.74	36.09	0.10	50.84	36.19	63.86	53.86	-13.02	-17.67	L2
0.2340	43.58	28.17	0.10	43.68	28.27	62.31	52.31	-18.63	-24.04	L2
0.3660	32.16	19.54	0.11	32.27	19.65	58.59	48.59	-26.32	-28.94	L2
1.2420	16.85	11.13	0.13	16.98	11.26	56.00	46.00	-39.02	-34.74	L2
13.5340	30.17	20.80	0.44	30.61	21.24	60.00	50.00	-29.39	-28.76	L2

Remark:

1. The measuring frequencies range between 0.15 MHz and 30 MHz.
2. The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.
3. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10kHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9kHz.
4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)
5. "-" means Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

Test Plots***Conducted emissions (Line 1)******Conducted emissions (Line 2)*****--End Report--**