

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a Ble voice & Infrared remote control with Bluetooth 5.0 function operating in 2402-2480MHz. The EUT is powered by DV 2*1.5V by AAA battery. For more detailed features description, please refer to the user's manual.

Standalone SAR evaluation for BT function

Bluetooth Version: 5.0 BLE mode

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 1.0dBi Max

The nominal conducted output power specified: -1.0dBm (+/-3dB)

The nominal radiated output power (e.i.r.p) specified: 0dBm (+/- 3dB)

According to the KDB 447498:

The maximum peak radiated emission for the EUT is 98.0dB μ V/m at 3m in the frequency 2402MHz

The EIRP = $[(FS * D)^2 / 30]$ mW = 2.77dBm

which is within the production variation.

The minimum peak radiated emission for the EUT is 94.5dB μ V/m at 3m in the frequency 2480MHz

The EIRP = $[(FS * D)^2 / 30]$ mW = -0.73dBm

which is within the production variation.

The maximum conducted output power specified is 2dBm = 1.58mW

The source-based time-averaging conducted output power

= 1.58 * Duty factor mW (where Duty Factor \leq 1)

= 1.58mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.480) mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.