



TEST REPORT

Part 15 Subpart C 15.247

Equipment under test remo+ Chime

Model name CHMU-1709

FCC ID 2ANMR-CHMU-1709

Applicant OLIVE AND DOVE CO., LTD.

Manufacturer OLIVE AND DOVE CO., LTD.

Date of test(s) 2017.11.01 ~ 2017.11.09

Date of issue 2017.11.21

Issued to

OLIVE AND DOVE CO., LTD.

803 Polaris bldg., 381, Seongnam-daero, Bundang-gu,

Seongnam-si, Gyeonggi-do, South Korea

Tel: +82-31-715-0717/ Fax: +82-31-715-0719

Issued by



KES Co., Ltd.

C-3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,

Gyeonggi-do, Korea

473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea

Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	Report approval by :
	
Kwon-se Kim Test engineer	Jeff Do Technical manager



KES Co., Ltd.

C-3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-RF-17T0117
Page (2) of (55)

Revision history

Revision	Date of issue	Test report No.	Description
-	2017.11.21	KES-RF-17T0117	Initial

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



TABLE OF CONTENTS

1.	General information	4
1.1.	EUT description	4
1.2.	Test configuration	4
1.3.	Device modifications.....	4
1.4.	Information about derivative model	4
1.5.	Frequency/channel operations	5
1.6.	Worst case data rate	5
1.7.	Accessory information.....	5
2.	Summary of tests	6
3.	Test results.....	7
3.1.	6 dB bandwidth	7
3.2.	Output power.....	11
3.3.	Power spectral density.....	13
3.4.	Radiated restricted band and emissions.....	17
3.5.	Conducted spurious emissions & band edge	48
3.6.	AC conducted emissions	52
Appendix A.	Measurement equipment	54
Appendix B.	Test setup photos	55

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



1. General information

Applicant: OLIVE AND DOVE CO., LTD.
Applicant address: 803 Polaris bldg., 381, Seongnam-daero, Bundang-gu,
Seongnam-si, Gyeonggi-do, South Korea
Test site: KES Co., Ltd.
Test site address: C-3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, Korea
473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea
Test Facility: FCC Accreditation Designation No.: KR0100, Registration No.: 444148
FCC rule part(s): 15.247
FCC ID: 2ANMR-CHMU-1709
Test device serial No.: Production Pre-production Engineering

1.1. EUT description

Equipment under test: remo+ Chime
Frequency range: 2412 MHz ~ 2462 MHz (11b/g/n_HT20)
Model: CHMU-1709
Modulation technique: DSSS, OFDM
Number of channels: 11ch (11b/g/n_HT20)
Antenna specification: Antenna type : PCB antenna, Peak gain : 3.77 dBi
Power source: DC 5 V

1.2. Test configuration

The **OLIVE AND DOVE CO., LTD. remo+ Chime FCC ID: 2ANMR-CHMU-1709** was tested per the guidance of KDB 558074 D01 v04, ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

1.3. Device modifications

N/A

1.4. Information about derivative model

N/A

1.5. Frequency/channel operations

Ch.	Frequency (MHz)	Mode
01	2412	802.11b/g/n_HT20
⋮	⋮	⋮
06	2437	802.11b/g/n_HT20
⋮	⋮	⋮
11	2462	802.11b/g/n_HT20

1.6. Worst case data rate

1. Radiated emission was performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.
2. Worst-case data rates were:
802.11b: **1 Mbps**
802.11g: **6 Mbps**
802.11n_HT20: **MCS0**

1.7. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
-	-	-	-	-



KES Co., Ltd.

C-3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-RF-17T0117
Page (6) of (55)

2. Summary of tests

Reference	Parameter	Test results
15.247(a)(2)	6 dB bandwidth	Pass
15.247(b)(3)	Peak output power	Pass
15.247(e)	Power spectral density	Pass
15.205 15.209	Radiated restricted band and emission	Pass
15.247(d)	Conducted spurious emission and band edge	Pass
15.207(a)	AC conducted emissions	Pass

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

3. Test results

3.1. 6 dB bandwidth

Test procedure

KDB 558074 D01 v04 – Section 8.1 or 8.2

Used test method is section 8.1.

Section 8.1

1. RBW = 100 kHz.
2. VBW $\geq 3 \times$ RBW.
3. Detector = peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Section 8.2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq 3 \times$ RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate 902 ~ 928 MHz, 2 400 ~ 2 483.5 MHz, and 5 725 ~ 5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.



KES Co., Ltd.


C-3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-RF-17T0117
Page (8) of (55)

Test results

6 dB bandwidth of 20 MHz bandwidth				
Measured 6 dB bandwidth(MHz)				Limit(MHz)
Frequency(MHz)	802.11b	802.11g	802.11n	
2412	8.97	16.14	15.85	0.5
2437	8.97	16.14	15.85	
2462	8.97	16.28	15.77	


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



802.11n(HT20)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

3.2. Output power

Test procedure

KDB 558074 D01 v04 – section 9.1.1 or 9.1.3 and 9.2.3.2

Used test method is section 9.1.3 , 9.2.3.2

Section 9.1.1

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

1. Set the RBW \geq DTS bandwidth.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 3 \times$ RBW
4. Sweep time = auto couple
5. Detector = peak
6. Trace mode = max hold
7. Allow trace to fully stabilize
8. Use peak marker function to determine the peak amplitude level

Section 9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Section 9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 MHz, 2 400~2 483.5 MHz, and 5 725~5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4), The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.



KES Co., Ltd.

C-3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-RF-17T0117
Page (12) of (55)

Test results

Measured output power (dBm)						
Mode	2412 MHz		2437 MHz		2462 MHz	
	Peak	Average	Peak	Average	Peak	Average
11b	18.91	15.64	18.20	14.87	17.73	14.39
11g	20.79	12.75	21.10	13.14	20.33	11.93
11n_HT 20	20.58	12.89	20.91	13.13	20.08	11.80

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

3.3. Power spectral density

Test procedure

KDB 558074 D01 v04- section 10.2

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW : $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW(no less than 3 kHz) and repeat.

Limit

According to §15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.



KES Co., Ltd.


C-3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-RF-17T0117
Page (14) of (55)


Test results

PSD of 20 MHz bandwidth				
Measured PDS(dBm/3kHz)				Limit(dBm/3kHz)
Frequency(MHz)	802.11b	802.11g	802.11n	
2412	-8.00	-11.98	-12.77	8
2437	-8.31	-11.78	-12.43	
2462	-8.74	-13.40	-13.24	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


3.4. Radiated restricted band and emissions

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.




The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



Test procedure below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

Test procedure above 30 MHz

1. Spectrum analyzer settings for $f < 1$ GHz:
 - ① Span = wide enough to fully capture the emission being measured
 - ② RBW = 100 kHz
 - ③ VBW \geq RBW
 - ④ Detector = quasi peak
 - ⑤ Sweep time = auto
 - ⑥ Trace = max hold
2. Spectrum analyzer settings for $f \geq 1$ GHz: Peak
 - ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
 - ② RBW = 1 MHz
 - ③ VBW \geq 3 MHz
 - ④ Detector = peak
 - ⑤ Sweep time = auto
 - ⑥ Trace = max hold
 - ⑦ Trace was allowed to stabilize

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

3. Spectrum analyzer settings for $f \geq 1$ GHz: Average

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW $\geq 3 \times$ RBW
- ④ Detector = RMS, if span/(# of points in sweep) \leq (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- ⑤ Averaging type = power(i.e., RMS)
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- ⑥ Sweep = auto
- ⑦ Trace = max hold
- ⑧ Perform a trace average of at least 100 traces.
- ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

Note.

1. $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m/D_s)$
 $f \geq 30$ MHz, extrapolation factor of 20 dB/decade of distance. $F_d = 20 \log(D_m/D_s)$
Where:
 F_d = Distance factor in dB
 D_m = Measurement distance in meters
 D_s = Specification distance in meters
3. CF(Correction factors(dB)) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or F_d (dB)
4. Field strength(dB μ V/m) = Level(dB μ V) + CF (dB) + or DCF(dB)
5. Margin(dB) = Limit(dB μ V/m) - Field strength(dB μ V/m)
6. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation**.
8. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
9. All channels, modes (e.g. 802.11b/g/n (20 MHz BW)), and modulations/data rates were investigated among DTS band. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.



10. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated ($\mu V/m$)
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

Duty cycle


Regarding to KDB 558074 D01_v04, 6.0, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below.

Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100.

Test mode	T _{on} time (ms)	Period (ms)	Duty cycle (Linear)	Duty cycle (%)	Duty cycle correction factor (dB)
802.11b	4.202 9	4.724 6	0.889 6	88.96	0.51
802.11g	0.695 7	0.797 1	0.872 8	87.28	0.59
802.11n(HT20)	0.652 2	0.753 6	0.865 4	86.54	0.63

Duty cycle (Linear) = T_{on} time/Period

DCF(Duty cycle correction factor (dB)) = 10log(1/duty cycle)



N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Test results (Below 30 MHz)

Mode: 802.11g
 Distance of measurement: 3 meter
 Channel: 06 (Worst case)

Frequency (MHz)	Level (dB μ V)	Ant. Pol. (H/V)	CF (dB)	F _d (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
No spurious emissions were detected within 20 dB of the limit							




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Test results (Below 1 000 MHz) – Worst case

Mode: 802.11g
 Distance of measurement: 3 meter
 Channel: 06 (Worst case)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Test results (Above 1 000 MHz)

Mode: 802.11b
Distance of measurement: 3 meter
Channel: 01


- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 369.00	48.48	Peak	H	-6.77	-	41.71	74.00	32.29
1 560.10	47.76	Peak	H	-5.38	-	42.38	74.00	31.62
1 754.00	47.21	Peak	H	-3.52	-	43.69	74.00	30.31
1 982.60	46.92	Peak	H	-1.15	-	45.77	74.00	28.23
4 834.00	54.10	Peak	H	7.82	-	61.92	74.00	12.08
4 834.00	35.01	Avg	H	7.82	0.51	43.34	54.00	10.66
1 296.70	48.29	Peak	V	-7.24	-	41.05	74.00	32.95
1 568.70	47.69	Peak	V	-5.30	-	42.39	74.00	31.61
1 837.90	48.88	Peak	V	-2.68	-	46.20	74.00	27.80
2 165.00	49.88	Peak	V	-0.64	-	49.24	74.00	24.76
3 206.00	47.72	Peak	V	1.76	-	49.48	74.00	24.52
4 834.00	49.44	Peak	V	7.82	-	57.26	74.00	16.74
4 834.00	34.52	Avg	V	7.82	0.51	42.85	54.00	11.15


- Band edge

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 384.10	52.33	Peak	H	-0.23	-	52.10	74.00	21.90
2 386.35	49.21	Peak	V	-0.23	-	48.98	74.00	25.02

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



KES Co., Ltd.

C-3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr


Test report No.:
KES-RF-17T0117
Page (27) of (55)

Mode: 802.11b
Distance of measurement: 3 meter
Channel: 06

- **Spurious**

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 513.70	48.05	Peak	H	-5.84	-	42.21	74.00	31.79
1 751.10	47.64	Peak	H	-3.54	-	44.10	74.00	29.90
2 185.20	46.98	Peak	H	-0.61	-	46.37	74.00	27.63
4 878.00	51.63	Peak	H	8.17	-	59.80	74.00	14.20
4 878.00	35.64	Avg	H	8.17	0.51	44.32	54.00	9.68
1 837.90	48.36	Peak	V	-2.68	-	45.68	74.00	28.32
2 162.10	49.39	Peak	V	-0.65	-	48.74	74.00	25.26
3 250.00	47.68	Peak	V	1.76	-	49.44	74.00	24.57
4 877.70	51.24	Peak	V	8.16	-	59.40	74.00	14.60
4 877.70	34.93	Avg	V	8.16	0.51	43.60	54.00	10.40

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




Mode: 802.11b
 Distance of measurement: 3 meter
 Channel: 11

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 560.10	47.89	Peak	H	-5.38	-	42.51	74.00	31.49
1 754.00	47.69	Peak	H	-3.52	-	44.17	74.00	29.83
4 921.00	52.99	Peak	H	8.50	-	61.49	74.00	12.51
4 921.00	37.17	Avg	H	8.50	0.51	46.18	54.00	7.82
1 102.70	48.29	Peak	V	-8.48	-	39.81	74.00	34.19
1 837.90	48.58	Peak	V	-2.68	-	45.90	74.00	28.10
2 162.10	48.91	Peak	V	-0.65	-	48.26	74.00	25.74
4 921.10	50.32	Peak	V	8.50	-	58.82	74.00	15.18
4 921.10	35.06	Avg	V	8.50	0.51	44.07	54.00	9.93
7 396.00	46.55	Peak	V	12.10	-	58.65	74.00	15.35
7 396.00	32.60	Avg	V	12.10	0.51	45.21	54.00	8.79

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 484.06	51.27	Peak	H	-0.04	-	51.23	74.00	22.77
2 483.66	50.83	Peak	V	-0.05	-	50.78	74.00	23.22



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

**KES Co., Ltd.**

C-3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-RF-17T0117
Page (31) of (55)

Mode: 802.11g
Distance of measurement: 3 meter
Channel: 01


- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 513.70	47.80	Peak	H	-5.84	-	41.96	74.00	32.04
1 560.10	48.01	Peak	H	-5.38	-	42.63	74.00	31.37
1 751.10	47.11	Peak	H	-3.54	-	43.57	74.00	30.43
4 834.00	51.05	Peak	H	7.82	-	58.87	74.00	15.13
4 834.00	35.61	Avg	H	7.82	0.59	44.02	54.00	9.98
1 843.70	49.20	Peak	V	-2.62	-	46.58	74.00	27.42
2 165.00	51.12	Peak	V	-0.64	-	50.48	74.00	23.52
3 206.00	48.77	Peak	V	1.76	-	50.53	74.00	23.47
4 769.00	45.87	Peak	V	7.30	-	53.17	74.00	20.83
4 769.00	34.08	Avg	V	7.30	0.59	41.97	54.00	12.03


- Band edge

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 390.00	63.82	Peak	H	-0.22	-	63.60	74.00	10.40
2 390.00	47.25	Avg	H	-0.22	0.59	47.62	54.00	6.38
2 389.13	60.14	Peak	V	-0.22	-	59.92	74.00	14.08
2 390.00	45.62	Avg	V	-0.22	0.59	45.99	54.00	8.01

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



KES Co., Ltd.

C-3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr


Test report No.:
KES-RF-17T0117
Page (34) of (55)

Mode: 802.11g
Distance of measurement: 3 meter
Channel: 06

- **Spurious**

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 369.00	48.33	Peak	H	-6.77	-	41.56	74.00	32.44
1 751.10	47.95	Peak	H	-3.54	-	44.41	74.00	29.59
4 878.00	47.62	Peak	H	8.17	-	55.79	74.00	18.21
4 878.00	35.34	Avg	H	8.17	0.59	44.10	54.00	9.90
1 172.20	48.97	Peak	V	-8.04	-	40.93	74.00	33.07
1 837.90	48.46	Peak	V	-2.68	-	45.78	74.00	28.22
2 162.10	49.13	Peak	V	-0.65	-	48.48	74.00	25.52
3 250.00	46.57	Peak	V	1.76	-	48.33	74.00	25.68
4 877.70	46.82	Peak	V	8.16	-	54.98	74.00	19.02
4 877.70	34.54	Avg	V	8.16	0.59	43.29	54.00	10.71

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

**KES Co., Ltd.**

C-3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-RF-17T0117
Page (36) of (55)

Mode: 802.11g
Distance of measurement: 3 meter
Channel: 11

- Spurious


Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 369.00	49.35	Peak	H	-6.77	-	42.58	74.00	31.42
1 464.50	47.74	Peak	H	-6.19	-	41.55	74.00	32.45
1 754.00	47.59	Peak	H	-3.52	-	44.07	74.00	29.93
2 277.90	48.15	Peak	H	-0.43	-	47.72	74.00	26.28
4 943.00	49.84	Peak	H	8.67	-	58.51	74.00	15.49
4 921.00	36.91	Avg	H	8.50	0.59	46.00	54.00	8.00
1 837.90	49.55	Peak	V	-2.68	-	46.87	74.00	27.13
2 165.00	49.09	Peak	V	-0.64	-	48.45	74.00	25.55
3 293.00	47.89	Peak	V	1.75	-	49.64	74.00	24.36
4 921.10	49.03	Peak	V	8.50	-	57.53	74.00	16.47
4 921.10	35.03	Avg	V	8.50	0.59	44.12	54.00	9.88

- Band edge


Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 483.50	62.33	Peak	H	-0.05	-	62.28	74.00	11.72
2 483.50	44.74	Avg	H	-0.05	0.59	45.28	54.00	8.72
2 483.58	69.58	Peak	V	-0.05	-	69.53	74.00	4.47
2 483.66	49.46	Avg	V	-0.05	0.59	50.00	54.00	4.00

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Note.

1 Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Mode: 802.11n(HT20)
Distance of measurement: 3 meter
Channel: 01


- **Spurious**

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 369.00	48.69	Peak	H	-6.77	-	41.92	74.00	32.08
1 513.70	47.69	Peak	H	-5.84	-	41.85	74.00	32.15
1 560.10	47.66	Peak	H	-5.38	-	42.28	74.00	11.72
4 834.00	48.13	Peak	H	7.82	-	55.95	74.00	18.05
4 834.00	35.44	Avg	H	7.82	0.63	43.89	54.00	10.11
1 675.80	46.89	Peak	V	-4.26	-	42.63	74.00	31.37
1 843.70	48.79	Peak	V	-2.62	-	46.17	74.00	27.83
2 165.00	50.68	Peak	V	-0.64	-	50.04	74.00	23.96
3 206.00	48.14	Peak	V	1.76	-	49.90	74.00	24.10


- **Band edge**

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 390.00	65.39	Peak	H	-0.22	-	65.17	74.00	8.83
2 390.00	48.57	Avg	H	-0.22	0.63	48.98	54.00	5.02
2 390.00	61.51	Peak	V	-0.22	-	61.29	74.00	12.71
2 389.83	47.74	Avg	V	-0.22	0.63	48.15	54.00	5.85

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



KES Co., Ltd.

C-3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr


Test report No.:
KES-RF-17T0117
Page (42) of (55)

Mode: 802.11n(HT20)
Distance of measurement: 3 meter
Channel: 06

- **Spurious**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 560.10	48.43	Peak	H	-5.38	-	43.05	74.00	30.95
1 754.00	48.47	Peak	H	-3.52	-	44.95	74.00	29.05
4 878.00	47.10	Peak	H	8.17	-	55.27	74.00	18.73
4 878.00	35.70	Avg	H	8.17	0.63	44.50	54.00	9.50
1 837.90	48.34	Peak	V	-2.68	-	45.66	74.00	28.34
2 165.00	49.47	Peak	V	-0.64	-	48.83	74.00	25.17
3 250.00	47.02	Peak	V	1.76	-	48.78	74.00	25.23
4 878.00	46.80	Peak	V	8.17	-	54.97	74.00	19.03
4 878.00	36.45	Avg	V	8.17	0.63	45.25	54.00	8.75

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Note.

1. Average test would be performed if the peak were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Mode: 802.11n(HT20)
Distance of measurement: 3 meter
Channel: 11


- **Spurious**

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 513.70	47.70	Peak	H	-5.84	-	41.86	74.00	32.14
1 754.00	47.41	Peak	H	-3.52	-	43.89	74.00	30.11
4 921.00	52.64	Peak	H	8.50	-	61.14	74.00	12.86
4 921.00	37.73	Avg	H	8.50	0.63	46.86	54.00	7.14
1 832.10	47.87	Peak	V	-2.74	-	45.13	74.00	28.87
2 165.00	50.14	Peak	V	-0.64	-	49.50	74.00	24.50
3 293.00	47.70	Peak	V	1.75	-	49.45	74.00	24.55
4 921.10	49.08	Peak	V	8.50	-	57.58	74.00	16.42
4 921.10	36.14	Avg	V	8.50	0.63	45.27	54.00	8.73
7 374.00	46.24	Peak	V	12.00	-	58.24	74.00	15.76
7 374.00	33.65	Avg	V	12.00	0.63	46.28	54.00	7.72


- **Band edge**

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 483.90	67.98	Peak	H	-0.05	-	67.93	74.00	6.07
2 483.58	50.36	Avg	H	-0.05	0.63	50.94	54.00	3.06
2 484.22	65.91	Peak	V	-0.04	-	65.87	74.00	8.13
2 483.50	47.78	Avg	V	-0.05	0.63	48.36	54.00	5.64

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Test results (18 GHz to 30 GHz) – Worst case

Mode: 802.11g
 Distance of measurement: 3 meter
 Channel: 06 (Worst case)



Note.

1. No spurious emission were detected above 18 GHz.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

3.5 Conducted spurious emissions & band edge

Test procedure

Band edge

KDB 558074 D01 v04 – Section 11.3

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100 kHz
4. VBW = 300 kHz
5. Detector = Peak
6. Trace mode = max hold
7. Sweep time = auto
8. The trace was allowed to stabilize

Out of band emissions


KDB 558074 D01 v04 – Section 11.3

1. Start frequency was set to 30 MHz and stop frequency was set to 25 GHz for 2.4 GHz frequencies and 40 GHz for 5 GHz frequencies
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize


Limit

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))

Test results




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

802.11n(HT20)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

3.6 AC conducted emissions

Limit



According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted limit (dB μ V/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

Note:

1. All AC line conducted spurious emission are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and the appropriate frequencies. All data rates and modes were investigated for conducted spurious emission. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.
2. Both Cable loss and LISN factor are included in measurement level(QP Level or AV Level).

Test results

Hot Line																																																																																																																						
	<p>Final Result</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Frequency (MHz)</th> <th>QuasiPeak (dBµV)</th> <th>CAverage (dBµV)</th> <th>Limit (dBµV)</th> <th>Margin (dB)</th> <th>Meas. Time (ms)</th> <th>Bandwidth (kHz)</th> <th>Line</th> <th>Corr. (dB)</th> </tr> </thead> <tbody> <tr><td>0.270000</td><td>---</td><td>21.18</td><td>51.12</td><td>29.94</td><td>1000.0</td><td>9.000</td><td>N</td><td>19.5</td></tr> <tr><td>0.270000</td><td>40.26</td><td>---</td><td>61.12</td><td>20.86</td><td>1000.0</td><td>9.000</td><td>N</td><td>19.5</td></tr> <tr><td>1.175000</td><td>---</td><td>16.71</td><td>46.00</td><td>29.29</td><td>1000.0</td><td>9.000</td><td>N</td><td>20.1</td></tr> <tr><td>1.175000</td><td>19.49</td><td>---</td><td>56.00</td><td>36.51</td><td>1000.0</td><td>9.000</td><td>N</td><td>20.1</td></tr> <tr><td>4.965000</td><td>---</td><td>13.26</td><td>46.00</td><td>32.74</td><td>1000.0</td><td>9.000</td><td>N</td><td>19.8</td></tr> <tr><td>4.965000</td><td>21.25</td><td>---</td><td>56.00</td><td>34.75</td><td>1000.0</td><td>9.000</td><td>N</td><td>19.8</td></tr> <tr><td>5.410000</td><td>---</td><td>13.41</td><td>50.00</td><td>36.59</td><td>1000.0</td><td>9.000</td><td>N</td><td>19.7</td></tr> <tr><td>5.410000</td><td>22.25</td><td>---</td><td>60.00</td><td>37.75</td><td>1000.0</td><td>9.000</td><td>N</td><td>19.7</td></tr> <tr><td>5.540000</td><td>---</td><td>15.78</td><td>50.00</td><td>34.22</td><td>1000.0</td><td>9.000</td><td>N</td><td>19.7</td></tr> <tr><td>5.540000</td><td>24.74</td><td>---</td><td>60.00</td><td>35.26</td><td>1000.0</td><td>9.000</td><td>N</td><td>19.7</td></tr> </tbody> </table>	Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	0.270000	---	21.18	51.12	29.94	1000.0	9.000	N	19.5	0.270000	40.26	---	61.12	20.86	1000.0	9.000	N	19.5	1.175000	---	16.71	46.00	29.29	1000.0	9.000	N	20.1	1.175000	19.49	---	56.00	36.51	1000.0	9.000	N	20.1	4.965000	---	13.26	46.00	32.74	1000.0	9.000	N	19.8	4.965000	21.25	---	56.00	34.75	1000.0	9.000	N	19.8	5.410000	---	13.41	50.00	36.59	1000.0	9.000	N	19.7	5.410000	22.25	---	60.00	37.75	1000.0	9.000	N	19.7	5.540000	---	15.78	50.00	34.22	1000.0	9.000	N	19.7	5.540000	24.74	---	60.00	35.26	1000.0	9.000	N	19.7																		
Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)																																																																																																														
0.270000	---	21.18	51.12	29.94	1000.0	9.000	N	19.5																																																																																																														
0.270000	40.26	---	61.12	20.86	1000.0	9.000	N	19.5																																																																																																														
1.175000	---	16.71	46.00	29.29	1000.0	9.000	N	20.1																																																																																																														
1.175000	19.49	---	56.00	36.51	1000.0	9.000	N	20.1																																																																																																														
4.965000	---	13.26	46.00	32.74	1000.0	9.000	N	19.8																																																																																																														
4.965000	21.25	---	56.00	34.75	1000.0	9.000	N	19.8																																																																																																														
5.410000	---	13.41	50.00	36.59	1000.0	9.000	N	19.7																																																																																																														
5.410000	22.25	---	60.00	37.75	1000.0	9.000	N	19.7																																																																																																														
5.540000	---	15.78	50.00	34.22	1000.0	9.000	N	19.7																																																																																																														
5.540000	24.74	---	60.00	35.26	1000.0	9.000	N	19.7																																																																																																														
Neutral Line																																																																																																																						
	<p>Final Result</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Frequency (MHz)</th> <th>QuasiPeak (dBµV)</th> <th>CAverage (dBµV)</th> <th>Limit (dBµV)</th> <th>Margin (dB)</th> <th>Meas. Time (ms)</th> <th>Bandwidth (kHz)</th> <th>Line</th> <th>Corr. (dB)</th> </tr> </thead> <tbody> <tr><td>0.270000</td><td>---</td><td>21.83</td><td>51.12</td><td>29.29</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.5</td></tr> <tr><td>0.270000</td><td>40.96</td><td>---</td><td>61.12</td><td>20.16</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.5</td></tr> <tr><td>0.400000</td><td>---</td><td>15.06</td><td>47.85</td><td>32.79</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.7</td></tr> <tr><td>0.400000</td><td>33.92</td><td>---</td><td>57.85</td><td>23.93</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.7</td></tr> <tr><td>4.915000</td><td>---</td><td>17.56</td><td>46.00</td><td>28.44</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.8</td></tr> <tr><td>4.915000</td><td>27.49</td><td>---</td><td>56.00</td><td>28.51</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.8</td></tr> <tr><td>4.965000</td><td>---</td><td>18.20</td><td>46.00</td><td>27.80</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.8</td></tr> <tr><td>4.965000</td><td>28.05</td><td>---</td><td>56.00</td><td>27.95</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.8</td></tr> <tr><td>5.550000</td><td>---</td><td>20.58</td><td>50.00</td><td>29.42</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.7</td></tr> <tr><td>5.550000</td><td>30.36</td><td>---</td><td>60.00</td><td>29.64</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.7</td></tr> <tr><td>5.825000</td><td>---</td><td>17.43</td><td>50.00</td><td>32.57</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.7</td></tr> <tr><td>5.825000</td><td>27.63</td><td>---</td><td>60.00</td><td>32.37</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.7</td></tr> </tbody> </table>	Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	0.270000	---	21.83	51.12	29.29	1000.0	9.000	L1	19.5	0.270000	40.96	---	61.12	20.16	1000.0	9.000	L1	19.5	0.400000	---	15.06	47.85	32.79	1000.0	9.000	L1	19.7	0.400000	33.92	---	57.85	23.93	1000.0	9.000	L1	19.7	4.915000	---	17.56	46.00	28.44	1000.0	9.000	L1	19.8	4.915000	27.49	---	56.00	28.51	1000.0	9.000	L1	19.8	4.965000	---	18.20	46.00	27.80	1000.0	9.000	L1	19.8	4.965000	28.05	---	56.00	27.95	1000.0	9.000	L1	19.8	5.550000	---	20.58	50.00	29.42	1000.0	9.000	L1	19.7	5.550000	30.36	---	60.00	29.64	1000.0	9.000	L1	19.7	5.825000	---	17.43	50.00	32.57	1000.0	9.000	L1	19.7	5.825000	27.63	---	60.00	32.37	1000.0	9.000	L1	19.7
Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)																																																																																																														
0.270000	---	21.83	51.12	29.29	1000.0	9.000	L1	19.5																																																																																																														
0.270000	40.96	---	61.12	20.16	1000.0	9.000	L1	19.5																																																																																																														
0.400000	---	15.06	47.85	32.79	1000.0	9.000	L1	19.7																																																																																																														
0.400000	33.92	---	57.85	23.93	1000.0	9.000	L1	19.7																																																																																																														
4.915000	---	17.56	46.00	28.44	1000.0	9.000	L1	19.8																																																																																																														
4.915000	27.49	---	56.00	28.51	1000.0	9.000	L1	19.8																																																																																																														
4.965000	---	18.20	46.00	27.80	1000.0	9.000	L1	19.8																																																																																																														
4.965000	28.05	---	56.00	27.95	1000.0	9.000	L1	19.8																																																																																																														
5.550000	---	20.58	50.00	29.42	1000.0	9.000	L1	19.7																																																																																																														
5.550000	30.36	---	60.00	29.64	1000.0	9.000	L1	19.7																																																																																																														
5.825000	---	17.43	50.00	32.57	1000.0	9.000	L1	19.7																																																																																																														
5.825000	27.63	---	60.00	32.37	1000.0	9.000	L1	19.7																																																																																																														

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Appendix A. Measurement equipment

Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
Spectrum Analyzer	R&S	FSV40	101002	1 year	2018.07.04
8360B Series Swept Signal Generator	HP	83630B	3844A00786	1 year	2018.01.23
Power Meter	Anritsu	ML2495A	1438001	1 year	2018.01.23
Pulse Power Sensor	Anritsu	MA2411B	1339205	1 year	2018.01.23
Attenuator	Agilent	8493C	51401	1 year	2018.07.04
Loop Antenna	Schwarzbeck	FMZB1513	225	2 years	2019.05.10
Trilog-broadband antenna	SCHWARZBECK	VULB 9163	9168-714	2 years	2018.11.28
Horn Antenna	A.H	SAS-571	414	2 years	2019.02.15
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170550	2 years	2019.02.15
High Pass Filter	Wainwright Instrument Gmbh	WHJS3000-10TT	1	1 year	2018.07.03
Low Pass Filter	Wainwright Instrument Gmbh	WLK1.0/18G-10TT	1	1 year	2018.07.03
Preamplifier	HP	8449B	3008A00538	1 year	2018.01.19
Preamplifier	AGILENT	8449B	3008A01729	1 year	2018.05.31
EMI Test Receiver	R&S	ESR3	101781	1 year	2018.04.27
EMI Test Receiver	R&S	ESU26	100552	1 year	2018.04.19
Pulse Limiter	R&S	ESH3-Z2	101915	1 year	2017.12.13
LISN	R&S	ENV216	101787	1 year	2018.01.11

Peripheral devices

Device	Manufacturer	Model No.	Serial No.
Notebook Computer	LG Electronics Inc.,	LGS53	306QCZP560949
Test Board	N/A	N/A	N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.